

MPE Calculation For Symbol Hydra Wireless LAN

A 2.4GHz Spread Spectrum device has a measured output power of 50.7mW with a max gain of 14.2dBi on the worst case antenna with no cable loss. The equipment operates in the 2.4GHz ISM band. The equipment is proposed as meeting the OET65 requirements for use at 20cm.

The wavelength of the equipment is:

$$\frac{3 \times 10^8}{2462 \times 10^6} = 0.12\text{m}$$

Thus, the far field region is defined as being:

$$\frac{\lambda}{2\pi} = \frac{0.12}{6.283} = 0.019\text{m or } 19\text{mm}$$

Therefore, the formula below is applicable as any distance greater than 19mm is in the far field. Thus, predicting the worst case RF Power Density at 20cm from the antenna would be:

$$S = \frac{P \times G}{4\pi R^2} = \frac{50.7 \times 26.5}{12.57 \times 20^2} = 0.267\text{mW/cm}^2$$

where:

P = power measured in mW
G = antenna gain as numeric gain, (26.5 numeric / 14.2dBi)
R = distance in cm

MPE for Occupational/Controlled Exposure at 2462MHz is 5mW/cm²

MPE for General Population/Uncontrolled Exposure at 2462MHz is 1mW/cm²

Therefore, the unit under test has a power density, which is less than both the General Population and Occupational exposure limits. This is the case for the equipment under test in all conditions of operation.