



FCC RADIO TEST REPORT

FCC ID : UZ7RS5100
Equipment : Bar Code Scanner
Brand Name : Zebra
Model Name : RS5100
Applicant : Zebra Technologies Corporation
1 Zebra Plaza, Holtsville, NY 11742
Manufacturer : Zebra Technologies Corporation
1 Zebra Plaza, Holtsville, NY 11742
Standard : FCC Part 15 Subpart C §15.247

The product was received on Jul. 18, 2019 and testing was started from Aug. 27, 2019 and completed on Oct. 24, 2019. We, SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Louis Wu

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Product Specification of Equipment Under Test.....	5
1.3 Modification of EUT	6
1.4 Testing Location	6
1.5 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test.....	7
2.1 Carrier Frequency Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	11
2.4 Support Unit used in test configuration and system	11
2.5 EUT Operation Test Setup	12
2.6 Measurement Results Explanation Example.....	12
3 Test Result.....	13
3.1 Number of Channel Measurement	13
3.2 Hopping Channel Separation Measurement	15
3.3 Dwell Time Measurement.....	22
3.4 20dB and 99% Bandwidth Measurement	24
3.5 Output Power Measurement.....	36
3.6 Conducted Band Edges Measurement.....	39
3.7 Conducted Spurious Emission Measurement	46
3.8 Radiated Band Edges and Spurious Emission Measurement	56
3.9 AC Conducted Emission Measurement.....	60
3.10 Antenna Requirements.....	62
4 List of Measuring Equipment	63
5 Uncertainty of Evaluation.....	64
Appendix A. AC Conducted Emission Test Result	
Appendix B. Radiated Spurious Emission	
Appendix C. Radiated Spurious Emission Plots	
Appendix D. Duty Cycle Plots	
Appendix E. Setup Photographs	



History of this test report

Report No.	Version	Description	Issued Date
FR971801A	01	Initial issue of report	Oct. 28, 2019

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(1)	Number of Channels	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	Pass	-
3.4	2.1049	99% Occupied Bandwidth	Reporting only	-
3.5	15.247(b)(1)	Peak Output Power	Pass	-
3.6	15.247(d)	Conducted Band Edges	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass	Under limit 6.90 dB at 729.370 MHz
3.9	15.207	AC Conducted Emission	Pass	Under limit 20.11 dB at 0.157 MHz
3.10	15.203 & 15.247(b)	Antenna Requirement	Pass	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Dara Chiu

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Bar Code Scanner
Brand Name	Zebra
Model Name	RS5100
FCC ID	UZ7RS5100
Sample 1	EV Sample
Sample 2	DV Sample
EUT supports Radios application	Bluetooth BR/EDR/LE NFC tag
HW Version	DV
FW Version	R00
MFD	27SEP19
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer.

Specification of Accessories				
Battery	Brand Name	Zebra	Model Name	BT-000397
Power supply (50W)	Brand Name	Zebra	Part Number	PWR-BGA12V50W0WW
DC Line Cable (50W)	Brand Name	Zebra	Model Name	CBL-DC-388A1-01

Supported Unit Used in Test Configuration and System				
Terminal	Brand Name	Zebra	Model Name	WT6000
Cradle	Brand Name	Zebra	Model Name	RS5100 4-Slot Ring Scanner Charger

1.2 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Maximum Output Power to Antenna	Bluetooth BR(1Mbps) : 7.05 dBm (0.0051 W) Bluetooth EDR (2Mbps) : 9.49 dBm (0.0089 W) Bluetooth EDR (3Mbps) : 10.04 dBm (0.0101 W)
99% Occupied Bandwidth	Bluetooth BR(1Mbps) : 0.834MHz Bluetooth EDR (2Mbps) : 1.190MHz Bluetooth EDR (3Mbps) : 1.169MHz
Antenna Type / Gain	PIFA Antenna with gain 1.73 dBi
Type of Modulation	Bluetooth BR (1Mbps) : GFSK Bluetooth EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth EDR (3Mbps) : 8-DPSK

1.3 Modification of EUT

No modifications are made to the EUT during all test items.

1.4 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH05-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	Sporton Site No.	
	03CH16-HY	

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW0007

1.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	27	2429	54	2456
	1	2403	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	23	2425	50	2452	77	2479
	24	2426	51	2453	78	2480
	25	2427	52	2454	-	-
	26	2428	53	2455	-	-

2.2 Test Mode

Channel	Frequency	Bluetooth Average Output Power		
		GFSK / 1Mbps		
		DH1	DH3	DH5
Ch00	2402MHz	7.01 dBm	6.92 dBm	6.81 dBm
Ch39	2441MHz	6.40 dBm	6.29 dBm	6.24 dBm
Ch78	2480MHz	6.77 dBm	6.68 dBm	6.66 dBm

Channel	Frequency	Bluetooth Average Output Power		
		$\pi/4$ -DQPSK / 2Mbps		
		2DH1	2DH3	2DH5
Ch00	2402MHz	6.93 dBm	6.90 dBm	6.85 dBm
Ch39	2441MHz	6.34 dBm	6.29 dBm	6.24 dBm
Ch78	2480MHz	6.68 dBm	6.65 dBm	6.62 dBm

Channel	Frequency	Bluetooth Average Output Power		
		8-DPSK / 3Mbps		
		3DH1	3DH3	3DH5
Ch00	2402MHz	7.03 dBm	7.05 dBm	7.02 dBm
Ch39	2441MHz	6.29 dBm	6.35 dBm	6.29 dBm
Ch78	2480MHz	6.60 dBm	6.63 dBm	6.62 dBm

Channel	Frequency	Bluetooth Peak Output Power		
		GFSK / 1Mbps		
		DH1	DH3	DH5
Ch00	2402MHz	7.05 dBm	7.04 dBm	7.03 dBm
Ch39	2441MHz	6.36 dBm	6.35 dBm	6.33 dBm
Ch78	2480MHz	6.67 dBm	6.66 dBm	6.65 dBm

Channel	Frequency	Bluetooth Peak Output Power		
		$\pi/4$ -DQPSK / 2Mbps		
		2DH1	2DH3	2DH5
Ch00	2402MHz	9.49 dBm	9.48 dBm	9.47 dBm
Ch39	2441MHz	9.03 dBm	9.02 dBm	8.99 dBm
Ch78	2480MHz	9.45 dBm	9.43 dBm	9.42 dBm

Channel	Frequency	Bluetooth Peak Output Power		
		8-DPSK / 3Mbps		
		3DH1	3DH3	3DH5
Ch00	2402MHz	10.04 dBm	10.02 dBm	10.01 dBm
Ch39	2441MHz	9.61 dBm	9.60 dBm	9.59 dBm
Ch78	2480MHz	10.04 dBm	10.01 dBm	10.00 dBm

Remark: The data rate was set in 3Mbps for all the test items due to the highest RF output power.


- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report, and the worst mode of radiated spurious emissions is Bluetooth 3Mbps mode, and recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted Test Cases	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz	Mode 7: CH00_2402 MHz
	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz	Mode 8: CH39_2441 MHz
	Mode 3: CH78_2480 MHz	Mode 6: CH78_2480 MHz	Mode 9: CH78_2480 MHz
Radiated Test Cases	Bluetooth EDR 3Mbps 8-DPSK		
	Mode 1: CH00_2402 MHz with Scanner (SE4710)		
	Mode 2: CH39_2441 MHz with Scanner (SE4710)		
	Mode 3: CH78_2480 MHz with Scanner (SE4710)		
	Mode 4: CH78_2480 MHz with Scanner (SE4770)		
AC Conducted Emission	Mode 1: RS5100 4-Slot Ring Scanner Charger + Scanner 1 (SE4710) with Single trigger *2 + Scanner 2 (SE4770) with Single trigger *2 + AC Adapter (PWR-BGA12V50W0WW) for Sample 1		
Remark:			
1. For radiated test cases, the worst mode data rate 3Mbps was reported only since the highest RF output power in the preliminary tests. The conducted spurious emissions and conducted band edge measurement for other data rates were not worse than 3Mbps, and no other significantly frequencies found in conducted spurious emission.			
2. For Radiated Test Cases, the tests were performed with sample 2.			

2.3 Connection Diagram of Test System

<Bluetooth Tx Mode>



<AC Conducted Emission Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Base Station	R&S	CBT32	N/A	N/A	Unshielded, 1.8 m



2.5 EUT Operation Test Setup

The RF test items, utility “BT Regulatory Test app” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to contact with base station to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation;
RBW = 300kHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

3.1.4 Test Setup







3.1.5 Test Result of Number of Hopping Frequency

Test Engineer :	Owen Yang	Temperature :	21~25℃
		Relative Humidity :	51~54%
Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass

Number of Hopping Channel Plot on Channel 00 - 78



Date: 17.OCT.2019 19:28:18



Date: 17.OCT.2019 19:29:48

3.2 Hopping Channel Separation Measurement

3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels;
RBW = 300kHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.2.4 Test Setup



**3.2.5 Test Result of Hopping Channel Separation**


Test Engineer :	Owen Yang	Temperature :	21~25℃
		Relative Humidity :	51~54%

Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	Hopping Channel Separation Measurement (MHz)	Hopping Channel Separation Measurement Limit (MHz)	Pass/Fail
DH	1Mbps	1	0	2402	0.682	0.6175	Pass
DH	1Mbps	1	39	2441	0.682	0.6020	Pass
DH	1Mbps	1	78	2480	0.994	0.6155	Pass
2DH	2Mbps	1	0	2402	0.994	0.8770	Pass
2DH	2Mbps	1	39	2441	1.003	0.8741	Pass
2DH	2Mbps	1	78	2480	0.994	0.8770	Pass
3DH	3Mbps	1	0	2402	1.003	0.8539	Pass
3DH	3Mbps	1	39	2441	0.999	0.8539	Pass
3DH	3Mbps	1	78	2480	1.003	0.8509	Pass




<1Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 17.OCT.2019 19:50:13


Channel Separation Plot on Channel 39 - 40



Date: 17.OCT.2019 18:48:18






Channel Separation Plot on Channel 77 - 78



<2Mbps>

Channel Separation Plot on Channel 00 - 01




**Channel Separation Plot on Channel 39 - 40****Channel Separation Plot on Channel 77 - 78**




<3Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 17.OCT.2019 19:14:25


Channel Separation Plot on Channel 39 - 40



Date: 17.OCT.2019 19:18:39



Channel Separation Plot on Channel 77 - 78



Date: 17.OCT.2019 19:22:36

3.3 Dwell Time Measurement

3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW $\geq$ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.3.4 Test Setup




3.3.5 Test Result of Dwell Time

Test Engineer :	Owen Yang	Temperature :	21~25℃
		Relative Humidity :	51~54%

Mod.	Hopping Channel Number Rate	Hops Over Occupancy Time(hops)	Package Transfer Time (msec) (MHz)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Nomal	79	106.67	2.90	0.31	0.4	Pass
AFH	20	53.33	2.90	0.15	0.4	Pass

Package Transfer Time Plot



Date: 11.OCT.2019 16:34:20

Remark:

1. In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels. With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s), Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.

2. In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels. With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s), Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.

3. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

3.4 20dB and 99% Bandwidth Measurement

3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only


3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;
RBW $\geq$ 1% of the 20 dB bandwidth; VBW $\geq$ RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.
Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;
RBW $\geq$ 1-5% of the 99% bandwidth; VBW $\geq$ 3 * RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
6. Measure and record the results in the test report.

3.4.4 Test Setup



**3.4.5 Test Result of 20dB Bandwidth**

Test Engineer :	Owen Yang	Temperature :	21~25℃
		Relative Humidity :	51~54%

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	20db BW (MHz)	Pass/Fail
DH	1Mbps	1	0	2402	0.926	Pass
DH	1Mbps	1	39	2441	0.903	Pass
DH	1Mbps	1	78	2480	0.923	Pass
2DH	2Mbps	1	0	2402	1.316	Pass
2DH	2Mbps	1	39	2441	1.311	Pass
2DH	2Mbps	1	78	2480	1.316	Pass
3DH	3Mbps	1	0	2402	1.281	Pass
3DH	3Mbps	1	39	2441	1.281	Pass
3DH	3Mbps	1	78	2480	1.276	Pass




<1Mbps>

20 dB Bandwidth Plot on Channel 00




Date: 17.OCT.2019 18:45:03


20 dB Bandwidth Plot on Channel 39



Date: 17.OCT.2019 18:49:40

**20 dB Bandwidth Plot on Channel 78**

Date: 17.OCT.2019 18:53:48

<2Mbps>**20 dB Bandwidth Plot on Channel 00**

Date: 17.OCT.2019 19:11:16

20 dB Bandwidth Plot on Channel 39




20 dB Bandwidth Plot on Channel 78




<3Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 17.OCT.2019 19:15:55


20 dB Bandwidth Plot on Channel 39



Date: 17.OCT.2019 19:20:03



20 dB Bandwidth Plot on Channel 78




3.4.6 Test Result of 99% Occupied Bandwidth

Test Engineer :	Owen Yang	Temperature :	21~25℃
		Relative Humidity :	51~54%

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Bandwidth (MHz)	Pass/Fail
DH	1Mbps	1	0	2402	0.834	Pass
DH	1Mbps	1	39	2441	0.831	Pass
DH	1Mbps	1	78	2480	0.834	Pass
2DH	2Mbps	1	0	2402	1.181	Pass
2DH	2Mbps	1	39	2441	1.190	Pass
2DH	2Mbps	1	78	2480	1.187	Pass
3DH	3Mbps	1	0	2402	1.169	Pass
3DH	3Mbps	1	39	2441	1.169	Pass
3DH	3Mbps	1	78	2480	1.169	Pass

<1Mbps>

99% Occupied Bandwidth Plot on Channel 00





99% Occupied Bandwidth Plot on Channel 39



Date: 17.OCT.2019 18:50:12

99% Occupied Bandwidth Plot on Channel 78




Date: 17.OCT.2019 18:54:41




<2Mbps>

99% Occupied Bandwidth Plot on Channel 00



Date: 17.OCT.2019 19:12:24


99% Occupied Bandwidth Plot on Channel 39



Date: 17.OCT.2019 19:06:13



99% Occupied Bandwidth Plot on Channel 78



Date: 17.OCT.2019 19:02:09

<3Mbps>


99% Occupied Bandwidth Plot on Channel 00




Date: 17.OCT.2019 19:16:46



99% Occupied Bandwidth Plot on Channel 39



99% Occupied Bandwidth Plot on Channel 78



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.5 Output Power Measurement

3.5.1 Limit of Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following:
For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps, 2Mbps, 3Mbps and AFH modes are 0.125 watts.


3.5.2 Measuring Instruments

See list of measuring equipment of this test report.

3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

3.5.4 Test Setup



3.5.5 Test Result of Peak Output Power

Test Engineer :	Owen Yang	Temperature :	21~25℃
		Relative Humidity :	51~54%

DH	CH.	N _{TX}	Peak Power (dBm)	Power Limit (dBm)	Test Result
DH1	0	1	7.05	20.97	Pass
	39	1	6.36	20.97	Pass
	78	1	6.67	20.97	Pass

2DH	CH.	N _{TX}	Peak Power (dBm)	Power Limit (dBm)	Test Result
2DH1	0	1	9.49	20.97	Pass
	39	1	9.03	20.97	Pass
	78	1	9.45	20.97	Pass

3DH	CH.	N _{TX}	Peak Power (dBm)	Power Limit (dBm)	Test Result
3DH1	0	1	10.04	20.97	Pass
	39	1	9.61	20.97	Pass
	78	1	10.04	20.97	Pass

3.5.6 Test Result of Average Output Power (Reporting Only)

Test Engineer :	Owen Yang	Temperature :	21~25℃
		Relative Humidity :	51~54%

DH	CH.	N _{TX}	Average Power (dBm)	Duty Factor (dB)
DH1	0	1	7.01	5.12
	39	1	6.40	5.12
	78	1	6.77	5.12

2DH	CH.	N _{TX}	Average Power (dBm)	Duty Factor (dB)
2DH1	0	1	6.93	5.07
	39	1	6.34	5.07
	78	1	6.68	5.07

3DH	CH.	N _{TX}	Average Power (dBm)	Duty Factor (dB)
3DH1	0	1	7.05	5.03
	39	1	6.35	5.03
	78	1	6.63	5.03

3.6 Conducted Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.

3.6.4 Test Setup






3.6.5 Test Result of Conducted Band Edges

Test Engineer :	Owen Yang	Temperature :	21~25°C
		Relative Humidity :	51~54%


<1Mbps>

Low Band Edge Plot on Channel 00



Date: 17.OCT.2019 18:45:24

High Band Edge Plot on Channel 78




Date: 17.OCT.2019 18:54:06




<2Mbps>

Low Band Edge Plot on Channel 00



Date: 17.OCT.2019 19:11:51

High Band Edge Plot on Channel 78



Date: 17.OCT.2019 19:01:35



Spectrum

Ref Level 30.00 dBm Offset 25.00 dB RBW 100 kHz
Att 20 dB SWT 37.9 μ s VBW 300 kHz Mode Auto FFT

IPk Max

M1[1] -42.99 dBm 2.3996090 GHz

D1 6.610 dBm

D2 -13.390 dBm

M1

F1

Start 2.395 GHz 691 pts Stop 2.405 GHz

Spectrum

Ref Level 30.00 dBm Offset 25.00 dB RBW 100 kHz
Att 20 dB SWT 38 μ s VBW 300 kHz Mode Auto FFT

1Pk Max

M1[1] -44.09 dBm 2.4845070 GHz

D1 6.630 dBm
D2 -13.370 dBm

F1

Start 2.4775 GHz 691 pts Stop 2.4895 GHz


Date: 17.OCT.2019 19:24:39



3.6.6 Test Result of Conducted Hopping Mode Band Edges


<1Mbps>

Hopping Mode Low Band Edge Plot



Date: 17.OCT.2019 18:57:02


Hopping Mode High Band Edge Plot



Date: 17.OCT.2019 18:56:34


<2Mbps>

Hopping Mode Low Band Edge Plot



Date: 17.OCT.2019 18:57:41


Hopping Mode High Band Edge Plot



Date: 17.OCT.2019 18:58:01


<3Mbps>

Hopping Mode Low Band Edge Plot



Date: 17.OCT.2019 19:31:29

Hopping Mode High Band Edge Plot



Date: 17.OCT.2019 19:27:29

3.7 Conducted Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.7.2 Measuring Instruments

See list of measuring equipment of this test report.

3.7.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.7.4 Test Setup




3.7.5 Test Result of Conducted Spurious Emission

Test Engineer :	Owen Yang	Temperature :	21~25℃
		Relative Humidity :	51~54%


<1Mbps>

CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 17.OCT.2019 18:46:51


1Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz



Date: 17.OCT.2019 18:47:17



CSE Plot on Ch 39 between 30MHz ~ 3 GHz



CSE Plot on Ch 39 between 2 GHz ~ 25 GHz

