

TEST REPORT

Product Name : TWS Earbuds with Digital Display
Model Number : MA-3915, V40089W, V40089W-BLK,
V40089W-WHT, MUZ3012, MUZ3012-WHT
FCC ID : 2AAPK-MA-3915

Prepared for : Shenzhen Kingsun Enterprises Co., Ltd.
Address : 25/F, CEC Information Building, Xinwen Rd., Shenzhen,
Guangdong, P.R.China

Prepared by : EMTEK (SHENZHEN) CO., LTD.
Address : Building 69, Majialong Industry Zone, Nanshan District,
Shenzhen, Guangdong, China

Tel: (0755) 26954280
Fax: (0755) 26954282

Report Number : ENS2304280322W00102R
Date(s) of Tests : May 16, 2023 to June 07, 2023
Date of issue : June 07, 2023

Table of Contents

1. TEST RESULT CERTIFICATION	3
2. EUT SPECIFICATION	5
3. TEST REQUIREMENT	6
4. MEASUREMENT RESULT	7



1. TEST RESULT CERTIFICATION

Applicant : Shenzhen Kingsun Enterprises Co., Ltd.

Address : 25/F, CEC Information Building, Xinwen Rd., Shenzhen, Guangdong, P.R.China

Manufacturer : Shenzhen Kingsun Enterprises Co., Ltd.

Address : 25/F, CEC Information Building, Xinwen Rd., Shenzhen, Guangdong, P.R.China

Factory : Shenzhen Ning Tong Da Electronics Co., Ltd

Address : 3 / F, Building A1, Changrui Industrial Park, No. 55 Guanlan Guihuapinshun Road, Longhua District, Shenzhen

EUT : TWS Earbuds with Digital Display

Model Name : MA-3915, V40089W, V40089W-BLK, V40089W-WHT, MUZ3012, MUZ3012-WHT

Trademark : N/A

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
§ 15.247(i), § 2.1093	PASS

The above equipment was tested by EMTEK(SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules FCC § 15.247(i), § 2.1093.

The test results of this report relate only to the tested sample identified in this report

Date of Test : May 16, 2023 to June 07, 2023



Prepared by : _____

Una Yu /Editor



Reviewer : _____

Joe Xia/Supervisor



Approve & Authorized Signer : _____

Lisa Wang/Manager



Modified History

Version	Report No.	Revision Date	Summary
	ENS2304280322W00102R	/	Original Report



2. EUT Specification

Characteristics	Description
Product:	TWS Earbuds with Digital Display
Model Number:	MA-3915, V40089W, V40089W-BLK, V40089W-WHT, MUZ3012, MUZ3012-WHT All products are the same, only the model number and color of appearance are different Here we selected MA-3915 for all the test
Sample:	1#
Device Type:	Bluetooth V5.3
Data Rate:	1Mbps for GFSK modulation 2Mbps for $\pi/4$ -DQPSK modulation 3Mbps for 8DPSK modulation
Modulation:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Operating Frequency Range(s) :	2402-2480MHz
Number of Channels:	0.66 dBm(0.001164W)
Transmit Power Max:	Chip Antenna
Antenna Gain:	2.67 dBi
Power supply:	DC 5V from USB, DC 3.7V from battery
Evaluation applied:	☐ MPE Evaluation ☒ SAR Evaluation

3. Test Requirement

RF EXPOSURE EVALUATION

According to §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,²⁴ where

- $f_{\text{(GHz)}}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval. One antenna is available for the EUT. The minimum separation distance is 5mm.

4. Measurement Result

Antenna gain: 2.67 dBi

When a single module works, the measurement results are as follows:

BT1

Transmit Frequency (MHz)	Mode	Measured Power (dBm)	E.I.R.P (dBm)	Tune up Power (dBm)	Max tune up power (dBm)	Calculation Result	1-g SAR
2402	GFSK	-0.68	1.99	1±1	2	0.4912658	3
2441	GFSK	-1.68	0.99	0±1	1	0.3933815	3
2480	GFSK	-1.13	1.54	1±1	2	0.4991785	3
2402	Π/4-DQPSK	0.05	2.72	2±1	3	0.6184670	3
2441	Π/4-DQPSK	-0.89	1.78	1±1	2	0.4952379	3
2480	Π/4-DQPSK	-0.47	2.20	2±1	3	0.6284284	3
2402	8DPSK	0.66	3.33	3±1	4	0.7786038	3
2441	8DPSK	-0.54	2.13	2±1	3	0.6234676	3
2480	8DPSK	-0.12	2.55	2±1	3	0.6284284	3

According to KDB 447498, no stand-alone required for BT antenna, and no simultaneous SAR measurement is required.

*** End of Report ***