

Allgon AB

RF TEST REPORT

Report Type:

FCC Part 15.225& ISED RSS-210 RF report

Model:

D5-42, CL-AL018-1

REPORT NUMBER:

2410B2085SHA-001

ISSUE DATE:

January 10, 2025

DOCUMENT CONTROL NUMBER:

TTRFFCCPART15C_V1 © 2018 Intertek



Applicant : Allgon AB
August Barks gata 30A, SE-421 32 Västra Frölunda, Sweden

Manufacturer : Allgon AB
August Barks gata 30A, SE-421 32 Västra Frölunda, Sweden

FCC ID : 2BC3H2316B
IC : 31388-2316B

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

47CFR Part 15 (2023): Radio Frequency Devices (Subpart C)

RSS-210 Issue 11 (June 25, 2024): Licence-Exempt Radio Apparatus: Category I Equipment

RSS-Gen Issue 5, Amendment 1 (March 2019), Amendment 2 (February 2021): General Requirements for Compliance of Radio Apparatus

ANSI C63.10 (2020): American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

PREPARED BY:**REVIEWED BY:**

Project Engineer
Erick Liu



Reviewer
Wakeyou Wang

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TEST REPORT

Content

REVISION HISTORY.....	4
MEASUREMENT RESULT SUMMARY	5
1 GENERAL INFORMATION	6
1.1 DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	6
1.2 TECHNICAL SPECIFICATION.....	6
1.3 DESCRIPTION OF TEST FACILITY.....	7
2 TEST SPECIFICATIONS.....	8
2.1 STANDARDS OR SPECIFICATION	8
2.2 MODE OF OPERATION DURING THE TEST	8
2.3 TEST SOFTWARE LIST	8
2.4 TEST PERIPHERALS LIST.....	8
2.5 TEST ENVIRONMENT CONDITION:.....	8
2.6 INSTRUMENT LIST	9
2.7 MEASUREMENT UNCERTAINTY.....	10
3 FUNDAMENTAL EMISSION AND EMISSION MASK.....	11
3.1 LIMIT	11
3.2 MEASUREMENT PROCEDURE	11
3.3 TEST RESULTS OF FUNDAMENTAL EMISSIONS	12
4 EMISSION OUTSIDE THE FREQUENCY BAND	14
4.1 LIMIT	14
4.2 MEASUREMENT PROCEDURE	14
4.3 TEST RESULTS OF RADIATED EMISSIONS	16
5 FREQUENCY STABILITY (TEMPERATURE VARIATION)	20
5.1 TEST LIMIT	20
5.2 TEST CONFIGURATION	20
5.3 TEST PROCEDURE AND TEST SETUP	21
5.4 TEST PROTOCOL.....	21
6 FREQUENCY STABILITY (VOLTAGE VARIATION)	22
6.1 TEST LIMIT	22
6.2 TEST CONFIGURATION	22
6.3 TEST PROCEDURE AND TEST SETUP	22
6.4 TEST PROTOCOL.....	23
7 CONDUCTED EMISSIONS	24
7.1 LIMIT	24
7.2 TEST CONFIGURATION	24
7.3 MEASUREMENT PROCEDURE	25
7.4 TEST RESULTS OF CONDUCTED EMISSIONS.....	25
8 99% AND 20DB BANDWIDTH	26
8.1 LIMIT.....	26
8.2 TEST CONFIGURATION	26
8.3 TEST PROCEDURE AND TEST SET UP	27
8.4 TEST PROTOCOL	28
9 ANTENNA REQUIREMENT.....	29

Revision History

Report No.	Version	Description	Issued Date
2410B2085SHA-001	Rev. 01	Initial issue of report	January 10, 2025

Measurement result summary

TEST ITEM	FCC REFERENCE	IC REFERENCE	RESULT
20dB Bandwidth&99% Bandwidth	15.215(c) 2.1049	RSS-Gen Issue 5 Clause 6.6	Pass
Fundamental Field Strength and Emission Mask	15.205 & 15.225(a) (b) (c)	RSS 210 B.6	Pass
Emission outside the frequency band	15.225(d) /15.109	RSS 210 B.6	Pass
Power line conducted emission	15.207	RSS-Gen Issue 5 Clause 8.8	NA
Frequency Stability	15.225(e)	RSS 210 B.6	Pass
Antenna requirement	15.203	RSS-GEN 6.8	Pass

Notes: 1: NA =Not Applicable

2: Determination of the test conclusion is based on IEC Guide 115 in consideration of measurement uncertainty.

TEST REPORT

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

Product name:	Transceiver
Type/Model:	D5-42, CL-AL018-1
Host model:	T36-01
Description of EUT:	EUT is a wireless transceiver module, all models are the same except for the model name. The EUT was tested together with the host device.
Rating:	2.8V DC Host: 5-45VDC 1A, 3.7VDC 2000mAh, Li-ion battery
EUT type:	<input checked="" type="checkbox"/> Table top <input type="checkbox"/> Floor standing
Software Version:	/
Hardware Version:	/
Sample received date:	November 11, 2024
Date of test:	November 12, 2024 – December 6, 2024

1.2 Technical Specification

Operation Frequency Band:	13.556 ~ 13.567MHz
Normal Working Frequency:	13.56MHz
Channel Number:	1
Type of Modulation:	ASK
Antenna Designation:	Fixed Internal Loop Antenna

TEST REPORT

1.3 Description of Test Facility

Name:	Intertek Testing Services (Shanghai FTZ) Co., Ltd.
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L21189
	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier: CN0014
	VCCI Registration Lab Registration No.: R-14243, G-10845, C-14723, T-12252
	A2LA Accreditation Lab Certificate Number: 3309.02

2 TEST SPECIFICATIONS

2.1 Standards or specification

47CFR Part 15 (2023)

RSS-210 Issue 11 (June 25, 2024):

RSS-Gen Issue 5, Amendment 1 (March 2019), Amendment 2 (February 2021)

ANSI C63.10 (2020)

2.2 Mode of operation during the test

While testing, the internal modulation and continuously transmission were applied.

2.3 Test software list

Test Items	Software	Manufacturer	Version
Conducted emission	ESxS-K1	R&S	V2.1.0
Radiated emission	ES-K1	R&S	V1.71

2.4 Test peripherals list

Item No	Description	Band and Model	S/No
-	-	-	-

2.5 Test environment condition:

Test items	Temperature	Humidity
Radiated emission	26°C	53% RH
Power line conducted emission	NA	NA

2.6 Instrument list

Radiated Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Test Receiver	R&S	ESIB 26	EC 3045	2025-09-14
<input checked="" type="checkbox"/>	Bilog Antenna	TESEQ	CBL 6112D	EC 4206	2025-10-23
<input type="checkbox"/>	Pre-amplifier	R&S	AFS42-00101800-25-S-42	EC5262	2025-06-10
<input type="checkbox"/>	Horn antenna	R&S	HF 906	EC 3049	2025-01-16
<input type="checkbox"/>	Horn antenna	ETS	3117	EC 4792-1	2025-03-14
<input type="checkbox"/>	Horn antenna	TOYO	HAP18-26W	EC 4792-3	2025-07-07
<input checked="" type="checkbox"/>	Active loop antenna	Schwarzbeck	FMZB1519	EC 5345	2025-03-23
<input type="checkbox"/>	Horn antenna	ETS	3116c	Ec5955	2025-01-16
RF test					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	PXA Signal Analyzer	Keysight	N9030A	EC 5338	2025-09-08
<input type="checkbox"/>	Power sensor	Agilent	U2021XA	EC 5338-1	2025-03-01
<input type="checkbox"/>	Vector Signal Generator	Agilent	N5182B	EC 5175	2025-03-01
<input type="checkbox"/>	MXG Analog Signal Generator	Agilent	N5181A	EC 5338-2	2025-03-01
<input type="checkbox"/>	Mobile Test System	Litepoint	lqxel	EC 5176	2025-01-09
<input type="checkbox"/>	Test Receiver	R&S	ESCI 7	EC 4501	2025-01-09
Additional instrument					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 3442	2025-01-09

TEST REPORT

2.7 Measurement uncertainty

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Frequency	Expanded Uncertainty (k=2)
Conducted emission at mains ports	9kHz ~ 150kHz	3.52 dB
	150kHz ~ 30MHz	3.19 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	4.90 dB
Radiated Emissions above 1 GHz	1GHz ~ 6GHz	5.02 dB
	6GHz ~ 18GHz	5.28 dB
Occupied Channel Bandwidth	/	± 0.88 %

3 Fundamental Emission and Emission Mask

Test result: Pass

3.1 Limit

Frequencies (MHz)	Limit at 30m (dBuV/m)	Limit at 3m (dBuV/m)
13.110 – 13.410	40.50	80.50
13.410 – 13.553	50.50	90.50
13.553 – 13.567	84.00	124.00
13.567 – 13.710	50.50	90.50
13.710 – 14.010	40.50	80.50



3.2 Measurement Procedure

- The EUT was placed on a 0.8m plank above the ground at a 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- Both X and Y axes of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to PK Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:


- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

3.3 Test Results of Fundamental Emissions



TEST REPORT

Z



Antenna Polarization	Frequency (MHz)	Corrected Reading (dBuV/m)	Limit (dBuV/m)	Margin	Detector
X	13.56	43.2	124.00	80.8	PK
Y	13.56	33.4	124.00	90.6	PK
Z	13.56	43.0	124.00	81.0	PK

Remark: 1. Correct Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.
 2. Corrected Reading = Original Receiver Reading + Correct Factor
 3. Margin = Limit - Corrected Reading

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,
 Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV,
 Limit = 40.00dBuV/m.
 Then Correct Factor = 30.20 + 2.00 – 32.00 = 0.20dB/m;
 Corrected Reading = 10dBuV + 0.20dB/m = 10.20dBuV/m;
 Margin = 40.00dBuV/m - 10.20dBuV/m = 29.80dB.

4 Emission outside the frequency band

Test result: Pass

4.1 Limit

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

4.2 Measurement Procedure

For Radiated emission below 30MHz:

- The EUT was placed on a 0.8m plank above the ground at a 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- Both X and Y axes of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz:

- The EUT was placed on a 0.8m plank above the ground at a 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

TEST REPORT

- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f) The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:



- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
- 3. All modes of operation were evaluated and the worst-case emissions were reported

TEST REPORT

4.3 Test Results of Radiated Emissions


The EUT has been tested in all three orthogonal planes, it has the worst case when it is in horizontal position for both below 30MHz & above 30MHz.

Test data below 30MHz:



TEST REPORT

Z



Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Detector	Polar
568.738kHz	72.50	58.90	-13.60	PK	X
1.167MHz	66.30	35.70	-30.60	PK	X
1.765MHz	69.50	31.20	-38.30	PK	X
11.097MHz	69.50	28.60	-40.90	PK	X
18.574MHz	69.50	26.50	-43.00	PK	X
508.918kHz	73.50	61.80	-11.70	PK	Y
1.167MHz	66.30	36.20	-30.10	PK	Y
1.885MHz	69.50	30.40	-39.10	PK	Y
22.104MHz	69.50	27.20	-42.30	PK	Y
568.738kHz	72.50	59.40	-13.10	PK	Z
1.107MHz	66.70	38.70	-28.00	PK	Z
1.586MHz	63.60	30.90	-32.70	PK	Z
1.885MHz	69.50	29.80	-39.70	PK	Z
21.625MHz	69.50	27.10	-42.40	PK	Z

Remark: 1. Correct Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.



2. Level = Original Receiver Reading + Correct Factor

3. Delta = Level - Limit

4. If the PK Level is lower than AV limit, the AV test can be elided.

TEST REPORT

Test data from 30MHz to 1000MHz:



TEST REPORT

No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Detector	Polar
1*	618.887MHz	46.00	23.71	-22.29	PK	Hor
2*	677.281MHz	46.00	24.84	-21.16	PK	Hor
3*	720.834MHz	46.00	25.73	-20.27	PK	Hor
4*	783.108MHz	46.00	28.15	-17.85	PK	Hor
5*	869.050MHz	46.00	29.20	-16.80	PK	Hor
6*	959.745MHz	46.00	31.43	-14.57	PK	Hor
7*	573.200MHz	46.00	22.67	-23.33	PK	Ver
8*	695.032MHz	46.00	25.05	-20.95	PK	Ver
9*	759.246MHz	46.00	28.76	-17.24	PK	Ver
10*	815.506MHz	46.00	26.01	-19.99	PK	Ver
11*	869.050MHz	46.00	31.09	-14.91	PK	Ver
12*	935.883MHz	46.00	30.72	-15.28	PK	Ver

- Remark: 1. Correct Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.
2. Level = Original Receiver Reading + Correct Factor
3. Delta = Level - Limit
4. If the PK Level is lower than AV limit, the AV test can be elided.


5 Frequency Stability (Temperature Variation)

Test result: PASS

5.1 Test limit

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to $+50$ degrees C at normal supply voltage.

5.2 Test Configuration



5.3 Test procedure and test setup

Test Procedure as per ANSI 63.10 clause 6.8.1.

5.4 Test protocol

Voltage (V)	Temp (°C)	Freq measured (MHz)	Freq nominal (MHz)	Tolerance (%)	Limit (%)
3.7	-20	13.561	13.560	0.007	0.01
	-10	13.561		0.007	
	0	13.560		0	
	10	13.560		0	
	20	13.560		0	
	30	13.560		0	
	40	13.561		0.007	
	50	13.561		0.007	


6 Frequency Stability (Voltage Variation)

Test result: PASS

6.1 Test limit

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

6.2 Test Configuration



6.3 Test procedure and test setup

Test Procedure as per ANSI 63.10 clause 6.8.2.

6.4 Test protocol

Temp (°C)	Voltage (V)	Freq Measured (MHz)	Freq nominal (MHz)	Tolerance (%)	Limit (%)
20	3.7	13.560	13.560	0	0.01
	3.145	13.561		0.007	

7 Conducted emissions


Test result: NA

7.1 Limit

Frequency of Emission (MHz)	Conducted Emissions Limit (dBuV)	
	QP	AV
0.15-0.5	66 to 56*	56 to 46 *
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

7.2 Test Configuration



TEST REPORT**7.3 Measurement Procedure**

Measured levels of ac power-line conducted emission shall be the emission voltages from the voltage probe, where permitted, or across the 50 Ω LISN port (to which the EUT is connected), where permitted, terminated into a 50 Ω measuring instrument. All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer. For those measurements using a LISN, the 50 Ω measuring port is terminated by a measuring instrument having 50 Ω input impedance. All other ports are terminated in 50 Ω loads.

Tabletop devices shall be placed on a platform of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The vertical conducting plane or wall of an RF-shielded (screened) room shall be located 40 cm to the rear of the EUT. Floor-standing devices shall be placed either directly on the reference ground-plane or on insulating material as described in ANSI C63.4. All other surfaces of tabletop or floor-standing EUTs shall be at least 80 cm from any other grounded conducting surface, including the case or cases of one or more LISNs.

The bandwidth of the test receiver is set at 9 kHz.

7.4 Test Results of Conducted Emissions

NA.


8 99% and 20dB Bandwidth

Test result: Pass

8.1 Limit

The 20dB bandwidth should be fallen in the allocated operating frequency range.
No limit for 99% bandwidth.

8.2 Test configuration



8.3 Test procedure and test set up

The measurement was applied in a 3m semi-anechoic chamber.


The center of the loop antenna shall be 1 m above the horizontal metal ground plane.

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set RBW = 1 % to 5 % of the OBW
3. Set VBW $\geq 3 \cdot$ RBW
4. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
5. Use the 99 % power bandwidth function of the instrument (if available).
6. the 20dB bandwidth is also measured with the same setting.

8.4 Test protocol

	Lower point (MHz)	Higher point (MHz)	Bandwidth (MHz)	Allocated bandwidth (MHz)
99% Bandwidth	13.429	13.693	0.264	/
20dB Bandwidth	13.556	13.564	0.008	13.553 ~ 13.567



9 Antenna requirement

Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

Result:

EUT uses permanently attached antenna to the intentional radiator, so it can comply with the provisions of this section.

***** END *****