



TÜVRheinland®
Precisely Right.

RF Exposure Report

FCC Part 2.1091

EUT Name: Powerview Gen3 Motor Control Board
Model No.: 1016000015

Prepared for:

Hunter Douglas Window Fashions, Inc
1 Duette Way
Broomfield, CO 80020 U.S.A.

Prepared by:

TUV Rheinland of North America, Inc.
5015 Brandin Ct. Fremont CA 94538 USA
Tel: (929) 249-9123
Fax: (925) 249-9124
<http://www.tuv.com/>

Report/Issue Date: April 17, 2023
Report Number: US23IR08.001 Rev1.0
Job Number: P00979800

TABLE OF CONTENTS

1	PRODUCT SPECIFICATIONS.....	5
1.1	PRODUCT DESCRIPTION.....	5
1.2	PRODUCT SPECIFICATIONS.....	5
1.3	AIR INTERFACES	5
2	RF EXPOSURE EVALUATION	6
2.1	PURPOSE	6
2.2	EXEMPTION THRESHOLD	6
2.3	MAXIMUM PERMISSIBLE EXPOSURE LIMIT	6
2.4	ASSESSMENT METHODS	7
2.5	ASSESSMENT CALCULATION	7
2.6	CONCLUSION.....	7

Statement of Compliance

Manufacturer: Hunter Douglas Window Fashions, Inc
1 Duette Way
Broomfield, CO 80020 U.S.A.
Name of Equipment: Powerview Gen3 Motor Control Board
Model No. 1016000015
Application of Regulations: FCC Part 2.1091

Guidance Documents:

FCC Part 2.1091

Test Methods:

FCC Part 1.1310, KDB 447498 D01

The electromagnetic compatibility test and documented data described in this report has been performed and recorded by TUV Rheinland, in accordance with the standards and procedures listed herein. As the responsible authorized agent of the EMC laboratory, I hereby declare that the equipment described above has been shown to be compliant with the EMC requirements of the stated regulations and standards based on these results. If any special accessories and/or modifications were required for compliance, they are listed in this report.

This report must not be used to claim product endorsement by A2LA or any agency of the U.S. Government. This report shall not be reproduced except in full, without the written authorization of TUV Rheinland of North America.

Osvaldo Casorla April 17, 2023

Test Engineer Date

Rachana Khanduri April 17, 2023

Laboratory Signatory Date



Test Cert. # 3331.02

Revisions

Revision No.	Date	Reason for Change	Author
1.0	4/17/23	Original Report	OC

Note: Latest revision report will replace all previous reports.

1 Product Specifications

1.1 Product Description

1.2 Product Specifications

EUT Specifications	
Exposure Type	☒ General Population / Uncontrolled ☐ Occupational / Controlled
Multiple Antenna Feeds:	☐ Yes and how many 1 ☒ No
Hardware Version	1016000015
Software Version	n/a
Antenna	2.4ghz FlexPIFA, LSR 330-0149 (001-0014)
Antenna Gain	1.58 dBi
Power Settings	8dBm
*All EUT specifications are provided by the manufacturer or the TUV direct customer. Note: Information supplied by the customer and can affect the validity of results.	

1.3 Air Interfaces

Air Interface	Supported Capabilities	Modulation	Maximum Duty Cycle %	Band (MHz)	Frequency Range (MHz)	Maximum Output Power Including Tolerance (dBm)
BLE	• BLE 1Mbps, 2Mbps	• GFSK	100	2400 – 2483.5 MHz	2402 – 2480 MHz	4.96

2 RF Exposure Evaluation

2.1 Purpose

This report will demonstrate the compliance of RF exposure to the human body of the 1016000015 according to FCC rule part 2.1091. All transmitters, regardless if it is categorically excluded, are assessed to ensure the product can operate in manners that meet or exceed the minimum test separation distance as required by KDB 447498.

2.2 Exemption Threshold

Table 2. Single RF Sources Subject to Routine Environmental Evaluation under MPE-Based Exemptions, $R \geq \lambda/2\pi$

Transmitter Frequency	Threshold ERP
0.3 – 1.34	$1,920 R^2$
1.34 – 30	$3,450 R^2/f^2$
30 – 300	$3.83 R^2$
300 – 1,500	$0.0128 R^2 f$
1,500 – 100,000	$19.2 R^2$

Note: Transmitter Frequency is in MHz, Threshold ERP is in watts, R is in meters, f is in MHz.

2.3 Maximum Permissible Exposure Limit

The Maximum Permissible Exposure (MPE) limits according to FCC rule part 1.1310 for general population/uncontrolled exposure is as follows:

Frequency Range (MHz)	E-field strength (V/m)	H-field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500	-	-	f/1500	30
1,500-100,000	-	-	1.0	30

* = Plane-wave equivalent power density

2.4 Assessment Methods

The power density is calculated according to the following equation

$$S = \frac{EIRP}{4\pi R^2}$$

Where

S = Power Density (mW/cm²)

EIRP = Effective Isotropic Radiated Power (mW)

R = Minimum distance between the human body and antenna (cm)

When the calculated power density exceeds the MPE limits, the power density is measured.

2.5 Assessment Calculation

The maximum output power and antenna gain is declared by the manufacturer and used in this assessment.
The minimum RF exposure distance during normal operation is 20 cm.

Stand Alone Analysis

Frequency (MHz)	Operating Mode	Max. Conducted Power (mW)	Numeric Antenna Gain	Ei Power Density (mW/cm ²)	Eref Power Density Limit (mW/cm ²)	Percentage of Limit %
2402	BLE 1Mbps	3.13	1.44	0.001	1.0	0.09

Exemption Analysis

Frequency (MHz)	Operating Mode	Max. Conducted Power (mW)	Numeric Antenna Gain	ERP (W)	Exemption Limit ERP (W)	Percentage of Limit %
2402	BLE 1Mbps	3.13	1.44	0.003	0.77	0.39

Note: Calculations for this report are based on highest power measurement and its antenna gain.

2.6 Conclusion

The EUT was found to be exempt from RF Exposure evaluation.

The EUT was found to be compliant to the requirements of FCC part 1.1310 and part 2.1091 with a minimum distance of 20 cm.