



# SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, TaoYuan Hsien, Taiwan, R.O.C.  
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / [www.sporton.com.tw](http://www.sporton.com.tw)

## FCC RADIO TEST REPORT

Applicant's company	TomTom BV.
Applicant Address	Rembrandtplein 35, 1017 CT Amsterdam, The Netherlands
FCC ID	S4LONE
Manufacturer's company	Inventec Appliances Corp.
Manufacturer Address	37, Wugong 5 <sup>th</sup> Rd., Wugu Shiang, Taipei, Taiwan 248

Product Name	GPS Tracking System
Brand Name	TomTom
Model Name	TomTom ONE
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz
Receive Date	Feb. 7, 2006
Test Date	Feb. 16, 2006
Submission Type	Class II Change



### Statement

**Test result included is only for the Bluetooth part of the product.**

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.

NVLAP<sup>®</sup>

Lab Code: 200079-0

## Table of Contents

<b>1. CERTIFICATE OF COMPLIANCE .....</b>	<b>1</b>
<b>2. SUMMARY OF THE TEST RESULT .....</b>	<b>2</b>
<b>3. GENERAL INFORMATION .....</b>	<b>3</b>
3.1. Product Details.....	3
3.2. Accessories.....	3
3.3. Table for Filed Antenna.....	3
3.4. Table for Carrier Frequencies .....	4
3.5. Table for Test Modes .....	4
3.6. Table for Testing Locations.....	4
3.7. Table for Supporting Units .....	5
3.8. Table for Parameters of Test Software Setting .....	5
3.9. Test Configurations .....	6
<b>4. TEST RESULT .....</b>	<b>8</b>
4.1. AC Power Line Conducted Emissions Measurement.....	8
4.2. Radiated Emissions Measurement .....	12
4.3. Band Edge Emissions Measurement .....	26
4.4. Antenna Requirements .....	28
<b>5. LIST OF MEASURING EQUIPMENTS .....</b>	<b>29</b>
<b>6. SPORTON COMPANY PROFILE .....</b>	<b>30</b>
6.1. Test Location.....	30
<b>7. NVLAP CERTIFICATE OF ACCREDITATION .....</b>	<b>31</b>
<b>APPENDIX A. PHOTOGRAPHS OF EUT.....</b>	<b>A1 ~ A24</b>
<b>APPENDIX B. TEST PHOTOS.....</b>	<b>B1 ~ B3</b>



## History of This Test Report

Original Issue Date: Feb. 16, 2006

Report No.: FR612302

No additional attachment.

Additional attachment were issued as following record:

Attachment No.	Issue Date	Description

## 1. CERTIFICATE OF COMPLIANCE

Product Name : GPS Tracking System  
Brand Name : TomTom  
Model Name : TomTom ONE  
Applicant : TomTom BV.  
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Feb. 7, 2006 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

  
**Wayne Hsu / Supervisor**  
Sporton International Inc.

## 2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	13.22 dB
4.2	15.247(b)(1)	Maximum Peak Conducted Output Power	Complies	-
4.3	15.247(a)(1)	Hopping Channel Separation	Complies	-
4.4	15.247(b)(1)	Number of Hopping Frequency	Complies	-
4.5	15.247(a)(1)	Dwell Time	Complies	-
4.6	15.247(d)	Radiated Emissions	Complies	3.13 dB
4.7	15.247(d)	Band Edge Emissions	Complies	4.31 dB
4.8	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	$\pm 2.26\text{dB}$	Confidence levels of 95%
Maximum Peak Conducted Output Power	$\pm 0.5\text{dB}$	Confidence levels of 95%
Hopping Channel Separation / Dwell Time	$\pm 6.25 \times 10^{-7}$	Confidence levels of 95%
Radiated Emissions / Band Edge Emissions	$\pm 3.72\text{dB}$	Confidence levels of 95%

### 3. GENERAL INFORMATION

#### 3.1. Product Details

EUT is a GPS Tracking System with Bluetooth radio function. Only the radio detail of Bluetooth is shown in the table below. For more detailed features description, please refer to the manufacturer's specifications or user's manual.

Items	Description
Radio Type	Intentional Transceiver (Bluetooth)
Power Type	Input: 100~240V AC / Output: 5V DC / 3.7 V DC from battery
Interface Type	Mini USB; Audio Port; SD Card; DC Adapter Port
Modulation	FHSS (GFSK)
Data Rate (Mbps)	1
Frequency Range	2400 ~ 2483.5MHz
Channel Number	79
Channel Band Width (99%)	792 kHz
Conducted Output Power	1.63 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

#### 3.2. Accessories

Power	Brand	Model	Rating
Adapter 1	tomtom	A10P1-05MP	Input: 100~240V AC Output: 5V DC / 3.7 V DC from battery
Others	Description		
USB Cable	This cable enables USB communication between EUT and a host PC.		
Plug for EU	Supply Power		
Plug for UK	Plug converter		

#### 3.3. Table for Filed Antenna

Ant.	Antenna Type	Connector	Gain (dBi)
1	Chip Antenna	NA	-3

### 3.4. Table for Carrier Frequencies

Frequency Band	Channel No.	Frequency
2400~2483.5MHz	0	2402 MHz
	1	2403 MHz
	:	:
	38	2440 MHz
	39	2441 MHz
	40	2442 MHz
	:	:
	77	2479 MHz
	78	2480 MHz

### 3.5. Table for Test Modes

Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Conducted Emissions	Normal Link	1 Mbps	Hopping 0~78	1
Max. Conducted Output Power	GFSK	1 Mbps	0/39/78	NA
Hopping Channel Separation	GFSK	1 Mbps	0~1/39~40/77~78	NA
Number of Hopping Frequency	GFSK	1 Mbps	0~78	NA
Dwell Time	DH1/DH3/DH5	1 Mbps	0/39/78	NA
Radiated Emissions Below 1GHz	GFSK	1 Mbps	39	1
Radiated Emissions Above 1GHz Band Edge Emissions	GFSK	1 Mbps	0/39/78	1

### 3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH03-HY	SAC	Hwa Ya	101377	IC 4088	-
CO04-HY	Conduction	Hwa Ya	101377	IC 4088	-
TH01-HY	OVEN Room	Hwa Ya	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

Please refer section 6 for Test Site Address.

### 3.7. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook	DELL	D400	DoC
Modem	ACEEX	DM-1414	DoC
Flash	-	-	DoC
Earphone	-	-	DoC

### 3.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

#### Power Parameters of Bluetooth


Test Software Version	Bluetest		
Frequency	2402 MHz	2441 MHz	2480 MHz
Power Parameters	Default	Default	Default

Power setting is refer to original Sporton project number: FR592307.




### 3.9. Test Configurations

#### 3.9.1. Radiation Emissions Test Configuration



### 3.9.2. AC Power Line Conduction Emissions Test Configuration



## 4. TEST RESULT

### 4.1. AC Power Line Conducted Emissions Measurement

#### 4.1.1. Limit

For a Low-power Radio-frequency Device which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15 ~ 0.5	66 ~ 56	56 ~ 46
0.5 ~ 5	56	46
5 ~ 30	60	50

#### 4.1.2. Measuring Instruments and Setting


Please refer to section 5 in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

#### 4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

#### 4.1.4. Test Setup Layout



1. If cables, which hang closer than 40 cm to the horizontal metal groundplane, cannot be shortened to appropriate length, the excess shall be folded back and forth forming a bundle 30 cm to 40 cm long.
2. Excess mains cord shall be bundled in the centre or shortened to appropriate length.
3. EUT is connected to one artificial mains network (AMN). All AMNs and ISNs may alternatively be connected to a vertical reference plane or metal wall.
4. All other units of a system are powered from a second AMN. A multiple outlet strip can be used for multiple mains cords.
5. AMN and ISN are 80 cm from the EUT and at least 80 cm from other units and other metal planes.
6. Mains cords and signal cables shall be positioned for their entire lengths, as far as possible, at 40 cm from the vertical reference plane.
7. Cables of hand operated devices, such as keyboards, mice, etc. shall be placed as for normal usage.
8. Peripherals shall be placed at a distance of 10 cm from each other and from the controller, except for the monitor which, if this is an acceptable installation practice, shall be placed directly on the top of the controller.
9. I/O signal cable intended for external connection.
10. The end of the I/O signal cables which are not connected to an AE may be terminated, if required, using correct terminating impedance.
11. If used, the current probe shall be placed at 0,1 m from the ISN.

#### 4.1.5. Test Deviation


There is no deviation with the original standard.

#### 4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


#### 4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	22	Humidity	40%
Test Engineer	Ted Chiu	Phase	Line
Configuration	Normal Link		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.2001960	47.38	-16.22	63.60	47.08	0.10	0.20	QP
2	0.2001960	38.68	-14.92	53.60	38.38	0.10	0.20	Average
3	0.3005850	37.05	-23.18	60.23	36.63	0.10	0.32	QP
4	0.3005850	26.13	-24.10	50.23	25.71	0.10	0.32	Average
5	0.7004460	29.27	-16.73	46.00	28.44	0.10	0.73	Average
6	0.7004460	30.56	-25.44	56.00	29.73	0.10	0.73	QP
7	0.8002340	29.94	-26.06	56.00	29.14	0.10	0.70	QP
8	0.8002340	28.84	-17.16	46.00	28.04	0.10	0.70	Average
9	1.100	30.52	-25.48	56.00	29.84	0.10	0.58	QP
10	1.100	28.76	-17.24	46.00	28.08	0.10	0.58	Average
11	2.701	37.17	-18.83	56.00	36.82	0.10	0.25	QP
12	2.701	32.78	-13.22	46.00	32.43	0.10	0.25	Average

Temperature	22	Humidity	40%
Test Engineer	Ted Chiu	Phase	Neutral
Configuration	Normal Link		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.2010370	48.98	-14.59	63.57	48.68	0.10	0.20	QP
2	0.2010370	35.66	-17.91	53.57	35.36	0.10	0.20	Average
3	0.2999830	38.13	-22.11	60.24	37.71	0.10	0.32	QP
4	0.2999830	27.38	-22.86	50.24	26.96	0.10	0.32	Average
5	0.5007460	31.54	-24.46	56.00	31.23	0.10	0.21	QP
6	0.5007460	25.67	-20.33	46.00	25.36	0.10	0.21	Average
7	0.7015820	27.22	-18.78	46.00	26.39	0.10	0.73	Average
8	0.7015820	29.12	-26.88	56.00	28.29	0.10	0.73	QP
9	2.100	27.68	-18.32	46.00	27.35	0.10	0.23	Average
10	2.100	32.61	-23.39	56.00	32.28	0.10	0.23	QP
11	2.700	35.17	-20.83	56.00	34.82	0.10	0.25	QP
12	2.700	31.05	-14.95	46.00	30.70	0.10	0.25	Average

Note:

Level = Read Level + LISN Factor + Cable Loss.

## 4.2. Radiated Emissions Measurement

### 4.2.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(KHz)	300
0.490 ~ 1.705	24000/F(KHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

### 4.2.2. Measuring Instruments and Setting

Please refer to section 5 in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (other emission)	100KHz / 100KHz for peak

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz ~ 150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz ~ 30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz ~ 1000MHz / RB 120kHz for QP




#### 4.2.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.




#### 4.2.4. Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor =  $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [9.54 dB].

#### 4.2.5. Test Deviation

There is no deviation with the original standard.

#### 4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.2.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	24	Humidity	54%
Test Engineer	Vic	Configurations	Channel 39

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.


#### 4.2.8. Results of Radiated Emissions (30MHz~1GHz)

Temperature	24	Humidity	54%
Test Engineer	Vic	Configurations	Channel 39

Horizontal




	Freq	Level	Over Limit	Read Level	Limit Line	Cable Loss	Antenna Factor	Preamplifier	Remark	Table Pos	Ant Pos
	MHz	dBuV/m	dB	dBuV	dBuV/m	dB	dB/m	dB		deg	cm
1 @	74.710	34.26	-5.74	53.18	40.00	1.45	9.66	30.03	Peak	---	---
2 @	117.550	39.23	-4.27	56.07	43.50	1.71	11.54	30.09	Peak	---	---
3 @	196.430	35.31	-8.19	47.53	43.50	2.39	15.52	30.13	Peak	---	---




	Freq	Level	Over	Read	Limit	Cable	Antenna	Preamp		Table	Ant
	MHz	dBuV/m	Limit	Level	Line	Loss	Factor	Factor	Remark	Pos	Pos
			dB	dBuV	dBuV/m	dB	dB/m	dB		deg	cm
1	237.600	38.03	-7.97	52.31	46.00	2.69	13.26	30.23	Peak	---	---
2	316.800	35.69	-10.31	48.72	46.00	3.11	14.32	30.46	Peak	---	---
3	387.200	33.09	-12.91	43.93	46.00	3.43	16.43	30.71	Peak	---	---

# Vertical



	Freq	Level	Over	Read	Limit	CableAntenna	Preamp		Table	Ant
	MHz	dBuV/m	Limit	Level	Line	Loss	Factor	Factor	Pos	Pos
			dB	dBuV	dBuV/m	dB	dB/m	dB	deg	cm
1	74.710	36.87	-3.13	55.79	40.00	1.45	9.66	30.03	Peak	---
2	117.550	38.16	-5.34	55.00	43.50	1.71	11.54	30.09	Peak	---
3	175.180	38.18	-5.32	51.79	43.50	2.27	14.20	30.08	Peak	---



	Freq	Level	Over Limit	Read Level	Limit Line	CableAntenna Loss Factor	Preamp Factor	Remark	Table Pos	Ant Pos
	MHz	dBuV/m	dB	dBuV	dBuV/m	dB	dB/m	dB	deg	cm
1	237.600	38.48	-7.52	52.76	46.00	2.69	13.26	30.23 Peak	---	---
2	516.000	35.19	-10.81	45.11	46.00	3.98	16.72	30.62 Peak	---	---
3	580.000	36.29	-9.71	43.32	46.00	4.15	19.53	30.71 Peak	---	---

#### Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).


Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Pol. : V is Vertical Polarization ; H is Horizontal Polarization.

#### 4.2.9. Results for Radiated Emissions (1GHz~10<sup>th</sup> Harmonic)


Temperature	24	Humidity	54%
Test Engineer	Vic	Configurations	Channel 0

Horizontal



	Freq	Level	Over	Read	Limit	Cable	Antenna	Preamp		Table	Ant
	MHz	dBuV/m	Limit	Level	Line	Loss	Factor	Factor	Remark	Pos	Pos
			dB	dBuV	dBuV/m	dB	dB/m	dB		deg	cm
1	1972.000	40.86	-33.14	43.53	74.00	2.67	27.35	32.70	Peak	---	---
2	4804.000	48.24	-5.76	43.62	54.00	4.06	33.10	32.54	Average	---	---
3	4804.000	56.62	-17.38	52.00	74.00	4.06	33.10	32.54	PEAK	---	---
4	7206.000	50.92	-23.08	42.19	74.00	5.19	35.90	32.35	PEAK	---	---

# Vertical




	Freq	Level	Over Limit	Read Level	Limit Line	CableAntenna Loss	Antenna Factor	Preamplifier Factor	Remark	Table Pos	Ant Pos
	MHz	dBuV/m	dB	dBuV	dBuV/m	dB	dB/m	dB		deg	cm
1	1846.000	40.28	-33.72	43.67	74.00	2.56	26.84	32.79	Peak	---	---
2	4804.000	53.31	-20.69	48.69	74.00	4.06	33.10	32.54	PEAK	---	---
3	4804.000	44.93	-9.07	40.31	54.00	4.06	33.10	32.54	Average	---	---
4	7206.000	51.52	-22.48	42.78	74.00	5.19	35.90	32.35	PEAK	---	---




Temperature	24	Humidity	54%
Test Engineer	Vic	Configurations	Channel 39

# Horizontal



	Freq	Level	Over	Read	Limit	Cable	Antenna	Preamp		Table	Ant
	MHz	dBuV/m	Limit	Level	Line	Loss	Factor	Factor	Remark	Pos	Pos
			dB	dBuV	dBuV/m	dB	dB/m	dB		deg	cm
1	1676.000	39.09	-34.91	43.51	74.00	2.39	26.11	32.91	PEAK	---	---
2 @	4884.000	47.19	-6.81	42.44	54.00	4.09	33.21	32.55	Average	---	---
3 @	4884.000	55.57	-18.43	50.82	74.00	4.09	33.21	32.55	PEAK	---	---
4 @	7323.000	42.79	-11.21	33.89	54.00	5.32	36.19	32.61	Average	---	---
5 @	7323.000	51.17	-22.83	42.27	74.00	5.32	36.19	32.61	PEAK	---	---


# Vertical



	Freq	Level	Over	Read	Limit	CableAntenna	Preamp		Table	Ant
	MHz	dBuV/m	Limit	Level	Line	Loss	Factor	Factor	Pos	Pos
	MHz	dBuV/m	dB	dBuV	dBuV/m	dB	dB/m	dB	deg	cm
1	1628.000	39.44	-34.56	44.15	74.00	2.35	25.89	32.95	PEAK	---
2 @	4884.000	51.62	-22.38	46.88	74.00	4.09	33.21	32.55	PEAK	---
3 @	4884.000	43.24	-10.76	38.49	54.00	4.09	33.21	32.55	Average	---
4 @	7323.000	50.29	-23.71	41.40	74.00	5.32	36.19	32.61	PEAK	---


Temperature	24	Humidity	54%
Test Engineer	Vic	Configurations	Channel 78

# Horizontal



	Freq	Level	Over	Read	Limit	CableAntenna	Preamp		Table	Ant
	MHz	dBuV/m	Limit	Level	Line	Loss	Factor	Factor	Pos	Pos
			dB	dBuV	dBuV/m	dB	dB/m	dB	deg	cm
1	1774.000	39.36	-34.64	43.17	74.00	2.49	26.55	32.85	Peak	---
2	4960.000	45.32	-8.68	40.41	54.00	4.12	33.34	32.56	Average	---
3	4960.000	53.70	-20.30	48.80	74.00	4.12	33.34	32.56	PEAK	---
4	7440.000	50.52	-23.48	41.46	74.00	5.45	36.48	32.87	PEAK	---

# Vertical



	Freq	Level	Over	Read	Limit	Cable	Antenna	Preamp		Table	Ant
	MHz	dBuV/m	Limit	Level	Line	Loss	Factor	Factor	Remark	Pos	Pos
	MHz	dBuV/m	dB	dBuV	dBuV/m	dB	dB/m	dB		deg	cm
1	1678.000	39.33	-34.67	43.75	74.00	2.39	26.11	32.91	Peak	---	---
2	4964.000	49.78	-24.22	44.87	74.00	4.12	33.34	32.56	PEAK	---	---
3	7440.000	49.70	-24.30	40.64	74.00	5.45	36.48	32.87	PEAK	---	---

## Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Pol. : V is Vertical Polarization ; H is Horizontal Polarization.

### 4.3. Band Edge Emissions Measurement

#### 4.3.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(KHz)	300
0.490 ~ 1.705	24000/F(KHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

#### 4.3.2. Measuring Instruments and Setting

Please refer to section 5 in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (other emission)	100 KHz / 100 KHz for Peak

#### 4.3.3. Test Procedures

1. The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around bandedges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

#### 4.3.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.6.4.

#### 4.3.5. Test Deviation

There is no deviation with the original standard.

#### 4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.3.7. Test Result of Band Edge and Fundamental Emissions

Temperature	24	Humidity	54%
Test Engineer	Vic	Configurations	Channel 0, 78

##### Channel 0

	Freq	Level	Over Limit	Read Level	Limit Line	Cable Loss	Antenna Factor	Preamplifier Factor	Remark	Table Pos	Ant Pos
	MHz	dBuV/m	dB	dBuV	dBuV/m	dB	dB/m	dB		deg	cm
1 0	2390.000	55.06	-18.94	24.32	74.00	2.53	28.21	0.00	Peak	---	---
2 0	2401.770	95.06	21.06	64.32	74.00	2.53	28.21	0.00	Peak	---	---
1 0	2390.000	46.68	-7.32	15.94	54.00	2.53	28.21	0.00	Average	---	---
2 0	2401.770	86.68	32.68	55.94	54.00	2.53	28.21	0.00	Average	---	---

Channel 1 is fundamental frequency at 2402 MHz.

##### Channel 78

	Freq	Level	Over Limit	Read Level	Limit Line	Cable Loss	Antenna Factor	Preamplifier Factor	Remark	Table Pos	Ant Pos
	MHz	dBuV/m	dB	dBuV	dBuV/m	dB	dB/m	dB		deg	cm
1 0	2479.860	95.34	21.34	64.48	74.00	2.49	28.37	0.00	Peak	---	---
2 0	2483.500	58.07	-15.93	27.21	74.00	2.49	28.37	0.00	Peak	---	---
1 0	2479.860	86.96	32.96	56.10	54.00	2.49	28.37	0.00	Average	---	---
2 0	2483.500	49.69	-4.31	18.83	54.00	2.49	28.37	0.00	Average	---	---

Channel 2 is fundamental frequency at 2480 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Receiving maximum band edge emissions are Vertical Polarization /Horizontal Polarization.

## 4.4. Antenna Requirements

### 4.4.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

### 4.4.2. Antenna Connector Construction

Please refer to section 3.3 in this test report, all antenna connectors comply with the requirements.

## 5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9kHz – 2.75GHz	Oct. 19, 2005	Conduction (CO04-HY)
LISN	MessTec	NNB-2/16Z	2001/009	9kHz – 30MHz	Apr. 26, 2005	Conduction (CO04-HY)
LISN (Support Unit)	EMCO	3810/2NM	9708-1839	9kHz – 30MHz	Mar. 14, 2005	Conduction (CO04-HY)
RF Cable-CON	UTIFLEX	3102-26886-4	CB049	9kHz – 30MHz	Apr. 20, 2005	Conduction (CO04-HY)
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	N/A	Conduction (CO04-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30 MHz - 1 GHz 3m	Jun. 16, 2005	Radiation (03CH03-HY)
Amplifier	SCHAFFNER	CPA9231A	3565	9 kHz - 2 GHz	Jan. 18, 2006	Radiation (03CH03-HY)
Amplifier	Agilent	8449B	3008A02120	1 GHz - 26.5 GHz	May 31, 2005	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP40	100004/040	9 kHz - 40 GHz	Sep. 30, 2005	Radiation (03CH03-HY)
Biconical Antenna	SCHWARZBECK	VHBB 9124	301	30 MHz - 200 MHz	Jul. 22, 2005	Radiation (03CH03-HY)
Log Antenna	SCHWARZBECK	VUSLP 9111	221	200 MHz - 1 GHz	Jul. 22, 2005	Radiation (03CH03-HY)
Horn Antenna	EMCO	3115	6741	1 GHz - 18 GHz	Apr. 22, 2005	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30 MHz - 1 GHz	Feb. 22, 2005	Radiation (03CH03-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1 GHz - 40 GHz	Dec.01, 2005	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 - 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Amplifier	MITEQ	AMF-6F-260400	923364	26.5 GHz - 40 GHz	Jan. 24, 2006*	Radiation (03CH03-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	May 24, 2004*	Radiation (03CH03-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15 GHz - 40 GHz	Jun. 09, 2004*	Radiation (03CH03-HY)
Data Generator	Tektronix	DG2030	063-2920-50	0.1Hz~400MHz	Jun. 02, 2005	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is two year.



## 6. SPORTON COMPANY PROFILE

SPORTON Lab. was established in 1986 with one shielded room: the first private EMI test facility, offering local manufacturers an alternative EMI test facility apart from ERSO. In 1988, one 3M and 10M/3M open area test site were setup and also obtained official accreditation from FCC, VCCI and NEMKO. In 1993, a Safety laboratory was founded and obtained accreditation from UL of USA, CSA of Canada and TUV (Rhineland & PS) of Germany. In 1995, one EMC lab, including EMI and EMS test facilities was setup. In 1997, SPORTON Group has provided financial expense to relocate the headquarter to Orient Scientific Park in Taipei Hsien to offer more comprehensive, more qualified and better service to local suppliers and manufactures. In 1999, Safety Group and Component Group were setup. In 2001, SPORTON has established 3M/10M chamber in Hwa Ya Technology Park.

### 6.1. Test Location

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 02-2696-2468 FAX : 02-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 03-327-3456 FAX : 03-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 02-2601-1640 FAX : 02-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihsu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 02-2631-4739 FAX : 02-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 02-8227-2020 FAX : 02-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 <sup>nd</sup> Rd., Taipei 114, Taiwan, R.O.C. TEL : 02-2794-8886 FAX : 02-2794-9777
JHUBEI	ADD : No.8, Lane 728, Bo-ai St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C. TEL : 03-656-9065 FAX : 03-656-9085

## 7. NVLAP CERTIFICATE OF ACCREDITATION

United States Department of Commerce  
National Institute of Standards and Technology



### Certificate of Accreditation to ISO/IEC 17025:1999

NVLAP LAB CODE: 200079-0

**Sporton International, Inc. Hwa Ya EMC Laboratory**

Tao Yuan Hsien 333

TAIWAN


*is recognized by the National Voluntary Laboratory Accreditation Program for conformance with criteria set forth in  
NIST Handbook 150:2001 and all requirements of ISO/IEC 17025:1999.*

*Accreditation is granted for specific services, listed on the Scope of Accreditation, for:*

**ELECTROMAGNETIC COMPATIBILITY AND TELECOMMUNICATIONS**

2006-01-01 through 2006-12-31

*Effective dates*



*For the National Institute of Standards and Technology*