

MPE TEST REPORT

Applicant	Smawave Technology Co. , Ltd
FCC ID	2AU8HSRL620
Product	5G ODU_NA
Brand	Smawave
Model	SRL620
Report No.	R2408A1140-M1
Issue Date	November 21, 2024

Eurofins TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC 47 CFR Part 1 1.1310**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Prepared by: Wei Fangying

Approved by: Xu Kai

Eurofins TA Technology (Shanghai) Co., Ltd.

Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

Table of Contents

1	Test Laboratory	3
1.1	Notes of the Test Report.....	3
1.2	Test Facility	3
1.3	Testing Location.....	3
1.4	Laboratory Environment	3
2	Description of Equipment Under Test	4
3	Maximum Tune up and Antenna Gain	6
4	MPE Limit.....	7
5	RF Exposure Evaluation Result.....	9
	ANNEX A: The EUT Appearance	11

1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **Eurofins TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2 Test Facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

1.3 Testing Location

Company: Eurofins TA Technology (Shanghai) Co., Ltd.
Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <https://www.eurofins.com/electrical-and-electronics>
E-mail: Kain.Xu@cpt.eurofinscn.com

1.4 Laboratory Environment

Temperature	Min. = 18°C, Max. = 25°C
Relative humidity	Min. = 20%, Max. = 80%
Ground system resistance	< 0.5 Ω
Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

2 Description of Equipment Under Test

Client Information

Applicant	Smawave Technology Co., Ltd
Applicant address	2/F, Building 8, 1001 North Qinzhou Road, Xuhui District, Shanghai, China
Manufacturer	Smawave Technology Co., Ltd
Manufacturer address	2/F, Building 8, 1001 North Qinzhou Road, Xuhui District, Shanghai, China

General Technologies

EUT Description			
Model	SRL620		
Lab internal SN	R2408A1140/S01		
Hardware Version	V1.0		
Software Version	SQA2090_V1.1.4-NA		
Frequency	Band	TX (MHz)	RX (MHz)
	LTE Band 2	1850 ~ 1910	1930 ~ 1990
	LTE Band 4	1710 ~ 1755	2110 ~ 2155
	LTE Band 5	824 ~ 849	869 ~ 894
	LTE Band 7	2500 ~ 2570	2620 ~ 2690
	LTE Band 12	699 ~ 716	729 ~ 746
	LTE Band 13	777 ~ 787	746 ~ 756
	LTE Band 14	788 ~ 798	758 ~ 768
	LTE Band 17	704 ~ 716	734 ~ 746
	LTE Band 25	1850 ~ 1915	1930 ~ 1995
	LTE Band 26	824 ~ 849	869 ~ 894
	LTE Band 30	2305 ~ 2315	2350 ~ 2360
	LTE Band 38	2570 ~ 2620	2570 ~ 2620
	LTE Band 41	2496 ~ 2690	2496 ~ 2690
	LTE Band 48	3550 ~ 3700	3550 ~ 3700
	LTE Band 66	1710 ~ 1780	2110 ~ 2180
	LTE Band 71	663 ~ 698	617 ~ 652
	NR Band n2	1850 ~ 1910	1930 ~ 1990
	NR Band n5	824 ~ 849	869 ~ 894

	NR Band n7	2500 ~ 2570	2620 ~ 2690
	NR Band n12	699 ~ 716	729 ~ 746
	NR Band n13	777 ~ 787	746 ~ 756
	NR Band n14	788 ~ 798	758 ~ 768
	NR Band n25	1850 ~ 1915	1930 ~ 1995
	NR Band n26	824 ~ 849	869 ~ 894
	NR Band n30	2305 ~ 2315	2350 ~ 2360
	NR Band n38	2570 ~ 2620	2570 ~ 2620
	NR Band n41	2496 ~ 2690	2496 ~ 2690
	NR Band n48	3550 ~ 3700	3550 ~ 3700
	NR Band n66	1710 ~ 1780	2110 ~ 2180
	NR Band n71	663 ~ 698	617 ~ 652
	NR Band n77	3300 ~ 4200	3300 ~ 4200
	NR Band n78	3450 ~ 3800	3450 ~ 3800
Date of Sample Received	August 19, 2024		
Note: 1. The EUT is sent from the applicant to Eurofins TA and the information of the EUT is declared by the applicant. 2. All indications of Pass/Fail in this report are opinions expressed by Eurofins TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.			

3 Maximum Tune up and Antenna Gain

The numeric gain (G) of the antenna with a gain specified in dB is determined by

$$\text{Numeric gain (G)} = 10^{(\text{antenna gain}/10)}$$

Band	Maximum Tune up Power		Antenna Gain (dBi)	Numeric Gain
	(dBm)	(mW)		
LTE Band 2	25.00	316.228	5.5	3.548
LTE Band 4	25.00	316.228	5.0	3.162
LTE Band 5	25.00	316.228	3.0	1.995
LTE Band 7	25.00	316.228	5.0	3.162
LTE Band 12	25.00	316.228	2.5	1.778
LTE Band 13	25.00	316.228	2.5	1.778
LTE Band 14	25.00	316.228	3.0	1.995
LTE Band 17	25.00	316.228	2.0	1.585
LTE Band 25	25.00	316.228	5.5	3.548
LTE Band 26	25.00	316.228	3.0	1.995
LTE Band 30	25.00	316.228	6.0	3.981
LTE Band 38	28.00	630.957	5.0	3.162
LTE Band 41	28.00	630.957	5.0	3.162
LTE Band 48	22.00	158.489	13.0	19.953
LTE Band 66	25.00	316.228	5.0	3.162
LTE Band 71	25.00	316.228	2.0	1.585
NR Band n2	25.00	316.228	5.5	3.548
NR Band n5	25.00	316.228	3.0	1.995
NR Band n7	25.00	316.228	5.0	3.162
NR Band n12	25.00	316.228	2.5	1.778
NR Band n13	25.00	316.228	2.5	1.778
NR Band n14	25.00	316.228	3.0	1.995
NR Band n25	25.00	316.228	5.5	3.548
NR Band n26	25.00	316.228	3.0	1.995
NR Band n30	25.00	316.228	6.0	3.981
NR Band n38	28.00	630.957	5.0	3.162
NR Band n41	31.00	1258.925	5.0	3.162
NR Band n48	22.00	158.489	13.0	19.953
NR Band n66	25.00	316.228	5.0	3.162
NR Band n71	25.00	316.228	2.0	1.585
NR Band n77	31.00	1258.925	13.0	19.953
NR Band n78	31.00	1258.925	13.0	19.953

4 MPE Limit

According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure (MPE) are as following.

TABLE 1 – LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Note1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.

Note2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

The maximum permissible exposure for 300~1500 MHz is $f/1500$, for 1500~100,000MHz is 1.0. So

Band	The Maximum Permissible Exposure (mW/cm ²)
LTE Band 2	1.000
LTE Band 4	1.000
LTE Band 5	0.549
LTE Band 7	1.000
LTE Band 12	0.466
LTE Band 13	0.518
LTE Band 14	0.525
LTE Band 17	0.469
LTE Band 25	1.000
LTE Band 26	0.549
LTE Band 30	1.000
LTE Band 38	1.000
LTE Band 41	1.000
LTE Band 48	1.000
LTE Band 66	1.000
LTE Band 71	0.442
NR Band n2	1.000
NR Band n5	0.549
NR Band n7	1.000
NR Band n12	0.466
NR Band n13	0.518
NR Band n14	0.525
NR Band n25	1.000
NR Band n26	0.549
NR Band n30	1.000
NR Band n38	1.000
NR Band n41	1.000
NR Band n48	1.000
NR Band n66	1.000
NR Band n71	0.442
NR Band n77	1.000
NR Band n78	1.000

5 RF Exposure Evaluation Result

RF exposure evaluation method is based on KDB 447498 D01, this calculation is based on the conducted power, maximum power and antenna gain with provides the minimum separation distance. The formula shown below is from OET Bulletin 65 Edition 97-01 Per KDB 447498 D01:

$$S = PG / 4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = Time-average maximum tune up procedure (in appropriate units, e.g., mW)

G = the numeric gain of the antenna

R = distance to the center of radiation of the antenna (20 cm = limit for MPE)

Band	Maximum Tune up (dBm)	Antenna Gain (dBi)	Maximum EIRP (dBm)	PG (mW)	4□* Limit Value	Min. Distance (cm)	Safety Distance (cm)	Result (mW/cm ²)	Limit Value (mW/cm ²)
LTE Band 2	25.00	5.5	30.500	1122.018	12.566	9.449	44.709	0.044	1.000
LTE Band 4	25.00	5.0	30.000	1000.000	12.566	8.921		0.040	1.000
LTE Band 5	25.00	3.0	28.000	630.957	6.899	9.563		0.025	0.549
LTE Band 7	25.00	5.0	30.000	1000.000	12.566	8.921		0.040	1.000
LTE Band 12	25.00	2.5	27.500	562.341	5.856	9.799		0.022	0.466
LTE Band 13	25.00	2.5	27.500	562.341	6.509	9.295		0.022	0.518
LTE Band 14	25.00	3.0	28.000	630.957	6.597	9.779		0.025	0.525
LTE Band 17	25.00	2.0	27.000	501.187	5.894	9.222		0.020	0.469
LTE Band 25	25.00	5.5	30.500	1122.018	12.566	8.921		0.040	1.000
LTE Band 26	25.00	3.0	28.000	630.957	6.899	9.563		0.025	0.549
LTE Band 30	25.00	6.0	31.000	1258.925	12.566	10.009		0.050	1.000
LTE Band 38	28.00	5.0	33.000	1995.262	12.566	12.601		0.079	1.000
LTE Band 41	28.00	5.0	33.000	1995.262	12.566	12.601		0.079	1.000
LTE Band 48	22.00	13.0	35.000	3162.278	12.566	15.863		0.125	1.000
LTE Band 66	25.00	5.0	30.000	1000.000	12.566	8.921		0.040	1.000
LTE Band 71	25.00	2.0	27.000	501.187	5.554	9.499		0.020	0.442
NR Band n2	25.00	5.5	30.500	1122.018	12.566	9.449		0.044	1.000
NR Band n5	25.00	3.0	28.000	630.957	6.899	9.563		0.025	0.549
NR Band n7	25.00	5.0	30.000	1000.000	12.566	8.921		0.040	1.000
NR Band n12	25.00	2.5	27.500	562.341	5.856	9.799		0.022	0.466
NR Band n13	25.00	2.5	27.500	562.341	6.509	9.295		0.022	0.518
NR Band n14	25.00	3.0	28.000	630.957	6.597	9.779		0.025	0.525

NR Band n25	25.00	5.5	30.500	1122.018	12.566	8.921		0.040	1.000
NR Band n26	25.00	3.0	28.000	630.957	6.899	9.563		0.025	0.549
NR Band n30	25.00	6.0	31.000	1258.925	12.566	10.009		0.050	1.000
NR Band n38	28.00	5.0	33.000	1995.262	12.566	12.601		0.079	1.000
NR Band n41	31.00	5.0	36.000	3981.072	12.566	17.799		0.158	1.000
NR Band n48	22.00	13.0	35.000	3162.278	12.566	15.863		0.125	1.000
NR Band n66	25.00	5.0	30.000	1000.000	12.566	8.921		0.040	1.000
NR Band n71	25.00	2.0	27.000	501.187	5.554	9.499		0.020	0.442
NR Band n77	31.00	13.0	44.000	25118.864	12.566	44.709		0.996	1.000
NR Band n78	31.00	13.0	44.000	25118.864	12.566	44.709		0.996	1.000

Note: $\pi = 3.1416$

Safety Distance = Max. (Min. Distance)

R= Safety Distance

Note: For transmitters, minimum separation distance is 44.709cm, even if calculations indicate MPE distance is less.

IMPORTANT NOTE: To comply with the FCC RF exposure compliance requirements, the antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter. No change to the antenna or the device is permitted. Any change to the antenna or the device could result in the device exceeding the RF exposure requirements and void user's authority to operate the device.

ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.

*****END OF REPORT *****