

1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 General Information

Client Information

Applicant:	SUNVALLEYTEK INTERNATIONAL, INC.
Address of applicant:	46724 Lakeview Blvd, Fremont, CA 94538-6529
Manufacturer:	Shenzhen NearbyExpress Technology Development Company Limited
Address of manufacturer:	333 Bulong Road, Jialianda Industrial Park, Building 1, Bantian, Longgang District, Shenzhen, China, 518129

General Description of EUT:

Product Name:	LED FLOOR LAMP
Trade Name:	/
Model No.:	TT-DL035
FCC ID:	2AFDGTT-DL035
Rated Voltage:	Adapter: DC 24.0V

Technical Characteristics of EUT:

Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz for 802.11b/g/n(HT20) 2422-2452MHz for 80.211n(HT40)
RF Output Power:	17.04dBm (Conducted)
Type of Modulation:	CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM
Data Rate:	1-11Mbps, 6-54Mbps, up to 150Mbps
Quantity of Channels:	11/7
Channel Separation:	5MHz
Type of Antenna:	Integral
Antenna Gain:	2dBi
Lowest Internal Frequency:	40MHz

1.2 Standard Applicable

According to § 1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz: * = Plane-wave equivalents power density

1.3 MPE Calculation Method

$$S = (30 \cdot P \cdot G) / (377 \cdot R^2)$$

S = power density (in appropriate units, e.g., mw/cm²)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

1.4 MPE Calculation Result

Maximum Tune-Up output power: 18.0 (dBm)

Maximum peak output power at antenna input terminal: 63.10 (mW)

Prediction distance: >20(cm)

Prediction frequency: 2437 (MHz)

Antenna gain: 2 (dBi)

Directional gain (numeric gain): 1.58

The worst case is power density at prediction frequency at 20cm: 0.02(mw/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm²)

Result: Pass

1.5 Test Setup Photos

