Report No.: R2411A1739-R1

802.11ax(20) 242TONE_CH1

RF Test Report



Frequency	MaxPeak	Average	Limit	Margin	Meas.	Height	Pol	Azimuth	Corr.
(MHz)	(dB£gV/m)	(dB£gV/m)	(dB£gV/m)	(dB)	Time	(cm)		(deg)	(dB/m)
					(ms)				
1176.250000	40.82		74.00	33.18	500.0	200.0	V	68.0	-9.3
1185.500000		29.77	54.00	24.23	500.0	200.0	Η	311.0	-9.1
1421.750000	42.80		74.00	31.20	500.0	200.0	V	318.0	-7.4
1429.250000		30.71	54.00	23.29	500.0	200.0	V	291.0	-7.4
1550.000000	43.84		74.00	30.16	500.0	200.0	V	0.0	-6.7
1682.000000		32.09	54.00	21.91	500.0	200.0	Н	350.0	-6.0
1807.250000	44.20		74.00	29.80	500.0	200.0	V	349.0	-5.4
1839.250000		32.23	54.00	21.77	500.0	200.0	V	291.0	-5.2
2019.750000	45.23		74.00	28.77	500.0	200.0	Η	306.0	-4.4
2078.250000		33.69	54.00	20.31	500.0	200.0	V	0.0	-3.9
2826.750000	49.04		74.00	24.96	500.0	200.0	H	27.0	-1.1
2906.750000		36.91	54.00	17.09	500.0	200.0	V	349.0	-1.0



Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
	· · ·	· · · /	· · · ·	• •	(ms)				• •
3686.250000	41.40		74.00	32.60	500.0	200.0	Н	20.0	-5.5
3870.000000		30.53	54.00	23.47	500.0	200.0	Η	27.0	-4.8
5356.875000	45.50		74.00	28.50	500.0	200.0	V	34.0	-0.5
5443.125000		34.49	54.00	19.51	500.0	200.0	V	42.0	-0.2
6382.500000	47.83		74.00	26.17	500.0	200.0	V	18.0	1.1
6836.250000		37.10	54.00	16.90	500.0	200.0	Н	27.0	1.5
7378.125000	47.86		74.00	26.14	500.0	200.0	Н	45.0	2.2
7389.375000		37.13	54.00	16.87	500.0	200.0	V	0.0	2.3
12639.375000		39.68	54.00	14.32	500.0	200.0	Η	45.0	5.4
12691.875000	50.57		74.00	23.43	500.0	200.0	V	0.0	5.5
17413.125000		42.66	54.00	11.34	500.0	200.0	V	0.0	10.1
17632.500000	55.45		74.00	18.55	500.0	200.0	Н	20.0	10.1

802.11ax(40) 484TONE_CH3



Frequency	MaxPeak	Average	Limit	Margin	Meas.	Height	Pol	Azimuth	Corr.
(MHz)	(dBµV/m)	(dBµV/m)	(dBµV/m)	(dB)	Time	(cm)		(deg)	(dB)
					(ms)				
3849.375000	41.39		74.00	32.61	500.0	200.0	Н	20.0	-4.8
3885.000000		30.55	54.00	23.45	500.0	200.0	Н	20.0	-4.8
5281.875000		34.52	54.00	19.48	500.0	200.0	V	10.0	-0.6
5415.000000	45.20		74.00	28.80	500.0	200.0	V	0.0	-0.2
5913.750000	48.14		74.00	25.86	500.0	200.0	Н	45.0	0.0
6716.250000		36.94	54.00	17.06	500.0	200.0	Н	35.0	1.3
7395.000000		37.15	54.00	16.85	500.0	200.0	V	26.0	2.3
9746.250000	48.49		74.00	25.51	500.0	200.0	V	34.0	3.0
12688.125000	50.01		74.00	23.99	500.0	200.0	V	18.0	5.5
12690.000000		39.63	54.00	14.37	500.0	200.0	V	42.0	5.5
16726.875000		42.15	54.00	11.85	500.0	200.0	V	45.0	7.9
17988.750000	55.28		74.00	18.72	500.0	200.0	V	2.0	10.7

🔅 eurofins

RF Test Report



Frequency	MaxPeak	Average	Limit	Margin	Meas.	Height	Pol	Azimuth	Corr.
(MHz)	(dB£gV/m)	(dB£gV/m)	(dB£gV/m)	(dB)	Time	(cm)		(deg)	(dB/m)
					(ms)				
1177.250000	41.21		74.00	32.79	500.0	200.0	V	274.0	-9.3
1190.000000		29.75	54.00	24.25	500.0	200.0	Н	336.0	-9.0
1308.000000	42.29		74.00	31.71	500.0	200.0	V	322.0	-8.1
1402.750000		31.08	54.00	22.92	500.0	200.0	V	242.0	-7.6
1683.500000		32.26	54.00	21.74	500.0	200.0	V	221.0	-6.0
1724.500000	43.99		74.00	30.01	500.0	200.0	Н	111.0	-5.9
2062.750000		33.77	54.00	20.23	500.0	200.0	V	269.0	-4.1
2066.000000	45.11		74.00	28.89	500.0	200.0	Η	80.0	-4.1
2304.500000		34.77	54.00	19.23	500.0	200.0	V	260.0	-2.8
2349.000000	46.55		74.00	27.45	500.0	200.0	Н	234.0	-3.0
2894.000000		37.34	54.00	16.66	500.0	200.0	V	318.0	-1.1
2986.750000	49.19		74.00	24.81	500.0	200.0	V	242.0	-0.7

RF Test Report

Report No.: R2411A1739-R1

During the test, the Radiates Emission from 18GHz to 26.5GHz was performed in all modes with all channels. The test data of the worst-case condition was recorded in this report.



Frequency	MaxPeak	Average	Limit	Margin	Meas.	Height	Pol	Azimuth	Corr.
(MHz)	(dB£gV/m)	(dB£gV/m)	(dB£gV/m)	(dB)	Time	(cm)		(deg)	(dB/m)
					(ms)				
18160.437500		35.51	54.00	18.49	500.0	100.0	Η	105.0	-5.8
18318.750000	47.20		74.00	26.80	500.0	200.0	۷	150.0	-5.8
20398.062500		35.69	54.00	18.31	500.0	100.0	V	143.0	-5.2
20448.000000	46.95		74.00	27.05	500.0	100.0	V	259.0	-4.9
20752.937500	48.34		74.00	25.66	500.0	100.0	۷	236.0	-4.6
21138.625000		36.49	54.00	17.51	500.0	100.0	V	259.0	-4.2
22030.062500	48.78		74.00	25.22	500.0	100.0	Η	0.0	-3.8
22532.625000		37.29	54.00	16.71	500.0	200.0	V	223.0	-3.4
24752.187500	48.29		74.00	25.71	500.0	200.0	٧	63.0	-2.7
24760.687500		36.66	54.00	17.34	500.0	100.0	V	347.0	-2.7
25728.625000	48.13		74.00	25.87	500.0	200.0	Η	319.0	-2.4
26382.062500		36.86	54.00	17.14	500.0	100.0	V	101.0	-2.2

RF Test Report

Bluetooth LE

During the test, the Radiates Emission from 9kHz to 1GHz was performed in all modes with all channels. The test data of the worst-case condition was recorded in this report.







Radiates Emission from 30MHz to 1GHz

Frequency (MHz)	Quasi-Peak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)
33.510000	13.94	40.00	26.06	100.0	V	36.0	17.8
53.043750	16.88	40.00	23.12	185.0	Н	190.0	20.9
81.697500	11.23	40.00	28.77	125.0	V	359.0	15.6
121.103750	12.48	43.50	31.02	209.0	Н	242.0	16.9
173.918750	16.71	43.50	26.79	125.0	Н	208.0	20.0
261.993750	16.16	46.00	29.84	100.0	V	9.0	20.1

Remark: 1. Correction Factor = Antenna factor + Insertion loss (cable loss + amplifier gain) 2. Margin = Limit – Quasi-Peak



Bluetooth LE-Channel 0



Frequency	MaxPeak	Average	Limit	Margin	Meas.	Height	Pol	Azimuth	Corr.
(MHz)	(dB£gV/m)	(dB£gV/m)	(dB£gV/m)	(dB)	Time	(cm)		(deg)	(dB/m)
					(ms)				
1041.250000		28.18	54.00	25.82	500.0	200.0	Н	303.0	-10.5
1056.000000	39.85		74.00	34.15	500.0	200.0	V	21.0	-10.4
1189.000000	40.49		74.00	33.51	500.0	200.0	V	69.0	-9.0
1193.750000		29.34	54.00	24.66	500.0	200.0	Н	256.0	-8.9
1416.000000		30.55	54.00	23.45	500.0	200.0	Н	286.0	-7.4
1429.000000	42.49		74.00	31.51	500.0	200.0	V	291.0	-7.4
1656.500000		31.72	54.00	22.28	500.0	200.0	V	121.0	-6.1
1711.500000	43.75		74.00	30.25	500.0	200.0	V	77.0	-5.9
2056.750000	44.92		74.00	29.08	500.0	200.0	V	9.0	-4.2
2067.250000		33.24	54.00	20.76	500.0	200.0	V	0.0	-4.1
2874.250000	47.96		74.00	26.04	500.0	200.0	Н	278.0	-1.1
2908.250000		36.29	54.00	17.71	500.0	200.0	V	95.0	-1.0





Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
					(ms)				
3489.375000	43.05		74.00	30.95	500.0	200.0	Н	45.0	-5.9
3489.375000		33.38	54.00	20.62	500.0	200.0	Н	45.0	-5.9
5197.500000	45.53		74.00	28.47	500.0	200.0	V	26.0	-0.8
5388.750000		34.56	54.00	19.44	500.0	200.0	V	34.0	-0.3
6772.500000		37.43	54.00	16.57	500.0	200.0	Η	18.0	1.4
6832.500000	48.81		74.00	25.19	500.0	200.0	Н	18.0	1.5
7374.375000		37.41	54.00	16.59	500.0	200.0	Н	0.0	2.2
7391.250000	48.73		74.00	25.27	500.0	200.0	V	34.0	2.3
12675.000000	50.79		74.00	23.21	500.0	200.0	V	45.0	5.5
12675.000000		40.24	54.00	13.76	500.0	200.0	Н	26.0	5.5
17748.750000		44.74	54.00	9.26	500.0	200.0	V	26.0	10.2
17780.625000	55.56		74.00	18.44	500.0	200.0	Н	18.0	10.3



Bluetooth LE-Channel 19



Frequency	MaxPeak	Average	Limit	Margin	Meas.	Height	Pol	Azimuth	Corr.
(MHz)	(dB£gV/m)	(dB£gV/m)	(dB£gV/m)	(dB)	Time	(cm)		(deg)	(dB/m)
					(ms)				
1048.500000		28.04	54.00	25.96	500.0	200.0	Η	0.0	-10.5
1112.000000	41.10		74.00	32.90	500.0	200.0	Η	0.0	-10.0
1196.750000		29.44	54.00	24.56	500.0	200.0	Н	220.0	-8.9
1281.000000	40.67		74.00	33.33	500.0	200.0	Н	0.0	-8.3
1427.250000		30.71	54.00	23.29	500.0	200.0	Η	352.0	-7.4
1436.500000	42.36		74.00	31.64	500.0	200.0	V	167.0	-7.3
1668.000000	43.76		74.00	30.24	500.0	200.0	Н	122.0	-6.1
1702.500000		32.05	54.00	21.95	500.0	200.0	Η	317.0	-6.0
2063.250000	45.36		74.00	28.64	500.0	200.0	Н	253.0	-4.1
2064.000000		33.59	54.00	20.41	500.0	200.0	Η	313.0	4.1
2920.750000	48.43		74.00	25.57	500.0	200.0	Η	211.0	-1.0
2971.000000		36.91	54.00	17.09	500.0	200.0	Η	140.0	-0.7



Frequency (MHz)	MaxPeak (dBuV/m)	Average	Limit (dBuV/m)	Margin (dB)	Meas.	Height	Pol	Azimuth	Corr.
(11112)	(uoµv/m)	(uoµv/iii)	(uoµv/iii)	(ub)	(ms)	(ciii)		(ueg)	(ub)
3611.250000	42.18		74.00	31.82	500.0	200.0	V	27.0	-5.7
3873.750000		30.88	54.00	23.12	500.0	200.0	V	45.0	-4.8
5338.125000	45.06		74.00	28.94	500.0	200.0	Η	3.0	-0.5
5443.125000		34.54	54.00	19.46	500.0	200.0	Η	11.0	-0.2
6688.125000	48.61		74.00	25.39	500.0	200.0	V	45.0	1.3
6840.000000		37.32	54.00	16.68	500.0	200.0	Н	3.0	1.4
7380.000000		37.68	54.00	16.32	500.0	200.0	V	42.0	2.2
9817.500000	48.57		74.00	25.43	500.0	200.0	Н	3.0	3.0
12626.250000	50.31		74.00	23.69	500.0	200.0	Η	0.0	5.3
12673.125000		39.72	54.00	14.28	500.0	200.0	V	45.0	5.5
17745.000000	55.68		74.00	18.32	500.0	200.0	Н	3.0	10.2
17773.125000		44.48	54.00	9.52	500.0	200.0	Н	19.0	10.2

RF Test Report

Bluetooth LE-Channel 39



Frequency	MaxPeak	Average	Limit	Margin	Meas.	Height	Pol	Azimuth	Corr.
(MHz)	(dB£gV/m)	(dB£gV/m)	(dB£gV/m)	(dB)	Time	(cm)		(deg)	(dB/m)
					(ms)				
1076.500000	40.91		74.00	33.09	500.0	200.0	Н	321.0	-10.3
1200.250000		29.57	54.00	24.43	500.0	200.0	Н	184.0	-8.8
1367.500000	41.87		74.00	32.13	500.0	200.0	V	230.0	-7.7
1427.250000		30.62	54.00	23.38	500.0	200.0	Н	142.0	-7.4
1546.250000	41.57		74.00	32.43	500.0	200.0	Н	308.0	-6.7
1657.000000		32.00	54.00	22.00	500.0	200.0	Н	330.0	-6.1
1726.500000	44.01		74.00	29.99	500.0	200.0	Н	330.0	-5.8
1852.250000		31.95	54.00	22.05	500.0	200.0	Н	308.0	-5.2
2072.750000		33.72	54.00	20.28	500.0	200.0	Н	67.0	-4.0
2073.750000	45.39		74.00	28.61	500.0	200.0	Н	207.0	-4.0
2989.250000		36.98	54.00	17.02	500.0	200.0	Η	266.0	-0.6
2998.250000	48.22		74.00	25.78	500.0	200.0	Н	321.0	-0.6

Report No.: R2411A1739-R1



Frequency	MaxPeak	Average	Limit	Margin	Meas.	Height	Pol	Azimuth	Corr.
(MHz)	(dBµV/m)	(dBµV/m)	(dBµV/m)	(dB)	lime (ma)	(cm)		(deg)	(dB)
					(ms)				
3493.125000	41.22		74.00	32.78	500.0	200.0	V	42.0	-5.9
3862.500000		30.94	54.00	23.06	500.0	200.0	Н	45.0	-4.8
5390.625000	46.23		74.00	27.77	500.0	200.0	Η	34.0	-0.3
5401.875000		34.53	54.00	19.47	500.0	200.0	V	3.0	-0.2
6673.125000	48.54		74.00	25.46	500.0	200.0	Η	18.0	1.3
6862.500000		37.08	54.00	16.92	500.0	200.0	Н	26.0	1.4
7421.250000		37.59	54.00	16.41	500.0	200.0	Η	0.0	2.3
7749.375000	48.87		74.00	25.13	500.0	200.0	Η	26.0	2.3
12663.750000		39.96	54.00	14.04	500.0	200.0	Н	26.0	5.4
12678.750000	52.25		74.00	21.75	500.0	200.0	V	42.0	5.5
17685.000000	55.59		74.00	18.41	500.0	200.0	Η	42.0	10.1
17775.000000		44.35	54.00	9.65	500.0	200.0	V	42.0	10.3

RF Test Report

Report No.: R2411A1739-R1

During the test, the Radiates Emission from 18GHz to 26.5GHz was performed in all modes with all channels. The test data of the worst-case condition was recorded in this report.



Frequency	MaxPeak	Average	Limit	Margin	Meas.	Height	Pol	Azimuth	Corr.
(MHz)	(dB£gV/m)	(dB£gV/m)	(dB£gV/m)	(dB)	Time	(cm)		(deg)	(dB/m)
					(ms)				
18014.875000	47.15		74.00	26.85	500.0	200.0	V	114.0	-5.7
18157.250000		35.32	54.00	18.68	500.0	200.0	Н	157.0	-5.8
20351.312500	46.66		74.00	27.34	500.0	100.0	Н	118.0	-5.4
20451.187500		35.37	54.00	18.63	500.0	100.0	V	359.0	-4.9
21131.187500	47.99		74.00	26.01	500.0	100.0	V	280.0	-4.2
21202.375000		36.71	54.00	17.29	500.0	200.0	V	55.0	-4.3
22158.625000	48.77		74.00	25.23	500.0	200.0	Η	356.0	-3.7
22542.187500		36.98	54.00	17.02	500.0	200.0	Н	342.0	-3.4
24404.750000		36.53	54.00	17.47	500.0	100.0	Н	196.0	-3.1
24451.500000	48.02		74.00	25.98	500.0	200.0	Н	218.0	-3.1
25779.625000		36.49	54.00	17.51	500.0	200.0	V	128.0	-2.5
26404.375000	48.08		74.00	25.92	500.0	200.0	V	87.0	-2.1

5.7. Conducted Emission

Ambient Condition

Temperature	Relative humidity		
15°C ~ 35°C	20% ~ 80%		

Methods of Measurement

The EUT is placed on a non-metallic table of 80cm height above the horizontal metal reference ground plane. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.10. Connect the AC power line of the EUT to the L.I.S.N. Use EMI receiver to detect the average and Quasi-peak value. RBW is set to 9 kHz, VBW is set to 30kHz. The measurement result should include both L line and N line. The test is in transmitting mode.

Test Setup



Note: AC Power source is used to change the voltage 120V/60Hz.

Limits

Frequency	Conducted Limits(dBµV)						
(MHz)	Quasi-peak	Average					
0.15 - 0.5	66 to 56 *	56 to 46*					
0.5 - 5	56	46					
5 - 30 60 50							
* Decreases with the logarithm of the frequency.							

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor k = 1.96, U = 2.69 dB.

RF Test Report

Test Results:

Following plots, Blue trace uses the peak detection and Green trace uses the average detection.

Wi-Fi 2.4GHz

During the test, the Conducted Emission was performed in all modes with all channels. The test data of the worst-case condition was recorded in this report.



Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.16		32.64	55.28	22.64	1000.0	9.000	L1	ON	20.9
0.17	48.16		65.17	17.01	1000.0	9.000	L1	ON	20.9
0.37	35.17		58.54	23.37	1000.0	9.000	L1	ON	20.9
0.39		21.44	48.05	26.61	1000.0	9.000	L1	ON	20.9
0.89		13.78	46.00	32.22	1000.0	9.000	L1	ON	20.3
1.27	18.19		56.00	37.81	1000.0	9.000	L1	ON	20.0
2.24		11.98	46.00	34.02	1000.0	9.000	L1	ON	19.6
3.30	14.89		56.00	41.11	1000.0	9.000	L1	ON	19.5
11.87		12.33	50.00	37.67	1000.0	9.000	L1	ON	19.4
12.03	17.20		60.00	42.80	1000.0	9.000	L1	ON	19.4
20.32	21.71		60.00	38.29	1000.0	9.000	L1	ON	19.7
20.85		16.11	50.00	33.89	1000.0	9.000	L1	ON	19.7

Remark: Correct factor=cable loss + LISN factor

L line Conducted Emission from 150 kHz to 30 MHz





Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.16	49.91		65.40	15.49	1000.0	9.000	Ν	ON	20.9
0.16		32.56	55.28	22.72	1000.0	9.000	Ν	ON	20.9
0.37	36.72		58.59	21.87	1000.0	9.000	Ν	ON	20.9
0.86		18.10	46.00	27.90	1000.0	9.000	Ν	ON	20.3
0.88	22.21		56.00	33.79	1000.0	9.000	Ν	ON	20.3
0.88		14.28	46.00	31.72	1000.0	9.000	Ν	ON	20.3
3.10		10.92	46.00	35.08	1000.0	9.000	Ν	ON	19.5
3.16	16.00		56.00	40.00	1000.0	9.000	Ν	ON	19.5
11.86		12.39	50.00	37.61	1000.0	9.000	Ν	ON	19.4
11.89	17.52		60.00	42.48	1000.0	9.000	Ν	ON	19.4
20.09	22.65		60.00	37.35	1000.0	9.000	Ν	ON	19.7
20.85		16.88	50.00	33.12	1000.0	9.000	Ν	ON	19.7

Remark: Correct factor=cable loss + LISN factor

N line Conducted Emission from 150 kHz to 30 MHz



Bluetooth LE

During the test, the Conducted Emission was performed in all modes with all channels. The test data of the worst-case condition was



Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.15		29.98	56.00	26.02	1000.0	9.000	L1	ON	20.9
0.16	45.73		65.52	19.79	1000.0	9.000	L1	ON	20.9
0.53		22.01	46.00	23.99	1000.0	9.000	L1	ON	20.7
0.59	32.71		56.00	23.29	1000.0	9.000	L1	ON	20.7
1.95	24.71		56.00	31.29	1000.0	9.000	L1	ON	19.7
2.10		19.52	46.00	26.48	1000.0	9.000	L1	ON	19.6
4.39		29.08	46.00	16.92	1000.0	9.000	L1	ON	19.4
4.89	36.48		56.00	19.52	1000.0	9.000	L1	ON	19.4
5.13		18.98	50.00	31.02	1000.0	9.000	L1	ON	19.4
5.17	38.35		60.00	21.65	1000.0	9.000	L1	ON	19.4
16.99		20.53	50.00	29.47	1000.0	9.000	L1	ON	19.6
17.18	34.77		60.00	25.23	1000.0	9.000	L1	ON	19.6

Remark: Correct factor=cable loss + LISN factor

L line Conducted Emission from 150 kHz to 30 MHz

🔅 eurofins

RF Test Report



Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.15	50.68		65.88	15.20	1000.0	9.000	Ν	ON	20.9
0.19		29.19	54.21	25.02	1000.0	9.000	Ν	ON	21.0
0.56	31.34		56.00	24.66	1000.0	9.000	Ν	ON	20.7
0.56		25.28	46.00	20.72	1000.0	9.000	Ν	ON	20.7
1.86	24.02		56.00	31.98	1000.0	9.000	Ν	ON	19.7
1.91		18.64	46.00	27.36	1000.0	9.000	Ν	ON	19.7
3.87	30.85		56.00	25.15	1000.0	9.000	Ν	ON	19.4
3.88		25.28	46.00	20.72	1000.0	9.000	Ν	ON	19.4
8.03	25.79		60.00	34.21	1000.0	9.000	Ν	ON	19.4
8.14		19.30	50.00	30.70	1000.0	9.000	Ν	ON	19.4
23.67	30.66		60.00	29.34	1000.0	9.000	Ν	ON	19.8
23.94		25.25	50.00	24.75	1000.0	9.000	Ν	ON	19.8

Remark: Correct factor=cable loss + LISN factor

N line Conducted Emission from 150 kHz to 30 MHz

6. Main Test Instruments

Name	Manufacturer	Туре	Serial Number	Calibration Date	Expiration Date
Power sensor	R&S	NRP18S	101954	2024-05-07	2025-05-06
Spectrum Analyzer	KEYSIGHT	N9020A	MY51330870	2024-05-07	2025-05-06
DC Power Supply	UNI-T	UTP1306S+	2205D0517426	2024-12-02	2025-12-01
Attenuator	HASCO	HA18A-10	0003	/	/
EMI Test Receiver	R&S	ESCI3	100948	2024-05-07	2025-05-06
Signal Analyzer	R&S	FSV40	101186	2024-05-07	2025-05-06
Loop Antenna	SCHWARZBECK	FMZB1519	1519-047	2023-04-16	2026-04-15
TRILOG Broadband Antenna	SCHWARZBECK	VULB 9163	1023	2023-07-14	2026-07-13
Horn Antenna	SCHWARZBECK	BBHA 9120D	430	2024-07-18	2027-07-17
Amplifier	MWPA.CN	MWLA-01020 0G40	YQ2103039B01	2024-05-07	2025-05-06
Horn Antenna	ETS-Lindgren	3160-09	00102643	2024-09-24	2027-09-23
Horn Antenna	STEATITE	QSH-SL-26-4 0-K-15	16779	2023-01-17	2026-01-16
Amplifier	MicroWave	KLNA-180400 50	220826001	2024-05-08	2025-05-07
Antenna mast	ETS	2070-2	00095628	/	/
Software	R&S	EMC32	9.26.01	/	/
Artificial main network	R&S	ENV216	102191	2024-12-02	2026-12-01
EMI Test Receiver	R&S	ESR	101667	2024-05-07	2025-05-06
Software	R&S	EMC32	10.35.10	/	/



ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.



ANNEX B: Test Setup Photos

The Test Setup Photos are submitted separately.

****** END OF REPORT ******