

RF EXPOSURE TEST REPORT

Applicant	Belkin International, Inc.
Address	12045 East Waterfront Drive, Playa Vista, CA 90094 USA

Manufacturer or Supplier	Belkin International, Inc.
Address	12045 East Waterfront Drive, Playa Vista, CA 90094 USA
Product	BOOST↑CHARGE™ Wireless Charging Stand 15W
Additional Product	Wireless Charging Stand 15W, see items 1.1
Brand Name	belkin, playa
Model	WIB002
Additional Model & Model Difference	PW0006, see items 1.1
Date of tests	Aug. 01, 2020 ~ Aug. 26, 2020

The submitted sample of the above equipment has been tested according to the requirements of the following standard:

- ☒ 47 CFR PART 1, Subpart I, Section 1.1310
- ☒ KDB 680106 D01

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Lucas Chen Project Engineer / EMC Department	Approved by Glyn He Assistant Manager/ EMC Department
	 Data: Sep. 25, 2020

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute you unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

RF EXPOSURE TEST REPORT	1
RELEASE CONTROL RECORD	3
1. GENERAL INFORMATION	4
1.1. GENERAL DESCRIPTION OF EUT	4
2. RF EXPOSURE MEASUREMENT	5
2.1 LIMITS	5
2.2 DESCRIPTION OF SUPPORT UNITS	5
2.3 CONFIGURATION OF SYSTEM UNDER TEST	6
2.4 TEST SETUP FOR WPC	6
2.5 EQUIPMENTS USED DURING TEST	7
2.6 TEST POINT DESCRIPTION	7
2.7 TEST RESULTS	8
3. PHOTOGRAPHS OF THE TEST CONFIGURATION	24



Test Report No.: FM200727N001

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FM200727N001	Original release	Sep. 25, 2020

1. GENERAL INFORMATION

1.1. GENERAL DESCRIPTION OF EUT

FCC ID	K7SWIB002
PRODUCT	BOOST↑CHARGE™ Wireless Charging Stand 15W
ADDITIONAL PRODUCT	Wireless Charging Stand 15W
MODEL NO.	WIB002
ADDITIONAL MODEL	PW0006
POWER SUPPLY	Input: 12V=1.8A from adapter Output: 15W
MODULATION TECHNOLOGY	FSK
OPERATING FREQUENCY RANGE	110KHz ~ 205KHz
ANTENNA TYPE	Loop Antenna
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	USB-A to USB-C cable: Shielded, detachable 1.2m

NOTES:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- For the test results, the EUT had been tested with all conditions, but only the worst case was shown in test report.
- Please refer to the EUT photo document (Reference No.: 200727N001-1) for detailed product photo.
- Additional model PW0006 is identical with test model WIB002 except the model no. and brand name for trading purpose.
- Model list:

Product	Brand	Model no.
BOOST CHARGE Wireless Charging Stand 15W	belkin	WIB002
Wireless Charging Stand 15W	playa	PW0006

- The EUT can be powered by adapter as list as attach:

ADAPTER	
BRAND:	belkin
MODEL:	DSA-24QFA FUS A
INPUT:	AC 100-240V, 50/60Hz, 0.8A
OUTPUT:	USB-C 5V=3A, 9V=2.7A, 12V=2.0A
DC LINE:	N/A

2. RF EXPOSURE MEASUREMENT

2.1 LIMITS

§ 1.1310 The criteria listed in table 1 shall be used to evaluate the environmental impact of human exposure to radiofrequency(RF) radiation as specified in § 1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of § 2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

Reference KDB 680106 D01 RF Exposure Wireless Charging App v03


The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

2.2 DESCRIPTION OF SUPPORT UNITS


The EUT has been tested with associated equipment below

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	iPhone X	Apple	MQA52CH/A	N/A	N/A

2.3 CONFIGURATION OF SYSTEM UNDER TEST



2.4 TEST SETUP FOR WPC



Note: Measurements should be made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device.




2.5 EQUIPMENTS USED DURING TEST

Item	Test Equipment	Manufacturer	Model No.	S/No	Due date.
1	3m Semi-Anechoic Chamber	ETS-LINDGRE N	7m*4m*3m	NSEMC003	2021-03-19
2	B-field Probe	Narda	Y2006	L-0017	2020-12-23
3	E-Field probe	Narda	NBM-520	2403/01B	2020-12-23

NOTE: 1. The test was performed in RS chamber.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

2.6 TEST POINT DESCRIPTION



2.7 TEST RESULTS

Mode 1 Standby

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	1.17	1.22	1.13	0.49	1.13
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-612.83	-612.78	-612.87	-613.51	-612.87
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-305.83	-305.78	-305.87	-306.51	-305.87

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.244	0.248	0.242	0.248	0.27
Max H-field (A/m)	0.194	0.197	0.193	0.197	0.215
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.436	-1.433	-1.437	-1.433	-1.415
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.621	-0.618	-0.622	-0.618	-0.600

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode2 Charging Mode with iPhone X 10% Charger (at center)

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	1.72	1.56	0.61	0.7	1.21
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-612.28	-612.44	-613.39	-613.3	-612.79
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-305.28	-305.44	-306.39	-306.3	-305.79

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.239	0.243	0.241	0.221	0.243
Max H-field (A/m)	0.190	0.193	0.192	0.176	0.193
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.440	-1.437	-1.438	-1.454	-1.437
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.625	-0.622	-0.623	-0.639	-0.622

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode3 Charging Mode with iPhone X 50% Charger (at center)

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	1.68	1.49	0.67	0.82	1.14
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-612.32	-612.51	-613.33	-613.18	-612.86
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-305.32	-305.51	-306.33	-306.18	-305.86

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.237	0.246	0.247	0.254	0.251
Max H-field (A/m)	0.189	0.196	0.197	0.202	0.200
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.441	-1.434	-1.433	-1.428	-1.430
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.626	-0.619	-0.618	-0.613	-0.615

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode4 Charging Mode with iPhone X 90% Charger (at center)

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	1.64	1.42	0.66	0.79	1.16
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-612.36	-612.58	-613.34	-613.21	-612.84
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-305.36	-305.58	-306.34	-306.21	-305.84

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.238	0.245	0.248	0.248	0.267
Max H-field (A/m)	0.189	0.195	0.197	0.197	0.213
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.441	-1.435	-1.433	-1.433	-1.417
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.626	-0.620	-0.618	-0.618	-0.602

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode5 Charging Mode with iPhone X 10% Charger (shift 5mm to right)

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	1.85	1.46	0.78	0.75	1.18
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-612.15	-612.54	-613.22	-613.25	-612.82
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-305.15	-305.54	-306.22	-306.25	-305.82

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.237	0.222	0.246	0.244	0.254
Max H-field (A/m)	0.189	0.177	0.196	0.194	0.202
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.441	-1.453	-1.434	-1.436	-1.428
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.626	-0.638	-0.619	-0.621	-0.613

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode6 Charging Mode with iPhone X 50% Charger (shift 5mm to right)

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	1.87	1.49	0.85	0.76	1.27
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-612.13	-612.51	-613.15	-613.24	-612.73
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-305.13	-305.51	-306.15	-306.24	-305.73

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.239	0.248	0.253	0.221	0.241
Max H-field (A/m)	0.190	0.197	0.201	0.176	0.192
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.440	-1.433	-1.429	-1.454	-1.438
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.625	-0.618	-0.614	-0.639	-0.623

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode 7 Charging Mode with iPhone X 90% Charger (shift 5mm to right)

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	1.85	1.52	0.78	0.71	1.32
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-612.15	-612.48	-613.22	-613.29	-612.68
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-305.15	-305.48	-306.22	-306.29	-305.68

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.228	0.246	0.254	0.231	0.228
Max H-field (A/m)	0.182	0.196	0.202	0.184	0.182
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.448	-1.434	-1.428	-1.446	-1.448
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.633	-0.619	-0.613	-0.631	-0.633

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode8 Charging Mode with iPhone X 10% Charger (shift 5mm to left)

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	2.12	1.64	0.87	0.81	1.46
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-611.88	-612.36	-613.13	-613.19	-612.54
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-304.88	-305.36	-306.13	-306.19	-305.54

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.221	0.246	0.231	0.231	0.245
Max H-field (A/m)	0.176	0.196	0.184	0.184	0.195
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.454	-1.434	-1.446	-1.446	-1.435
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.639	-0.619	-0.631	-0.631	-0.620

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode9 Charging Mode with iPhone X 50% Charger (shift 5mm to left)

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	2.23	1.23	0.97	0.81	1.42
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-611.77	-612.77	-613.03	-613.19	-612.58
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-304.77	-305.77	-306.03	-306.19	-305.58

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.234	0.237	0.236	0.221	0.226
Max H-field (A/m)	0.186	0.189	0.188	0.176	0.180
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.444	-1.441	-1.442	-1.454	-1.450
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.629	-0.626	-0.627	-0.639	-0.635

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode10 Charging Mode with iPhone X 90% Charger (shift 5mm to left)

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	1.99	1.32	0.87	0.88	0.92
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-612.01	-612.68	-613.13	-613.12	-613.08
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-305.01	-305.68	-306.13	-306.12	-306.08

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.223	0.246	0.254	0.223	0.204
Max H-field (A/m)	0.178	0.196	0.202	0.178	0.162
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.452	-1.434	-1.428	-1.452	-1.468
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.637	-0.619	-0.613	-0.637	-0.653

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode11 Charging Mode with iPhone X 10% Charger (shift 5mm to top)

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	2.31	1.45	0.97	0.92	1.22
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-611.69	-612.55	-613.03	-613.08	-612.78
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-304.69	-305.55	-306.03	-306.08	-305.78

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.237	0.224	0.231	0.246	0.222
Max H-field (A/m)	0.189	0.178	0.184	0.196	0.177
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.441	-1.452	-1.446	-1.434	-1.453
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.626	-0.637	-0.631	-0.619	-0.638

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode12 Charging Mode with iPhone X 50% Charger (shift 5mm to top)

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	2.35	1.44	1.13	0.87	1.35
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-611.65	-612.56	-612.87	-613.13	-612.65
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-304.65	-305.56	-305.87	-306.13	-305.65

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.234	0.226	0.227	0.213	0.241
Max H-field (A/m)	0.186	0.180	0.181	0.170	0.192
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.444	-1.450	-1.449	-1.460	-1.438
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.629	-0.635	-0.634	-0.645	-0.623

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode13 Charging Mode with iPhone X 90% Charger (shift 5mm to top)

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	2.36	1.52	1.22	0.76	1.22
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-611.64	-612.48	-612.78	-613.24	-612.78
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-304.64	-305.48	-305.78	-306.24	-305.78

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.244	0.237	0.239	0.234	0.226
Max H-field (A/m)	0.194	0.189	0.190	0.186	0.180
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.436	-1.441	-1.440	-1.444	-1.450
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.621	-0.626	-0.625	-0.629	-0.635

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode14 Charging Mode with iPhone X 10% Charger (shift 5mm to bottom)

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	2.45	1.64	1.26	0.89	1.35
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-611.55	-612.36	-612.74	-613.11	-612.65
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-304.55	-305.36	-305.74	-306.11	-305.65

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.226	0.245	0.251	0.223	0.238
Max H-field (A/m)	0.180	0.195	0.200	0.178	0.189
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.450	-1.435	-1.430	-1.452	-1.441
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.635	-0.620	-0.615	-0.637	-0.626

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode15 Charging Mode with iPhone X 50% Charger (shift 5mm to bottom)

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	2.33	1.57	1.18	0.76	1.25
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-611.67	-612.43	-612.82	-613.24	-612.75
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-304.67	-305.43	-305.82	-306.24	-305.75

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.245	0.234	0.226	0.228	0.254
Max H-field (A/m)	0.195	0.186	0.180	0.182	0.202
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.435	-1.444	-1.450	-1.448	-1.428
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.620	-0.629	-0.635	-0.633	-0.613

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode16 Charging Mode with iPhone X 90% Charger (shift 5mm to bottom)

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	2.27	1.29	1.12	0.87	1.34
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-611.73	-612.71	-612.88	-613.13	-612.66
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-304.73	-305.71	-305.88	-306.13	-305.66

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.224	0.254	0.234	0.213	0.238
Max H-field (A/m)	0.178	0.202	0.186	0.170	0.189
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.452	-1.428	-1.444	-1.460	-1.441
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.637	-0.613	-0.629	-0.645	-0.626

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode17 Charging Mode with iPhone X 10% 3mm airgap Charger (at center)

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	2.45	2.81	2.06	0.67	2.57
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-611.55	-611.19	-611.94	-613.33	-611.43
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-304.55	-304.19	-304.94	-306.33	-304.43

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.245	0.244	0.241	0.243	0.243
Max H-field (A/m)	0.195	0.194	0.192	0.193	0.193
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.435	-1.436	-1.438	-1.437	-1.437
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.620	-0.621	-0.623	-0.622	-0.622

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode18 Charging Mode with iPhone X 50% 3mm airgap Charger (at center)

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	2.54	2.49	2.34	0.97	2.55
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-611.46	-611.51	-611.66	-613.03	-611.45
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-304.46	-304.51	-304.66	-306.03	-304.45

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.241	0.246	0.244	0.238	0.245
Max H-field (A/m)	0.192	0.196	0.194	0.189	0.195
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.438	-1.434	-1.436	-1.441	-1.435
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.623	-0.619	-0.621	-0.626	-0.620

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode19 Charging Mode with iPhone X 90% 3mm airgap Charger (at center)

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	2.64	2.28	2.33	1.11	2.67
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-611.36	-611.72	-611.67	-612.89	-611.33
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-304.36	-304.72	-304.67	-305.89	-304.33

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.254	0.244	0.238	0.227	0.256
Max H-field (A/m)	0.202	0.194	0.189	0.181	0.204
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.428	-1.436	-1.441	-1.449	-1.426
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.613	-0.621	-0.626	-0.634	-0.611

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode20 Charging Mode with iPhone X 10% 3mm airgap Charger (shift 5mm to right)

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	2.67	2.37	2.13	1.21	2.57
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-611.33	-611.63	-611.87	-612.79	-611.43
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-304.33	-304.63	-304.87	-305.79	-304.43

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.467	0.435	0.422	0.324	0.428
Max H-field (A/m)	0.372	0.346	0.336	0.258	0.341
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.258	-1.284	-1.294	-1.372	-1.289
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.443	-0.469	-0.479	-0.557	-0.474

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode21 Charging Mode with iPhone X 50% 3mm airgap Charger (shift 5mm to right)

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	2.66	2.49	2.11	1.33	2.67
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-611.34	-611.51	-611.89	-612.67	-611.33
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-304.34	-304.51	-304.89	-305.67	-304.33

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.432	0.342	0.344	0.321	0.423
Max H-field (A/m)	0.344	0.272	0.274	0.256	0.337
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.286	-1.358	-1.356	-1.374	-1.293
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.471	-0.543	-0.541	-0.559	-0.478

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode22 Charging Mode with iPhone X 90% 3mm airgap Charger (shift 5mm to right)

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	2.16	2.15	2.43	1.64	2.12
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-611.84	-611.85	-611.57	-612.36	-611.88
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-304.84	-304.85	-304.57	-305.36	-304.88

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.345	0.337	0.245	0.244	0.431
Max H-field (A/m)	0.275	0.268	0.195	0.194	0.343
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.355	-1.362	-1.435	-1.436	-1.287
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.540	-0.547	-0.620	-0.621	-0.472

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode23 Charging Mode with iPhone X 10% 3mm airgap Charger (shift 5mm to left)

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	2.37	2.54	2.69	1.68	2.55
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-611.63	-611.46	-611.31	-612.32	-611.45
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-304.63	-304.46	-304.31	-305.32	-304.45

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.436	0.432	0.358	0.346	0.422
Max H-field (A/m)	0.347	0.344	0.285	0.275	0.336
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.283	-1.286	-1.345	-1.355	-1.294
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.468	-0.471	-0.530	-0.540	-0.479

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode24 Charging Mode with iPhone X 50% 3mm airgap Charger (shift 5mm to left)

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	2.15	2.11	2.57	1.28	2.39
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-611.85	-611.89	-611.43	-612.72	-611.61
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-304.85	-304.89	-304.43	-305.72	-304.61

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.435	0.342	0.228	0.345	0.423
Max H-field (A/m)	0.346	0.272	0.182	0.275	0.337
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.284	-1.358	-1.448	-1.355	-1.293
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.469	-0.543	-0.633	-0.540	-0.478

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode25 Charging Mode with iPhone X 90% 3mm airgap Charger (shift 5mm to left)

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	2.34	2.11	2.67	1.22	2.64
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-611.66	-611.89	-611.33	-612.78	-611.36
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-304.66	-304.89	-304.33	-305.78	-304.36

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.435	0.467	0.455	0.345	0.478
Max H-field (A/m)	0.346	0.372	0.362	0.275	0.381
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.284	-1.258	-1.268	-1.355	-1.249
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.469	-0.443	-0.453	-0.540	-0.434

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode26 Charging Mode with iPhone X 10% 3mm airgap Charger (shift 5mm to top)

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	2.1	2.13	2.45	1.34	2.39
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-611.9	-611.87	-611.55	-612.66	-611.61
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-304.9	-304.87	-304.55	-305.66	-304.61

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.325	0.345	0.356	0.229	0.458
Max H-field (A/m)	0.259	0.275	0.283	0.182	0.365
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.371	-1.355	-1.347	-1.448	-1.265
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.556	-0.540	-0.532	-0.633	-0.450

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode27 Charging Mode with iPhone X 50% 3mm airgap Charger (shift 5mm to top)

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	2.34	2.11	2.39	1.24	2.49
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-611.66	-611.89	-611.61	-612.76	-611.51
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-304.66	-304.89	-304.61	-305.76	-304.51

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.368	0.345	0.346	0.332	0.422
Max H-field (A/m)	0.293	0.275	0.275	0.264	0.336
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.337	-1.355	-1.355	-1.366	-1.294
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.522	-0.540	-0.540	-0.551	-0.479

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode28 Charging Mode with iPhone X 90% 3mm airgap Charger (shift 5mm to top)

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	2.1	2.34	2.42	1.19	2.27
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-611.9	-611.66	-611.58	-612.81	-611.73
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-304.9	-304.66	-304.58	-305.81	-304.73

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.445	0.448	0.442	0.387	0.421
Max H-field (A/m)	0.354	0.357	0.352	0.308	0.335
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.276	-1.273	-1.278	-1.322	-1.295
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.461	-0.458	-0.463	-0.507	-0.480

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode29 Charging Mode with iPhone X 10% 3mm airgap Charger (shift 5mm to bottom)

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	2.34	2.45	2.22	2.01	2.19
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-611.66	-611.55	-611.78	-611.99	-611.81
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-304.66	-304.55	-304.78	-304.99	-304.81

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.456	0.442	0.342	0.334	0.546
Max H-field (A/m)	0.363	0.352	0.272	0.266	0.435
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.267	-1.278	-1.358	-1.364	-1.195
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.452	-0.463	-0.543	-0.549	-0.380

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode30 Charging Mode with iPhone X 50% 3mm airgap Charger (shift 5mm to bottom)

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	2.37	2.67	2.33	1.97	2.33
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-611.63	-611.33	-611.67	-612.03	-611.67
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-304.63	-304.33	-304.67	-305.03	-304.67

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.345	0.337	0.339	0.324	0.425
Max H-field (A/m)	0.275	0.268	0.270	0.258	0.338
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.355	-1.362	-1.360	-1.372	-1.292
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.540	-0.547	-0.545	-0.557	-0.477

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

Charging Mode31 Charging Mode with iPhone X 90% 3mm airgap Charger (shift 5mm to bottom)

E-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max E-field (V/m)	2.31	2.66	2.13	1.96	2.29
Limit (V/m)	614	614	614	614	614
Margin (V/m)	-611.69	-611.34	-611.87	-612.04	-611.71
50% Limit (V/m)	307	307	307	307	307
50% Margin (V/m)	-304.69	-304.34	-304.87	-305.04	-304.71

H-Field Measurement					
Distance	15cm				20cm
EUT Side	Left	Right	Top	Bottom	Z-axis
Max H-field (uT)	0.229	0.225	0.234	0.345	0.358
Max H-field (A/m)	0.182	0.179	0.186	0.275	0.285
Limit (A/m)	1.63	1.63	1.63	1.63	1.63
Margin (A/m)	-1.448	-1.451	-1.444	-1.355	-1.345
50% Limit (A/m)	0.815	0.815	0.815	0.815	0.815
50% Margin (A/m)	-0.633	-0.636	-0.629	-0.540	-0.530

Measurements was made from all sides and the top of the primary/client pair, with the 15 cm or 20 cm measured from the center of the probe(s) to the edge of the device. The highest emission level was recorded.

3. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

--- END ---