



FCC RF Test Report

(2.4G)

Applicant: Hangzhou Roombanker Technology Co., Ltd.

Address of Applicant: A#801 Wantong center, Hangzhou, China

Equipment Under Test (EUT)

Product Name: US Deadbolt lock

Model No.: DSL-090-1

FCC ID: 2AUXBDL-090-1

Applica2.4G Standards: FCC CFR Title 47 Part 15C (§15.247)

Date of Sample Receipt: 20 Mar., 2023

Date of Test: 21 Mar., to 24 Mar., 2023

Date of Report Issued: 24 Mar., 2023

Test Result: PASS

Tested by:

June Li

Date:

24 Mar., 2023

Reviewed by:

Wenwen Zhang

Date:


24 Mar., 2023

Approved by:

Wenwen Zhang

Date:

24 Mar., 2023



This equipment has been shown to be capable of compliance with the applicable 2.4G technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in above the application standard version. Test results reported herein relate only to the item(s) tested.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

1 Version

Version No.	Date	Description
00	24 Mar., 2023	Original

2 Contents

Page

Cover Page	1
1 Version	2
2 Contents.....	3
3 General Information.....	4
3.1 Client Information	4
3.2 General Description of E.U.T.	4
3.3 Test Mode and Test Environment	5
3.4 Description of Test Auxiliary Equipment	5
3.5 Measurement Uncertainty	5
3.6 Additions to, Deviations, or Exclusions from the Method	5
3.7 Laboratory Facility	5
3.8 Laboratory Location.....	5
3.9 Test Instruments List	6
4 Measurement Setup and Procedure	7
4.1 Test Channel	7
4.2 Test Setup	7
4.3 Test Procedure	9
5 Test Results.....	10
5.1 Summary	10
5.1.1 Clause and Data Summary.....	10
5.1.2 Test Limit.....	11
5.2 Antenna requirement.....	12
5.3 Emissions in Restricted Frequency Bands.....	13
5.4 Emissions in Non-restricted Frequency Bands	29

3 General Information

3.1 Client Information

Applicant:	Hangzhou Roombanker Technology Co., Ltd.
Address:	A#801 Wantong center, Hangzhou, China
Manufacturer:	Hangzhou Roombanker Technology Co., Ltd.
Address:	A#801 Wantong center, Hangzhou, China
Factory:	Zhejiang Dusun Electron Co., Ltd.
Address:	NO.640 FengQing str.,DeQing, ZheJiang, China

3.2 General Description of E.U.T.

Product Name:	US Deadbolt lock
Model No.:	DSL-090-1
Operation Frequency:	2402 MHz - 2480 MHz
Channel Numbers:	40
Channel Separation:	2MHz
Modulation Technology:	GFSK
Antenna Type:	Internal Antenna
Antenna Gain:	0 dBi (declare by applicant)
Antenna transmit mode:	SISO (1TX, 1RX)
Power Supply:	DC 6V (4*AA Battery)
Test Sample Condition:	The test samples were provided in good working order with no visi2.4G defects.

3.3 Test Mode and Test Environment

Test Mode:	
Transmitting mode	Keep the EUT in continuous transmitting with modulation
Remark: 1. For radiated spurious emission (below 1GHz), pre-scan all data speed, found 1 Mbps (1M PHY) was worse case mode. The report only reflects the test data of worst mode. 2. Channel Low, Mid and High for each type band with rated data rate were chosen for full testing. The field strength of spurious radiation emission was measured as EUT stand-up position (H mode) and lie down position (E1, E2 mode) for these modes. Just the worst case position (H mode) shown in report.	
Operating Environment:	
Temperature:	15°C ~ 35°C
Humidity:	20 % ~ 75 % RH
Atmospheric Pressure:	1008 mbar

3.4 Description of Test Auxiliary Equipment

The EUT has been tested as an independent unit.

3.5 Measurement Uncertainty

Parameter	Expanded Uncertainty (Confidence of 95%(U = 2Uc(y)))
Radiated Emission (30MHz ~ 1GHz) (3m SAC)	3.8 dB
Radiated Emission (1GHz ~ 18GHz) (3m SAC)	3.6 dB
Radiated Emission (18GHz ~ 40GHz) (3m SAC)	5.34 dB
Radiated Emission (30MHz ~ 1GHz) (10m SAC)	3.7 dB
Note: All the measurement uncertainty value were shown with a coverage k=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.	

3.6 Additions to, Deviations, or Exclusions from the Method

No

3.7 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations: ● FCC - Designation No.: CN1211 JianYan Testing Group Shenzhen Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551. ● ISED – CAB identifier.: CN0021 The 3m Semi-anechoic chamber and 10m Semi-anechoic chamber of JianYan Testing Group Shenzhen Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1. ● CNAS - Registration No.: CNAS L15527 JianYan Testing Group Shenzhen Co., Ltd. is accredited to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L15527. ● A2LA - Registration No.: 4346.01 This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: https://portal.a2la.org/scopepdf/4346-01.pdf
--

3.8 Laboratory Location

JianYan Testing Group Shenzhen Co., Ltd. Address: No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China. Tel: +86-755-23118282, Fax: +86-755-23116366 Email: info-JYTee@lets.com, Website: http://jyt.lets.com
--

3.9 Test Instruments List

Radiated Emission(3m SAC):					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	ETS	9m*6m*6m	WXJ001-1	04-14-2021	04-13-2024
Loop Antenna	Schwarzbeck	FMZB 1519 B	WXJ002-4	01-10-2023	01-09-2024
BiConiLog Antenna	Schwarzbeck	VULB9163	WXJ002	01-10-2023	01-09-2024
Horn Antenna	Schwarzbeck	BBHA9120D	WXJ002-2	01-10-2023	01-09-2024
Horn Antenna	Schwarzbeck	BBHA9170	WXJ002-5	04-07-2022	04-06-2023
Pre-amplifier (30MHz ~ 1GHz)	Schwarzbeck	BBV9743B	WXJ001-2	01-10-2023	01-09-2024
Pre-amplifier (1GHz ~ 18GHz)	SKET	LNPA_0118G-50	WXJ001-3	01-10-2023	01-09-2024
Pre-amplifier (18GHz ~ 40GHz)	RF System	TRLA-180400G45B	WXJ002-7	03-30-2022	03-29-2023
EMI Test Receiver	Rohde & Schwarz	ESRP7	WXJ003-1	01-10-2023	01-09-2024
Spectrum Analyzer	Rohde & Schwarz	FSP 30	WXJ004	01-10-2023	01-09-2024
Spectrum Analyzer	KEYSIGHT	N9010B	WXJ004-2	10-17-2022	10-16-2023
Coaxial Ca2.4G (30MHz ~ 1GHz)	JYTSZ	JYT3M-1G-NN-8M	WXG001-4	01-18-2023	01-17-2024
Coaxial Ca2.4G (1GHz ~ 18GHz)	JYTSZ	JYT3M-18G-NN-8M	WXG001-5	01-18-2023	01-17-2024
Coaxial Ca2.4G (18GHz ~ 40GHz)	JYTSZ	JYT3M-40G-SS-8M	WXG001-7	01-18-2023	01-17-2024
Band Reject Filter Group	Tonscend	JS0806-F	WXJ089	N/A	
Test Software	Tonscend	TS+	Version: 3.0.0.1		

Radiated Emission(10m SAC):					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
10m SAC	ETS	RFSD-100-F/A	WXJ090	04-28-2021	04-27-2024
BiConiLog Antenna	SCHWARZBECK	VULB 9168	WXJ090-1	04-01-2022	03-31-2023
BiConiLog Antenna	SCHWARZBECK	VULB 9168	WXJ090-2	03-31-2022	03-30-2023
EMI Test Receiver	R&S	ESR 3	WXJ090-3	03-30-2022	03-29-2023
EMI Test Receiver	R&S	ESR 3	WXJ090-4	03-30-2022	03-29-2023
Low Pre-amplifier	Bost	LNA 0920N	WXJ090-6	01-10-2023	01-09-2024
Low Pre-amplifier	Bost	LNA 0920N	WXJ090-7	01-10-2023	01-09-2024
Ca2.4G	Bost	JYT10M-1G-NN-10M	WXG002-7	01-18-2023	01-17-2024
Ca2.4G	Bost	JYT10M-1G-NN-10M	WXG002-8	01-18-2023	01-17-2024
Test Software	R&S	EMC32	Version: 10.50.40		

Conducted Method:					
Test Equipment	Manufacturer	Model No.	Manage No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
Spectrum Analyzer	Keysight	N9010B	WXJ004-3	10-27-2021	10-26-2022
				10-17-2022	10-16-2023
Temperature Humidity Chamber	ZHONG ZHI	CZ-A-80D	WXJ032-3	01-09-2023	01-08-2025
Power Detector Box	MWRFTTEST	MW100-PSB	WXJ007-4	11-19-2021	11-18-2022
				10-17-2022	10-16-2023
DC Power Supply	Keysight	E3642A	WXJ025-2	N/A	
RF Control Unit	MWRFTTEST	MW100-RFCB	WXG006	N/A	
Test Software	MWRFTTEST	MTS 8310	Version: 2.0.0.0		

4 Measurement Setup and Procedure

4.1 Test Channel


According to ANSI C63.10-2013 chapter 5.6.1 Table 4 requirement, select lowest channel, middle channel, and highest channel in the frequency range in which device operates for testing. The detailed frequency points are as follows:

Lowest channel		Middle channel		Highest channel	
Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
0	2402	20	2442	39	2480


4.2 Test Setup


1) Radiated emission measurement:

Below 1GHz (10m SAC)



Above 1GHz (3m SAC)





4.3 Test Procedure

Test method	Test step
Radiated emission	For below 1GHz: - The EUT was placed on the tabletop of a rotating table 0.8 m the ground at a 10 m semi anechoic chamber. The measurement distance from the EUT to the receiving antenna is 10 m. - EUT works in each mode of operation that needs to be tested , and having the EUT continuously working, respectively on 3 axis (X, Y & Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations. - Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data. For above 1GHz: - The EUT was placed on the tabletop of a rotating table 1.5 m the ground at a 3 m fully anechoic room. The measurement distance from the EUT to the receiving antenna is 3 m. - EUT works in each mode of operation that needs to be tested , and having the EUT continuously working, respectively on 3 axis (X, Y & Z) and considered typical configuration to obtain worst position. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations. - Open the test software to control the test antenna and test turntable. Perform the test, save the test results, and export the test data.
Conducted test method	- The 2.4G antenna port of EUT was connected to the test port of the test system through an RF cable. - The EUT is keeping in continuous transmission mode and tested in all modulation modes. - Open the test software, prepare a test plan, and control the system through the software. After the test is completed, the test report is exported through the test software.

5 Test Results

5.1 Summary

5.1.1 Clause and Data Summary

Test items	Standard clause	Test data	Result
Antenna Requirement	15.203 15.247 (b)(4)	See Section 5.2	Pass
Conducted Output Power	15.247 (b)(3)	Appendix A – 2.4G-1M Appendix A – 2.4G-2M Appendix A – 2.4G-S2 Appendix A – 2.4G-S8	Pass
6dB Emission Bandwidth 99% Occupied Bandwidth	15.247 (a)(2)	Appendix A – 2.4G-1M Appendix A – 2.4G-2M Appendix A – 2.4G-S2 Appendix A – 2.4G-S8	Pass
Power Spectral Density	15.247 (e)	Appendix A – 2.4G-1M Appendix A – 2.4G-2M Appendix A – 2.4G-S2 Appendix A – 2.4G-S8	Pass
Band-edge Emission Conduction Spurious Emission	15.247 (d)	Appendix A – 2.4G-1M Appendix A – 2.4G-2M Appendix A – 2.4G-S2 Appendix A – 2.4G-S8	Pass
Emissions in Restricted Frequency Bands	15.205 15.247 (d)	See Section 5.3	Pass
Emissions in Non-restricted Frequency Bands	15.209 15.247(d)	See Section 5.4	Pass
Remark: 1. Pass: The EUT complies with the essential requirements in the standard. 2. N/A: Not Applicable. 3. The cable insertion loss used by “RF Output Power” and other conduction measurement items is 0.5dB (provided by the customer).			
Test Method:	ANSI C63.10-2013 KDB 558074 D01 15.247 Meas Guidance v05r02		

5.1.2 Test Limit


Test items	Limit																														
Conducted Output Power	For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.																														
6dB Emission Bandwidth	The minimum 6 dB bandwidth shall be at least 500 kHz.																														
99% Occupied Bandwidth	N/A																														
Power Spectral Density	For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.																														
Band-edge Emission Conduction Spurious Emission	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).																														
Emissions in Restricted Frequency Bands Emissions in Non-restricted Frequency Bands	<table><tr><th rowspan="2">Frequency (MHz)</th><th colspan="2">Limit (dBµV/m)</th><th rowspan="2">Detector</th></tr><tr><th>@ 3m</th><th>@ 10m</th></tr><tr><td>30 – 88</td><td>40.0</td><td>30.0</td><td>Quasi-peak</td></tr><tr><td>88 – 216</td><td>43.5</td><td>33.5</td><td>Quasi-peak</td></tr><tr><td>216 – 960</td><td>46.0</td><td>36.0</td><td>Quasi-peak</td></tr><tr><td>960 – 1000</td><td>54.0</td><td>44.0</td><td>Quasi-peak</td></tr></table> Note: The more stringent limit applies at transition frequencies. <table><tr><th rowspan="2">Frequency</th><th colspan="2">Limit (dBµV/m) @ 3m</th></tr><tr><th>Average</th><th>Peake</th></tr><tr><td>Above 1 GHz</td><td>54.0</td><td>74.0</td></tr></table> Note: The measurement bandwidth shall be 1 MHz or greater.	Frequency (MHz)	Limit (dBµV/m)		Detector	@ 3m	@ 10m	30 – 88	40.0	30.0	Quasi-peak	88 – 216	43.5	33.5	Quasi-peak	216 – 960	46.0	36.0	Quasi-peak	960 – 1000	54.0	44.0	Quasi-peak	Frequency	Limit (dBµV/m) @ 3m		Average	Peake	Above 1 GHz	54.0	74.0
Frequency (MHz)	Limit (dBµV/m)		Detector																												
	@ 3m	@ 10m																													
30 – 88	40.0	30.0	Quasi-peak																												
88 – 216	43.5	33.5	Quasi-peak																												
216 – 960	46.0	36.0	Quasi-peak																												
960 – 1000	54.0	44.0	Quasi-peak																												
Frequency	Limit (dBµV/m) @ 3m																														
	Average	Peake																													
Above 1 GHz	54.0	74.0																													

5.2 Antenna requirement

Standard requirement:	FCC Part 15 C Section 15.203 /247(b)(4)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
15.247(b) (4) requirement: (4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
E.U.T Antenna:	
The 2.4G antenna is an Internal antenna which cannot replace by end-user, the best case gain of the antenna is 0 dBi. See product internal photos for details.	

5.3 Emissions in Restricted Frequency Bands

Product Name:	US Deadbolt lock	Product Model:	DSL-090-1
Test By:	June	Test mode:	2.4G Tx (1M)
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	DC 6V		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2342.52	23.86	35.24	59.10	74.00	14.90	PK	Vertical
2	2342.52	12.79	35.24	48.03	54.00	5.97	AV	Vertical
3	2365.17	23.61	35.41	59.02	74.00	14.98	PK	Vertical
4	2365.17	12.72	35.41	48.13	54.00	5.87	AV	Vertical
5	2390.00	12.46	35.60	48.06	54.00	5.94	AV	Vertical
6	2390.00	23.44	35.60	59.04	74.00	14.96	PK	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	US Deadbolt lock	Product Model:	DSL-090-1
Test By:	June	Test mode:	2.4G Tx (1M)
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	DC 6V		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2347.03	24.31	35.27	59.58	74.00	14.42	PK	Horizontal
2	2347.03	12.83	35.27	48.10	54.00	5.90	AV	Horizontal
3	2366.49	24.50	35.42	59.92	74.00	14.08	PK	Horizontal
4	2366.49	12.69	35.42	48.11	54.00	5.89	AV	Horizontal
5	2390.00	12.49	35.60	48.09	54.00	5.91	AV	Horizontal
6	2390.00	22.44	35.60	58.04	74.00	15.96	PK	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	US Deadbolt lock	Product Model:	DSL-090-1
Test By:	June	Test mode:	2.4G Tx (1M)
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	DC 6V		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2483.50	13.20	35.51	48.71	54.00	5.29	AV	Vertical
2	2483.50	27.26	35.51	62.77	74.00	11.23	PK	Vertical
3	2488.03	12.56	35.50	48.06	54.00	5.94	AV	Vertical
4	2488.03	23.70	35.50	59.20	74.00	14.80	PK	Vertical
5	2492.14	24.05	35.49	59.54	74.00	14.46	PK	Vertical
6	2492.14	12.54	35.49	48.03	54.00	5.97	AV	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	US Deadbolt lock	Product Model:	DSL-090-1
Test By:	June	Test mode:	2.4G Tx (1M)
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	DC 6V		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2483.50	12.98	35.51	48.49	54.00	5.51	AV	Horizontal
2	2483.50	24.45	35.51	59.96	74.00	14.04	PK	Horizontal
3	2488.80	12.56	35.50	48.06	54.00	5.94	AV	Horizontal
4	2488.80	23.53	35.50	59.03	74.00	14.97	PK	Horizontal
5	2492.30	23.70	35.49	59.19	74.00	14.81	PK	Horizontal
6	2492.30	12.51	35.49	48.00	54.00	6.00	AV	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	US Deadbolt lock	Product Model:	DSL-090-1
Test By:	June	Test mode:	2.4G Tx (2M)
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	DC 6V		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2341.49	24.37	35.23	59.60	74.00	14.40	PK	Vertical
2	2341.49	12.82	35.23	48.05	54.00	5.95	AV	Vertical
3	2366.40	23.91	35.42	59.33	74.00	14.67	PK	Vertical
4	2366.40	12.63	35.42	48.05	54.00	5.95	AV	Vertical
5	2390.00	12.45	35.60	48.05	54.00	5.95	AV	Vertical
6	2390.00	22.29	35.60	57.89	74.00	16.11	PK	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	US Deadbolt lock	Product Model:	DSL-090-1
Test By:	June	Test mode:	2.4G Tx (2M)
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	DC 6V		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2338.48	23.74	35.21	58.95	74.00	15.05	PK	Horizontal
2	2338.48	12.71	35.21	47.92	54.00	6.08	AV	Horizontal
3	2358.69	23.71	35.36	59.07	74.00	14.93	PK	Horizontal
4	2358.69	12.71	35.36	48.07	54.00	5.93	AV	Horizontal
5	2390.00	12.62	35.60	48.22	54.00	5.78	AV	Horizontal
6	2390.00	23.24	35.60	58.84	74.00	15.16	PK	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	US Deadbolt lock	Product Model:	DSL-090-1
Test By:	June	Test mode:	2.4G Tx (2M)
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	DC 6V		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2483.50	13.72	35.51	49.23	54.00	4.77	AV	Vertical
2	2483.50	27.58	35.51	63.09	74.00	10.91	PK	Vertical
3	2488.84	12.52	35.50	48.02	54.00	5.98	AV	Vertical
4	2488.84	23.80	35.50	59.30	74.00	14.70	PK	Vertical
5	2492.93	23.39	35.49	58.88	74.00	15.12	PK	Vertical
6	2492.93	12.60	35.49	48.09	54.00	5.91	AV	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	US Deadbolt lock	Product Model:	DSL-090-1
Test By:	June	Test mode:	2.4G Tx (2M)
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	DC 6V		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2483.50	13.13	35.51	48.64	54.00	5.36	AV	Horizontal
2	2483.50	24.79	35.51	60.30	74.00	13.70	PK	Horizontal
3	2488.16	12.69	35.50	48.19	54.00	5.81	AV	Horizontal
4	2488.16	23.98	35.50	59.48	74.00	14.52	PK	Horizontal
5	2491.66	23.86	35.50	59.36	74.00	14.64	PK	Horizontal
6	2491.66	12.56	35.50	48.06	54.00	5.94	AV	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	US Deadbolt lock	Product Model:	DSL-090-1
Test By:	June	Test mode:	2.4G Tx (S2)
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	DC 6V		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2342.80	24.01	35.24	59.25	74.00	14.75	PK	Vertical
2	2342.80	12.86	35.24	48.10	54.00	5.90	AV	Vertical
3	2365.64	23.96	35.41	59.37	74.00	14.63	PK	Vertical
4	2365.64	12.84	35.41	48.25	54.00	5.75	AV	Vertical
5	2390.00	12.43	35.60	48.03	54.00	5.97	AV	Vertical
6	2390.00	22.03	35.60	57.63	74.00	16.37	PK	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	US Deadbolt lock	Product Model:	DSL-090-1
Test By:	June	Test mode:	2.4G Tx (S2)
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	DC 6V		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2343.74	23.89	35.25	59.14	74.00	14.86	PK	Horizontal
2	2343.74	12.87	35.25	48.12	54.00	5.88	AV	Horizontal
3	2363.95	24.26	35.40	59.66	74.00	14.34	PK	Horizontal
4	2363.95	12.56	35.40	47.96	54.00	6.04	AV	Horizontal
5	2390.00	12.49	35.60	48.09	54.00	5.91	AV	Horizontal
6	2390.00	22.95	35.60	58.55	74.00	15.45	PK	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	US Deadbolt lock	Product Model:	DSL-090-1
Test By:	June	Test mode:	2.4G Tx (S2)
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	DC 6V		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2483.50	12.79	35.51	48.30	54.00	5.70	AV	Vertical
2	2483.50	25.70	35.51	61.21	74.00	12.79	PK	Vertical
3	2488.67	12.48	35.50	47.98	54.00	6.02	AV	Vertical
4	2488.67	23.84	35.50	59.34	74.00	14.66	PK	Vertical
5	2493.42	24.07	35.49	59.56	74.00	14.44	PK	Vertical
6	2493.42	12.35	35.49	47.84	54.00	6.16	AV	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	US Deadbolt lock	Product Model:	DSL-090-1
Test By:	June	Test mode:	2.4G Tx (S2)
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	DC 6V		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2483.50	12.73	35.51	48.24	54.00	5.76	AV	Horizontal
2	2483.50	23.76	35.51	59.27	74.00	14.73	PK	Horizontal
3	2488.23	12.61	35.50	48.11	54.00	5.89	AV	Horizontal
4	2488.23	24.02	35.50	59.52	74.00	14.48	PK	Horizontal
5	2492.80	24.17	35.49	59.66	74.00	14.34	PK	Horizontal
6	2492.80	12.84	35.49	48.33	54.00	5.67	AV	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	US Deadbolt lock	Product Model:	DSL-090-1
Test By:	June	Test mode:	2.4G Tx (S8)
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	DC 6V		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2339.89	24.25	35.22	59.47	74.00	14.53	PK	Vertical
2	2339.89	12.82	35.22	48.04	54.00	5.96	AV	Vertical
3	2366.30	24.06	35.42	59.48	74.00	14.52	PK	Vertical
4	2366.30	12.72	35.42	48.14	54.00	5.86	AV	Vertical
5	2390.00	12.47	35.60	48.07	54.00	5.93	AV	Vertical
6	2390.00	22.12	35.60	57.72	74.00	16.28	PK	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	US Deadbolt lock	Product Model:	DSL-090-1
Test By:	June	Test mode:	2.4G Tx (S8)
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	DC 6V		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2337.82	24.29	35.20	59.49	74.00	14.51	PK	Horizontal
2	2337.82	12.59	35.20	47.79	54.00	6.21	AV	Horizontal
3	2368.37	23.97	35.43	59.40	74.00	14.60	PK	Horizontal
4	2368.37	13.02	35.43	48.45	54.00	5.55	AV	Horizontal
5	2390.00	12.59	35.60	48.19	54.00	5.81	AV	Horizontal
6	2390.00	22.56	35.60	58.16	74.00	15.84	PK	Horizontal

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	US Deadbolt lock	Product Model:	DSL-090-1
Test By:	June	Test mode:	2.4G Tx (S8)
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	DC 6V		




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2483.50	12.75	35.51	48.26	54.00	5.74	AV	Vertical
2	2483.50	23.96	35.51	59.47	74.00	14.53	PK	Vertical
3	2488.62	12.58	35.50	48.08	54.00	5.92	AV	Vertical
4	2488.62	24.35	35.50	59.85	74.00	14.15	PK	Vertical
5	2492.32	23.50	35.49	58.99	74.00	15.01	PK	Vertical
6	2492.32	12.65	35.49	48.14	54.00	5.86	AV	Vertical

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Product Name:	US Deadbolt lock	Product Model:	DSL-090-1
Test By:	June	Test mode:	2.4G Tx (S8)
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	DC 6V		



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2483.50	12.87	35.51	48.38	54.00	5.62	AV	Horizontal
2	2483.50	25.19	35.51	60.70	74.00	13.30	PK	Horizontal
3	2488.34	12.64	35.50	48.14	54.00	5.86	AV	Horizontal
4	2488.34	23.58	35.50	59.08	74.00	14.92	PK	Horizontal
5	2493.26	23.75	35.49	59.24	74.00	14.76	PK	Horizontal
6	2493.26	12.49	35.49	47.98	54.00	6.02	AV	Horizontal


Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

5.4 Emissions in Non-restricted Frequency Bands

Below 1GHz:

Product Name:	US Deadbolt lock	Product Model:	DSL-090-1
Test By:	June	Test mode:	2.4G Tx (1M)
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Vertical & Horizontal
Test Voltage:	DC 6V		



Critical Freqs

Frequency (MHz)	MaxPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
165.703000	22.00	33.50	11.50	100.0	V	249.0	-14.9
206.540000	28.03	33.50	5.47	100.0	V	179.0	-17.7
398.309000	23.72	36.00	12.28	100.0	V	58.0	-11.8
579.990000	28.21	36.00	7.79	100.0	V	346.0	-7.6
893.542500	27.40	36.00	8.60	100.0	V	335.0	-1.7
966.632000	28.14	44.00	15.86	100.0	V	191.0	-0.2

Remark:

1. Level = Reading + Factor(Antenna Factor + Cable Loss – Preamplifier Factor).

Above 1GHz:

2.4G Tx (1M PHY)						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4804.00	54.43	-9.08	45.35	74.00	28.65	Vertical
4804.00	56.37	-9.08	47.29	74.00	26.71	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4804.00	46.95	-9.08	37.87	54.00	16.13	Vertical
4804.00	47.26	-9.08	38.18	54.00	15.82	Horizontal
Test channel: Middle channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4884.00	54.82	-8.59	46.23	74.00	27.77	Vertical
4884.00	56.68	-8.59	48.09	74.00	25.91	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4884.00	47.32	-8.59	38.73	54.00	15.27	Vertical
4884.00	47.02	-8.59	38.43	54.00	15.57	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4960.00	54.66	-8.03	46.63	74.00	27.37	Vertical
4960.00	56.34	-8.03	48.31	74.00	25.69	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4960.00	47.26	-8.03	39.23	54.00	14.77	Vertical
4960.00	47.16	-8.03	39.13	54.00	14.87	Horizontal
Remark: 1. Level = Reading + Factor. 2. Test Frequency up to 25GHz, and the emission levels of other frequencies are lower than the limit 20dB, not show in test report.						

2.4G Tx (2M PHY)						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4804.00	55.06	-9.08	45.98	74.00	28.02	Vertical
4804.00	56.73	-9.08	47.65	74.00	26.35	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4804.00	47.42	-9.08	38.34	54.00	15.66	Vertical
4804.00	47.06	-9.08	37.98	54.00	16.02	Horizontal
Test channel: Middle channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4884.00	55.08	-8.59	46.49	74.00	27.51	Vertical
4884.00	57.17	-8.59	48.58	74.00	25.42	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4884.00	47.12	-8.59	38.53	54.00	15.47	Vertical
4884.00	47.03	-8.59	38.44	54.00	15.56	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4960.00	54.95	-8.03	46.92	74.00	27.08	Vertical
4960.00	57.37	-8.03	49.34	74.00	24.66	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4960.00	46.91	-8.03	38.88	54.00	15.12	Vertical
4960.00	46.89	-8.03	38.86	54.00	15.14	Horizontal
Remark: 1. Level = Reading + Factor. 2. Test Frequency up to 25GHz, and the emission levels of other frequencies are lower than the limit 20dB, not show in test report.						

BEL Tx (Coded PHY, S=2)						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4804.00	55.32	-9.08	46.24	74.00	27.76	Vertical
4804.00	57.51	-9.08	48.43	74.00	25.57	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4804.00	47.01	-9.08	37.93	54.00	16.07	Vertical
4804.00	46.87	-9.08	37.79	54.00	16.21	Horizontal
Test channel: Middle channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4884.00	54.90	-8.59	46.31	74.00	27.69	Vertical
4884.00	57.03	-8.59	48.44	74.00	25.56	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4884.00	46.80	-8.59	38.21	54.00	15.79	Vertical
4884.00	47.07	-8.59	38.48	54.00	15.52	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4960.00	54.95	-8.03	46.92	74.00	27.08	Vertical
4960.00	57.19	-8.03	49.16	74.00	24.84	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4960.00	46.90	-8.03	38.87	54.00	15.13	Vertical
4960.00	47.39	-8.03	39.36	54.00	14.64	Horizontal
Remark: 1. Level = Reading + Factor. 2. Test Frequency up to 25GHz, and the emission levels of other frequencies are lower than the limit 20dB, not show in test report.						

BEL Tx (Coded PHY, S=8)						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4804.00	54.68	-9.08	45.60	74.00	28.40	Vertical
4804.00	57.20	-9.08	48.12	74.00	25.88	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4804.00	46.61	-9.08	37.53	54.00	16.47	Vertical
4804.00	47.12	-9.08	38.04	54.00	15.96	Horizontal
Test channel: Middle channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4884.00	54.70	-8.59	46.11	74.00	27.89	Vertical
4884.00	57.40	-8.59	48.81	74.00	25.19	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4884.00	46.53	-8.59	37.94	54.00	16.06	Vertical
4884.00	47.60	-8.59	39.01	54.00	14.99	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4960.00	54.34	-8.03	46.31	74.00	27.69	Vertical
4960.00	57.40	-8.03	49.37	74.00	24.63	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBμV)	Factor (dB)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
4960.00	46.93	-8.03	38.90	54.00	15.10	Vertical
4960.00	47.36	-8.03	39.33	54.00	14.67	Horizontal
Remark: 1. Level = Reading + Factor. 2. Test Frequency up to 25GHz, and the emission levels of other frequencies are lower than the limit 20dB, not show in test report.						

-----End of report-----