

FCC ID : 2ASWB-S12

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

11.1 Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d = Power density in mW/cm²

P_{out} =output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π =3.1416

R= distance between observation point and center of the radiator in cm (R=20cm)

Pd the limit of MPE, $1\text{mW}/\text{cm}^2$. If we know the maximum gain of the nd total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

11.2 Measurement Result

Tune-up power

Mode	2.4G WLAN
802.11b	11±1 dBm
802.11g	16±1 dBm
802.11n HT20	18±1 dBm

Antenna Gain: 2.0dBi
WIFI

Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm2)	Power density Limits (mW/cm2)
802.11b	2412	18.39	11±1	12	1.585	0.0050	1
	2437	18.11	11±1	12	1.585	0.0050	1
	2462	17.91	11±1	12	1.585	0.0050	1
802.11g	2412	22.33	16±1	17	1.585	0.0158	1
	2437	22.08	16±1	17	1.585	0.0158	1
	2462	21.87	16±1	17	1.585	0.0158	1
802.11n (HT20)	2412	21.13	18±1	19	1.585	0.0250	1
	2437	21.10	18±1	19	1.585	0.0250	1
	2462	20.84	18±1	19	1.585	0.0250	1

Sincerely,

Yonghua Huang

Signature

Yonghua Huang/Certification Engineer

Company Name: Ecovacs Robotics Co Ltd

Address: NO 108 SHI HU RD (W) WU ZHONG ZONE, SUZHOU, JIANGSU, 215128, CN