

FCC ID:2A6FW-Y813BT

RF EXPOSURE EVALUATION

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)	
	(A) Limits	for Occupational/Controlled	Exposures		
0.3–3.0	614	1.63	*(100)	6	
3.0–30	1842/f	4.89/f	*(900/f ²)	6	
30–300	61.4	0.163	1.0	6	
300–1500			f/300	6	
1500–100,000			5	6	
	(B) Limits for	General Population/Uncontro	olled Exposure		
0.3–1.34	614	1.63 *(100)		30	
1.34–30	824/f	2.19/f	*(180/f ²)	30	
30–300	27.5	0.073	0.2	30	
300–1500		-	f/1500	30	
1500–100,000			1.0	30	

f = frequency in MHz

Friis transmission formula: Pd = (Pout*G)/(4*pi*r²)

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW;

G = gain of antenna in linear scale, Pi = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

Shenzhen ZKT Technology Co., Ltd. 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, Chin





Test Result of RF Exposure Evaluation

				BT				
Mode	Frequency	Output power	Tune-up power	Max tune-up power	Max tune-up power	Power Density at R=20cm	Limit	Result
	(MHz)	(dBm)	(dBm)	(dBm)	(mW)	(mW/cm ²)	(mW/cm ²)	
GFSK	2480	6.262	6±1	7	5.01	0.002054	1.0	PASS
π/4-DQPSK	2480	6.285	6±1	7	5.01	0.002054	1.0	PASS
8-DPSK	2480	6.165	6±1	7	5.01	0.002054	1.0	PASS
	S			BLE				
Mode	Frequency	Output power	Tune-up power	Max tune-up power	Max tune-up power	Power Density at R=20cm	Limit	Result
	(MHz)	(dBm)	(dBm)	(dBm)	(mW)	(mW/cm ²)	(mW/cm ²)	
GFSK	2480	6.223	6±1	7	5.01	0.002054	1.0	PASS

Note: Antenna Gain = 3.14dBi

The device can not transmit with BT and BLE simultaneously.

Shenzhen ZKT Technology Co., Ltd. 1/F, No. 101, Building B, No. 6, Tangwel Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen,China

