





(3 times you had her) III Mose Switch Summ 3 Feet Balber 2 m behane k

Plane on

Plane and find the paper buffer by a account the adapter and automatically arms
to parting some. Overagifies they, the UE behavior 6.8.8 will observably that blue. If the education discourse a presidually convented device. It will convent. If not, it will wait for a new derival to by to consect to WHMs is inversed. If we connection is made affair a nomine, the adapter self-extraordically shall determine the  $\alpha$ · Proper and held the paper bullion for I assessed State V Self Inde Japa vid Subment Self Inde 14

**Basic Operation** 





## I. Not a CRE Type C spins and content the pringles to any active Type I port. 3. The Peace LEO Indicator will have writte and Radi when extents in changing

- No recommend changing the put for at least 2 hours before using it for the first time. ■Weet the polypter realist to used continuously the longer. Note the belony tests, it can be
- connected to a changing power expely within you are using it.

  It is not recommended that you was tire function frequently, because it you affect.
  the service life of the lasting.

How to use-Pairing in RX mode

- 3. Set the adjuster to RV roads and roads and one and of a 3 Swee audio cable / plus into the applicated the elegistra Joseph the other and into your blooksharkeds. audio resistinte disclosi l'associate historial, atr. ()
- 3. Press and hald the power button of the adapter for 1 seconds to turn it on and arrier pairing mode. The LID indicator A and E of the edupter will afterwardly flack
- 3. Activate the Bioment Automore or your transmitting device
- (pittors), billist, etc.) and search for hearing filestools (feetow). A find  $^{\circ}$  TL  $^{\circ}$  in the search weaths and tap on it to connect. Dross convented, the (ES) indicator is on the adapter will be salid binar. Per (ED) indicator 8 will be off.

to parting those, if there is no Blasticoth those connected to the property the Blasticoth Indicates high well finds for I mendes and the adaptic will shall describe. adventicity. Was the first assembly connection, if the adapter and blanks the Section and Sectional conception, the adaptive and Structural Section and convent

(If Charging Fort

44

- 1. Follow the previous instructions in the " New to see painting in MI mode section to pair the adapter with your first above.
- 2. Moutile citch the edisphal "MYS" harbor to enter painting mode ( The US): indicator A/R of the laborar will alternately fact titue.
- 8. Turn on the second Statement assets. Find "12" in the count mouth and los-
- 4. After painting is completed, the LED indicators 4 and 8 of the adapter will burn this and remain on. At this time, the edigric has already connected to her Burkovite devices considerancies

- · Only site decise carrying must Persugh the playing at any time. You have to stop the result one the one denice to play on the other.
- · Wast the adapter is parent with the spring Bluetach spore. We list Sharmon's decision and not obscurrency have the adapter. All the adjuster is already connected to two Bigetisets decrees pleutomenants
- mustle (Sch the "NFR" butter, and the adapter direct arter parting result-

## How to use-Pairing in TX mode



Not the subplies to 15 coronel if to prior floorishability device | belonium, made player, als: 1 cornect and end of a 5 from audio calls / play into the scalls part of the subplier and the other and into the audio sub past of the floorishability device.

- 4) 1.5 cm function to 2 NCA make valid to substitute the connecting the orderine to 4 TV arithmen's 1.5 cm and to corput just. This valid is included to the patchage.

In TX mode, the adapter is able to pair with few Wastandh sience exphonent/species at the same time.

2. Politics the province individuals in the "New to our puring in TX mode senten-to part the adapter with your feet feature.

- 2 , Goodste Click the Julignor "MER" bottom to writer pairing mode ( The LES) indicator A/B of the subpter will alternately fluid blood.
- 3 . Turn on the second Blueborth device . Make sure this device is also in parmy
- After parting in completed, the IXD traillation A and B of the adopter will been blue out terrain on. At this time, the adapter has arrestly intrested to bee Blankwill decrease simultaneously.

2.6

P-11

- Where you pain with two decision both care play recall, at the caree time.

# How to connect to your TV with Bluetooth adapter?

Sing 2: Using the 3-time states with own provided to convery your TO to the adapter the No world. Long proof this power fluction of the adaptes like 16 model, there have an your fluctioned insolute to when drawn and long is your to the adaptes. Bit for the powering is accorded, your structure and to to have your Yorking this beatlest.



they is for HCX this section. Hence they she the part labored "dudle set", two or two part will



Mag & Simment the 3.5 feet pushes solder in the NSA and nanoprior solds that we perceived Previous Willia common your To be the adapter for TK model, Turn-on your Municipi hapdon or other decision and and room in each fee degree! After the pairing to occasion in our decision for solution been placed to the region from feedbal.



## PRECAUTIONS

m-24

## **Officetoeth®**

The Shartenini " ward must and organ are regressed treatments cannot by Shartenin WL Inc. And my use of tauth mosts by harveylepige international inc. is used frames. Other trademarks and trade comes are from all their registrion services.



SIZE:92\*110MM

T1\_User Manual\_20240515\_v1.0

FECERÓNS O ....

mia

F12

P.7

# **FCC Warning**

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

**Note:** This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- -Reorient or relocate the receiving antenna.
- -Increase the separation between the equipment and receiver.
- -Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
  - -Consult the dealer or an experienced radio/TV technician for help.

## Radiation Exposure Statement

To comply with FCC RF exposure compliance requirements, this grant is applicable to only mobile configurations. The antennas used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter.

# **IC Warning**

- English: This device contains licence-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's licence-exempt RSS(s). Operation is subject to the following two conditions:
- 1. This device may not cause interference.
- 2. This device must accept any interference, including interference that may cause undesired operation of the device.
- French: Cet appareil contient des émetteurs/récepteurs exemptés de licence qui sont conformes aux RSS exemptés de licence d'innovation, sciences et développement économique Canada. Le fonctionnement est soumis aux deux conditions suivantes:
- 1. Cet appareil ne peut pas causer d'interférences.
- 2. Cet appareil doit accepter toute interférence, y compris les interférences qui peuvent causer un fonctionnement indésirable de l'appareil.

## Radiation Exposure Statement

To comply with FCC RF exposure compliance requirements, this grant is applicable to only mobile configurations. The antennas used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter.

Pour se conformer aux exigences de conformité d'exposition RF de la FCC, cette subvention est applicable uniquement aux configurations mobiles. Les antennes utilisées pour cet émetteur doivent être installées de manière à fournir une distance de séparation d'au moins 20 cm de toutes les personnes et ne doivent pas être colocalisées ou fonctionner conjointement avec toute autre antenne ou émetteur.