

A home heat monitor to suit your corporate needs.



INPUT

Hall Effect Module

REPORTING & OUTPUTS

Reporting	Tank level (5% variation)
	Low battery
	High/Excessive draw
	Fill Detection
	Temperature
Data Interface	API
	Email (to supplier and/or consumer)
	Raw data
	Online dashboard
	Client mobile app
Automated Testing	Network status
	Lead sensor status
	Battery status

ELECTRICAL SPECIFICATIONS

Battery Pack 3 Volts Model 123 Lithium

RADIO SPECIFICATIONS

Technologies Bluetooth

ENVIRONMENTAL SPECIFICATIONS

Operating & storage temp. range	-40 °C to 60 °C	-40 °F to 140 °F
Relative humidity range	0% to 100%	
Enclosure rating	IP68	
Warranty	5+ years	

CERTIFICATIONS

Monitors are third-party QPS Evaluation Services Inc. certified for use in hazardous locations

Approved for Class 1, Div. 2, Groups C&D T3, and ISSED, FCC

DIMENSIONS

Height	5.12 cm	2 in
Width	5.36 cm	2.11 in
Depth	4.81 cm	1.9 in

OPTION

GPS (mobile tank)

ORDERING TM5030BG-GA3020
TM6030BG