

FCC AND IC CERTIFICATION TEST REPORT

FOR

Applicant	:	ION Audio, LLC
Address	:	200 Scenic View Drive, Cumberland, RI 02864 U.S.A.
Equipment under Test	:	HIGH-POWER BLUETOOTH PA SYSTEM WITH LIGHTS
Model No.	:	TOTAL PA GLOW 3, TOTAL PA SUPREME, TOTAL PA PREMIER
Project Code	:	iPA122, iPA123, iPA126
Trade Mark	:	
FCC ID	:	2AB3E-IPA123
IC	:	10541A-IPA123
Manufacturer	:	ION Audio, LLC
Address	:	200 Scenic View Drive, Cumberland, RI 02864 U.S.A.

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan
City, Guangdong Province, China, 523808

Tel: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

REPORT

TABLE OF CONTENTS

	Test report declares.....	4
1.	Summary of test results	6
2.	General test information.....	7
2.1.	Description of EUT	7
2.2.	Accessories of EUT.....	8
2.3.	Assistant equipment used for test.....	8
2.4.	Block diagram of EUT configuration for test	8
2.5.	Deviations of test standard.....	8
2.6.	Test environment conditions	9
2.7.	Test laboratory	9
2.8.	Measurement uncertainty.....	9
3.	Equipment used during test	10
4.	Maximum Peak Output Power	11
4.1.	Block diagram of test setup.....	11
4.2.	Limits	11
4.3.	Test Procedure.....	11
4.4.	Test Result	11
4.5.	Original test data	12
5.	20dB Bandwidth and 99% Bandwidth.....	14
5.1.	Block diagram of test setup.....	14
5.2.	Limits	14
5.3.	Test Procedure.....	14
5.4.	Test Result	14
5.5.	Original test data	15
6.	Carrier Frequency Separation.....	17
6.1.	Block diagram of test setup.....	17
6.2.	Limits	17
6.3.	Test Procedure.....	17
6.4.	Test Result	17
6.5.	Original test data	17
7.	Number Of Hopping Channel.....	19
7.1.	Block diagram of test setup.....	19
7.2.	Limits	19
7.3.	Test Procedure.....	19
7.4.	Test Result	19
7.5.	Original test data	19
8.	Dwell Time.....	21

8.1.	Block diagram of test setup.....	21
8.2.	Limits	21
8.3.	Test Procedure.....	21
8.4.	Test Result	21
8.5.	Original test data	22
9.	Band Edge Compliance (conducted method).....	26
9.1.	Block diagram of test setup.....	26
9.2.	Limit.....	26
9.3.	Test result.....	26
9.4.	Original test data	26
10.	Radiated emission.....	30
10.1.	Block diagram of test setup.....	30
10.2.	Limit.....	31
10.3.	Test Procedure.....	32
10.4.	Test result.....	34
11.	RF Conducted Spurious Emissions	38
11.1.	Block diagram of test setup.....	38
11.2.	Limits	38
11.3.	Test Procedure.....	38
11.4.	Test Result	39
11.5.	Original test data	39
12.	Band Edge Compliance (radiated method).....	46
12.1.	Block diagram of test setup.....	46
12.2.	Limit.....	46
12.3.	Test Procedure.....	46
12.4.	Test result.....	46
13.	Power Line Conducted Emission.....	55
13.1.	Block diagram of test setup.....	55
13.2.	Power Line Conducted Emission Limits	55
13.3.	Test Procedure.....	55
13.4.	Test Result	56
14.	Antenna Requirements	59
14.1.	Limit.....	59
14.2.	Result	59
15.	Test setup photograph	60
16.	Photos of the EUT	62

TEST REPORT DECLARE

Applicant	:	ION Audio, LLC
Address	:	200 Scenic View Drive, Cumberland, RI 02864 U.S.A.
Equipment under Test	:	HIGH-POWER BLUETOOTH PA SYSTEM WITH LIGHTS
Model No.	:	TOTAL PA GLOW 3, TOTAL PA SUPREME, TOTAL PA PREMIER
Trade mark	:	
Manufacturer	:	ION Audio, LLC
Address	:	200 Scenic View Drive, Cumberland, RI 02864 U.S.A.

Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C, RSS-247 Issue 2 February 2017.

Test procedure used:

ANSI C63.10:2013, RSS-Gen Issue 5, March 2019 Amendment 1.

We Declare:

The equipment described above is tested by Dongguan Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Dongguan Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC&IC standards.

Report No.:	DDT-R19082907-1E4		
Date of Receipt:	Oct. 21, 2019	Date of Test:	Oct. 21, 2019 ~ Nov. 25, 2019

Prepared By:

Approved By:

Sam Li/Engineer

Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision history

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Nov. 25, 2019	

1. Summary of test results

Description of Test Item	Standard	Results
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1) ANSI C63.10:2013 RSS-247 Issue 2	PASS
20dB Bandwidth and 99% Bandwidth	FCC Part 15: 15.215 ANSI C63.10:2013 RSS-247 Issue 2	PASS
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1) ANSI C63.10:2013 RSS-247 Issue 2	PASS
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10:2013 RSS-247 Issue 2	PASS
Dwell Time	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10:2013 RSS-247 Issue 2	PASS
Radiated Emission	FCC Part 15: 15.209 FCC Part 15: 15.247(d) ANSI C63.10:2013 RSS-247 Issue 2 RSS-Gen Issue 5	PASS
Band Edge Compliance	FCC Part 15: 15.247(d) ANSI C63.10:2013 RSS-247 Issue 2 RSS-Gen Issue 5	PASS
Power Line Conducted Emissions	FCC Part 15: 15.207 ANSI C63.10:2013 RSS-Gen Issue 5	PASS
Antenna requirement	FCC Part 15: 15.203 RSS-Gen Issue 5	PASS

2. General test information

2.1. Description of EUT

EUT* Name	: HIGH-POWER BLUETOOTH PA SYSTEM WITH LIGHTS
Model Number	: TOTAL PA GLOW 3, TOTAL PA SUPREME, TOTAL PA PREMIER
Difference of model number	: All models are identical except the appearance and model number, therefore the test performed on the model TOTAL PA GLOW 3.
EUT function description	: Please reference user manual of this device
Power supply	: 100-120V~, 50/60Hz
Radio Specification	: Bluetooth V5.0
Operation frequency	: 2402MHz-2480MHz
Modulation	: GFSK, $\pi/4$ -DQPSK
Data rate	: 1Mbps, 2Mbps
Antenna Type	: Integral PCB antenna, maximum PK gain: -0.58 dBi
Sample Type	: Series production

Note: EUT is the ab. of equipment under test.

Channel information					
Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	27	2429MHz	54	2456MHz
1	2403MHz	28	2430MHz	55	2457MHz
2	2404MHz	29	2431MHz	56	2458MHz
3	2405MHz	30	2432MHz	57	2459MHz
4	2406MHz	31	2433MHz	58	2460MHz
5	2407MHz	32	2434MHz	59	2461MHz
6	2408MHz	33	2435MHz	60	2462MHz
7	2409MHz	34	2436MHz	61	2463MHz
8	2410MHz	35	2437MHz	62	2464MHz
9	2411MHz	36	2438MHz	63	2465MHz
10	2412MHz	37	2439MHz	64	2466MHz
11	2413MHz	38	2440MHz	65	2467MHz
12	2414MHz	39	2441MHz	66	2468MHz
13	2415MHz	40	2442MHz	67	2469MHz
14	2416MHz	41	2443MHz	68	2470MHz
15	2417MHz	42	2444MHz	69	2471MHz
16	2418MHz	43	2445MHz	70	2472MHz
17	2419MHz	44	2446MHz	71	2473MHz
18	2420MHz	45	2447MHz	72	2474MHz
19	2421MHz	46	2448MHz	73	2475MHz
20	2422MHz	47	2449MHz	74	2476MHz
21	2423MHz	48	2450MHz	75	2477MHz
22	2424MHz	49	2451MHz	76	2478MHz
23	2425MHz	50	2452MHz	77	2479MHz
24	2426MHz	51	2453MHz	78	2480MHz
25	2427MHz	52	2454MHz		
26	2428MHz	53	2455MHz		


2.2. Accessories of EUT

Description of Accessories	Manufacturer	Model number	Serial No.	Other
Microphone	N/A	N/A	N/A	Length: 4.50m, shielded
AC cable	N/A	N/A	N/A	Length: 1.5m, unshielded
Remote control	N/A	N/A	N/A	N/A
Factory 1: Built-in LED power board	Guangzhou brilliant electronic co. LTD	N/A	N/A	Alternative
Factory 2: Built-in LED power board	Guangzhou Yongchen Technology Co., Ltd	N/A	N/A	
Factory 1: Transformer	NINGGO ZHONG CE E.T ELECTRONICS CO.LTD	N/A	N/A	Alternative
Factory 2: Transformer	Ningbo Rongqian Electrical Appliance Co.,Ltd	N/A	N/A	

2.3. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	EMC Compliance	SN
Notebook	Lenovo Beijing Co. Ltd.	ThinkPad	FCC/CE	TP00015A

2.4. Block diagram of EUT configuration for test



Test software: FCC Assist.EXE

The test software was used to control EUT work in Continuous Tx mode, and select test channel, wireless mode as below table.

Tested mode, channel, information		
Mode	Channel	Frequency (MHz)
GFSK hopping on Tx mode	CH0 to CH78	2402 to 2480
$\pi/4$ -DQPSK hopping on Tx mode	CH0 to CH78	2402 to 2480
GFSK hopping off Tx mode	CH0	2402
	CH39	2441
	CH78	2480
$\pi/4$ -DQPSK hopping off Tx mode	CH0	2402
	CH39	2441
	CH78	2480

2.5. Deviations of test standard

No Deviation.

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	21-25°C
Humidity range:	40-75%
Pressure range:	86-106kPa

2.7. Test laboratory

Dongguan Dongdian Testing Service Co., Ltd

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

Tel: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com

CNAS Accreditation No. L6451; A2LA Accreditation No. 3870.01

Designation Number: CN1182; Test Firm Registration Number: 540522

Industry Canada site registration number: 10288A-1

2.8. Measurement uncertainty

Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power (Conducted) (Spectrum analyzer)	0.86dB (10MHz ≤ f < 3.6GHz); 1.38dB (3.6GHz ≤ f < 8GHz)
Peak Output Power (Conducted) (Power Sensor)	0.74dB
Power Spectral Density	0.74dB (10MHz ≤ f < 3.6GHz); 1.38dB (3.6GHz ≤ f < 8GHz)
Frequencies Stability	6.7 × 10 ⁻⁸ (Antenna couple method) 5.5 × 10 ⁻⁸ (Conducted method)
Conducted spurious emissions	0.86dB (10MHz ≤ f < 3.6GHz); 1.40dB (3.6GHz ≤ f < 8GHz) 1.66dB (8GHz ≤ f < 22GHz)
Uncertainty for radio frequency (RBW<20kHz)	3×10 ⁻⁸
Temperature	0.4°C
Humidity	2%
Uncertainty for Radiation Emission test (30MHz-1GHz)	4.70dB (Antenna Polarize: V) 4.84dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1GHz-40GHz)	4.10dB (1-6GHz) 4.40dB (6GHz-18GHz) 3.54dB (18GHz-26GHz) 4.30dB (26GHz-40GHz)
Uncertainty for Power line conduction emission test	3.32dB (150kHz-30MHz)

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.


3. Equipment used during test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
RF Connected Test (Tonscend RF Measurement System)					
Spectrum analyzer	R&S	FSU26	200071	Sep. 29, 2019	1 Year
Spectrum analyzer	R&S	FSU26	201124	Sep. 29, 2019	1 Year
Wideband Radio Communication tester	R&S	CMW500	117491	Jun. 25, 2019	1 Year
Vector Signal Generator	Agilent	E8267D	US49060192	Sep. 29, 2019	1 Year
Vector Signal Generator	Agilent	N5182A	MY48180737	Jun. 25, 2019	1 Year
Power Sensor	Agilent	U2021XA	MY55150010	Jun. 28, 2019	1 Year
Power Sensor	Agilent	U2021XA	MY55150011	Jun. 28, 2019	1 Year
Temp & Humi Programmable	ZHIXIANG	ZXGDJS-150L	ZX170110-A	Sep. 29, 2019	1 Year
Test Software	JS Tonscent	JS1120-3	Ver.2.7	N/A	N/A
USB Data acquisition	Agilent	U2531A	TW55043503	N/A	N/A
Radiation 2#chamber (below 1G)					
Test Receiver	R&S	ESCI	100551	Sep. 29, 2019	1 Year
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	9163-994	Nov. 15, 2019	1 Year
RF Cable	MI Cable	N/A	DDT-F02-233	Sep. 29, 2019	1 Year
RF Cable	MI Cable	N/A	DDT-F02-234	Sep. 29, 2019	1 Year
RF Cable	MI Cable	N/A	DDT-F02-235	Sep. 29, 2019	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A
Radiation 1#chamber (above 1G)					
EMI Test Receiver	R&S	ESU8	100316	Sep. 29, 2019	1 Year
Spectrum analyzer	Agilent	E4447A	MY50180031	Jun. 25, 2019	1 Year
Trilog Broadband Antenna	Schwarzbeck	VULB9163	9163-462	Nov. 15, 2019	1 Year
Active Loop antenna	Schwarzbeck	FMZB-1519	1519-038	Sep. 29, 2019	1 Year
Double Ridged Horn Antenna	R&S	HF907	100276	Nov. 15, 2019	1 Year
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	790	Sep. 29, 2019	1 Year
Pre-amplifier	TERA-MW	TRLA-0040 G35	101303	Sep. 29, 2019	1 Year
RF Cable	HUBSER	CP-X2+ CP-X1	W11.03+ W12.02	Sep. 29, 2019	1 Year
RF Cable	N/A	SMAJ-SMAJ -1M+11M	17070133+17070131	Sep. 29, 2019	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A
Power Line Conducted Emissions Test					
Test Receiver	R&S	ESU8	100316	Sep. 29, 2019	1 Year
LISN 1	R&S	ENV216	101109	Sep. 29, 2019	1 Year
LISN 2	R&S	ESH2-Z5	100309	Sep. 29, 2019	1 Year
Pulse Limiter	R&S	ESH3-Z2	101242	Sep. 29, 2019	1 Year
CE Cable 1	HUBSER	ESU8/RF2	W10.01	Sep. 29, 2019	1 Year

Test software	Audix	E3	V 6.11111b	N/A	N/A
---------------	-------	----	------------	-----	-----

4. Maximum Peak Output Power

4.1. Block diagram of test setup



4.2. Limits

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W.

4.3. Test Procedure


- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) Measure the maximum output power of EUT by spectrum analyzer with PK detector and RBW=3MHz (above 20dB bandwidth of measured signal), VBW=10MHz


Note: The attenuator loss was inputted into spectrum analyzer as amplitude offset.

4.4. Test Result

Mode	Antenna	Freq (MHz)	Result (dBm)	Limit (dBm)	Conclusion
GFSK	ANT1	2402	1.62	21	PASS
	ANT1	2441	2.56	21	PASS
	ANT1	2480	2.87	21	PASS
$\pi/4$ -DQPSK	ANT1	2402	2.07	21	PASS
	ANT1	2441	2.92	21	PASS
	ANT1	2480	3.18	21	PASS


4.5. Original test data






Date: 20.NOV.2019 13:12:13

2DH5_ANT1_2441



Date: 20.NOV.2019 13:12:49

2DH5_ANT1_2480



Date: 20.NOV.2019 13:13:15

5. 20dB Bandwidth and 99% Bandwidth

5.1. Block diagram of test setup

Same as section 4.1

5.2. Limits

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.


5.3. Test Procedure


- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30 kHz RBW and 100 kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

5.4. Test Result

Mode	Freq. (MHz)	20dB bandwidth Result (MHz)	99% bandwidth Result (MHz)	Conclusion
GFSK	2402	0.951	0.852	PASS
	2441	0.954	0.855	PASS
	2480	0.951	0.852	PASS
$\pi/4$ -DQPSK	2402	1.317	1.197	PASS
	2441	1.314	1.194	PASS
	2480	1.314	1.203	PASS


5.5. Original test data






Date: 19.NOV.2019 14:44:40

2DH5_ANT1_2441



Date: 19.NOV.2019 14:46:32

2DH5_ANT1_2480



Date: 19.NOV.2019 14:48:02

6. Carrier Frequency Separation

6.1. Block diagram of test setup

Same as section 4.1

6.2. Limits

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.


6.3. Test Procedure


- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) The carrier frequency was measured by spectrum analyzer with 100 kHz RBW and 300 kHz VBW.

6.4. Test Result

Mode	Channel separation (MHz)	20dB bandwidth (MHz) (worse case)	Limit (MHz) 2/3 of 20dB bandwidth	Conclusion
GFSK	0.997	0.954	≥ 0.636	PASS
$\pi/4$ -DQPSK	1.000	1.317	≥ 0.878	PASS

6.5. Original test data





7. Number Of Hopping Channel

7.1. Block diagram of test setup

Same as section 4.1

7.2. Limits

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


7.3. Test Procedure


- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) The number of hopping channel was measured by spectrum analyzer with 100 kHz RBW and 300 kHz VBW.

7.4. Test Result

Mode	Number of hopping channel	Limit	Conclusion
GFSK	79	>15	PASS
$\pi/4$ -DQPSK	79	>15	PASS

7.5. Original test data





8. Dwell Time

8.1. Block diagram of test setup

Same as section 4.1

8.2. Limits

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

8.3. Test Procedure


- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$
- (3) Measure the hopping number and on time of each pulse with spectrum analyzer in zero span set, and calculate dwell time with formula $\text{Dwell time} = \text{total hops} \times \text{pulse's on time}$.


8.4. Test Result

Mode	Dwell time (s)	Pulse's on time (ms)	Total hops	Limit	Conclusion
DH1	0.119	0.38	316	<400ms	PASS
DH3	0.184	1.63	113	<400ms	PASS
DH5	0.176	2.88	61	<400ms	PASS
2DH1	0.121	0.39	315	<400ms	PASS
2DH3	0.157	1.64	96	<400ms	PASS
2DH5	0.193	2.89	67	<400ms	PASS

Note: $\text{Dwell time} = \text{total hops} \times \text{pulse's on time}$.


8.5. Original test data






Date: 19.NOV.2019 15:00:08

DH5_ANT1_HOP




Date: 19.NOV.2019 15:00:27




Date: 19.NOV.2019 15:01:01

2DH1_ANT1_HOP




Date: 19.NOV.2019 15:01:23




Date: 19.NOV.2019 15:01:57

2DH3_ANT1_HOP




Date: 19.NOV.2019 15:02:36




Date: 19.NOV.2019 15:03:10

2DH5_ANT1_HOP



Date: 19.NOV.2019 15:03:36



Date: 19.NOV.2019 15:04:10

9. Band Edge Compliance (conducted method)

9.1. Block diagram of test setup

Same as section 4.1


9.2. Limit


All restriction band should comply with 15.209, other emission should be at least 20dB below the fundamental.

9.3. Test result


Mode	Freq (MHz)	Conclusion
GFSK	Hopping off 2402	PASS
	Hopping off 2480	PASS
	Hopping on	PASS
$\pi/4$ -DQPSK	Hopping off 2402	PASS
	Hopping off 2480	PASS
	Hopping on	PASS

9.4. Original test data







DH5_ANT1_Low



DH5_ANT1_High




2DH5_ANT1_Low




Date: 20.NOV.2019 13:12:29

2DH5_ANT1_High



Date: 20.NOV.2019 13:13:25

2DH5_ANT1_Low



Date: 20.NOV.2019 13:17:51


2DH5_ANT1_High




10. Radiated emission

10.1. Block diagram of test setup


In 3m Anechoic Chamber Test Setup Diagram for 9kHz-30MHz



In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test an appropriate high pass filter was inserted in the input port of AMP.

10.2. Limit

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

(2) FCC 15.209 Limit.

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V}/\text{m}$	$\text{dB}(\mu\text{V})/\text{m}$
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Note: (1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000MHz, radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3\text{m}}(\text{dB}\mu\text{V}/\text{m}) = \text{Limit}_{30\text{m}}(\text{dB}\mu\text{V}/\text{m}) + 40\text{Log}(30\text{m}/3\text{m})$$

(3) Limit for this EUT

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions or comply with 15.209 limits.

10.3. Test Procedure

- (1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a semi-anechoic chamber for above 1G.
- (2) Test antenna was located 3m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9kHz-30MHz	Active Loop antenna	3m
30MHz-1GHz	Trilog Broadband Antenna	3m
1GHz-18GHz	Double Ridged Horn Antenna(1GHz-18GHz)	3m
18GHz-40GHz	Horn Antenna(18GHz-40GHz)	1m

According ANSI C63.10:2013 clause 6.4.4.2 and 6.5.3, for measurements below 30 MHz, the loop antenna was positioned with its plane vertical from the EUT and rotated about its vertical axis for maximum response at each azimuth position around the EUT. And the loop antenna also be positioned with its plane horizontal at the specified distance from the EUT. The center of the

loop is 1 m above the ground. for measurement above 30MHz, the Trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9kHz to 25GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1m to 4m (Except loop antenna, it's fixed 1m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9kHz to 25GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18GHz to 25GHz, so below final test was performed with frequency range from 9kHz to 18GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10:2013 on Radiated Emission test.

(5) The emissions from 9kHz to 1GHz were measured based on CISPR QP detector except for the frequency bands 9-90kHz, 110-490kHz, for emissions from 9kHz-90kHz,110kHz-490kHz and above 1GHz were measured based on average detector, for emissions above 1GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9kHz to 1GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9kHz-150kHz	200Hz
150kHz-30MHz	9kHz
30MHz-1GHz	120kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; About Average measure refer to ANSI C63.10:2013 clause 4.1.4.2.2 procedure for average measure).

10.4. Test result

PASS. (See below detailed test result)

All the emissions except fundamental emission from 9 kHz to 25GHz were comply with 15.209 limits.

Note1: According exploratory test no any obvious emission was detected from 9kHz to 30MHz and 18GHz to 25GHz.

Note2: For emissions below 1GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1GHz, the final test was only performed with EUT working in $\pi/4$ -DQPSK, Tx 2480MHz mode.


Note3: For emissions above 1GHz. If peak results comply with AV limit, AV Result is deemed to comply with AV limit.

Radiated Emission test (below 1GHz)

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 2# **E:\2019 RE2# Report Data\Q19082907-1E\20191121 RE.EM6**
Test Date : 2019-11-22 **Tested By** : Van
EUT : HIGH-POWER BLUETOOTH PA SYSTEM WITH LIGHTS **Model Number** : TOTAL PA GLOW 3
Power Supply : AC 120V/60Hz **Test Mode** : Tx mode
Condition : Temp:26.1°C, Humi:59%, Press:101.4kPa **Antenna/Distance** : 2018 VULB 9163 2#/3m/VERTICAL
Memo :

Data: 23



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	50.41	10.95	14.67	3.85	29.47	40.00	-10.53	QP	VERTICAL
2	79.24	21.17	8.14	4.07	33.38	40.00	-6.62	QP	VERTICAL
3	85.90	22.50	9.55	4.12	36.17	40.00	-3.83	QP	VERTICAL
4	191.75	15.05	11.04	4.80	30.89	43.50	-12.61	QP	VERTICAL
5	255.62	21.55	12.89	5.13	39.57	46.00	-6.43	QP	VERTICAL
6	324.46	19.50	14.35	5.49	39.34	46.00	-6.66	QP	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.


2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 2# **E:\2019 RE2# Report Data\Q19082907-1E\20191121 RE.EM6**
Test Date : 2019-11-22 **Tested By** : Van
EUT : HIGH-POWER BLUETOOTH PA SYSTEM WITH LIGHTS **Model Number** : TOTAL PA GLOW 3
Power Supply : AC 120V/60Hz **Test Mode** : Tx mode
Condition : Temp:26.1°C, Humi:59%, Press:101.4kPa **Antenna/Distance** : 2018 VULB 9163 2#/3m/HORIZONTAL
Memo :

Data: 24



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	34.04	11.01	11.94	3.67	26.62	40.00	-13.38	QP	HORIZONTAL
2	73.10	14.05	8.51	4.03	26.59	40.00	-13.41	QP	HORIZONTAL
3	171.39	10.72	9.40	4.69	24.81	43.50	-18.69	QP	HORIZONTAL
4	260.14	19.59	13.02	5.16	37.77	46.00	-8.23	QP	HORIZONTAL
5	324.46	18.81	14.35	5.49	38.65	46.00	-7.35	QP	HORIZONTAL
6	454.31	18.93	16.33	6.10	41.36	46.00	-4.64	QP	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

Radiated Emission test (above 1GHz)

Freq. (MHz)	Read level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit (dBμV/ m)	Margin (dB)	Detector type	Polarization
Tx mode 2402MHz									
4804.00	60.93	31.21	43.84	5.52	53.82	74.00	-20.18	Peak	HORIZONTAL
4804.00	57.36	31.21	43.84	5.52	50.25	54.00	-3.75	Average	HORIZONTAL
7206.00	46.04	35.81	43.23	6.40	45.02	74.00	-28.98	Peak	HORIZONTAL
9364.00	43.68	37.65	42.79	8.22	46.76	74.00	-27.24	Peak	HORIZONTAL
10911.00	44.24	39.38	41.57	8.98	51.03	74.00	-22.97	Peak	HORIZONTAL
13444.00	44.31	40.05	42.35	10.88	52.89	74.00	-21.11	Peak	HORIZONTAL
4804.00	61.39	31.21	43.84	5.52	54.28	74.00	-19.72	Peak	VERTICAL
4804.00	57.39	31.21	43.84	5.52	50.28	54.00	-3.72	Average	VERTICAL
7205.00	47.38	35.81	43.23	6.40	46.36	74.00	-27.64	Peak	VERTICAL
8871.00	44.74	37.35	42.18	7.85	47.76	74.00	-26.24	Peak	VERTICAL
11200.00	44.17	39.32	41.83	9.02	50.68	74.00	-23.32	Peak	VERTICAL
14141.00	42.77	41.32	41.75	11.12	53.46	74.00	-20.54	Peak	VERTICAL
Tx mode 2441MHz									
4884.00	60.96	31.37	43.77	5.55	54.11	74.00	-19.89	Peak	HORIZONTAL
4884.00	57.31	31.37	43.77	5.55	50.46	54.00	-3.54	Average	HORIZONTAL
8021.00	45.17	37.01	43.12	7.35	46.41	74.00	-27.59	Peak	HORIZONTAL
11200.00	45.35	39.32	41.83	9.02	51.86	74.00	-22.14	Peak	HORIZONTAL
13240.00	45.12	39.52	42.57	10.80	52.87	74.00	-21.13	Peak	HORIZONTAL
14464.00	42.73	40.90	41.73	11.16	53.06	74.00	-20.94	Peak	HORIZONTAL
4884.00	61.32	31.37	43.77	5.55	54.47	74.00	-19.53	Peak	VERTICAL
4884.00	57.43	31.37	43.77	5.55	50.58	54.00	-3.42	Average	VERTICAL
7324.00	46.71	35.99	43.28	6.54	45.96	74.00	-28.04	Peak	VERTICAL
10520.00	44.92	38.83	42.50	8.88	50.13	74.00	-23.87	Peak	VERTICAL
12951.00	45.20	38.89	42.84	10.63	51.88	74.00	-22.12	Peak	VERTICAL
13750.00	43.43	40.85	42.03	11.00	53.25	74.00	-20.75	Peak	VERTICAL
Tx mode 2480MHz									
4960.00	60.43	31.52	43.71	5.57	53.81	74.00	-20.19	Peak	HORIZONTAL
4960.00	57.38	31.52	43.71	5.57	50.76	54.00	-3.24	Average	HORIZONTAL
7426.00	46.31	36.14	43.32	6.66	45.79	74.00	-28.21	Peak	HORIZONTAL
9619.00	44.81	37.83	43.07	8.43	48.00	74.00	-26.00	Peak	HORIZONTAL
11030.00	44.55	39.47	41.43	9.00	51.59	74.00	-22.41	Peak	HORIZONTAL
13274.00	44.40	39.61	42.53	10.82	52.30	74.00	-21.70	Peak	HORIZONTAL
4960.00	60.06	31.52	43.71	5.57	53.44	74.00	-20.56	Peak	VERTICAL
4960.00	57.36	31.52	43.71	5.57	50.74	54.00	-3.26	Average	VERTICAL
7834.00	45.38	36.75	43.22	7.14	46.05	74.00	-27.95	Peak	VERTICAL
10554.00	44.45	38.88	42.42	8.88	49.79	74.00	-24.21	Peak	VERTICAL
12050.00	46.29	38.61	42.70	9.18	51.38	74.00	-22.62	Peak	VERTICAL
13257.00	43.83	39.57	42.55	10.81	51.66	74.00	-22.34	Peak	VERTICAL
Result: Pass									

Note: 1. 30MHz~25GHz: (Scan with GFSK, $\pi/4$ -DQPSK, worse case is $\pi/4$ -DQPSK Mode)

2. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

3. For emissions above 1GHz. If peak results comply with AV limit, AV Result is deemed to comply with AV limit.

11. RF Conducted Spurious Emissions

11.1. Block diagram of test setup

Same as section 4.1

11.2. Limits

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

11.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	Test frequency
RBW:	100kHz
VBW:	300kHz
Span	Wide enough to capture the peak level of the in-band emission
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:


RBW:	100kHz
VBW:	300kHz
Span	Encompass frequency range to be measured
Number of measurement points	$\geq \text{span}/\text{RBW}$
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold


(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band

11.4. Test Result

Mode	Freq. (MHz)	Conclusion
GFSK	Hopping off 2402	PASS
	Hopping off 2441	PASS
	Hopping off 2480	PASS
$\pi/4$ -DQPSK	Hopping off 2402	PASS
	Hopping off 2441	PASS
	Hopping off 2480	PASS


11.5. Original test data






Date: 19.NOV.2019 14:40:52

DH5_ANT1_2441_Ref




Date: 19.NOV.2019 14:41:48

DH5_ANT1_2441_30~1000




Date: 19.NOV.2019 14:41:56

DH5_ANT1_2441_1000~26500




Date: 19.NOV.2019 14:42:22

DH5_ANT1_2480_Ref




Date: 19.NOV.2019 14:43:45

DH5 ANT1 2480 30~1000




Date: 19.NOV.2019 14:43:53

DH5_ANT1_2480_1000~26500




Date: 19.NOV.2019 14:44:13

2DH5_ANT1_2402_Ref




Date: 19.NOV.2019 14:45:13

2DH5_ANT1_2402_30~1000




Date: 19.NOV.2019 14:45:21

2DH5_ANT1_2402_1000~26500




Date: 19.NOV.2019 14:46:03

2DH5_ANT1_2441_Ref




Date: 19.NOV.2019 14:46:51

2DH5_ANT1_2441_30~1000




Date: 19.NOV.2019 14:47:00

2DH5_ANT1_2441_1000~26500




Date: 19.NOV.2019 14:47:38

2DH5_ANT1_2480_Ref




Date: 19.NOV.2019 14:48:45

2DH5_ANT1_2480_30~1000




Date: 19.NOV.2019 14:48:53

2DH5_ANT1_2480_1000~26500



12. Band Edge Compliance (radiated method)

12.1. Block diagram of test setup



12.2. Limit

All restriction band should comply with 15.209, other emission should be at least 20dB below the fundamental.

12.3. Test Procedure

Same with clause 10.3 except change investigated frequency range from 2310MHz to 2410MHz and 2475MHz to 2500MHz.

Remark: All restriction band have been tested, and only the worst case is shown in report.

12.4. Test result

PASS. (See below detailed test result)

Remark: hopping on and hopping off mode all have been test, hopping off mode is worse and reported only.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19082907-1E IPA123\FCC
ABOVE 1G.EM6

Test Date : 2019-11-19

Tested By : Jacky

EUT : HIGH-POWER BLUETOOTH PA SYSTEM
WITH LIGHTS

Model Number : TOTAL PA GLOW 3


Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Condition : Temp:24.5'C, Humi:55%, Press:100.1kPa **Antenna/Distance** : 2019 BBHA 9120 D/3m/HORIZONTAL

Memo : DH5 2402

Data: 9



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2377.80	54.10	27.18	43.26	3.71	41.73	74.00	-32.27	Peak	HORIZONTAL
2	2390.00	50.24	27.23	43.27	3.73	37.93	74.00	-36.07	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19082907-1E IPA123\FCC
ABOVE 1G.EM6

Test Date : 2019-11-19

Tested By : Jacky

EUT : HIGH-POWER BLUETOOTH PA SYSTEM
WITH LIGHTS

Model Number : TOTAL PA GLOW 3


Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Condition : Temp:24.5'C, Humi:55%, Press:100.1kPa **Antenna/Distance** : 2019 BBHA 9120 D/3m/VERTICAL

Memo : DH5 2402

Data: 10



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2365.80	54.34	27.14	43.25	3.69	41.92	74.00	-32.08	Peak	VERTICAL
2	2390.00	50.30	27.23	43.27	3.73	37.99	74.00	-36.01	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19082907-1E IPA123\FCC
ABOVE 1G.EM6

Test Date : 2019-11-19

Tested By : Jacky

EUT : HIGH-POWER BLUETOOTH PA SYSTEM
WITH LIGHTS

Model Number : TOTAL PA GLOW 3


Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Condition : Temp:24.5'C, Humi:55%, Press:100.1kPa **Antenna/Distance** : 2019 BBHA 9120 D/3m/VERTICAL

Memo : DH5 2480

Data: 11



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	59.60	27.54	43.37	3.87	47.64	74.00	-26.36	Peak	VERTICAL
2	2484.25	59.52	27.55	43.37	3.87	47.57	74.00	-26.43	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19082907-1E IPA123\FCC
ABOVE 1G.EM6

Test Date : 2019-11-19

Tested By : Jacky

EUT : HIGH-POWER BLUETOOTH PA SYSTEM
WITH LIGHTS

Model Number : TOTAL PA GLOW 3


Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Condition : Temp:24.5'C, Humi:55%, Press:100.1kPa **Antenna/Distance** : 2019 BBHA 9120 D/3m/HORIZONTAL

Memo : DH5 2480

Data: 12



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	64.21	27.54	43.37	3.87	52.25	74.00	-21.75	Peak	HORIZONTAL
2	2483.80	64.16	27.54	43.37	3.87	52.20	74.00	-21.80	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19082907-1E IPA123\FCC
ABOVE 1G.EM6

Test Date : 2019-11-19

Tested By : Jacky

EUT : HIGH-POWER BLUETOOTH PA SYSTEM
WITH LIGHTS

Model Number : TOTAL PA GLOW 3


Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Condition : Temp:24.5'C, Humi:55%, Press:100.1kPa **Antenna/Distance** : 2019 BBHA 9120 D/3m/HORIZONTAL

Memo : 2DH5 2402

Data: 13



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2324.70	55.20	27.00	43.20	3.63	42.63	74.00	-31.37	Peak	HORIZONTAL
2	2390.00	52.35	27.23	43.27	3.73	40.04	74.00	-33.96	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19082907-1E IPA123\FCC
ABOVE 1G.EM6

Test Date : 2019-11-19

Tested By : Jacky

EUT : HIGH-POWER BLUETOOTH PA SYSTEM
WITH LIGHTS

Model Number : TOTAL PA GLOW 3


Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Condition : Temp:24.5'C, Humi:55%, Press:100.1kPa **Antenna/Distance** : 2019 BBHA 9120 D/3m/VERTICAL

Memo : 2DH5 2402

Data: 14



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2322.50	54.93	27.00	43.20	3.62	42.35	74.00	-31.65	Peak	VERTICAL
2	2390.00	49.79	27.23	43.27	3.73	37.48	74.00	-36.52	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19082907-1E IPA123\FCC
ABOVE 1G.EM6

Test Date : 2019-11-19

Tested By : Jacky

EUT : HIGH-POWER BLUETOOTH PA SYSTEM
WITH LIGHTS

Model Number : TOTAL PA GLOW 3


Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Condition : Temp:24.5°C, Humi:55%, Press:100.1kPa **Antenna/Distance** : 2019 BBHA 9120 D/3m/HORIZONTAL

Memo : 2DH5 2480

Data: 15



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	64.72	27.54	43.37	3.87	52.76	74.00	-21.24	Peak	HORIZONTAL
2	2483.70	64.34	27.54	43.37	3.87	52.38	74.00	-21.62	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19082907-1E IPA123\FCC
ABOVE 1G.EM6

Test Date : 2019-11-19

Tested By : Jacky

EUT : HIGH-POWER BLUETOOTH PA SYSTEM
WITH LIGHTS

Model Number : TOTAL PA GLOW 3


Power Supply : AC 120V/60Hz

Test Mode : Tx mode

Condition : Temp:24.5'C, Humi:55%, Press:100.1kPa **Antenna/Distance** : 2019 BBHA 9120 D/3m/VERTICAL

Memo : 2DH5 2480

Data: 16



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	59.20	27.54	43.37	3.87	47.24	74.00	-26.76	Peak	VERTICAL
2	2484.20	59.78	27.55	43.37	3.87	47.83	74.00	-26.17	Peak	VERTICAL


Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

13. Power Line Conducted Emission

13.1. Block diagram of test setup



13.2. Power Line Conducted Emission Limits

Frequency	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

13.3. Test Procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

Configuration EUT to simulate typical usage as described in clause 2.4 and test equipment as described in clause 10.2 of this report.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

13.4. Test Result

PASS. (See below detailed test result)

Note1: All emissions not reported below are too low against the prescribed limits.

Note2: "----" means Peak detection; "----" means Average detection.

Note3: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/60Hz, recorded worse case.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 5# Shield Room

D:\2019 report data\Q19082907-1E\ION_IPA123_CE.EM6

Test Date : 2019-11-18

Tested By : Jerry

EUT : HIGH-POWER BLUETOOTH PA
SYSTEM WITH LIGHTS

Model Number : TOTAL PA GLOW 3

Power Supply : AC 120V/60Hz


Test Mode : Tx mode

Condition : Temp:24.5°C, Humi:55.5%,
Press:100.1kPa

LISN : 2018 ENV216 2#/NEUTRAL

Memo :

Data: 63



Item	Freq.	Read Level	LISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Over Limit	Detector	Phase
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)		
1	0.18	22.16	9.66	0.18	9.78	41.78	64.46	-22.68	QP	NEUTRAL
2	0.18	12.58	9.66	0.18	9.78	32.20	54.46	-22.26	Average	NEUTRAL
3	0.64	21.30	9.64	0.21	9.78	40.93	56.00	-15.07	QP	NEUTRAL
4	0.64	15.39	9.64	0.21	9.78	35.02	46.00	-10.98	Average	NEUTRAL
5	2.87	22.85	9.64	0.34	9.61	42.44	56.00	-13.56	QP	NEUTRAL
6	2.87	9.26	9.64	0.34	9.61	28.85	46.00	-17.15	Average	NEUTRAL
7	3.06	30.65	9.64	0.35	9.58	50.22	56.00	-5.78	QP	NEUTRAL
8	3.06	10.95	9.64	0.35	9.58	30.52	46.00	-15.48	Average	NEUTRAL
9	3.08	33.23	9.64	0.35	9.58	52.80	56.00	-3.20	QP	NEUTRAL
10	3.08	11.49	9.64	0.35	9.58	31.06	46.00	-14.94	Average	NEUTRAL
11	6.09	21.82	9.67	0.38	9.35	41.22	60.00	-18.78	QP	NEUTRAL
12	6.09	9.13	9.67	0.38	9.35	28.53	50.00	-21.47	Average	NEUTRAL

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 5# Shield Room

D:\2019 report data\Q19082907-1E\ION_IPA123_CE.EM6

Test Date : 2019-11-18

Tested By : Jerry

EUT : HIGH-POWER BLUETOOTH PA
SYSTEM WITH LIGHTS

Model Number : TOTAL PA GLOW 3

Power Supply : AC 120V/60Hz


Test Mode : Tx mode

Condition : Temp:24.5°C, Humi:55.5%,
Press:100.1kPa

LISN : 2018 ENV216 2#/LINE

Memo :

Data: 64



Item	Freq.	Read Level	LISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Over Limit	Detector	Phase
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)		
1	0.17	22.17	9.66	0.17	9.78	41.78	65.03	-23.25	QP	LINE
2	0.17	12.66	9.66	0.17	9.78	32.27	55.03	-22.76	Average	LINE
3	1.49	21.03	9.64	0.28	9.78	40.73	56.00	-15.27	QP	LINE
4	1.49	15.36	9.64	0.28	9.78	35.06	46.00	-10.94	Average	LINE
5	2.81	25.96	9.64	0.34	9.62	45.56	56.00	-10.44	QP	LINE
6	2.81	7.45	9.64	0.34	9.62	27.05	46.00	-18.95	Average	LINE
7	2.88	27.23	9.64	0.34	9.61	46.82	56.00	-9.18	QP	LINE
8	2.88	16.63	9.64	0.34	9.61	36.22	46.00	-9.78	Average	LINE
9	3.03	29.62	9.64	0.35	9.59	49.20	56.00	-6.80	QP	LINE
10	3.03	12.89	9.64	0.35	9.59	32.47	46.00	-13.53	Average	LINE
11	6.09	16.87	9.67	0.38	9.35	36.27	60.00	-23.73	QP	LINE
12	6.09	5.64	9.67	0.38	9.35	25.04	50.00	-24.96	Average	LINE

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

14. Antenna Requirements

14.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

14.2. Result

The antenna used for this product is integral PCB antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only -0.58 dBi.