

REC44M - Belly Label

Outlined

amped|wireless

Model: REC44M
Designed in the USA, Assembled in China.

High Power Plug-In AC2600 Wi-Fi Range Extender with MU-MIMO

S/N:

MAC (2.4G Hz):

MAC (5GHz):

WPS Pin:

Login Settings:
Web Menu: <http://setup.ampedwireless.com>
IP Address: 192.168.1.240

Wi-Fi Settings:
2.4GHz SSID: Amped_REC44M_2.4
5GHz SSID: Amped_REC44M_5.0

Factory Default Settings:
Hold down Reset button for 10 seconds.
Input Power Rating: 100-240v~0.5A, 50/60Hz

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:
(1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

FC









amped|wireless 

Model: REC44M

Designed in the USA, Assembled in China.

High Power Plug-In AC2600 Wi-Fi Range Extender with MU-MIMO

S/N:

MAC (2.4GHz):

MAC (5GHz):

WPS Pin:

Login Settings:

Web Menu: <http://setup.ampedwireless.com>

IP Address: 192.168.1.240

Wi-Fi Settings:

2.4GHz SSID: Amped_REC44M_2.4

5GHz SSID: Amped_REC44M_5.0

Factory Default Settings:

Hold down Reset button for 10 seconds.

Input Power Rating: 100-240v ~ 0.5A, 50/60Hz

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:
(1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

