

RF EXPOSURE EVALUATION 2AXCUYAS-DGC100

Product	:	Digital Camera							
Model Name	:	YAS-DGC100,DB73,YASHICA City 100,D3,LY-10L,LC-10							
Brand	:	N/A							
Report No.	:	PTC24120516301E-FC02							
Prepared for									
DeBen Technology (shenzhen) Co.,Ltd									
5F, 12 Buildings, Xinxintian Industrial Zone, Xinsha Road, Shajing Street, Baoan District, Shenzhen									
Prepared by									
Precise Testing & Certification Co., Ltd.									
Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China.									



Standard Requirement

According to § 15.247(i) and § 1.1307b(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See KDB 447498 D01 General RF Exposure Guidance v06, section 4. 3. 1.

The 1-g and 10-g SAR test exclusion thresholds for 100MHz to 6GHz at test separation distances \leq 50mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]*[$\sqrt{f(GHz)}$] \leq 3.0 for 1-g SAR and \leq 7.5 for 10-g SAR extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison.

The test exclusions are applicable only when the minimum test separation distance is \leq 50mm and for transmission frequencies between 100MHz and 6GHz. When the minimum test separation distance is <5mm, a distance of 5mm is applied to determine SAR test exclusion. Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to quality

for TCB approval.

Channel (MHz)	Maximum output power (dBm)	Tune up tolerance (dBm)	Max Tune Up Power (mW)	Distance (mm)	Calculation results	Limit	Operating Mode
2437(11B)	7.11	7.11±1	6.47	5	2.02	3	802.11b

According to KDB 447498, no stand-alone required for Wi-Fi antenna, and no simultaneous SAR measurement is required.

Signature

Simon th

Simon Pu Manager Date: 2024-12-15