



EMC TEST Report

FCC ID: H8GCR710

This report concerns (check one) : Original Grant Class II Change

Issued Date : Sep. 22, 2006 Report No. : 0608C101 Equipment : RF Mouse Model No. : R7-10

Applicant: A-FOUR TECH CO., LTD.

Address: 6F, NO.108, Min-Chuan Rd., Hsin-Tien, Taipei Taiwan, R.O.C.

Tested by: Neutron Engineering Inc. EMC Laboratory Data of Test: Aug. 30, 2006 ~ Sep. 20, 2006

Testing Engineer

Technical Manager

Authorized Signatory

Tru (Pike Lee) (Sett Yang Chi nd

NEUTRON ENGINEERING INC.

No. 132-1, *L*ane 329, Sec. 2, Palain Rd., Shijr City, Taipei, Taiwan *TEL : (02)* 2646-5426 *FAX : (02)* 2646-6815









Declaration

Neutron represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (**NML**) of **R.O.C.**, or National Institute of Standards and Technology (**NIST**) of **U.S.A**.

Neutron's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **Neutron** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **Neutron** issued reports.

Neutron's reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **Neutron-self**, extracts from the test report shall not be reproduced except in full with **Neutron**'s authorized written approval.

Neutron's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.





Table of Contents	Page
1. CERTIFICATION	4
2 . SUMMARY OF TEST RESULTS	5
2.1 TEST FACILITY	6
2.2 MEASUREMENT UNCERTAINTY	6
3 . GENERAL INFORMATION	7
3.1 GENERAL DESCRIPTION OF EUT	7
3.2 DESCRIPTION OF TEST MODES	8
3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	9
3.4 DESCRIPTION OF SUPPORT UNITS	10
4 . EMC EMISSION TEST	11
4.1 RADIATED EMISSION MEASUREMENT	11
4.1.1 RADIATED EMISSION LIMITS 4.1.2 MEASUREMENT INSTRUMENTS LIST	11 12
4.1.3 TEST PROCEDURE	12
4.1.4 DEVIATION FROM TEST STANDARD	12
4.1.5 TEST SETUP 4.1.6 EUT OPERATING CONDITIONS	13 14
4.1.7 TEST RESULTS	15
5 . EUT TEST PHOTO	19
6 . PRODUCT LABELING	20



1. CERTIFICATION

Equipment: RF Mouse Trade Name: A4TECH Model No.: R7-10 Applicant: A-FOUR TECH CO., LTD. Data of Test: Aug. 30, 2006 ~ Sep. 20, 2006 Test Item: ENGINEERING SAMPLE Standards: FCC Part15, Subpart C / RSS-210: 2004/ ANCI C63.4 : 2003

The above equipment has been tested and found compliance with the requirement of the relative standards by Neutron Engineering Inc. EMC Laboratory.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. NEI-FCCP-1-0608C101) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of NVLAP and CNLA according to the ISO-17025 quality assessment standard and technical standard(s).



2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards: (Antenna to EUT distance is 3 m)

FCC Part15, Subpart C							
Standard	Test Item	Limit	Frequency Range (MHz)	Judgment			
15.207	Conducted Emission	Class B	0.15 - 30	N/A			
15.209	Radiated Emission	Class B	30-1000	PASS			
15.227	Radiated Emission	10000 μV/m (80dBμV/m) @ 3m	26.96-27.28	PASS			

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report



2.1 TEST FACILITY

The test facilities used to collect the test data in this report is **OS02** at the location of No.132-1, Lane 329, Sec. 2, Palain Road, Shijr City, Taipei, Taiwan.

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of **k=2**, providing a level of confidence of approximately **95** % \circ

A. Conducted Measurement :

Test Site	Method	Measurement Frequency Range	U, (dB)	NOTE
C01	ANSI	150 KHz ~ 30MHz	1.94	

B. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	Ant. H / V	nt. /V U, (dB) NOTE	
OS-01	ANSI	30MHz ~ 200MHz	V	3.82	
		30MHz ~ 200MHz	Н	3.60	
		200MHz ~ 1,000MHz	V	3.86	
		200MHz ~ 1,000MHz	Н	3.94	
OS-02	ANSI	30MHz ~ 200MHz	V	2.48	
		30MHz ~ 200MHz	Н	2.16	
		200MHz ~ 1,000MHz	V	2.50	
		200MHz ~ 1,000MHz	Н	2.66	



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	RF Mouse			
Trade Name	A4TECH			
Model No.	R7-10			
OEM Brand/Model No.	N/A			
Model Difference	N/A			
	The EUT is a RF Mouse.			
	A. Operation Frequency	CH1: 27.045 MHz CH2: 27.145 MHz		
	B. Modulation Type	FSK		
	C. Equipment Type	I (Transfer of messages)		
Product Description	D. Channel Separation	100 KHz		
	E. Antenna Designation	Integral Antenna		
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.			
Power Supply	DC 3V, 7mA			
Connecting I/O Port(s)	Please refer to the User's Manual			
Products Covered	N/A			
EUT Modification(s)	N/A			

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Test Mode	Description		
Mode 1	CH1		
Mode 2	CH2		

For Radiated Test				
Final Test Mode	Description			
Mode 1	CH1			
Mode 2	CH2			







3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
E-1	RF Mouse	A4TECH	R7-10	H8GCR710	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note
	N/A	N/A	N/A	

Note:

(1) The support equipment was authorized by Declaration of Confirmation.

(2) For detachable type I/O cable should be specified the length in cm in ^[]Length ^[] column.





4. EMC EMISSION TEST

4.1 RADIATED EMISSION MEASUREMENT

4.1.1 RADIATED EMISSION LIMITS (Frequency Range 30MHz-1000MHz)

Measurement	Quasi-Peak Mode		Quasi-Peak Mode		Note	
Frequency Range	Class A	A Limits	Class B Limits		CISPR	
(MHz)	(dBu	V/m)	(dBu	V/m)	FCC	
	10m	30m	10m	3m	Std.	
30.00 -230.00	40.00	30.00	30.00	40.00	CISPR	
230.0 -1000.0	47.00	37.00	37.00	47.00	CISPR	
30.00 - 88.00	39.00	N/A	30.00	40.00	FCC	
88.00 - 216.0	43.50	N/A	33.50	43.50	FCC	
216.0 -960.0	46.00	N/A	36.00	46.00	FCC	
above 960.0	49.50	N/A	46.00	54.00	FCC	

Notes:

- (1) The tighter limit applies at the band edges.
- (2) Emission level (dBuV/m)=20log Emission level (uV/m).
- (3) A measuring distance of 10m is a primary used. However, either 3m or 10m (instead of 10m) distance my be allowed. If the distance is 3m, add 10dB to the QP-limit above. If the distance is 10m, subtract 10dB from the QP-limit above.



Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Log-Bicon Antenna	MESS-ELEKTRONIK	VULB 9160	3058	Nov. 29, 2006
2	Test Cable	N/A	10M_OS02	N/A	Nov. 29, 2006
3	Test Cable	N/A	OS02-1/-2/-3	N/A	Nov. 29, 2006
4	Pre-Amplifier	Anritsu	MH648A	M09961	Nov. 29, 2006
5	EMI Test Receiver	R&S	ESCI	100082	Feb. 01, 2007
6	Antenna Mast	Chance Most	CMTB-1.5	N/A	N/A
7	Turn Table	Chance Most	CMTB-1.5	N/A	N/A
8	Loop Ant	EMCO	6502	00042960	Jan. 13, 2008

4.1.2 MEASUREMENT INSTRUMENTS LIST

Remark: " N/A" denotes No Model No. / Serial No. and No Calibration specified.

4.1.3 TEST PROCEDURE

- a. The measuring distance of at 10 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3m or 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.4 DEVIATION FROM TEST STANDARD No deviation



4.1.5 TEST SETUP

(A) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(B) Radiated Emission Test Set-UP Frequency Over 1 GHz





- 4.1.6 EUT OPERATING CONDITIONS
- (a) Only radiated testing was performed during the max. EMI emission evaluation. Conducted testing excepted because of the EUT is a battery operating device and no any other cable connection to PC device.
- (b) The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



4.1.7 TEST RESULTS

EUT :	RF Mouse	Model No. :	R7-10
Temperature :	27.7 °C	Relative Humidity:	69 %
Pressure :	1012 hPa	Test Power :	DC 3V
Test Mode :	CH1		

Freq.	Ant.Pol.	DetectorMode	Reading	Ant./CL/	Actual FS	Limit-3m	Safe Margins	Noto
(MHz)	H/V	(PK/AV)	(dBuV)	Amp. CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	INOLE
27.05		Peak	27.68	8.70	36.38	80.00	- 43.62	F
59.98	V	Peak	40.44	- 6.64	33.80	40.00	- 6.20	Н
166.95	V	Peak	37.64	- 4.92	32.72	43.50	- 10.78	Н
204.56	V	Peak	39.16	- 7.38	31.78	43.50	- 11.72	Н
216.04	V	Peak	38.86	- 6.78	32.08	46.00	- 13.92	Н
228.53	V	Peak	38.52	- 6.16	32.36	46.00	- 13.64	Н
597.26	V	Peak	39.25	2.54	41.79	46.00	- 4.21	Н

Remark :

- (1) Spectrum Setting:
 - 9 KHz 150 KHz, RBW= 1 KHz, VBW=1 KHz, Sweep time = 200 ms.
 - 150 K Hz 30 MHz, RBW= 9 KHz, VBW=9 KHz, Sweep time = 200 ms.
 - 30 MHz 1000 MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms.
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measure-ment didn't perform \circ
- (3) The Log-Bicon Antenna will use to test frequency range from 30MHz to 1000MHz and the Loop Antenna will use to test frequency below 30MHz.
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not how in table \circ





EUT :	RF Mouse	Model No. :	R7-10
Temperature :	27.7 °C	Relative Humidity:	69 %
Pressure :	1012 hPa	Test Power :	DC 3V
Test Mode :	CH1		

Freq.	Ant.Pol.	DetectorMode	Reading	Ant./CL/	Actual FS	Limit-3m	Safe Margins	Note
(MHz)	H/V	(PK/AV)	(dBuV)	Amp. CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	note
27.05		Peak	27.68	8.70	36.38	80.00	- 43.62	F
60.02	Н	Peak	37.66	- 6.64	31.02	40.00	- 8.98	Н
193.22	Н	Peak	38.43	- 7.44	30.99	43.50	- 12.51	Н
203.79	Н	Peak	38.73	- 7.42	31.31	43.50	- 12.19	Н
280.07	Н	Peak	36.83	- 4.52	32.31	46.00	- 13.69	Н
299.41	Н	Peak	40.16	- 4.07	36.09	46.00	- 9.91	Н
597.06	Н	Peak	36.73	2.53	39.26	46.00	- 6.74	Н

Remark :

(1) Spectrum Setting:

9 KHz – 150 KHz, RBW= 1 KHz, VBW=1 KHz, Sweep time = 200 ms. 150 K Hz – 30 MHz, RBW= 9 KHz, VBW=9 KHz, Sweep time = 200 ms. 30 MHz – 1000 MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms.

- (2) All readings are Peak unless otherwise stated QP in column of "Note ... Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measure-ment didn't perform •
- (3) The Log-Bicon Antenna will use to test frequency range from 30MHz to 1000MHz and the Loop Antenna will use to test frequency below 30MHz.
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not how in table \circ





EUT:	RF Mouse	Model No. :	R7-10
Temperature :	27.7 °C	Relative Humidity:	69 %
Pressure :	1012 hPa	Test Power :	DC 3V
Test Mode :	CH2		

Freq.	Ant.Pol.	DetectorMode	Reading	Ant./CL/	Actual FS	Limit-3m	Safe Margins	Noto
(MHz)	H/V	(PK/AV)	(dBuV)	Amp. CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	INOLE
27.15		Peak	28.35	8.70	37.05	80.00	- 42.95	F
60.10	V	Peak	41.12	- 6.65	34.47	40.00	- 5.53	Н
166.95	V	Peak	38.30	- 4.92	33.38	43.50	- 10.12	Н
204.11	V	Peak	39.34	- 7.40	31.94	43.50	- 11.56	Н
216.10	V	Peak	38.55	- 6.78	31.77	46.00	- 14.23	Н
225.61	V	Peak	37.98	- 6.30	31.68	46.00	- 14.32	Н
597.30	V	Peak	38.63	2.54	41.17	46.00	- 4.83	Н

Remark :

(1) Spectrum Setting:

9 KHz – 150 KHz, RBW= 1 KHz, VBW=1 KHz, Sweep time = 200 ms. 150 K Hz – 30 MHz, RBW= 9 KHz, VBW=9 KHz, Sweep time = 200 ms.

30 MHz - 1000 MHz, RBW= 100KHz, VBW=100KHz, Sweep time = 200 ms.

(2) All readings are Peak unless otherwise stated QP in column of 『Note』. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measure-ment didn't perform ∘

(3) The Log-Bicon Antenna will use to test frequency range from 30MHz to 1000MHz and the Loop Antenna will use to test frequency below 30MHz.

(4) If the peak scan value lower limit more than 20dB, then this signal data does not how in table \circ



EUT :	RF Mouse	Model No. :	R7-10
Temperature :	27.7 °C	Relative Humidity:	69 %
Pressure :	1012 hPa	Test Power :	DC 3V
Test Mode :	CH2		

	-	-						
Freq.	Ant.Pol.	DetectorMode	Reading	Ant./CL/	Actual FS	Limit-3m	Safe Margins	Noto
(MHz)	H/V	(PK/AV)	(dBuV)	Amp. CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	NOLE
27.15		Peak	28.35	8.70	37.05	80.00	- 42.95	F
60.22	Н	Peak	37.91	- 6.67	31.24	40.00	- 8.76	Н
193.20	Н	Peak	38.43	- 7.44	30.99	43.50	- 12.51	Н
203.98	Н	Peak	39.01	- 7.41	31.60	43.50	- 11.90	Н
279.99	Н	Peak	41.24	- 4.53	36.71	46.00	- 9.29	Н
299.50	Н	Peak	42.98	- 4.06	38.92	46.00	- 7.08	Н
596.96	Н	Peak	38.10	2.53	40.63	46.00	- 5.37	Н

Remark :

(1) Spectrum Setting:

9 KHz – 150 KHz, RBW= 1 KHz, VBW=1 KHz, Sweep time = 200 ms.

150 K Hz - 30 MHz, RBW= 9 KHz, VBW=9 KHz, Sweep time = 200 ms.

- 30 MHz 1000 MHz, RBW= 100 KHz, VBW=100 KHz, Sweep time = 200 ms.
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measure-ment didn't perform \circ
- (3) The Log-Bicon Antenna will use to test frequency range from 30MHz to 1000MHz and the Loop Antenna will use to test frequency below 30MHz.
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not how in table \circ





Neutron Engineering Inc.

ATTACHMENT

PHOTOGRAPHS OF EUT