

FCC §15.247 (i), §2.1091 - RF Exposure

# FCC ID: 2AVRVPTHRM100

## Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

**Limits for Occupational / Controlled Exposure** 

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)	
0.3-3.0	614	1.63	(100)*	6	
3.0-30	1842 / f	4.89 / f	(900 / f)*	6	
30-300	61.4	0.163	1.0	6	
300-1500			F/300	6	
1500-100,000			5	6	

Note: *f* is frequency in MHz

## **Limits for General Population / Uncontrolled Exposure**

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz

<sup>\* =</sup> Power density limit is applicable at frequencies greater than 100 MHz

<sup>\* =</sup> Plane-wave equivalent power density



#### MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=0.2m

#### **TEST RESULTS**

Modulation	Test frequency (KHz)	Output Power (dBuV/m)	Output Power (dBm)
Wireless charge	112.2	84.39	-16

Below 1GHz: dBm=dBuV/m-95.2-6

	Tune up Produce power	Maximum  peak  output  power  (dBm)	Output power to antenna (mW)	Antenna Gain (numeric)	Pow er Dens ity (S)	Limit (mW / cm2	Result
ВТ	2±1	3	2.00	1.611(2.07dBi)	0.00639	1	Pass
Wireless charge	-16±1	-15	0.03	1(0dBi)	0.00006	1	Pass

## For the Max simultaneous transmission:

	Power Density (S) (mW/ cm2)	Total Power Density (S)	Limit	Result
ВТ	0.00639	0.00645	4	Door
Wireless charge	0.00006	0.00645	l	Pass

For the max result : 0.00645 ≤ 1.0, compliance with FCC's RF Exposure