

FCC 47 CFR MPE REPORT

INMUSIC BRANDS INC

Solid State Media/Bluetooth Player

Model Number: DN-F350

Project Code: DP24

FCC ID: Y4O-DP24

| | |
|--------------------------|---|
| Prepared for: | INMUSIC BRANDS INC |
| | 200 SCENIC VIEW DRIVE, SUITE 201, CUMBERLAND, RI |
| | 02864, U.S.A. |
| Prepared By: | EST Technology Co., Ltd. |
| | San Tun Management Zone, Houjie District, Dongguan, China |
| Tel: 86-769-83081888-808 | |

| | |
|-----------------|---------------------------|
| Report Number: | ESTE-R1705003 |
| Date of Test: | March 16 ~ April 27, 2017 |
| Date of Report: | May 02, 2017 |

Maximum Permissible Exposure

1、Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a)、Limits for Occupational / Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm ²) | Averaging Times E 2 , H 2 or S (minutes) |
|-----------------------|----------------------------------|-----------------------------------|---|--|
| 0.3-3.0 | 614 | 1.63 | (100)* | 6 |
| 3.0-30 | 1842/f | 4.89/f | (900/f)* | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | | | F/300 | 6 |
| 1500-10000 | | | 5 | 6 |

(b)、Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm ²) | Averaging Times E 2 , H 2 or S (minutes) |
|-----------------------|----------------------------------|-----------------------------------|---|--|
| 0.3-1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34-30 | 824/f | 2.19/f | (180/f)* | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | | | F/1500 | 30 |
| 1500-10000 | | | 1.0 | 30 |

Note: f=frequency in MHz; *Plane-wave equivalent power density

2、MPE Calculation Method

$$E \text{ (V/m)} = (30 \cdot P \cdot G)^{0.5} / d \quad \text{Power Density: } P_d \text{ (W/m}^2\text{)} = E^2 / 377$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$P_d = (30 \cdot P \cdot G) / (377 \cdot d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

3、Calculated Result and Limit

| Mode | Frequency (MHz) | Peak output power (dBm) | Peak output power (mW) | Target power (dBm) | Antenna gain | | Power Density (S) (mW /cm ²) | Limited of Power Density (S) (mW /cm ²) | Test Result |
|--------|--------------------|----------------------------------|---------------------------------|----------------------------|--------------|----------|--|---|----------------|
| | | | | | (dBi) | (Linear) | | | |
| GFSK | 2402 | 2.715 | 1.869 | 2±2 | -0.55 | 0.881 | 0.00044 | 1 | Compiles |
| | 2440 | 3.647 | 2.316 | 3±2 | -0.55 | 0.881 | 0.00044 | 1 | Compiles |
| | 2480 | 3.859 | 2.432 | 3±2 | -0.55 | 0.881 | 0.00055 | 1 | Compiles |
| 8-DPSK | 2402 | 4.398 | 2.753 | 4±2 | -0.55 | 0.881 | 0.00070 | 1 | Compiles |
| | 2441 | 5.057 | 3.204 | 5±2 | -0.55 | 0.881 | 0.00088 | 1 | Compiles |
| | 2480 | 5.180 | 3.296 | 5±2 | -0.55 | 0.881 | 0.00088 | 1 | Compiles |
| BLE | 2402 | 2.070 | 1.611 | 2±2 | -0.55 | 0.881 | 0.00044 | 1 | Compiles |
| | 2441 | 2.690 | 1.858 | 2±2 | -0.55 | 0.881 | 0.00044 | 1 | Compiles |
| | 2480 | 1.950 | 1.567 | 1±2 | -0.55 | 0.881 | 0.00035 | 1 | Compiles |