



FCC TEST REPORT

FCC ID: 2ATCG-BB832QI4A

On Behalf of

Shanghai Ibeelink technology Co., LTD
2.4G Bluetooth Module
Model No.: BB832-QI4A

Prepared for : Shanghai Ibeelink technology Co., LTD
Address : Rm 3900, Building No.2, No.1,Haikun Road, Fengxian District,
Shanghai, P.R. China

Prepared By : Shenzhen Alpha Product Testing Co., Ltd.
Address : Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,
Shenzhen, Guangdong, China

Report Number : A2005306-C01-R01
Date of Receipt : June 3, 2020
Date of Test : June 4, 2020-June 11, 2020
Date of Report : June 11, 2020
Version Number : V0

TABLE OF CONTENTS

Description	Page
1. Summary of Standards And Results-----	6
1.1. Description of Standards and Results -----	6
2. General Information -----	7
2.1. Description of Device (EUT)-----	7
2.2. Accessories of Device (EUT) -----	8
2.3. Tested Supporting System Details -----	8
2.4. Block Diagram of connection between EUT and simulators -----	8
2.5. Test Mode Description -----	8
2.6. Test Conditions -----	8
2.7. Test Facility -----	9
2.8. Measurement Uncertainty -----	9
2.9. Test Equipment List -----	10
3. Spurious Emission -----	11
3.1. Test Limits -----	11
3.2. Test Procedure -----	11
3.3. Test Setup -----	12
3.4. Test Results -----	13
4. Power Line Conducted Emission-----	17
4.1. Test Limits -----	17
4.2. Test Procedure -----	17
4.3. Test Setup -----	17
4.4. Test Results -----	18
5. Conducted Maximum Output Power -----	20
5.1. Test limits -----	20
5.2. Test Procedure -----	20
5.3. Test Setup -----	20
5.4. Test Results -----	20
6. Peak Power Spectral Density-----	21
6.1. Test limits -----	21
6.2. Test Procedure -----	21
6.3. Test Setup -----	21
6.4. Test Results -----	21
7. Bandwidth-----	26
7.1. Test limits -----	26
7.2. Test Procedure -----	26
7.3. Test Setup -----	26
7.4. Test Results -----	26
8. Band Edge Check-----	35
8.1. Test limits -----	35
8.2. Test Procedure -----	35
8.3. Test Setup -----	35
8.4. Test Results -----	35
9. Antenna Requirement -----	42
9.1. Standard Requirement -----	42
9.2. Antenna Connected Construction-----	42

9.3. Results -----	42
10. Test setup photo-----	43
10.1. Photos of Radiated emission -----	43
10.2. Photos of Conducted Emission test-----	44
11. EUT photo-----	45

TEST REPORT DECLARATION

Applicant : Shanghai Ibeelink technology Co., LTD
Address : Rm 3900, Building No.2, No.1,Haikun Road, Fengxian District, Shanghai, P.R. China
Manufacturer : Shanghai Ibeelink technology Co., LTD
Address : Rm 3900, Building No.2, No.1,Haikun Road, Fengxian District, Shanghai, P.R. China
EUT Description : 2.4G Bluetooth Module
(A) Model No. : BB832-QI4A
(B) Trademark : N/A

Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247

ANSI C63.10-2013

The device described above is tested by Shenzhen Alpha Product Testing Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C limits both conducted and radiated emissions. The test results are contained in this test report and Shenzhen Alpha Product Testing Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After the test, our opinion is that EUT compliance with the requirement of the above standards.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Alpha Product Testing Co., Ltd.

Tested by (name + signature).....:

Lucas Pang
Project Engineer



Approved by (name + signature).....:

Simple Guan
Project Manager



Date of issue.....:

June 11, 2020

Revision History

Revision	Issue Date	Revisions	Revised By
V0	June 11, 2020	Initial released Issue	Lucas Pang

1. SUMMARY OF STANDARDS AND RESULTS

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Test Item	Test Requirement	Standards Paragraph	Result
Conducted Emission	FCC PART 15	15.207	P
6dB Bandwidth	FCC PART 15	15.247 (a)(2)	P
Output Power	FCC PART 15	15.247 (b)(3)	P
Radiated Spurious Emission	FCC PART 15	15.247 (c)	P
Conducted Spurious & Band Edge Emission	FCC PART 15	15.247 (d)	P
Power Spectral Density	FCC PART 15	15.247 (e)	P
Radiated Band Edge Emission	FCC PART 15	15.205	P
Antenna Requirement	FCC PART 15	15.203	P
Note:	1. P is an abbreviation for Pass. 2. F is an abbreviation for Fail. 3. N/A is an abbreviation for Not Applicable.		

2. GENERAL INFORMATION

2.1. Description of Device (EUT)

EUT Name	: 2.4G Bluetooth Module
Trade Name	: N/A
Model No.	: BB832-QI4A
DIFF	: N/A
Power supply	: DC 1.7-3.6V
Radio Technology	: Bluetooth V5.0 BLE
Operation frequency	: 2402 MHz -2480 MHz
Modulation	: GFSK
Modulation rate	: 1Mbps, 2Mbps
Antenna Type	: PCB Antenna, Maximum Gain is 2.5dBi
Software	: BB832-QI4A v1.0
Hardware	: BB832-QI4A v1.12
Intend use environment	: Residential, commercial and light industrial environment

2.2.Accessories of Device (EUT)

Accessories1 : /
 Manufacturer : /
 Model : /
 Ratings : /

2.3.Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number	Certification or SDOC
1	Notebook PC	ACER	ASPIRE M1830	PTSF90C00305005C AC3000	SDOC

2.4.Block Diagram of connection between EUT and simulators

EUT

2.5.Test Mode Description

Tested mode, channel, and data rate information		
Mode	Channel	Frequency (MHz)
GFSK (1M)	Low :CH1	2402
	Middle: CH20	2440
	High: CH40	2480
GFSK (2M)	Low :CH1	2402
	Middle: CH20	2440
	High: CH40	2480

2.6.Test Conditions

Items	Required	Actual
Temperature range:	15-35℃	24℃
Humidity range:	25-75%	56%
Pressure range:	86-106kPa	980kPa

2.7. Test Facility

Shenzhen Alpha Product Testing Co., Ltd
Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103,
Shenzhen, Guangdong, China

June 21, 2018 File on Federal Communication Commission
Registration Number: 293961

July 25, 2017 Certificated by IC
Registration Number: 12135A

2.8. Measurement Uncertainty

(95% confidence levels, k=2)

Item	Uncertainty
Uncertainty for Power point Conducted Emissions Test	2.74dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	2.13 dB(Polarize: V)
	2.57dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	3.77dB(Polarize: V)
	3.80dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz)	4.13dB(Polarize: H)
	4.16dB(Polarize: V)
Uncertainty for radio frequency	5.4×10^{-8}
Uncertainty for conducted RF Power	0.37dB
Uncertainty for temperature	0.2°C
Uncertainty for humidity	1%
Uncertainty for DC and low frequency voltages	0.06%

2.9.Test Equipment List

Equipment	Manufacture	Model No.	Serial No.	Last cal.	Cal Interval
9*6*6 anechoic chamber	CHENYU	9*6*6	N/A	2019.09.06	3Year
Spectrum analyzer	ROHDE&SCHWARZ	FSV40-N	102137	2019.09.05	1 Year
Spectrum analyzer	Agilent	N9020A	MY499100060	2019.09.05	1 Year
Receiver	ROHDE&SCHWARZ	ESR	1316.3003K03-10208 2-Wa	2019.09.06	1 Year
Receiver	R&S	ESCI	101165	2019.09.05	1 Year
Bilog Antenna	Schwarzbeck	VULB 9168	VULB9168-438	2019.09.07	2Year
Horn Antenna	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D(1201)	2020.04.12	2Year
Active Loop Antenna	SCHWARZBECK	FMZB 1519B	00059	2019.09.07	2Year
Cable	Resenberger	N/A	No.1	2019.09.05	1 Year
Cable	Resenberger	N/A	No.2	2019.09.05	1 Year
Cable	Resenberger	N/A	No.3	2019.09.05	1 Year
Pre-amplifier	HP	HP8347A	2834A00455	2019.09.05	1 Year
Pre-amplifier	Agilent	8449B	3008A02664	2019.09.05	1 Year
L.I.S.N.#1	Schwarzbeck	NSLK8126	8126466	2019.09.05	1 Year
L.I.S.N.#2	ROHDE&SCHWARZ	ENV216	101043	2019.09.05	1 Year
20db Attenuator	ICPROBING	IATS1	82347	2019.08.26	1 Year
Horn Antenna	SCHWARZBECK	BBHA9170	00946	2019.09.07	2 Year
Preamplifier	SKET	LNPA_1840-50	SK2018101801	2019.09.06	1 Year
Power Meter	Agilent	E9300A	MY41496625	2019.09.06	1 Year
Temp. & Humid. Chamber	Weihuang	WHTH-1000-40-880	100631	2019.09.06	1 Year
Switching Mode Power Supply	JUNKE	JK12010S	20140927-6	2019.09.05	1 Year

3. SPURIOUS EMISSION

3.1. Test Limits

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Harmonic emissions limits comply with below 54 dBuV/m at 3m. Other emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or comply with the radiated emissions limits specified in section 15.209(a) limit in the table below has to be followed.

NOTE:

- a) The tighter limit applies at the band edges.
- b) $\text{Emission Level(dB uV/m)} = 20 \log \text{Emission Level(uv/m)}$

3.2. Test Procedure

The measuring distance of 3m shall be used for measurements at frequency up to 1GH and above 1GHz, The EUT was placed on a rotating 0.8 m high above ground for below 1GHz and 1.5m high for above 1GHz testing, The table was rotated 360 degrees to determine the position of the highest radiation


The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set of make measurement.

The initial step in collecting conducted emission data is a spectrum analyzer Peak detector mode pre-scanning the measurement frequency range. Significant Peaks are then marked. and then Qusia Peak Detector mode premeasured


If Peak value comply with QP limit Below 1GHz. The EUT deemed to comply with QP limit. But the Peak value and average value both need to comply with applicable limit above 1GHz.

For the actual test configuration, please see the test setup photo.


3.3. Test Setup



Below 30MHz Test Setup



Above 30MHz Test Setup



Above 1GHz Test Setup

3.4. Test Results

Test Condition

Continual Transmitting in maximum power.

9KHz~150KHz	RBW200Hz	VBW1KHz
150KHz~30MHz	RBW9KHz	VBW 30KHz
30MHz~1GHz	RBW120KHz	VBW 300KHz
Above1GHz	RBW1MHz	VBW 3MHz

We have scanned the 10th harmonic from 9 kHz to the EUT.


Detailed information please see the following page.

From 9KHz to 30MHz: Conclusion: PASS

Note: 1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


2. Only show the test data of the worst Channel in this report.

Antenna polarity: Horizontal



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		37.1940	8.42	14.10	22.52	40.00	-17.48	peak		
2		61.0242	9.74	12.87	22.61	40.00	-17.39	peak		
3	*	125.6217	14.68	13.35	28.03	43.50	-15.47	peak		
4		149.2761	9.79	15.00	24.79	43.50	-18.71	peak		
5		322.3014	9.03	14.67	23.70	46.00	-22.30	peak		
6		582.3337	10.57	19.87	30.44	46.00	-15.56	peak		

Antenna polarity: Vertical



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		41.0743	8.64	14.34	22.98	40.00	-17.02	peak		
2		56.6921	8.61	13.46	22.07	40.00	-17.93	peak		
3		158.8345	9.65	15.04	24.69	43.50	-18.81	peak		
4		233.9221	10.15	12.40	22.55	46.00	-23.45	peak		
5		419.5491	10.08	16.72	26.80	46.00	-19.20	peak		
6	*	913.8228	8.73	24.23	32.96	46.00	-13.04	peak		

Notes: Above is below 1GHz test data. This report only shall the worst case mode for TX 2402MHz.

Test Mode: TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	42.46	V	33.98	10.22	34.25	52.41	74	21.59	PK
4804	32.69	V	33.98	10.22	34.25	42.64	54	11.36	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
4804	42.43	H	33.98	10.22	34.25	52.38	74	21.62	PK
4804	31.73	H	33.98	10.22	34.25	41.68	54	12.32	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
Test Mode: TX Mid									
4880	41.91	V	33.98	10.22	34.25	51.86	74	22.14	PK
4880	32.76	V	33.98	10.22	34.25	42.71	54	11.29	AV
7320	/	/	/	/	/	/	/	/	/
9760	/	/	/	/	/	/	/	/	/
4880	41.96	H	33.98	10.22	34.25	51.91	74	22.09	PK
4880	31.40	H	33.98	10.22	34.25	41.35	54	12.65	AV
7320	/	/	/	/	/	/	/	/	/
9760	/	/	/	/	/	/	/	/	/
Test Mode: TX High									
4960	41.86	V	33.98	10.22	34.25	51.81	74	22.19	PK
4960	32.80	V	33.98	10.22	34.25	42.75	54	11.25	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
4960	42.83	H	33.98	10.22	34.25	52.78	74	21.22	PK
4960	31.41	H	33.98	10.22	34.25	41.36	54	12.64	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
Note:									
1, Result = Read level + Antenna factor + cable loss-Amp factor									
2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.									

4. POWER LINE CONDUCTED EMISSION

4.1. Test Limits

Frequency MHz	Limits dB(μ V)	
	Quasi-peak Level	Average Level
0.15 -0.50	66 -56*	56 - 46*
0.50 -5.00	56	46
5.00 -30.00	60	50


Notes: 1. *Decreasing linearly with logarithm of frequency.
 2. The lower limit shall apply at the transition frequencies.
 3. The limit decreases in line with the logarithm of the frequency in range of 0.15 to 0.50 MHz.

4.2. Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10:2013 on Conducted Emission Measurement.

The bandwidth of test receiver is set at 9 kHz.


4.3. Test Setup



4.4. Test Results


Pass

Polarity: L



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.1980	41.49	9.92	51.41	63.69	-12.28	peak	
2	*	0.4620	35.33	9.95	45.28	56.66	-11.38	peak	
3		1.0980	33.67	9.91	43.58	56.00	-12.42	peak	
4		1.8420	33.63	9.89	43.52	56.00	-12.48	peak	
5		6.8400	24.65	10.11	34.76	60.00	-25.24	peak	
6		13.1639	33.09	10.29	43.38	60.00	-16.62	peak	

Polarity: N



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1	*	0.1500	45.35	9.94	55.29	66.00	-10.71	peak	
2		0.2038	41.72	9.92	51.64	63.45	-11.81	peak	
3		0.4319	33.00	9.95	42.95	57.22	-14.27	peak	
4		0.8639	32.26	9.96	42.22	56.00	-13.78	peak	
5		1.6978	34.35	9.89	44.24	56.00	-11.76	peak	
6		14.9039	34.32	10.33	44.65	60.00	-15.35	peak	

Note: All modes and channels have been tested and only the TX 2402MHz mode with the worst data is listed.

5. CONDUCTED MAXIMUM OUTPUT POWER

5.1. Test limits

Please refer section RSS-247 & 15.247.

5.2. Test Procedure


Details see the KDB 558074 D01 15.247 Meas Guidance v05r02

5.2.1 Place the EUT on the table and set it in transmitting mode.

5.2.2 Measure out each mode and each bands peak output power of EUT.

Note: The cable loss and attenuator loss were offset into measure device as amplitude offset.

5.3. Test Setup



5.4. Test Results

GFSK(1M)

Channel	Frequency (MHz)	PK Output Power (dBm)	PK Output Power (mW)	Limit (dBm)	Result
CH1	2402	2.510	1.782	30	Pass
CH20	2440	2.754	1.885	30	Pass
CH40	2480	1.754	1.498	30	Pass

GFSK(2M)

Channel	Frequency (MHz)	PK Output Power (dBm)	PK Output Power (mW)	Limit (dBm)	Result
CH1	2402	2.507	1.781	30	Pass
CH20	2440	2.745	1.881	30	Pass
CH40	2480	1.767	1.502	30	Pass

6. PEAK POWER SPECTRAL DENSITY

6.1. Test limits

6.1.1 Please refer section RSS-247 & 15.247.

6.1.2 For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

6.1.3 The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

6.2. Test Procedure

Details see the KDB 558074 D01 15.247 Meas Guidance v05r02

6.2.1 Place the EUT on the table and set it in transmitting mode.


6.2.2 Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

6.2.3 Set the spectrum analyzer as $RBW = 3\text{kHz}$ (Set the RBW to: $3\text{ kHz} \leq RBW \leq 100\text{ kHz}$), $VBW = 10\text{kHz}$ (Set the $VBW \geq 3 \times RBW$), $\text{span} = 1.5 \times \text{DTS bandwidth}$., detail see the test plot.

6.2.4 Record the max reading.

6.2.5 Repeat the above procedure until the measurements for all frequencies are completed.

6.3. Test Setup



6.4. Test Results


Pass

The test results are listed in next pages.

GFSK (1M)


Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	BLE	2402	Ant 1	-15.489	8	Pass
NVNT	BLE	2440	Ant 1	-15.567	8	Pass
NVNT	BLE	2480	Ant 1	-16.25	8	Pass

PSD NVNT BLE 2402MHz Ant1




Date: 11.JUN.2020 04:56:52

PSD NVNT BLE 2440MHz Ant1



Date: 11.JUN.2020 05:14:31

PSD NVNT BLE 2480MHz Ant1




Date: 11.JUN.2020 05:13:05

GFSK (2M)


Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	BLE	2402	Ant 1	-17.295	8	Pass
NVNT	BLE	2440	Ant 1	-17.145	8	Pass
NVNT	BLE	2480	Ant 1	-17.804	8	Pass

PSD NVNT BLE 2402MHz Ant1




Date: 11.JUN.2020 05:26:32

PSD NVNT BLE 2440MHz Ant1



Date: 11.JUN.2020 05:29:21

PSD NVNT BLE 2480MHz Ant1



Date: 11.JUN.2020 05:36:09

7. BANDWIDTH

7.1. Test limits

Please refer section RSS-247 & 15.247


For direct sequence systems, the minimum 6dB bandwidth shall be at least 500 kHz.

7.2. Test Procedure

Details see the KDB 558074 D01 15.247 Meas Guidance v05r02

- a) The bandwidth is measured at an amplitude level reduced 20dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.
- b) The test receiver set $RBW = 100\text{kHz}$, $VBW \geq 3 * RBW = 300\text{kHz}$, Sweep time set auto, detail see the test plot.

7.3. Test Setup



7.4. Test Results


Pass

The test results are listed in next pages.


GFSK(1M)

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE	2402	Ant 1	1.0303	0.6918	0.5	Pass
NVNT	BLE	2440	Ant 1	1.0329	0.6844	0.5	Pass
NVNT	BLE	2480	Ant 1	1.0359	0.6896	0.5	Pass


OBW NVNT BLE 2402MHz Ant1



-6 dB BW NVNT BLE 2402MHz Ant1




OBW NVNT BLE 2440MHz Ant1




Date: 11.JUN.2020 05:14:02

-6 dB BW NVNT BLE 2440MHz Ant1




Date: 11.JUN.2020 05:14:16

OBW NVNT BLE 2480MHz Ant1



Date: 11.JUN.2020 05:10:28

-6 dB BW NVNT BLE 2480MHz Ant1




Date: 11.JUN.2020 05:10:41


GFSK(2M)

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE	2402	Ant 1	1.8614	1.1902	0.5	Pass
NVNT	BLE	2440	Ant 1	1.8664	1.1874	0.5	Pass
NVNT	BLE	2480	Ant 1	1.8726	1.1914	0.5	Pass

OBW NVNT BLE 2402MHz Ant1



-6 dB BW NVNT BLE 2402MHz Ant1




OBW NVNT BLE 2440MHz Ant1




Date: 11.JUN.2020 05:29:00

-6 dB BW NVNT BLE 2440MHz Ant1




Date: 11.JUN.2020 05:29:14

OBW NVNT BLE 2480MHz Ant1



Date: 11.JUN.2020 05:35:36

-6 dB BW NVNT BLE 2480MHz Ant1



Date: 11.JUN.2020 05:35:49

8. BAND EDGE CHECK

8.1. Test limits

Please refer section RSS-GEN&15.247.

8.2. Test Procedure

Details see the KDB 558074 D01 15.247 Meas Guidance v05r02

8.2.1 Put the EUT on a 0.8m high table, power on the EUT. Emissions were scanned and measured rotating the EUT to 360 degrees, Find the maximum Emission

8.2.2 Check the spurious emissions out of band.

8.2.3 RBW 1MHz ,VBW 3MHz ,peak detector for peak value , RBW 1MHz ,VBW 3MHz ,RMS detector for AV value.

8.3. Test Setup

Same as 5.2.2.


8.4. Test Results

Pass


The test results are listed in next pages.

GFSK (1M)


Band Edge NVNT BLE 2402MHz Ant1 Ref



Band Edge NVNT BLE 2402MHz Ant1 Emission




Band Edge NVNT BLE 2480MHz Ant1 Ref



Date: 11.JUN.2020 05:10:53


Band Edge NVNT BLE 2480MHz Ant1 Emission



Date: 11.JUN.2020 05:10:57


GFSK (2M)

Band Edge NVNT BLE 2402MHz Ant1 Ref



Date: 11.JUN.2020 05:26:37

Band Edge NVNT BLE 2402MHz Ant1 Emission




Date: 11.JUN.2020 05:26:42

Band Edge NVNT BLE 2480MHz Ant1 Ref



Date: 11.JUN.2020 05:36:14

Band Edge NVNT BLE 2480MHz Ant1 Emission




Date: 11.JUN.2020 05:36:17


Radiated Method: GFSK(1M)

Test Mode: CH-L

Polarization: Vertical




Polarization: Horizontal




Test Mode: CH-H

Polarization: Vertical




Polarization: Horizontal




Radiated Method: GFSK(2M)

Test Mode: CH-L

Polarization: Vertical




Polarization: Horizontal




Test Mode: CH-H

Polarization: Vertical



Polarization: Horizontal



9. ANTENNA REQUIREMENT

9.1. Standard Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

9.2. Antenna Connected Construction


The antenna is internal antenna and no consideration of replacement. Please see EUT photo for details.

9.3. Results

The EUT antenna is PCB Antenna. It complies with the standard requirement.

10. TEST SETUP PHOTO



10.1. Photos of Radiated emission





10.2.Photos of Conducted Emission test



11.EUT PHOTO





-----THE END OF REPORT-----