

FCC Test Report (BT-EDR)

Report No.: RF160715E05-2

FCC ID: UZ7AP7622

Test Model: AP-7622

Received Date: July 15, 2016

Test Date: Sep. 13 to 29, 2016

Issued Date: Oct. 28, 2016

Applicant: Zebra Technologies Corporation

Address: One Zebra Plaza, Holtsville, NY,11742, USA

Manufacturer: Zebra Technologies Corporation

Address: One Zebra Plaza, Holtsville, NY,11742, USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

Test Location (1): E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

Test Location (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin
Chu Hsien 307, Taiwan R.O.C.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	4
1 Certificate of Conformity	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Modification Record	6
3 General Information	7
3.1 General Description of EUT (BT-EDR)	7
3.2 Description of Test Modes	9
3.2.1 Test Mode Applicability and Tested Channel Detail	10
3.3 Description of Support Units	12
3.3.1 Configuration of System under Test	13
3.4 General Description of Applied Standards	16
4 Test Types and Results	17
4.1 Radiated Emission and Bandedge Measurement	17
4.1.1 Limits of Radiated Emission and Bandedge Measurement	17
4.1.2 Test Instruments	18
4.1.3 Test Procedures	19
4.1.4 Deviation from Test Standard	20
4.1.5 Test Setup	21
4.1.6 EUT Operating Conditions	22
4.1.7 Test Results (Mode 1)	23
4.1.8 Test Results (Mode 2)	35
4.2 Conducted Emission Measurement	41
4.2.1 Limits of Conducted Emission Measurement	41
4.2.2 Test Instruments	41
4.2.3 Test Procedures	42
4.2.4 Deviation From Test Standard	42
4.2.5 Test Setup	42
4.2.6 EUT Operating Condition	42
4.2.7 Test Results (Mode 1)	43
4.2.8 Test Results (Mode 2)	45
4.3 Number of Hopping Frequency Used	47
4.3.1 Limits of Hopping Frequency Used Measurement	47
4.3.2 Test Setup	47
4.3.3 Test Instruments	47
4.3.4 Test Procedure	47
4.3.5 Deviation from Test Standard	47
4.3.6 Test Results	48
4.4 Dwell Time on Each Channel	49
4.4.1 Limits of Dwell Time on Each Channel Measurement	49
4.4.2 Test Setup	49
4.4.3 Test Instruments	49
4.4.4 Test Procedures	49
4.4.5 Deviation from Test Standard	49
4.4.6 Test Results	50
4.5 Channel Bandwidth	54
4.5.1 Limits of Channel Bandwidth Measurement	54
4.5.2 Test Setup	54
4.5.3 Test Instruments	54
4.5.4 Test Procedure	54
4.5.5 Deviation from Test Standard	54
4.5.6 EUT Operating Condition	54
4.5.7 Test Results	55

4.6	Hopping Channel Separation	56
4.6.1	Limits of Hopping Channel Separation Measurement.....	56
4.6.2	Test Setup.....	56
4.6.3	Test Instruments	56
4.6.4	Test Procedure	56
4.6.5	Deviation from Test Standard	56
4.6.6	Test Results	57
4.7	Maximum Output Power.....	58
4.7.1	Limits of Maximum Output Power Measurement	58
4.7.2	Test Setup.....	58
4.7.3	Test Instruments	58
4.7.4	Test Procedure	58
4.7.5	Deviation from Test Standard	58
4.7.6	EUT Operating Condition	58
4.7.7	Test Results	59
4.8	Conducted Out of Band Emission Measurement.....	60
4.8.1	Limits of Conducted Out of Band Emission Measurement.....	60
4.8.2	Test Instruments	60
4.8.3	Test Procedure	60
4.8.4	Deviation from Test Standard	60
4.8.5	EUT Operating Condition	60
4.8.6	Test Results	60
5	Pictures of Test Arrangements.....	63
	Appendix – Information on the Testing Laboratories	64

Release Control Record

Issue No.	Description	Date Issued
RF160715E05-2	Original release.	Oct. 28, 2016

1 Certificate of Conformity

Product: Access Point

Brand: ZEBRA

Test Model: AP-7622

Sample Status: ENGINEERING SAMPLE

Applicant: Zebra Technologies Corporation

Test Date: Sep. 13 to 29, 2016

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :


Wendy Wu / Specialist

Date:

Oct. 28, 2016

Approved by :


May Chen / Manager

Date:

Oct. 28, 2016

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (SECTION 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -12.38dB at 23.12891MHz.
15.247(a)(1)(iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.
15.247(a)(1)(iii)	Dwell Time on Each Channel	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power	PASS	Meet the requirement of limit.
15.205 & 209 & 15.247(d)	Radiated Emissions & Band Edge Measurement	PASS	Meet the requirement of limit. Minimum passing margin is -3.9dB at 37.10MHz.
15.247(d)	Antenna Port Emission	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	Antenna connector is i-pex(MHF) not a standard connector.

NOTE: If The Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expended Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	1.83 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	5.43 dB
Radiated Emissions above 1 GHz	1GHz ~ 6GHz	3.72 dB
	6GHz ~ 18GHz	4.00 dB
	18GHz ~ 40GHz	4.11 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT (BT-EDR)

Product	Access Point
Brand	ZEBRA
Test Model	AP-7622
Status of EUT	ENGINEERING SAMPLE
SW Version	esdk 5.0.9.1
HW Version	ZEBRA ASPEN-C BCM47452 V20 D1 20160603_fischer.brd
Power Supply Rating	12Vdc from power adapter or 55Vdc from POE
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8DPSK
Modulation Technology	FHSS
Transfer Rate	Up to 3Mbps
Operating Frequency	2402MHz ~ 2480MHz
Number of Channel	79
Output Power	6.339mW
Antenna Type	Refer to Note
Antenna Connector	Refer to Note
Accessory Device	NA
Data Cable Supplied	NA

Note:

1. There are WLAN, BT technology used for the EUT.
2. Simultaneously transmission condition.

Condition	Technology		
1	WLAN (2.4GHz-Chain0)	WLAN (5GHz-Chain1)	BT
2	WLAN (2.4GHz-Chain1)	WLAN (5GHz-Chain0)	BT
3	WLAN (2.4GHz-Chain0)	WLAN (2.4GHz-Chain1)	BT
4	WLAN (5GHz-Chain0)	WLAN (5GHz-Chain1)	BT

Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found.

3. The EUT must be supplied with a power adapter and POE as following table:

Adapter (Only for test not for sale)		
Brand	Model No.	Spec.
HIPRO	HP-A0502R3D	Input: 100-240Vac, 50-60Hz, 2.4A Output: 12Vdc, 4.16A DC output cable (Unshielded, 1.8m with one core)
POE(Only for test not for sale)		
Brand	Model No.	Spec.
Symbol	PD-9001GR/AT/AC	Input: 100-240Vac, 50/60Hz, 0.67A Output: 55Vdc, 0.6A P/N : AP-PSBIAS-2P3-ATR

From above adapters and POE, the spurious emission above 1GHz worst case was found in **POE**. Therefore only the test data of the modes were recorded in this report individually.

4. The antennas provided to the EUT, please refer to the following table:

No.	PCB Chain No	Brand	Model	Antenna Gain(dBi) Including cable loss	Frequency range	Antenna Type	Connector type
1	Chain 0	NA	NA	3.64	2.4~2.4835GHz	Monopole	i-pex(MHF)
				4.14	5.15~5.25GHz	Monopole	i-pex(MHF)
				4.33	5.25~5.35GHz	Monopole	i-pex(MHF)
				4.66	5.47~5.725GHz	Monopole	i-pex(MHF)
				4.85	5.725~5.85GHz	Monopole	i-pex(MHF)
2	Chain 1	NA	NA	2.65	2.4~2.4835GHz	Monopole	i-pex(MHF)
				4.5	5.15~5.25GHz	Monopole	i-pex(MHF)
				5.77	5.25~5.35GHz	Monopole	i-pex(MHF)
				5.54	5.47~5.725GHz	Monopole	i-pex(MHF)
				4.78	5.725~5.85GHz	Monopole	i-pex(MHF)
3	BT	NA	NA	2.42	2.4~2.483GHz	Monopole	i-pex(MHF)

5. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Description of Test Modes

79 channels are provided for BT-EDR mode:

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE $\geq$ 1G	RE<1G	PLC	APCM	
1	√	√	√	√	Power from POE
2	-	√	√	-	Power from adapter

Where **RE $\geq$ 1G**: Radiated Emission above 1GHz **RE<1G**: Radiated Emission below 1GHz
PLC: Power Line Conducted Emission **APCM**: Antenna Port Conducted Measurement

NOTE:

1. The EUT had been pre-tested on the positioned of each 2 axis. The worst case was found when positioned on **Y-plane**.
2. "-" means no effect.

Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0	FHSS	GFSK	DH5

Antenna Port Conducted Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

Test Condition:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE $\geq$ 1G	25deg. C, 69%RH	120Vac, 60Hz	Weiwei Lo
RE<1G	28deg. C, 65%RH	120Vac, 60Hz	Andy Ho
PLC	25deg. C, 70%RH	120Vac, 60Hz	Barry Lee
APCM	25deg. C, 60%RH	120Vac, 60Hz	Anderson Chen

3.3 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Laptop	DELL	E6440	F9LYQ32	FCC DoC	Provided by Lab
B.	POE Adapter	Symbol	PD-9001GR/AT/AC	NA	NA	Supplied by client


Note:

1. All power cords of the above support units are non-shielded (1.8m).


ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	RJ-45 Cable	1	10	No	0	Provided by Lab
2.	DC Cable	1	1.8	No	1	Supplied by client
3.	AC Cable	1	1.8	No	0	Provided by Lab
4.	RJ-45 Cable	1	3	No	0	Provided by Lab
5.	Console Cable	1	1.5	No	0	Provided by Lab

3.3.1 Configuration of System under Test


Adapter Mode:



POE Mode (for Conduction test)



POE Mode (for other test)



3.4 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

Note: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Agilent	N9038A	MY51210202	Dec. 16, 2015	Dec. 15, 2016
Pre-Amplifier ^(*) EMCI	EMC001340	980142	Jan. 20, 2016	Jan. 19, 2018
Loop Antenna(*) Electro-Metrics	EM-6879	264	Dec. 16, 2014	Dec. 15, 2016
RF Cable	NA	LOOPCAB-001 LOOPCAB-002	Jan. 18, 2016	Jan. 17, 2017
Pre-Amplifier Mini-Circuits	ZFL-1000VH2B	AMP-ZFL-04	Nov. 11, 2015	Nov. 10, 2016
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-361	Jan. 07, 2016	Jan. 06, 2017
RF Cable	8D-FB	CHHCAB-001-1 CHHCAB-001-2	Oct. 04, 2015	Oct. 03, 2016
	RF-141	CHHCAB-004	Oct. 04, 2015	Oct. 03, 2016
Horn_Antenna FT-RF	HA-07M18G-NF	0000220091110	Jan. 18, 2016	Jan. 17, 2017
Pre-Amplifier Agilent	8449B	3008A01923	Oct. 27, 2015	Oct. 26, 2016
RF Cable	NA	131206 131213 131215 SNMY23685/4	Jan. 15, 2016	Jan. 14, 2017
Spectrum Analyzer Agilent	E4446A	MY48250254	Nov. 25, 2015	Nov. 24, 2016
Pre-Amplifier SPACEK LABS	SLKKa-48-6	9K16	Dec. 11, 2015	Dec. 10, 2016
Horn_Antenna SCHWARZBECK	BBHA 9170	9170-424	Jan. 18, 2016	Jan. 17, 2017
RF Cable	SUCOFLEX 102	36442/2 36434/2	Dec. 10, 2015	Dec.09, 2016
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Antenna Tower & Turn Table CT	CM100	NA	NA	NA
Boresight Antenna Fixture	FBA-01	FBA-WD02	NA	NA
Spectrum Analyzer R&S	FSP40	100060	May 11, 2016	May 10, 2017

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. *The calibration interval of the above test instruments is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
3. The test was performed in 966 Chamber No. H.
4. The FCC Site Registration No. is 797305.
5. The CANADA Site Registration No. is IC 7450H-3.
6. Loop antenna was used for all emissions below 30 MHz.
7. Tested Date: Sep. 16 to 29, 2016

4.1.3 Test Procedures

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Both X and Y axes of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- Connected the EUT with the Laptop which is placed on remote site.
- Controlling software (run tera term paste command) has been activated to set the EUT on specific status.

4.1.7 Test Results (Mode 1)

Above 1GHz Data:

BT_GFSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2382.00	54.9 PK	74.0	-19.1	1.74 H	288	54.0	0.9
2	2382.00	24.8 AV	54.0	-29.2	1.74 H	288	23.9	0.9
3	*2402.00	110.4 PK			1.74 H	288	109.3	1.1
4	*2402.00	80.3 AV			1.74 H	288	79.2	1.1
5	4804.00	55.2 PK	74.0	-18.8	1.42 H	208	44.5	10.7
6	4804.00	25.1 AV	54.0	-28.9	1.42 H	208	14.4	10.7
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2382.00	53.3 PK	74.0	-20.7	1.19 V	27	52.4	0.9
2	2382.00	23.2 AV	54.0	-30.8	1.19 V	27	22.3	0.9
3	*2402.00	103.7 PK			1.19 V	27	102.6	1.1
4	*2402.00	73.6 AV			1.19 V	27	72.5	1.1
5	4804.00	56.2 PK	74.0	-17.8	1.61 V	147	45.5	10.7
6	4804.00	26.1 AV	54.0	-27.9	1.61 V	147	15.4	10.7

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on $0.625 * 5$ per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1$ dB
7. Average value = peak reading + $20\log(\text{duty cycle})$.

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	109.5 PK			2.04 H	331	108.4	1.1
2	*2441.00	79.4 AV			2.04 H	331	78.3	1.1
3	4882.00	55.2 PK	74.0	-18.8	1.46 H	211	44.5	10.7
4	4882.00	25.1 AV	54.0	-28.9	1.46 H	211	14.4	10.7
5	7323.00	60.0 PK	74.0	-14.0	1.53 H	189	44.7	15.3
6	7323.00	29.9 AV	54.0	-24.1	1.53 H	189	14.6	15.3
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	104.2 PK			1.25 V	91	103.1	1.1
2	*2441.00	74.1 AV			1.25 V	91	73.0	1.1
3	4882.00	56.0 PK	74.0	-18.0	1.59 V	146	45.3	10.7
4	4882.00	25.9 AV	54.0	-28.1	1.59 V	146	15.2	10.7
5	7323.00	60.1 PK	74.0	-13.9	1.55 V	267	44.8	15.3
6	7323.00	30.0 AV	54.0	-24.0	1.55 V	267	14.7	15.3

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1 \text{ dB}$
7. Average value = peak reading + $20\log(\text{duty cycle})$.

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	109.1 PK			1.99 H	316	107.7	1.4
2	*2480.00	79.0 AV			1.99 H	316	77.6	1.4
3	2500.00	56.9 PK	74.0	-17.1	2.05 H	320	55.6	1.3
4	2500.00	26.8 AV	54.0	-27.2	2.05 H	320	25.5	1.3
5	4960.00	54.6 PK	74.0	-19.4	1.44 H	208	43.9	10.7
6	4960.00	24.5 AV	54.0	-29.5	1.44 H	208	13.8	10.7
7	7440.00	59.3 PK	74.0	-14.7	1.57 H	175	43.6	15.7
8	7440.00	29.2 AV	54.0	-24.8	1.57 H	175	13.5	15.7
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	103.8 PK			1.24 V	97	102.4	1.4
2	*2480.00	73.7 AV			1.24 V	97	72.3	1.4
3	2500.00	54.9 PK	74.0	-19.1	1.24 V	64	53.6	1.3
4	2500.00	24.8 AV	54.0	-29.2	1.24 V	64	23.5	1.3
5	4960.00	56.4 PK	74.0	-17.6	1.60 V	150	45.7	10.7
6	4960.00	26.3 AV	54.0	-27.7	1.60 V	150	15.6	10.7
7	7440.00	60.0 PK	74.0	-14.0	1.60 V	271	44.3	15.7
8	7440.00	29.9 AV	54.0	-24.1	1.60 V	271	14.2	15.7

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1 \text{ dB}$
7. Average value = peak reading + $20\log(\text{duty cycle})$.

BT_8DPSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	54.6 PK	74.0	-19.4	1.74 H	288	53.7	0.9
2	2390.00	24.5 AV	54.0	-29.5	1.74 H	288	23.6	0.9
3	*2402.00	108.4 PK			1.74 H	288	107.3	1.1
4	*2402.00	78.3 AV			1.74 H	288	77.2	1.1
5	4804.00	54.8 PK	74.0	-19.2	1.46 H	194	44.1	10.7
6	4804.00	24.7 AV	54.0	-29.3	1.46 H	194	14.0	10.7
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	51.8 PK	74.0	-22.2	1.27 V	93	50.9	0.9
2	2390.00	21.7 AV	54.0	-32.3	1.27 V	93	20.8	0.9
3	*2402.00	103.2 PK			1.27 V	93	102.1	1.1
4	*2402.00	73.1 AV			1.27 V	93	72.0	1.1
5	4804.00	56.7 PK	74.0	-17.3	1.66 V	119	46.0	10.7
6	4804.00	26.6 AV	54.0	-27.4	1.66 V	119	15.9	10.7

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1 \text{ dB}$
7. Average value = peak reading + $20\log(\text{duty cycle})$.

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	108.3 PK			1.73 H	289	107.2	1.1
2	*2441.00	78.2 AV			1.73 H	289	77.1	1.1
3	4882.00	55.2 PK	74.0	-18.8	1.46 H	203	44.5	10.7
4	4882.00	25.1 AV	54.0	-28.9	1.46 H	203	14.4	10.7
5	7323.00	58.6 PK	74.0	-15.4	1.63 H	193	43.3	15.3
6	7323.00	28.5 AV	54.0	-25.5	1.63 H	193	13.2	15.3
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	103.1 PK			1.29 V	93	102.0	1.1
2	*2441.00	73.0 AV			1.29 V	93	71.9	1.1
3	4882.00	56.9 PK	74.0	-17.1	1.70 V	130	46.2	10.7
4	4882.00	26.8 AV	54.0	-27.2	1.70 V	130	16.1	10.7
5	7323.00	59.6 PK	74.0	-14.4	1.70 V	262	44.3	15.3
6	7323.00	29.5 AV	54.0	-24.5	1.70 V	262	14.2	15.3

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1 \text{ dB}$
7. Average value = peak reading + $20\log(\text{duty cycle})$.

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	106.6 PK			1.22 H	72	105.2	1.4
2	*2480.00	76.5 AV			1.22 H	72	75.1	1.4
3	2500.00	56.9 PK	74.0	-17.1	1.22 H	72	55.6	1.3
4	2500.00	26.8 AV	54.0	-27.2	1.22 H	72	25.5	1.3
5	4960.00	54.8 PK	74.0	-19.2	1.49 H	213	44.1	10.7
6	4960.00	24.7 AV	54.0	-29.3	1.49 H	213	14.0	10.7
7	7440.00	59.1 PK	74.0	-14.9	1.61 H	180	43.4	15.7
8	7440.00	29.0 AV	54.0	-25.0	1.61 H	180	13.3	15.7
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	101.3 PK			1.25 V	104	99.9	1.4
2	*2480.00	71.2 AV			1.25 V	104	69.8	1.4
3	2500.00	54.1 PK	74.0	-19.9	1.25 V	104	52.8	1.3
4	2500.00	24.0 AV	54.0	-30.0	1.25 V	104	22.7	1.3
5	4960.00	56.7 PK	74.0	-17.3	1.65 V	135	46.0	10.7
6	4960.00	26.6 AV	54.0	-27.4	1.65 V	135	15.9	10.7
7	7440.00	59.9 PK	74.0	-14.1	1.66 V	256	44.2	15.7
8	7440.00	29.8 AV	54.0	-24.2	1.66 V	256	14.1	15.7

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: $20\log(3.125 / 100) = -30.1 \text{ dB}$
7. Average value = peak reading + $20\log(\text{duty cycle})$.

Below 1GHz Data:

BT_GFSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	49.04	29.3 QP	40.0	-10.7	1.98 H	117	37.8	-8.5
2	150.23	24.2 QP	43.5	-19.3	1.04 H	292	31.9	-7.7
3	204.82	23.4 QP	43.5	-20.1	1.02 H	42	34.2	-10.8
4	517.63	31.4 QP	46.0	-14.6	1.00 H	274	32.6	-1.2
5	625.01	38.0 QP	46.0	-8.0	1.53 H	322	36.7	1.3
6	949.39	37.2 QP	46.0	-8.8	1.00 H	252	30.3	6.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	36.91	35.8 QP	40.0	-4.2	2.06 V	315	44.9	-9.1
2	93.74	30.6 QP	43.5	-12.9	1.47 V	51	44.0	-13.4
3	375.03	30.7 QP	46.0	-15.3	1.00 V	201	35.4	-4.7
4	624.94	37.9 QP	46.0	-8.1	1.00 V	176	36.6	1.3
5	874.86	36.9 QP	46.0	-9.1	1.00 V	308	31.7	5.2
6	1000.00	39.8 QP	54.0	-14.2	1.46 V	60	32.3	7.5

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	49.07	28.9 QP	40.0	-11.1	2.01 H	120	37.4	-8.5
2	149.80	24.4 QP	43.5	-19.1	1.00 H	301	32.1	-7.7
3	204.65	23.8 QP	43.5	-19.7	1.00 H	48	34.6	-10.8
4	517.79	31.2 QP	46.0	-14.8	1.00 H	283	32.4	-1.2
5	624.76	38.4 QP	46.0	-7.6	1.54 H	325	37.1	1.3
6	949.88	37.3 QP	46.0	-8.7	1.00 H	250	30.4	6.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	37.10	35.8 QP	40.0	-4.2	2.02 V	295	44.9	-9.1
2	93.54	30.6 QP	43.5	-12.9	1.53 V	66	44.0	-13.4
3	374.91	30.2 QP	46.0	-15.8	1.01 V	221	34.9	-4.7
4	624.78	37.8 QP	46.0	-8.2	1.00 V	189	36.5	1.3
5	874.92	37.0 QP	46.0	-9.0	1.00 V	297	31.8	5.2
6	1000.00	40.1 QP	54.0	-13.9	1.52 V	60	32.6	7.5

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	48.88	29.2 QP	40.0	-10.8	2.00 H	102	37.7	-8.5
2	149.86	24.8 QP	43.5	-18.7	1.00 H	277	32.5	-7.7
3	204.62	24.2 QP	43.5	-19.3	1.02 H	40	35.0	-10.8
4	517.67	31.7 QP	46.0	-14.3	1.00 H	266	32.9	-1.2
5	624.97	38.2 QP	46.0	-7.8	1.50 H	292	36.9	1.3
6	949.81	37.8 QP	46.0	-8.2	1.00 H	251	30.9	6.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	37.10	36.1 QP	40.0	-3.9	1.92 V	293	45.2	-9.1
2	93.84	30.1 QP	43.5	-13.4	1.56 V	34	43.5	-13.4
3	374.95	30.5 QP	46.0	-15.5	1.01 V	231	35.2	-4.7
4	625.04	38.3 QP	46.0	-7.7	1.03 V	185	37.0	1.3
5	874.99	37.0 QP	46.0	-9.0	1.00 V	315	31.8	5.2
6	1000.00	40.1 QP	54.0	-13.9	1.49 V	64	32.6	7.5

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	49.04	29.0 QP	40.0	-11.0	1.97 H	111	37.5	-8.5
2	150.22	24.4 QP	43.5	-19.1	1.00 H	264	32.1	-7.7
3	204.71	24.2 QP	43.5	-19.3	1.00 H	62	35.0	-10.8
4	517.33	31.6 QP	46.0	-14.4	1.03 H	285	32.8	-1.2
5	624.94	37.8 QP	46.0	-8.2	1.39 H	325	36.5	1.3
6	949.79	37.8 QP	46.0	-8.2	1.00 H	243	30.9	6.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	36.65	35.6 QP	40.0	-4.4	2.05 V	274	44.7	-9.1
2	93.60	30.3 QP	43.5	-13.2	1.50 V	47	43.7	-13.4
3	374.95	30.3 QP	46.0	-15.7	1.00 V	214	35.0	-4.7
4	625.08	37.3 QP	46.0	-8.7	1.06 V	186	36.0	1.3
5	874.92	36.6 QP	46.0	-9.4	1.00 V	295	31.4	5.2
6	1000.00	39.9 QP	54.0	-14.1	1.45 V	36	32.4	7.5

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

BT_8DPSK

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	48.73	28.9 QP	40.0	-11.1	1.91 H	101	37.4	-8.5
2	150.37	24.2 QP	43.5	-19.3	1.03 H	304	31.9	-7.7
3	204.44	24.0 QP	43.5	-19.5	1.01 H	56	34.8	-10.8
4	517.32	31.8 QP	46.0	-14.2	1.02 H	284	33.0	-1.2
5	624.78	38.3 QP	46.0	-7.7	1.44 H	304	37.0	1.3
6	949.40	37.7 QP	46.0	-8.3	1.04 H	254	30.8	6.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	37.07	35.5 QP	40.0	-4.5	1.98 V	321	44.6	-9.1
2	94.06	30.5 QP	43.5	-13.0	1.46 V	47	43.9	-13.4
3	375.05	29.9 QP	46.0	-16.1	1.00 V	242	34.6	-4.7
4	624.97	38.3 QP	46.0	-7.7	1.01 V	185	37.0	1.3
5	874.93	37.0 QP	46.0	-9.0	1.04 V	308	31.8	5.2
6	1000.00	40.2 QP	54.0	-13.8	1.47 V	64	32.7	7.5

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	48.10	29.3 QP	40.0	-10.7	2.06 H	95	37.8	-8.5
2	150.14	24.5 QP	43.5	-19.0	1.05 H	292	32.2	-7.7
3	204.75	24.0 QP	43.5	-19.5	1.04 H	43	34.8	-10.8
4	517.68	31.5 QP	46.0	-14.5	1.03 H	251	32.7	-1.2
5	624.99	38.1 QP	46.0	-7.9	1.47 H	321	36.8	1.3
6	949.90	37.5 QP	46.0	-8.5	1.00 H	232	30.6	6.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	37.12	35.7 QP	40.0	-4.3	2.03 V	298	44.8	-9.1
2	93.54	30.4 QP	43.5	-13.1	1.44 V	50	43.8	-13.4
3	374.95	30.2 QP	46.0	-15.8	1.00 V	248	34.9	-4.7
4	625.03	38.2 QP	46.0	-7.8	1.00 V	176	36.9	1.3
5	875.08	36.3 QP	46.0	-9.7	1.00 V	321	31.1	5.2
6	1000.00	39.8 QP	54.0	-14.2	1.43 V	55	32.3	7.5

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

4.1.8 Test Results (Mode 2)

Below 1GHz Data:

BT_GFSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	48.80	30.4 QP	40.0	-9.6	1.47 H	211	38.9	-8.5
2	150.29	26.5 QP	43.5	-17.0	1.00 H	138	34.2	-7.7
3	204.75	26.1 QP	43.5	-17.4	1.44 H	197	36.9	-10.8
4	517.80	32.4 QP	46.0	-13.6	1.48 H	245	33.6	-1.2
5	624.87	38.7 QP	46.0	-7.3	1.43 H	228	37.4	1.3
6	949.31	38.5 QP	46.0	-7.5	1.47 H	127	31.6	6.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	37.28	33.8 QP	40.0	-6.2	1.41 V	252	42.8	-9.0
2	93.60	33.4 QP	43.5	-10.1	1.02 V	258	46.8	-13.4
3	375.04	32.0 QP	46.0	-14.0	1.51 V	229	36.7	-4.7
4	517.46	29.8 QP	46.0	-16.2	1.46 V	297	31.0	-1.2
5	625.01	40.4 QP	46.0	-5.6	1.42 V	241	39.1	1.3
6	874.91	38.7 QP	46.0	-7.3	1.00 V	263	33.5	5.2

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	48.55	30.3 QP	40.0	-9.7	1.54 H	194	38.8	-8.5
2	150.28	26.6 QP	43.5	-16.9	1.00 H	135	34.3	-7.7
3	204.52	26.2 QP	43.5	-17.3	1.48 H	199	37.0	-10.8
4	517.41	32.8 QP	46.0	-13.2	1.48 H	245	34.0	-1.2
5	624.89	39.3 QP	46.0	-6.7	1.50 H	211	38.0	1.3
6	949.21	38.4 QP	46.0	-7.6	1.45 H	133	31.5	6.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	37.15	33.5 QP	40.0	-6.5	1.45 V	246	42.5	-9.0
2	93.90	33.1 QP	43.5	-10.4	1.00 V	277	46.5	-13.4
3	375.05	32.0 QP	46.0	-14.0	1.52 V	233	36.7	-4.7
4	517.28	29.7 QP	46.0	-16.3	1.46 V	308	30.9	-1.2
5	625.09	40.5 QP	46.0	-5.5	1.31 V	229	39.2	1.3
6	874.94	38.6 QP	46.0	-7.4	1.04 V	269	33.4	5.2

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	48.69	30.2 QP	40.0	-9.8	1.45 H	215	38.7	-8.5
2	149.67	26.7 QP	43.5	-16.8	1.06 H	133	34.4	-7.7
3	204.90	26.0 QP	43.5	-17.5	1.40 H	226	36.8	-10.8
4	517.81	32.7 QP	46.0	-13.3	1.53 H	226	33.9	-1.2
5	625.03	39.2 QP	46.0	-6.8	1.55 H	223	37.9	1.3
6	949.06	38.6 QP	46.0	-7.4	1.46 H	134	31.7	6.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	37.37	33.5 QP	40.0	-6.5	1.41 V	254	42.5	-9.0
2	93.94	33.2 QP	43.5	-10.3	1.00 V	269	46.6	-13.4
3	374.98	32.2 QP	46.0	-13.8	1.46 V	231	36.9	-4.7
4	517.22	29.7 QP	46.0	-16.3	1.40 V	310	30.9	-1.2
5	625.06	40.3 QP	46.0	-5.7	1.26 V	229	39.0	1.3
6	874.86	39.1 QP	46.0	-6.9	1.05 V	270	33.9	5.2

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

BT_8DPSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	48.97	30.4 QP	40.0	-9.6	1.54 H	222	38.9	-8.5
2	149.80	26.7 QP	43.5	-16.8	1.00 H	143	34.4	-7.7
3	204.68	26.2 QP	43.5	-17.3	1.45 H	228	37.0	-10.8
4	517.66	32.4 QP	46.0	-13.6	1.46 H	244	33.6	-1.2
5	625.07	39.4 QP	46.0	-6.6	1.53 H	231	38.1	1.3
6	949.75	38.7 QP	46.0	-7.3	1.38 H	124	31.8	6.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	36.86	33.6 QP	40.0	-6.4	1.53 V	267	42.7	-9.1
2	94.09	33.2 QP	43.5	-10.3	1.00 V	261	46.6	-13.4
3	375.03	31.8 QP	46.0	-14.2	1.52 V	241	36.5	-4.7
4	517.49	29.9 QP	46.0	-16.1	1.52 V	317	31.1	-1.2
5	625.09	40.1 QP	46.0	-5.9	1.32 V	212	38.8	1.3
6	874.93	38.8 QP	46.0	-7.2	1.00 V	279	33.6	5.2

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	48.84	30.2 QP	40.0	-9.8	1.51 H	232	38.7	-8.5
2	150.08	26.8 QP	43.5	-16.7	1.00 H	139	34.5	-7.7
3	204.60	25.8 QP	43.5	-17.7	1.45 H	236	36.6	-10.8
4	517.55	32.5 QP	46.0	-13.5	1.52 H	215	33.7	-1.2
5	625.03	39.5 QP	46.0	-6.5	1.52 H	233	38.2	1.3
6	949.81	38.4 QP	46.0	-7.6	1.47 H	120	31.5	6.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	36.98	33.7 QP	40.0	-6.3	1.50 V	268	42.8	-9.1
2	93.96	33.2 QP	43.5	-10.3	1.00 V	276	46.6	-13.4
3	374.92	32.0 QP	46.0	-14.0	1.41 V	222	36.7	-4.7
4	517.74	30.0 QP	46.0	-16.0	1.40 V	295	31.2	-1.2
5	625.03	40.1 QP	46.0	-5.9	1.37 V	196	38.8	1.3
6	874.98	38.7 QP	46.0	-7.3	1.01 V	260	33.5	5.2

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	48.98	30.8 QP	40.0	-9.2	1.43 H	234	39.3	-8.5
2	150.20	26.3 QP	43.5	-17.2	1.00 H	150	34.0	-7.7
3	204.98	26.0 QP	43.5	-17.5	1.54 H	222	36.8	-10.8
4	518.00	32.3 QP	46.0	-13.7	1.47 H	238	33.5	-1.2
5	625.01	39.2 QP	46.0	-6.8	1.46 H	236	37.9	1.3
6	949.77	38.5 QP	46.0	-7.5	1.51 H	137	31.6	6.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	37.07	33.5 QP	40.0	-6.5	1.53 V	269	42.6	-9.1
2	93.89	33.4 QP	43.5	-10.1	1.00 V	261	46.8	-13.4
3	375.06	32.4 QP	46.0	-13.6	1.54 V	230	37.1	-4.7
4	517.36	29.8 QP	46.0	-16.2	1.53 V	300	31.0	-1.2
5	625.01	40.4 QP	46.0	-5.6	1.41 V	231	39.1	1.3
6	875.04	38.7 QP	46.0	-7.3	1.00 V	276	33.5	5.2

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver R&S	ESCS 30	100375	May 09, 2016	May 08, 2017
Line-Impedance Stabilization Network (for EUT) SCHWARZBECK	NSLK-8127	8127-522	Aug. 31, 2016	Aug. 30, 2017
Line-Impedance Stabilization Network (for Peripheral) R&S	ENV216	100072	June 13, 2016	June 12, 2017
RF Cable	5D-FB	COACAB-002	Mar. 04, 2016	Mar. 03, 2017
10 dB PAD Mini-Circuits	HAT-10+	CONATT-003	Sep. 13, 2016	Sep. 12, 2017
50 ohms Terminator	N/A	04	Nov. 18, 2015	Nov. 17, 2016
50 ohms Terminator	N/A	EMC-02	Oct. 01, 2015	Sep. 30, 2016
Software BVADT	BVADT_Cond_ V7.3.7.4	NA	NA	NA

Note:

1. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. C.
3. The VCCI Con C Registration No. is C-3611.
4. Tested Date: Sep. 13, 2016

4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation From Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Condition

Same as 4.1.6.


4.2.7 Test Results (Mode 1)

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	----------	-------------------	--------------------------------

No	Freq. [MHz]	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	10.31	34.60	21.87	44.91	32.18	66.00	56.00	-21.09	-23.82
2	0.17734	10.27	30.93	19.26	41.20	29.53	64.61	54.61	-23.41	-25.08
3	0.40391	10.25	28.80	22.50	39.05	32.75	57.77	47.77	-18.72	-15.02
4	0.69688	10.19	10.31	3.47	20.50	13.66	56.00	46.00	-35.50	-32.34
5	15.20703	10.78	20.26	14.18	31.04	24.96	60.00	50.00	-28.96	-25.04
6	22.35156	11.01	25.56	22.46	36.57	33.47	60.00	50.00	-23.43	-16.53

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	-------------	-------------------	--------------------------------

No	Freq. [MHz]	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15391	10.35	35.04	26.39	45.39	36.74	65.79	55.79	-20.40	-19.05
2	0.17734	10.27	31.19	20.33	41.46	30.60	64.61	54.61	-23.15	-24.01
3	0.40781	10.23	30.88	23.90	41.11	34.13	57.69	47.69	-16.58	-13.56
4	0.73984	10.22	16.74	10.56	26.96	20.78	56.00	46.00	-29.04	-25.22
5	14.90234	10.81	20.40	15.50	31.21	26.31	60.00	50.00	-28.79	-23.69
6	23.12891	11.06	28.26	26.56	39.32	37.62	60.00	50.00	-20.68	-12.38

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




4.2.8 Test Results (Mode 2)

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	----------	-------------------	--------------------------------

No	Freq. [MHz]	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15391	10.31	36.42	21.37	46.73	31.68	65.79	55.79	-19.06	-24.11
2	0.18125	10.27	33.13	19.22	43.40	29.49	64.43	54.43	-21.03	-24.94
3	0.38828	10.25	19.74	13.36	29.99	23.61	58.10	48.10	-28.11	-24.49
4	0.70859	10.18	9.29	4.78	19.47	14.96	56.00	46.00	-36.53	-31.04
5	15.38281	10.79	17.44	11.14	28.23	21.93	60.00	50.00	-31.77	-28.07
6	20.80859	10.97	11.09	5.33	22.06	16.30	60.00	50.00	-37.94	-33.70

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	-------------	-------------------	--------------------------------

No	Freq. [MHz]	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15781	10.34	36.41	21.97	46.75	32.31	65.58	55.58	-18.83	-23.27
2	0.18125	10.26	33.03	19.44	43.29	29.70	64.43	54.43	-21.14	-24.73
3	0.42734	10.23	24.34	18.33	34.57	28.56	57.30	47.30	-22.73	-18.74
4	0.68125	10.22	8.51	3.13	18.73	13.35	56.00	46.00	-37.27	-32.65
5	15.50781	10.83	16.99	10.41	27.82	21.24	60.00	50.00	-32.18	-28.76
6	20.32031	10.98	14.08	11.21	25.06	22.19	60.00	50.00	-34.94	-27.81

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




4.3 Number of Hopping Frequency Used

4.3.1 Limits of Hopping Frequency Used Measurement

At least 15 channels frequencies, and should be equally spaced.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure


- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- d. Set the SA on View mode and then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were complete.

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 Test Results

There are 79 hopping frequencies in the hopping mode. Please refer to next page for the test result. On the plots, it shows that the hopping frequencies are equally spaced.




4.4 Dwell Time on Each Channel

4.4.1 Limits of Dwell Time on Each Channel Measurement

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedures

- Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- Adjust the center frequency of SA on any frequency to be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- Repeat above procedures until all different time-slot modes have been completed.

4.4.5 Deviation from Test Standard

No deviation.

4.4.6 Test Results

GFSK



Mode	Number of transmission in a 31.6 (79Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
DH1	50 (times / 5 sec) * 6.32 = 316 times	0.474	149.78	400
DH3	27 (times / 5 sec) * 6.32 = 170.64 times	1.72	293.5	400
DH5	17 (times / 5 sec) * 6.32 = 107.44 times	2.992	321.46	400

NOTE: Test plots of the transmitting time slot are shown on next page.



BUREAU
VERITAS



DH1



Marker 1 [T1] -59.80 dBm
1.248000 ms
Delta 2 [T1] 1.51 dB
474.000000 us





DH3



Marker 1 [T1] -56.54 dBm
1.630000 ms
Delta 2 [T1] 0.59 dB
1.720000 ms



DH5



Marker 1 [T1] -57.17 dBm
2.480000 ms
Delta 2 [T1] 0.07 dB
2.992000 ms





8DPSK



Mode	Number of transmission in a 31.6 (79Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
3DH1	51 (times / 5 sec) * 6.32 = 322.32 times	0.474	152.78	400
3DH3	25 (times / 5 sec) * 6.32 = 158 times	1.72	271.76	400
3DH5	16 (times / 5 sec) * 6.32 = 101.12 times	3.056	309.02	400

NOTE: Test plots of the transmitting time slot are shown on next page.



3DH1



3DH3



3DH5




4.5 Channel Bandwidth

4.5.1 Limits of Channel Bandwidth Measurement

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dB bandwidth of hopping channel shall be a minimum limit for the hopping channel separation.

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- Repeat above procedures until all frequencies measured were complete.

4.5.5 Deviation from Test Standard


No deviation.

4.5.6 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.5.7 Test Results

Channel	Frequency (MHz)	20dB Bandwidth (MHz)	
		GFSK	8DPSK
0	2402	0.96	1.32
39	2441	0.94	1.33
78	2480	0.96	1.33




4.6 Hopping Channel Separation

4.6.1 Limits of Hopping Channel Separation Measurement

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

Measurement Procedure REF

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
- c. By using the MaxHold function record the separation of two adjacent channels.
- d. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were complete.


4.6.5 Deviation from Test Standard

No deviation.

4.6.6 Test Results

Channel	Frequency (MHz)	Adjacent Channel Separation (MHz)		20dB Bandwidth (MHz)		Minimum Limit (MHz)		Pass / Fail
		GFSK	8DPSK	GFSK	8DPSK	GFSK	8DPSK	
0	2402	1.00	1.00	0.96	1.32	0.64	0.88	Pass
39	2441	1.00	1.00	0.94	1.33	0.63	0.89	Pass
78	2480	1.00	1.00	0.96	1.33	0.64	0.89	Pass

NOTE: The minimum limit is two-third 20dB bandwidth.




4.7 Maximum Output Power

4.7.1 Limits of Maximum Output Power Measurement

The Maximum Output Power Measurement is 125mW.

4.7.2 Test Setup



4.7.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.7.4 Test Procedure

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- The center frequency of the spectrum analyzer is set to the fundamental frequency and using 3MHz RBW and 10 MHz VBW.
- Measure the captured power within the band and recording the plot.
- Repeat above procedures until all frequencies required were complete.

4.7.5 Deviation from Test Standard


No deviation.

4.7.6 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.7.7 Test Results

Channel	Frequency (MHZ)	Output Power (mW)		Output Power (dBm)		Power Limit (mW)	Pass / Fail
		GFSK	8DPSK	GFSK	8DPSK		
0	2402	6.339	5.794	8.02	7.63	125	Pass
39	2441	6.095	5.916	7.85	7.72	125	Pass
78	2480	4.624	4.498	6.65	6.53	125	Pass



4.8 Conducted Out of Band Emission Measurement

4.8.1 Limits of Conducted Out of Band Emission Measurement

Below -20dB of the highest emission level of operating band (in 100kHz RBW).

4.8.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.8.3 Test Procedure

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz and 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

4.8.4 Deviation from Test Standard

No deviation.


4.8.5 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.8.6 Test Results



The spectrum plots are attached on the following images. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

GFSK





8DPSK



Hopping disabled Low Channel





Hopping disabled High Channel



Hopping enabled Low Channel



Hopping enabled High Channel



5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---