

RF Exposure Report

Report No.: SA190614E02 R1

FCC ID: B94SNPRC1950

Test Model: SNPRC-1950

Received Date: June 14, 2019

Test Date: Aug. 30 to 31, 2019

Issued Date: Sep. 23, 2019

Applicant: HP Inc.

Address: 3390 East Harmony Road, MS 66 Fort Collins, CO 80528

Manufacturer: HP Singapore (Private) Limited

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

**FCC Registration /
Designation Number:** 723255 / TW2022

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	6
2.5 Calculation Result of Maximum Conducted Power.....	7

Release Control Record

Issue No.	Description	Date Issued
SA190614E02	Original release.	Sep. 18, 2019
SA190614E02 R1	Modify the applicant and manufacturer information.	Sep. 23, 2019

1 Certificate of Conformity

Product: 802.11a/b/g/n/ac (2.4 / 5 GHz) Wi-Fi radio + BT Radio Module

Brand:



Test Model: SNPRC-1950

Sample Status: ENGINEERING SAMPLE

Applicant: HP Inc.


Manufacturer: HP Singapore (Private) Limited

Test Date: Aug. 30 to 31, 2019

Standards: FCC CFR 47 Part 1.1310
FCC CFR 47 Part 2.1091
KDB 447498 D01 General RF Exposure Guidance v06
IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.


Prepared by :


Phoenix Huang / Specialist

Date:

Sep. 23, 2019

Approved by :


May Chen / Manager

Date:

Sep. 23, 2019

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20 cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

Internal Antenna						
Antenna No.	Brand	Model	Ant. Net Gain (dBi)	Frequency range (GHz)	Antenna Type	Connector Type
1	HP Inc.	SNPRC-1950	3.5	2.4-2.5	PCB	None
			4.5	5-6		
External Antenna						
2	Yageo	ANTX300P002B24553	0.9	2.4-2.5	PCB	i-pex(MHF)
			2.3	5.150-5.875		
3	Pulse	SZ0595D	2.5	2.4-2.5	PIFA	i-pex(MHF)
			3	4.9-5.9		
4	Yageo	ANTX200P002B24553	0.9	2.4-2.5	PCB	i-pex(MHF)
			2.3	5.150-5.875		
5	Pulse	SZ07751	2.5	2.4-2.5	PIFA	i-pex(MHF)
			3	4.9-5.9		

Note:

1. The external antenna will fix transmission on Chain 1
2. The Bluetooth technology will fix transmission on Chain 1

2.5 Calculation Result of Maximum Conducted Power

Operation Mode	Evaluation Frequency (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN (2.4GHz)	2437	516.416	3.5	20	0.23000	1
WLAN (U-NII-1)	5200	156.315	4.5	20	0.08765	1
WLAN (U-NII-2A)	5300	156.675	4.5	20	0.08785	1
WLAN (U-NII-2C)	5580	164.816	4.5	20	0.09241	1
WLAN (U-NII-3)	5745	145.546	4.5	20	0.08161	1
BT-EDR	2402	7.907	3.5	20	0.00352	1
BT-LE	2402	4.645	3.5	20	0.00207	1

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

Conclusion:

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

WLAN 2.4GHz + Bluetooth = $0.23000 / 1 + 0.00352 / 1 = 0.23352$

WLAN 5GHz + Bluetooth = $0.09241 / 1 + 0.00352 / 1 = 0.09593$

Therefore the maximum calculations of above situations are less than the "1" limit.

--- END ---