

FCC&IC Cerification - TEST REPORT

Report Number : **60/790.14.003.02** Date of Issue: 15th May 2014

Model : **EMR211**

Product type : **BLE connected IN/out thermometer**

FCC ID: : **NMTEMR211-01**

Applicant : **IDT Technology Limited**


Address : **Block C,9/F., Kaiser Estate,Phase1,41 Man Yue Street, Hunghom, Kowloon , Hong Kong**

Production Facility : **IDT Technology Limited**

Address : **Block C,9/F., Kaiser Estate,Phase1,41 Man Yue Street, Hunghom, Kowloon , Hong Kong**

Test Result : ☒ **Positive** ☐ **Negative** Total Pages: 11

Prepared by:



CHAN Kwong Ngai



Reviewed by:



Edmond FUNG

TÜV SÜD Hong Kong Ltd. is a subcontractor to TÜV Product Service, GmbH according to the principles outlined in ISO 17025.

TÜV SÜD Hong Kong Ltd. reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Hong Kong Ltd. shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Hong Kong Ltd. issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.

TABLE OF CONTENTS

| | | |
|-----|--|---|
| 1 | General Information | 3 |
| 1.1 | Summary of Test Result | 3 |
| 1.2 | Measurement Uncertainty | 3 |
| 2 | EUT Description..... | 4 |
| 3 | Test Methodology | 5 |
| 3.1 | Decision of Test Mode..... | 5 |
| 3.2 | Configuration of Test System Details | 5 |
| 3.3 | Test Site Environment | 5 |
| 4 | Emission Test | 6 |
| 4.1 | Conducted Emission Measurement | 6 |
| 4.2 | Radiated Interference Measurement..... | 7 |

1 General Information

1.1 Summary of Test Result

| FCC Rules | IC Rules | Description of Test | Result | Remark |
|------------|--------------|-----------------------------|--------|-----------------------|
| FCC§15.107 | ICES-003§6.1 | AC Line Conducted Emissions | NIL | Battery operated only |
| FCC§15.109 | ICES-003§6.2 | Radiated Emission | PASS | Meet Class B limit |

The test results of this report relate only to the tested sample(s) identified in this report. Manufacturer or whom it may concern should recognize the pass or fail of the test result.

1.2 Measurement Uncertainty

Conducted Emission

The measurement uncertainty is evaluated as ± 2.26 dB.

Radiated Emission

The measurement uncertainty is evaluated as ± 3.19 dB.

1.3 Measurement Uncertainty

Details about the Test Laboratory

Test site 1

Company name: TÜV SÜD HONG KONG LTD.
3/F, West Wing, Lakeside 2,
10 Science Park West Avenue,
Science Park, Shatin
HK.

Telephone: 852 2776 1323

Fax: 852 2776 1372

Test site 2

Company name: TMC-Telecommunication Metrology Center of M.I.I.T
No 52 Hua Yuanbei Road, Haidian District, Beijing, P.R.China

2 EUT Description

| | |
|--------------|--|
| Product | BLE connected IN/out thermometer |
| Model Number | EMR211 |
| Applicant | IDT Technology Limited Block C,9/F., Kaiser Estate,Phase1,41 Man Yue Street, Hunghom, Kowloon , Hong Kong |
| Manufacturer | IDT Technology Limited Block C,9/F., Kaiser Estate,Phase1,41 Man Yue Street, Hunghom, Kowloon , Hong Kong |

I/O Port Description:

| I/O Port Types | Q'TY | Test Description |
|----------------|------|------------------|
| 1). NIL | / | / |

3 Test Methodology

3.1 Decision of Test Mode

| Pre-Test Mode | |
|---------------|-----------------------------|
| EMC | Mode 1: 433MHz RF receiving |

3.2 Configuration of Test System Details

| Mode 1 | |
|---|--------------------------|
| <div style="border: 1px dashed black; padding: 20px; text-align: center; margin: 20px;"> <div style="border: 1px solid black; padding: 10px; display: inline-block;">EUT</div> </div> | |
| Signal Cable Type | Signal Cable Description |
| A / | / |

3.3 Test Site Environment

| Items | Test Item | Actual |
|----------------------------|--------------------|--------|
| Temperature (°C) | Conducted Emission | 25 |
| Humidity (%RH) | | 66 |
| Barometric pressure (mbar) | | 1004 |
| Temperature (°C) | Radiated Emission | 25 |
| Humidity (%RH) | | 62 |
| Barometric pressure (mbar) | | 1004 |

4 Emission Test

4.1 Conducted Emission Measurement

4.1.1 Limit

A.C. Mains Conducted Interference Limit

| Frequency (MHz) | Class A (dBuV) | | Class B (dBuV) | |
|-----------------|----------------|---------|----------------|---------|
| | Quasi-peak | Average | Quasi-peak | Average |
| 0.15 - 0.5 | 79 | 66 | 66 - 56 | 56 - 46 |
| 0.50 - 5.0 | 73 | 60 | 56 | 46 |
| 5.0 - 30.0 | 73 | 60 | 60 | 50 |

Note: (1) The lower limit shall apply at the transition frequencies.

(2) The limit decreases in line with the logarithm of the frequency in the range 0.15 to 0.50 MHz.

4.1.2 Test Instruments


| Equipment | Manufacturer | Model Number | Serial Number | Cal. Date | Remark |
|---------------|--------------|--------------|---------------|------------|--------|
| Test Receiver | R&S | ESCI | 100367 | 06/18/2013 | (1) |
| LISN | R&S | ENV216 | 101040 | 03/07/2014 | (1) |
| LISN | R&S | ENV216 | 101041 | 03/07/2014 | (1) |
| Test Site | ATL | TE02 | TE02 | N.C.R. | ----- |

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years.

Note: N.C.R. = No Calibration Request.

4.1.3 Test Setup

A.C. mains setup



4.1.4 Test Result

N/A (Battery operated only)

4.2 Radiated Interference Measurement

4.2.1 Limit

Under 1GHz test shall not exceed following value

| FCC 47 CFR PART 15 SUBPART B | | | | |
|------------------------------|--------------|--------|--------------|--------|
| Frequency range (MHz) | Class A | | Class B | |
| | Distance (m) | dBuV/m | Distance (m) | dBuV/m |
| 30 to 88 | 10 | 39 | 3 | 40 |
| 88 to 216 | 10 | 43.5 | 3 | 43.5 |
| 216 to 960 | 10 | 46.4 | 3 | 46 |
| Above 960 | 10 | 49.5 | 3 | 54 |

- Remark: 1. The tighter limit shall apply at the edge between two frequency bands.
2. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
3. RF Voltage (dBuV/m) = 20 log RF Voltage (uV/m)
4. Peak detector limit is corresponding to 20 dB above the maximum permitted average limit.

According to FCC Part 15.33 (b), for an unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a radiated emission limit is specified, up to the frequency shown in the following table:

| Highest frequency generated or used in the device or in which the device operated or tunes (MHz) | Upper frequency of measurement range (MHz) |
|--|--|
| Below 1.75 | 30 |
| 1.75-108 | 1000 |
| 108-500 | 2000 |
| 500-1000 | 5000 |
| Above 1000 | 5th harmonic of the highest frequency or 40GHz, whichever is lower |

4.2.2 Test Instruments


| 3 Meter Chamber | | | | | |
|----------------------------|--------------------------------|--------------|---------------|------------|--------|
| Equipment | Manufacturer | Model Number | Serial Number | Cal. Date | Remark |
| Pre Amplifier | Agilent | 8447D | 2944A11120 | 01/10/2014 | (1) |
| Pre Amplifier | Agilent | 8447D | 2944A11119 | 01/10/2014 | (1) |
| Test Receiver | R&S | ESCI | 100722 | 10/18/2013 | (1) |
| Test Receiver | R&S | ESCI | 101000 | 10/18/2013 | (1) |
| Broadband Antenna | SCHWARZBECK MESS-ELEKTRONIK | VULB 9160 | 9160-3268 | 06/06/2013 | (1) |
| Broadband Antenna | SCHWARZBECK MESS-ELEKTRONIK | VULB 9160 | 9160-3273 | 12/13/2013 | (1) |
| Horn Antenna (1~18GHz) | ETS-Lindgren | 3117 | 00128055 | 08/09/2013 | (1) |
| Horn Antenna (18~40GHz) | SCHWARZBECK MESS-ELEKTRONIK | BBHA9170 | 9170-320 | 06/21/2013 | (1) |

Remark: ⁽¹⁾ Calibration period 1 year. ⁽²⁾ Calibration period 2 years.


Note: N.C.R. = No Calibration Request.

4.2.3 Setup

Below 1GHz



Above 1GHz



4.2.4 Test Result

| | | | |
|---------------|-------------------|----------------------|--------------|
| Standard: | FCC 15.109 | Test Distance: | 3m |
| Test item: | Radiated Emission | Power: | DC 3.0V |
| Model Number: | EMR211 | Temp.(°C)/Hum.(%RH): | 22(°C)/54%RH |
| Mode: | 1 | Date: | 2014/04/06 |
| Range: | 30MHz-5GHz | | |

| Frequency (MHz) | Reading (dBuV) | Correct Factor (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark | Ant.Polar. H / V |
|--------------------|-------------------|--------------------------|--------------------|-------------------|----------------|--------|---------------------|
| 52.59 | 46.46 | -34.0 | 12.46 | 40.0 | -27.54 | QP | H |
| 87.12 | 46.66 | -37.9 | 8.76 | 40.0 | -31.24 | QP | H |
| 147.90 | 50.79 | -39.8 | 10.99 | 43.5 | -32.51 | QP | H |
| 344.68 | 48.67 | -31.4 | 17.27 | 46.0 | -28.73 | QP | H |
| 500.11 | 55.74 | -28.7 | 27.04 | 46.0 | -18.96 | QP | H |
| 754.21 | 49.99 | -24.2 | 25.79 | 46.0 | -20.21 | QP | H |
| 1243.54 | 58.96 | -18.6 | 40.36 | 74.0 | -33.64 | PK | H |
| 1243.54 | 50.20 | -18.6 | 31.60 | 54.0 | -22.40 | Ave. | H |
| 1923.99 | 56.09 | -12.0 | 44.09 | 74.0 | -29.91 | PK | H |
| 1923.99 | 43.41 | -12.0 | 31.41 | 54.0 | -22.59 | Ave. | H |
| 43.99 | 49.06 | -34.7 | 14.36 | 40.0 | -25.64 | QP | V |
| 104.92 | 54.86 | -34.2 | 20.66 | 43.5 | -22.84 | QP | V |
| 245.72 | 52.69 | -34.5 | 18.19 | 46.0 | -27.81 | QP | V |
| 382.90 | 50.62 | -31.5 | 19.12 | 46.0 | -26.88 | QP | V |
| 500.02 | 56.46 | -29.6 | 26.86 | 46.0 | -19.14 | QP | V |
| 677.39 | 57.16 | -26.3 | 30.86 | 46.0 | -15.14 | QP | V |
| 1228.73 | 55.02 | -18.0 | 37.02 | 74.0 | -36.98 | PK | V |
| 1228.73 | 50.83 | -18.0 | 32.83 | 54.0 | -21.17 | Ave. | V |
| 1725.12 | 56.14 | -13.2 | 42.94 | 74.0 | -31.06 | PK | V |
| 1725.12 | 44.70 | -13.2 | 31.50 | 54.0 | -22.50 | Ave. | V |

4.2.5 Test Photograph

Test Mode: Mode 1

Description: View of Radiated Emission Test (Below 1 GHz)



Test Mode: Mode 1

Description: View of Radiated Emission Test (Above 1 GHz)

