

RF Exposure Evaluation Declaration

Product Name : GPS Locator

Model No. : GL300VC

FCC ID: YQD-GL300VC

Applicant : Queclink Wireless Solutions Co.,Ltd

Address : Room 501, Building 9, No 99, TianZhou Road, Shanghai, China

Date of Receipt : 17-11-2014

Issued Date : 25-11-2014

Report No. : UL12620141117FCC026-5

Report Version : V1.0

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF, CNAS or any agency of the Government.

The test report shall not be reproduced except in full without the written approval of Unilab Corporation.

RF Exposure Evaluation Declaration

Issued Date : 17-11-2014

Report No. : UL12620141117FCC026-5



Product Name : GPS Locator

Applicant : Queclink Wireless Solutions Co.,Ltd

Address : Room 501, Building 9, No 99, TianZhou Road, Shanghai, China

Manufacturer : Queclink Wireless Solutions Co.,Ltd.

Address : Room 501, Building 9, No 99, TianZhou Road, Shanghai, China

Model No. : GL300VC

EUT Voltage : Extreme Low: 3.6V, Normal: 3.7V, Extreme High: 4.2V

Brand Name : Queclink

Applicable Standard : KDB 447498 D01 v05r02
FCC CFR Title 47 Part 1.1310
FCC CFR Title 47 Part 2.1093

Test Result : Complied

Performed Location : Unilab (Shanghai) Co.,Ltd.
FCC 2.948 register number is 714465
No.1350, Lianxi Road, Pudong New District, Shangha, China
[TEL:+86-21-5027-5125](tel:+86-21-5027-5125)/[FAX:+86-21-5027-5126](tel:+86-21-5027-5126)-876

Documented By :

Handwritten signature of Jingwei Li in black ink.

(Technical Engineer: Jingwei Li)

Reviewed By :

Handwritten signature of Forest Cao in black ink.

(Senior Engineer: Forest Cao)

Approved By :

Handwritten signature of Eva Wang in black ink.

(Supervisor: Eva Wang)

1. EUT Description

Product Name:	GPS Locator
Model Name:	GPS Locator
Hardware Version:	1.02
Software Version:	GL300VCR00A01V12M128_MXIC
RF Exposure Environment:	Uncontrolled
CDMA2000	
Support Band:	CDMA2000 BC0/BC1
Tx Frequency Range:	CDMA2000 BC0: 824.70 MHz to 848.31MHz CDMA2000 BC1: 1851.25MHz to 1908.75MHz
Rx Frequency Range:	CDMA2000 BC0: 869.70 MHz to 893.31MHz CDMA2000 BC1: 1931.25MHz to 1988.75MHz
Type of modulation:	QPSK
Antenna Type:	Touch spring
Antenna Peak Gain:	CDMA2000 BC0/BC1: 1.0dBi

2. RF Exposure Evaluation

2.1 Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range(MHz)	Electric Filed Strength (V/m)	Magnetic Filed Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A)Limits for Occupation/Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B)Limits for General Occupation/UnControlled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d = power density in mW/cm^2

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

$P_i = 3.1416$

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, $1 \text{ mW}/\text{cm}^2$. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2. Test Result of RF Exposure Evaluation

This device is evaluated by mobile device with general population/uncontrolled exposure condition. For this device, the calculation is using the most conservative values, and the results are as follows:

Test Mode	ERP (dBm)	EIRP (dBm)	Peak EIRP (mW)	Calculated RF Exposure at $d = 20\text{cm}$ (mW/cm^2)	MPE Limit (mW/cm^2)
CDMA2000 BC0	21.26	23.41	219.3	0.04	0.55
CDMA2000 BC1	/	23.14	206.1	0.04	1.00

Test Mode	Antenna Gain (dBi)	Maximum Output Power (dBm)	Maximum Output Power From Antenna (mW)	Calculated RF Exposure at $d = 20\text{cm}$ (mW/cm^2)	MPE Limit (mW/cm^2)
CDMA2000 BC0	1	25	398.11	0.08	0.55
CDMA2000 BC1	1	25	398.11	0.08	1.00

This device can pass RF exposure limit.