

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID:2AQA6-H6061

### EUT Specification

|                                   |                                                                                                                                                                                                                                          |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>EUT</b>                        | <b>Govee Glide Hexa Light Panels</b>                                                                                                                                                                                                     |
| <b>Frequency band (Operating)</b> | <input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz<br><input type="checkbox"/> WLAN: 5.18GHz ~ 5.24GHz<br><input type="checkbox"/> WLAN: 5.745GHz ~ 5.825GHz<br><input checked="" type="checkbox"/> Others: 2.402GHz~2.480GHz |
| <b>Device category</b>            | <input type="checkbox"/> Portable (<20cm separation)<br><input checked="" type="checkbox"/> Mobile (>20cm separation)<br><input type="checkbox"/> Others ____                                                                            |
| <b>Exposure classification</b>    | <input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm <sup>2</sup> )<br><input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm <sup>2</sup> )                                            |
| <b>Antenna diversity</b>          | <input type="checkbox"/> Single antenna<br><input checked="" type="checkbox"/> Multiple antennas<br><input type="checkbox"/> Tx diversity<br><input type="checkbox"/> Rx diversity<br><input type="checkbox"/> Tx/Rx diversity           |
| <b>Max. output power</b>          | BLE:-0.71dBm (0.0008W); 2.4G WIFI: 15.51dBm (0.0356W)                                                                                                                                                                                    |
| <b>Antenna gain (Max)</b>         | BLE: 2 dBi; 2.4G WIFI: 2 dBi                                                                                                                                                                                                             |
| <b>Evaluation applied</b>         | <input checked="" type="checkbox"/> MPE Evaluation<br><input type="checkbox"/> SAR Evaluation                                                                                                                                            |

Limits for Maximum Permissible Exposure(MPE)

| Frequency Range(MHz)                                         | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density(mW/cm <sup>2</sup> ) | Average Time |
|--------------------------------------------------------------|------------------------------|------------------------------|------------------------------------|--------------|
| <b>(A) Limits for Occupational/Control Exposures</b>         |                              |                              |                                    |              |
| <b>300-1500</b>                                              | --                           | --                           | <b>F/300</b>                       | <b>6</b>     |
| <b>1500-100000</b>                                           | --                           | --                           | <b>5</b>                           | <b>6</b>     |
| <b>(B) Limits for General Population/Uncontrol Exposures</b> |                              |                              |                                    |              |
| <b>300-1500</b>                                              | --                           | --                           | <b>F/1500</b>                      | <b>6</b>     |
| <b>1500-100000</b>                                           | --                           | --                           | <b>1</b>                           | <b>30</b>    |

## Friis transmission formula: $P_d = \frac{P_{out} * G}{4 * \pi * R^2}$

Where

$P_d$  = Power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in Mw

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm

$P_d$  the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## Measurement Result

| Operating Mode | Channel Frequency | Measured Power | Tune up tolerance | Max. Tune up Power | Antenna Gain | Power density at 20cm  | Power density Limits (mW/cm <sup>2</sup> ) |
|----------------|-------------------|----------------|-------------------|--------------------|--------------|------------------------|--------------------------------------------|
|                | (MHz)             | (dBm)          | (dBm)             | (dBm)              | (dBi)        | (mW/ cm <sup>2</sup> ) |                                            |
| 802.11b        | 2412              | 13.43          | 13.43 ±1          | 14.43              | 2            | 0.0087                 | 1                                          |
|                | 2437              | 12.91          | 12.91 ±1          | 13.91              | 2            | 0.0078                 | 1                                          |
|                | 2462              | 11.77          | 11.77 ±1          | 12.77              | 2            | 0.0060                 | 1                                          |
| 802.11g        | 2412              | 13.61          | 13.61 ±1          | 14.61              | 2            | 0.0091                 | 1                                          |
|                | 2437              | 15.38          | 15.38 ±1          | 16.38              | 2            | 0.0137                 | 1                                          |
|                | 2462              | 14.45          | 14.45 ±1          | 15.45              | 2            | 0.0111                 | 1                                          |
| 802.11n (HT20) | 2412              | 13.78          | 13.78 ±1          | 14.78              | 2            | 0.0095                 | 1                                          |
|                | 2437              | 15.51          | 15.51 ±1          | 16.51              | 2            | 0.0141                 | 1                                          |
|                | 2462              | 14.20          | 14.20 ±1          | 15.2               | 2            | 0.0104                 | 1                                          |
| BLE            | 2402              | -1.25          | -1.25 ±1          | -0.25              | 2            | 0.0003                 | 1                                          |
|                | 2440              | -0.71          | -0.71 ±1          | 0.29               | 2            | 0.0003                 | 1                                          |
|                | 2480              | -1.37          | -1.37 ±1          | -0.37              | 2            | 0.0003                 | 1                                          |

**Note: BT & 2.4G WIFI cannot support simultaneous transmission.**