



Test report No.: 22A0288R-RFUSV17S-A

## RF Exposure Report

Product Name	Internet Gateway
Trademark	Verizon
Model and /or type reference	WNC-CR200A
FCC ID	NKR-LV65C-T3
Applicant's name / address	Wistron NeWeb Corporation 20 Park Avenue II, Hsinchu Science Park, Hsinchu 308, Taiwan
Manufacturer's name	Wistron NeWeb Corporation
Test method requested, standard	KDB 447498 D01 v06 <input checked="" type="checkbox"/> Minimum test separation distance $\geq 20$ cm <input type="checkbox"/> For low power devices
Verdict Summary	IN COMPLIANCE
Documented By (Senior Project Specialist / Ida Tung)	Ida Tung
Approved By (Senior Engineer / Jack Hsu)	Jack Hsu
Approved By (Manager / Tim Sung)	Tim Sung
Date of Receipt	2022/10/13
Date of Issue	2023/06/09
Report Version	V1.0

---

## Competences and Guarantees

---

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

**IMPORTANT:** No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

## General conditions

---

1. The test results relate only to the samples tested.
2. The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.
3. This report must not be used to claim product endorsement by TAF or any agency of the government.
4. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.
5. Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Revision History

Report No.	Version	Description	Issued Date
22A0288R-RFUSV17S-A	V1.0	Initial issue of report.	2023/06/09

**1. General Information**

1.1. EUT Description

Product Name	Internet Gateway
Trademark	Verizon
Model and /or type reference	WNC-CR200A

Note: For more detailed information please refer to report No.: 22A0288R-RFUSV01S-A,  
22A0288R-RFUSV03S-A, 22A0288R-RFUSV03S-B, 22A0288R-RFUSV19S-A,  
22A0288R-RFUSV22S-A, 22A0288R-RFUSV23S-A and 22A0288R-RFUSV26S-A.

## 2. Test Facility

USA	FCC Registration Number: TW0033
Canada	CAB Identifier Number: TW3023 / Company Number: 26930

Site Description	Accredited by TAF
	Accredited Number: 3023

Test Laboratory	DEKRA Testing and Certification Co., Ltd.
	Linkou Laboratory
Address	No.5-22, Ruishukeng Linkou District, New Taipei City, 24451, Taiwan, R.O.C
Performed Location	No. 26, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan, R.O.C.
Phone Number	+886-3-275-7255
Fax Number	+886-3-327-8031

### 3. RF Exposure Evaluation

#### 3.1. Standard Applicable

According to KDB 447498 D01 (7.1), A minimum test separation distance  $\geq 20$  cm is required between the antenna and radiating structures of the device and nearby persons to apply mobile device exposure limits.

#### 3.2. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

##### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/ Uncontrolled Exposures				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is  $\leq 1.0$

### 3.3. Test Result of RF Exposure Evaluation

#### WLAN (CDD mode)

Band	E.I.R.P (dBm)	E.I.R.P (mW)	Power Density at R = 22 cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
2.4 GHz	32.570	1807.174	0.297	1.000
5 GHz	33.260	2118.361	0.348	1.000
6 GHz	20.710	117.761	0.019	1.000

#### WLAN (Beamforming mode)

Band	E.I.R.P (dBm)	E.I.R.P (mW)	Power Density at R = 22 cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
2.4 GHz	33.380	2177.710	0.358	1.000
5 GHz	33.320	2147.830	0.353	1.000
6 GHz	24.960	313.329	0.052	1.000

#### WWAN

Band	E.I.R.P (dBm)	E.I.R.P (mW)	Power Density at R = 22 cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
LTE Band 2	29.540	899.498	0.148	1.000
LTE Band 5 / CA_5B	28.830	763.836	0.126	0.549
LTE Band 13	28.310	677.642	0.111	0.518
LTE Band 48	22.950	197.242	0.032	1.000
LTE Band 66 / CA_66B / CA_66C	29.540	899.498	0.148	1.000
5G NR n2	29.540	899.498	0.148	1.000
5G NR n5	28.830	763.836	0.126	0.549
5G NR n48	22.950	197.242	0.032	1.000
5G NR n66	29.540	899.498	0.148	1.000
5G NR n77	29.980	995.405	0.164	1.000

Note: The conducted output power is refer to report No.: 22A0288R-RFUSV01S-A, 22A0288R-RFUSV03S-A, 22A0288R-RFUSV03S-B, 22A0288R-RFUSV19S-A, 22A0288R-RFUSV22S-A, 22A0288R-RFUSV23S-A and 22A0288R-RFUSV26S-A from the DEKRA, and the tune-up procedure provided by customer.

Co-location
<p>Conclusion:</p> <p>The formula of calculated the MPE is:</p> <p><math>CPD1 / LPD1 + CPD2 / LPD2 + .....etc. &lt; 1</math></p> <p>CPD = Calculation power density</p> <p>LPD = Limit of power density</p> <p><b>WiFi 2.4 GHz + WiFi 5 GHz + WiFi 6 GHz + WWAN = 0.358 + 0.353 + 0.052 + 0.230 = 0.993</b></p> <p>Therefore the maximum calculations of above situations are less than the “1” limit.</p>

Results	PASS
---------	------