

FCC REPORT

(WIFI)

Applicant: TECNO MOBILE LIMITED

Address of Applicant: FLAT 39 8/F BLOCK D WAH LOK INDUSTRIAL CENTRE 31-35
SHAN MEI STREET FOTAN NT

Equipment Under Test (EUT)

Product Name: Router

Model No.: TR660

Trade mark: TECNO

FCC ID: 2ADYY-TR660

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of sample receipt: 27 Jul., 2021

Date of Test: 27 Jul., to 26 Aug., 2021

Date of report issued: 01 Sep., 2021

Test Result: PASS*

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the JYT product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	26 Aug., 2021	Original
01	01 Sep., 2021	Update page 58

Tested by:

Mike.ou
Test Engineer

Date:

01 Sep., 2021

Reviewed by:

Winner Zhang
Project Engineer

Date:

01 Sep., 2021

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY.....	4
5 GENERAL INFORMATION.....	5
5.1 CLIENT INFORMATION.....	5
5.2 GENERAL DESCRIPTION OF E.U.T.....	5
5.3 TEST ENVIRONMENT AND MODE, AND TEST SAMPLES PLANS	6
5.4 DESCRIPTION OF SUPPORT UNITS.....	6
5.5 MEASUREMENT UNCERTAINTY.....	6
5.6 LABORATORY FACILITY.....	7
5.7 LABORATORY LOCATION	7
5.8 TEST INSTRUMENTS LIST.....	7
6 TEST RESULTS AND MEASUREMENT DATA.....	9
6.1 ANTENNA REQUIREMENT.....	9
6.2 CONDUCTED EMISSION	10
6.3 CONDUCTED OUTPUT POWER	15
6.4 OCCUPY BANDWIDTH	16
6.5 POWER SPECTRAL DENSITY	17
6.6 BAND EDGE	18
6.6.1 Conducted Emission Method.....	18
6.6.2 Radiated Emission Method.....	19
6.7 SPURIOUS EMISSION.....	60
6.7.1 Conducted Emission Method.....	60
6.7.2 Radiated Emission Method.....	61
7 TEST SETUP PHOTO	77
8 EUT CONSTRUCTIONAL DETAILS	80

4 Test Summary

Test Items	Section in CFR 47	Test Data	Result
Antenna requirement	15.203 & 15.247 (b)	See Section 6.1	Pass
AC Power Line Conducted Emission	15.207	See Section 6.2	Pass
Duty Cycle	ANSI C63.10-2013	Appendix A – 2.4G Wi-Fi	Pass
Conducted Peak Output Power	15.247 (b)(3)	Appendix A – 2.4G Wi-Fi	Pass
6dB Emission Bandwidth 99% Occupied Bandwidth	15.247 (a)(2)	Appendix A – 2.4G Wi-Fi	Pass
Power Spectral Density	15.247 (e)	Appendix A – 2.4G Wi-Fi	Pass
Conducted Band Edge	15.247 (d)	Appendix A – 2.4G Wi-Fi	Pass
Radiated Band Edge		See Section 6.6.2	Pass
Conducted Spurious Emission	15.205 & 15.209	Appendix A – 2.4G Wi-Fi	Pass
Radiated Spurious Emission		See Section 6.7.2	Pass
Remark: 1. Pass: The EUT complies with the essential requirements in the standard. 2. N/A: Not Applicable. 3. The cable insertion loss used by “RF Output Power” and other conduction measurement items is 0.5dB (provided by the customer).			
Test Method:	ANSI C63.10-2013 KDB 558074 D01 15.247 Meas Guidance v05r02		

5 General Information

5.1 Client Information

Applicant:	TECNO MOBILE LIMITED
Address:	FLAT 39 8/F BLOCK D WAH LOK INDUSTRIAL CENTRE 31-35 SHAN MEI STREET FOTAN NT
Manufacturer:	TECNO MOBILE LIMITED
Address:	FLAT 39 8/F BLOCK D WAH LOK INDUSTRIAL CENTRE 31-35 SHAN MEI STREET FOTAN NT
Factory:	SHENZHEN TECNO TECHNOLOGY CO.,LTD.
Address:	101, Building 24, Waijing Industrial Park, Fumin Community, Fucheng Street, Longhua District, Shenzhen City, P.R.China

5.2 General Description of E.U.T.

Product Name:	Router
Model No.:	TR660
Operation Frequency:	2412MHz~2462MHz: 802.11b/802.11g/802.11n(HT20)/802.11ax(HE20) 2422MHz~2452MHz: 802.11n(HT40)/802.11ax(HE40)
Channel numbers:	11: 802.11b/802.11g/802.11(HT20) /802.11ax(HE20) 7: 802.11n(HT40) /802.11ax(HE40)
Channel separation:	5MHz
Modulation technology: (IEEE 802.11b)	Direct Sequence Spread Spectrum (DSSS)
Modulation technology: (IEEE 802.11g/802.11n)	Orthogonal Frequency Division Multiplexing(OFDM)
Modulation technology: (IEEE 802.11ax)	Orthogonal Frequency Division Multiple Access (OFDMA)
Data speed (IEEE 802.11b):	1Mbps, 2Mbps, 5.5Mbps, 11Mbps
Data speed (IEEE 802.11g):	6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps
Data speed (IEEE 802.11n):	Up to 150Mbps
Data speed (IEEE 802.11ax):	20MHz: Up to 286.765Mbps 40MHz: Up to 573.529Mbps
Antenna Type:	Fixed High-Performance Antennas
TX Function:	2TX
Beamforming:	Support
Antenna gain:	ANT0: 4.81dBi ANT1: 5.63dBi
Directional Gain:	GTX: 8.64 dBi (Applied to IEEE 802.11ax)
AC adapter:	Adapter (1) Model: KL-WA120150-D Input: AC100-240V, 50/60Hz, 0.7A Output: DC 12.0V, 1.5A Adapter (2) Model: KL-WA120150-M Input: AC100-240V, 50/60Hz, 0.7A Output: DC 12.0V, 1.5A
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

Note: According to KDB 662911 D01, the directional gain $G_{TX} = G_{ANT} + 10\log(N_{ANT})$ dBi, where G_{ANT} is the maximum antenna gain in dBi, N_{ANT} is the number of outputs.

Operation Frequency each of channel for 802.11b/g/n(HT20)/ax(HE20)/n(HT40)/ax(HE40)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

- For 802.11n-HT40/ax-HE40 mode, the channel number is from 3 to 9;
- Channel 1, 6 & 11 selected for 802.11b/g/n-HT20/ax-HE20 as Lowest, Middle and Highest channel. Channel 3, 6 & 9 selected for 802.11n-HT40/ ax-HE40 as Lowest, Middle and Highest Channel.

5.3 Test environment and mode, and test samples plans

Operating Environment:	
Temperature:	24.0 °C
Humidity:	54 % RH
Atmospheric Pressure:	1010 mbar
Test mode:	
Transmitting mode	Keep the EUT in continuous transmitting with modulation
Radiated Emission: The sample was placed 0.8m (below 1GHz)/1.5m (above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages. We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:	
Per-scan all kind of data rate, the follow list were the worst case.	
Mode	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n-HT20	6.5Mbps
802.11n-HT40	13.5Mbps
802.11ax -HE20 (MIMO)	17.2Mbps
802.11ax -HE40 (MIMO)	34.4Mbps
Test Samples Plans:	
Samples Number	Used for Test Items
3#	Conducted measurements test method
1#	Radiated measurements test method
1#	EUT constructional details
Remark: JianYan Testing Group Shenzhen Co., Ltd. is only responsible for the test project data of the above samples, and will keep the above samples for a month.	

5.4 Description of Support Units

Manufacturer	Description	Model	S/N	FCC ID/DoC
Lenovo	PC	ThinkPad E450	PF-OKTSQQ 16/06	DoC

5.5 Measurement Uncertainty

Parameters	Expanded Uncertainty
Conducted Emission (9kHz ~ 30MHz)	±1.60 dB (k=2)
Radiated Emission (9kHz ~ 30MHz)	±3.12 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	±4.32 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	±5.16 dB (k=2)
Radiated Emission (18GHz ~ 40GHz)	±3.20 dB (k=2)

5.6 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Designation No.: CN1211**

JianYan Testing Group Shenzhen Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

● **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber of JianYan Testing Group Shenzhen Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

5.7 Laboratory Location

JianYan Testing Group Shenzhen Co., Ltd.

Address: No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Tel: +86-755-23118282, Fax: +86-755-23116366

Email: info-JYTee@lets.com, Website: <http://www.ccis-cb.com>

5.8 Test Instruments list

Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	ETS	9m*6m*6m	966	01-19-2021	01-18-2024
BiConiLog Antenna	SCHWARZBECK	VULB9163	497	03-03-2021	03-02-2022
Biconical Antenna	SCHWARZBECK	VUBA9117	359	06-18-2021	06-17-2022
Horn Antenna	SCHWARZBECK	BBHA9120D	916	03-03-2021	03-02-2022
Horn Antenna	SCHWARZBECK	BBHA9120D	1805	06-18-2021	06-17-2022
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170582	11-18-2020	11-17-2021
EMI Test Software	AUDIX	E3	Version: 6.110919b		
Pre-amplifier	HP	8447D	2944A09358	03-03-2021	03-02-2022
Pre-amplifier	CD	PAP-1G18	11804	03-03-2021	03-02-2022
Spectrum analyzer	Rohde & Schwarz	FSP30	101454	03-03-2021	03-02-2022
Spectrum analyzer	Rohde & Schwarz	FSP40	100363	11-18-2020	11-17-2021
EMI Test Receiver	Rohde & Schwarz	ESRP7	101070	03-03-2021	03-02-2022
Spectrum Analyzer	Agilent	N9020A	MY50510123	11-18-2020	11-17-2021
Signal Generator	Rohde & Schwarz	SMX	835454/016	03-03-2021	03-02-2022
Signal Generator	R&S	SMR20	1008100050	03-03-2021	03-02-2022
RF Switch Unit	MWRFTTEST	MW200	N/A	N/A	N/A
Test Software	MWRFTTEST	MTS8200	Version: 2.0.0.0		
Cable	ZDECL	Z108-NJ-NJ-81	1608458	03-03-2021	03-02-2022
Cable	MICRO-COAX	MFR64639	K10742-5	03-03-2021	03-02-2022
Cable	SUHNER	SUCOFLEX100	58193/4PE	03-03-2021	03-02-2022
DC Power Supply	XinNuoEr	WYK-10020K	1409050110020	09-25-2020	09-24-2021
Temperature Humidity Chamber	HengPu	HPGDS-500	20140828008	11-01-2020	10-31-2021
Simulated Station	Rohde & Schwarz	CMW500	140493	07-22-2021	07-21-2022

Conducted Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESCI	101189	03-03-2021	03-02-2022
Pulse Limiter	SCHWARZBECK	OSRAM 2306	9731	03-03-2021	03-02-2022
LISN	CHASE	MN2050D	1447	03-03-2021	03-02-2022
LISN	Rohde & Schwarz	ESH3-Z5	8438621/010	06-18-2021	06-17-2022
Cable	HP	10503A	N/A	03-03-2021	03-02-2022
EMI Test Software	AUDIX	E3	Version: 6.110919b		


Conducted method:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
Spectrum Analyzer	Keysight	N9010B	MY60240202	11-27-2020	11-26-2021
Vector Signal Generator	Keysight	N5182B	MY59101009	11-27-2020	11-26-2021
Analog Signal Generator	Keysight	N5173B	MY59100765	11-27-2020	11-26-2021
Power Detector Box	MWRF-test	MW100-PSB	MW201020JYT	11-27-2020	11-26-2021
Simulated Station	Rohde & Schwarz	CMW270	102335	11-27-2020	11-26-2021
RF Control Box	MWRF-test	MW100-RFCB	MW200927JYT	N/A	N/A
PDU	MWRF-test	XY-G10	N/A	N/A	N/A
Test Software	MWRF-tes	MTS 8310	Version: 2.0.0.0		
DC Power Supply	Keysight	E3642A	MY60296194	11-27-2020	11-26-2021

6 Test results and Measurement Data

6.1 Antenna requirement

Standard requirement:	FCC Part 15 C Section 15.203 /247(b)									
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: (4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.										
E.U.T Antenna:										
The Wi-Fi antenna is an Fixed High-Performance Antennas which cannot replace by end-user.The antennas information as below table: <table><tr><td>Operation Frequency</td><td>Antenna Number</td><td>Antenna Gain(dBi)</td></tr><tr><td rowspan="2">2412MHz~2462MHz</td><td>ANT0</td><td>4.81</td></tr><tr><td>ANT1</td><td>5.63</td></tr></table> According to above information, the antennas meet the requirements of this section			Operation Frequency	Antenna Number	Antenna Gain(dBi)	2412MHz~2462MHz	ANT0	4.81	ANT1	5.63
Operation Frequency	Antenna Number	Antenna Gain(dBi)								
2412MHz~2462MHz	ANT0	4.81								
	ANT1	5.63								


6.2 Conducted Emission

Test Requirement:	FCC Part 15 C Section 15.207		
Test Frequency Range:	150 kHz to 30 MHz		
Class / Severity:	Class B		
Receiver setup:	RBW=9 kHz, VBW=30 kHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test procedure	- The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.), which provides a 50ohm/50uH coupling impedance for the measuring equipment. - The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). - Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10(latest version) on conducted measurement.		
Test setup:	 Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m		
Test Instruments:	Refer to section 5.9 for details		
Test mode:	Refer to section 5.3 for details		
Test results:	Passed		

Measurement Data:

Adapter(1)

Product name:	Router	Product model:	TR660
Test by:	Mike	Test mode:	Wi-Fi Tx mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Humi: 55%




	Freq	Read Level	LISN Factor	Aux Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.158	47.32	10.22	-0.07	0.01	57.48	65.56	-8.08	QP
2	0.182	46.57	10.23	-0.12	0.01	56.69	64.42	-7.73	QP
3	0.219	45.02	10.24	-0.18	0.03	55.11	62.88	-7.77	QP
4	0.358	30.16	10.27	0.16	0.02	40.61	48.78	-8.17	Average
5	0.369	32.22	10.27	0.23	0.03	42.75	48.52	-5.77	Average
6	0.377	40.85	10.27	0.27	0.03	51.42	58.34	-6.92	QP
7	0.735	18.98	10.30	-0.28	0.03	29.03	46.00	-16.97	Average
8	1.135	17.41	10.32	0.32	0.08	28.13	46.00	-17.87	Average
9	2.678	19.71	10.34	-0.24	0.11	29.92	46.00	-16.08	Average
10	2.978	29.80	10.35	-0.21	0.07	40.01	56.00	-15.99	QP
11	5.993	34.13	10.46	0.73	0.09	45.41	60.00	-14.59	QP
12	8.323	20.21	10.54	1.63	0.10	32.48	50.00	-17.52	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Aux Factor + Cable Loss.

Product name:	Router	Product model:	TR660
Test by:	Mike	Test mode:	Wi-Fi Tx mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Neutral
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Humi: 55%




	Freq	Read Level	LISN Factor	Aux Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.162	48.50	10.20	0.01	0.01	58.72	65.34	-6.62	Peak
2	0.186	46.81	10.21	0.00	0.02	57.04	64.20	-7.16	Peak
3	0.373	38.55	10.26	-0.04	0.03	48.80	58.43	-9.63	Peak
4	0.373	33.44	10.26	-0.04	0.03	43.69	48.43	-4.74	Average
5	0.857	17.73	10.31	0.06	0.04	28.14	46.00	-17.86	Average
6	1.166	18.25	10.31	0.10	0.09	28.75	46.00	-17.25	Average
7	1.255	30.05	10.31	0.11	0.10	40.57	56.00	-15.43	Peak
8	2.650	18.19	10.33	0.27	0.11	28.90	46.00	-17.10	Average
9	3.740	18.00	10.37	0.46	0.08	28.91	46.00	-17.09	Average
10	4.114	31.52	10.38	0.53	0.08	42.51	56.00	-13.49	Peak
11	6.878	32.18	10.47	0.83	0.10	43.58	60.00	-16.42	Peak
12	8.729	21.12	10.55	1.18	0.11	32.96	50.00	-17.04	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Aux Factor + Cable Loss.

Adapter(2)

Product name:	Router	Product model:	TR660
Test by:	Mike	Test mode:	Wi-Fi Tx mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Humi: 55%




	Freq	Read	LISN	Aux	Cable	Level	Limit	Over	Remark
	MHz	dBuV	Factor	Factor	Loss	dBuV	dBuV	dB	
1	0.158	50.77	10.12	-0.07	0.01	60.83	65.56	-4.73	QP
2	0.162	34.02	10.13	-0.08	0.01	44.08	55.34	-11.26	Average
3	0.175	43.51	10.13	-0.11	0.01	53.54	64.72	-11.18	QP
4	0.198	27.48	10.14	-0.16	0.04	37.50	53.71	-16.21	Average
5	0.238	39.04	10.17	-0.20	0.02	49.03	62.17	-13.14	QP
6	0.389	31.99	10.28	0.34	0.04	42.65	58.08	-15.43	QP
7	0.398	20.99	10.28	0.40	0.04	31.71	47.90	-16.19	Average
8	2.527	15.52	10.56	-0.26	0.13	25.95	46.00	-20.05	Average
9	2.594	26.90	10.57	-0.25	0.12	37.34	56.00	-18.66	QP
10	5.867	16.59	10.69	0.68	0.09	28.05	50.00	-21.95	Average
11	10.733	27.35	10.86	2.22	0.12	40.55	60.00	-19.45	QP
12	11.745	16.70	10.91	2.58	0.10	30.29	50.00	-19.71	Average

Notes:

- An initial pre-scan was performed on the line and neutral lines with peak detector.
- Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- Final Level = Receiver Read level + LISN Factor + Aux Factor + Cable Loss.

Product name:	Router	Product model:	TR660
Test by:	Mike	Test mode:	Wi-Fi Tx mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Neutral
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Humi: 55%




	Freq	Read Level	LISN Factor	Aux Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.154	33.98	9.89	0.01	0.01	43.89	55.78	-11.89	Average
2	0.170	46.59	9.90	0.01	0.01	56.51	64.94	-8.43	QP
3	0.178	31.04	9.91	0.00	0.01	40.96	54.59	-13.63	Average
4	0.398	32.35	10.12	-0.06	0.04	42.45	57.90	-15.45	QP
5	0.402	22.26	10.12	-0.06	0.04	32.36	47.81	-15.45	Average
6	1.753	12.76	10.75	0.15	0.18	23.84	46.00	-22.16	Average
7	1.908	24.38	10.78	0.16	0.20	35.52	56.00	-20.48	QP
8	2.750	26.60	10.88	0.28	0.10	37.86	56.00	-18.14	QP
9	5.961	16.57	11.06	0.76	0.09	28.48	50.00	-21.52	Average
10	6.805	28.16	11.09	0.82	0.10	40.17	60.00	-19.83	QP
11	12.449	27.55	11.32	2.33	0.11	41.31	60.00	-18.69	QP
12	12.449	15.98	11.32	2.33	0.11	29.74	50.00	-20.26	Average

Notes:


1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Aux Factor + Cable Loss.

6.3 Conducted Output Power


Test Requirement:	FCC Part 15 C Section 15.247 (b)(3)
Limit:	SISO:30dBm; MIMO: 27.36dBm
Test setup:	
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed
Measurement Data:	Refer to Appendix A - 2.4G WIFI

Note: If the directional gain (G_{TX}) greater than 6 dBi, the limit shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi, about directional gain (G_{TX}), refer to clause 5.2 of this report. Directional gain = $G_{TX} = G_{ANT} + 10\log(N_{ANT})$ dBi > 6dBi, so according to KDB 558074 D01, when the power limit shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

6.4 Occupy Bandwidth


Test Requirement:	FCC Part 15 C Section 15.247 (a)(2)
Limit:	>500kHz
Test setup:	
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed
Measurement Data:	Refer to Appendix A - 2.4G WIFI

6.5 Power Spectral Density


Test Requirement:	FCC Part 15 C Section 15.247 (e)
Limit:	8dBm/3kHz
Test setup:	
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed
Measurement Data:	Refer to Appendix A - 2.4G WIFI

6.6 Band Edge

6.6.1 Conducted Emission Method


Test Requirement:	FCC Part 15 C Section 15.247 (d)
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph(b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
Test setup:	
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed
Measurement Data:	Refer to Appendix A - 2.4G WIFI

6.6.2 Radiated Emission Method

Test Requirement:	FCC Part 15 C Section 15.209 and 15.205				
Test Frequency Range:	2310 MHz to 2390 MHz and 2483.5 MHz to 2500 MHz				
Test Distance:	3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		RMS	1MHz	3MHz	Average Value
Limit:	Frequency	Limit (dBuV/m @3m)		Remark	
	Above 1GHz	54.00		Average Value	
		74.00		Peak Value	
Test Procedure:	1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.				
Test setup:					
Test Instruments:	Refer to section 5.9 for details				
Test mode:	Refer to section 5.3 for details				
Test results:	Passed				

802.11b-ANT0:

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11b Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2340.82	40.06	46.97	6.91	74.00	27.03	PK	Vertical
2	2342.13	32.65	39.57	6.92	54.00	14.43	AV	Vertical
3	2371.20	42.15	49.16	7.01	74.00	24.84	PK	Vertical
4	2372.46	34.67	41.69	7.02	54.00	12.31	AV	Vertical
5	2390.00	41.56	48.64	7.08	74.00	25.36	PK	Vertical
6	2390.00	34.56	41.64	7.08	54.00	12.36	AV	Vertical

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11b Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2333.75	31.31	38.20	6.89	54.00	15.80	AV	Horizontal
2	2334.12	39.48	46.37	6.89	74.00	27.63	PK	Horizontal
3	2360.38	31.63	38.61	6.98	54.00	15.39	AV	Horizontal
4	2360.87	40.20	47.18	6.98	74.00	26.82	PK	Horizontal
5	2390.00	36.39	43.47	7.08	74.00	30.53	PK	Horizontal
6	2390.00	28.99	36.07	7.08	54.00	17.93	AV	Horizontal

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11b Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2483.50	45.08	52.77	7.69	74.00	21.23	PK	Vertical
2	2483.50	40.05	47.74	7.69	54.00	6.26	AV	Vertical
3	2489.01	43.47	51.19	7.72	54.00	2.81	AV	Vertical
4	2489.15	48.20	55.93	7.73	74.00	18.07	PK	Vertical
5	2496.92	42.92	50.70	7.78	74.00	23.30	PK	Vertical
6	2497.10	37.06	44.84	7.78	54.00	9.16	AV	Vertical

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11b Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Huni: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2483.50	39.01	46.70	7.69	74.00	27.30	PK	Horizontal
2	2483.50	30.36	38.05	7.69	54.00	15.95	AV	Horizontal
3	2491.33	31.67	39.41	7.74	54.00	14.59	AV	Horizontal
4	2491.45	39.54	47.28	7.74	74.00	26.72	PK	Horizontal
5	2498.11	39.54	47.33	7.79	74.00	26.67	PK	Horizontal
6	2498.21	30.67	38.46	7.79	54.00	15.54	AV	Horizontal

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

802.11b-ANT1:

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11b Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2327.87	32.20	39.07	6.87	54.00	14.93	AV	Vertical
2	2328.08	40.85	47.72	6.87	74.00	26.28	PK	Vertical
3	2361.63	41.38	48.36	6.98	74.00	25.64	PK	Vertical
4	2361.64	34.05	41.03	6.98	54.00	12.97	AV	Vertical
5	2390.00	45.97	53.05	7.08	74.00	20.95	PK	Vertical
6	2390.00	40.65	47.73	7.08	54.00	6.27	AV	Vertical

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11b Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Huni: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2336.92	39.12	46.02	6.90	74.00	27.98	PK	Horizontal
2	2337.28	31.62	38.52	6.90	54.00	15.48	AV	Horizontal
3	2363.45	40.48	47.47	6.99	74.00	26.53	PK	Horizontal
4	2363.69	32.31	39.30	6.99	54.00	14.70	AV	Horizontal
5	2390.00	37.82	44.90	7.08	74.00	29.10	PK	Horizontal
6	2390.00	29.50	36.58	7.08	54.00	17.42	AV	Horizontal

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.

4. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11b Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2483.50	41.53	49.22	7.69	74.00	24.78	PK	Vertical
2	2483.50	34.68	42.37	7.69	54.00	11.63	AV	Vertical
3	2488.56	42.28	50.00	7.72	54.00	4.00	AV	Vertical
4	2488.76	46.74	54.46	7.72	74.00	19.54	PK	Vertical
5	2497.61	43.12	50.90	7.78	74.00	23.10	PK	Vertical
6	2497.94	35.85	43.64	7.79	54.00	10.36	AV	Vertical

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.

4. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11b Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2483.50	38.29	45.98	7.69	74.00	28.02	PK	Horizontal
2	2483.50	30.36	38.05	7.69	54.00	15.95	AV	Horizontal
3	2490.46	31.48	39.21	7.73	54.00	14.79	AV	Horizontal
4	2490.49	39.81	47.54	7.73	74.00	26.46	PK	Horizontal
5	2496.96	39.03	46.81	7.78	74.00	27.19	PK	Horizontal
6	2497.22	30.95	38.73	7.78	54.00	15.27	AV	Horizontal

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

802.11g-ANT0:

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11g Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2335.94	38.22	45.12	6.90	74.00	28.88	PK	Vertical
2	2335.94	30.12	37.02	6.90	54.00	16.98	AV	Vertical
3	2363.07	33.34	40.33	6.99	54.00	13.67	AV	Vertical
4	2363.28	42.23	49.22	6.99	74.00	24.78	PK	Vertical
5	2390.00	54.95	62.03	7.08	74.00	11.97	PK	Vertical
6	2390.00	46.14	53.22	7.08	54.00	0.78	AV	Vertical

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11g Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2333.01	37.50	44.39	6.89	74.00	29.61	PK	Horizontal
2	2333.24	29.90	36.79	6.89	54.00	17.21	AV	Horizontal
3	2367.24	30.31	37.31	7.00	54.00	16.69	AV	Horizontal
4	2367.28	38.04	45.04	7.00	74.00	28.96	PK	Horizontal
5	2390.00	38.19	45.27	7.08	74.00	28.73	PK	Horizontal
6	2390.00	29.53	36.61	7.08	54.00	17.39	AV	Horizontal

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11g Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2483.50	50.77	58.46	7.69	74.00	15.54	PK	Vertical
2	2483.50	39.27	46.96	7.69	54.00	7.04	AV	Vertical
3	2491.37	31.81	39.55	7.74	54.00	14.45	AV	Vertical
4	2491.55	44.31	52.05	7.74	74.00	21.95	PK	Vertical
5	2497.01	43.38	51.16	7.78	74.00	22.84	PK	Vertical
6	2497.04	29.63	37.41	7.78	54.00	16.59	AV	Vertical

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11g Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2483.50	30.69	38.38	7.69	54.00	15.62	AV	Horizontal
2	2483.50	43.01	50.70	7.69	74.00	23.30	PK	Horizontal
3	2492.51	27.99	35.74	7.75	54.00	18.26	AV	Horizontal
4	2492.57	37.56	45.31	7.75	74.00	28.69	PK	Horizontal
5	2496.73	36.77	44.55	7.78	74.00	29.45	PK	Horizontal
6	2496.89	28.25	36.03	7.78	54.00	17.97	AV	Horizontal

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

802.11g-ANT1:

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11g Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2324.60	28.21	35.07	6.86	54.00	18.93	AV	Vertical
2	2325.16	35.95	42.81	6.86	74.00	31.19	PK	Vertical
3	2365.27	46.31	53.31	7.00	74.00	20.69	PK	Vertical
4	2365.53	33.80	40.80	7.00	54.00	13.20	AV	Vertical
5	2390.00	58.48	65.56	7.08	74.00	8.44	PK	Vertical
6	2390.00	46.42	53.50	7.08	54.00	0.50	AV	Vertical

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.

4. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11g Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2331.30	27.60	34.48	6.88	54.00	19.52	AV	Horizontal
2	2331.50	35.40	42.28	6.88	74.00	31.72	PK	Horizontal
3	2364.09	35.61	42.60	6.99	74.00	31.40	PK	Horizontal
4	2364.46	27.66	34.65	6.99	54.00	19.35	AV	Horizontal
5	2390.00	40.25	47.33	7.08	74.00	26.67	PK	Horizontal
6	2390.00	29.98	37.06	7.08	54.00	16.94	AV	Horizontal

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11g Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2483.50	52.22	59.91	7.69	74.00	14.09	PK	Vertical
2	2483.50	38.75	46.44	7.69	54.00	7.56	AV	Vertical
3	2490.14	33.94	41.67	7.73	54.00	12.33	AV	Vertical
4	2490.14	47.78	55.51	7.73	74.00	18.49	PK	Vertical
5	2496.14	32.10	39.87	7.77	54.00	14.13	AV	Vertical
6	2496.28	44.81	52.58	7.77	74.00	21.42	PK	Vertical

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.

4. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11g Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2483.50	42.48	50.17	7.69	74.00	23.83	PK	Horizontal
2	2483.50	29.24	36.93	7.69	54.00	17.07	AV	Horizontal
3	2490.77	37.10	44.84	7.74	74.00	29.16	PK	Horizontal
4	2491.04	28.46	36.20	7.74	54.00	17.80	AV	Horizontal
5	2497.33	27.76	35.54	7.78	54.00	18.46	AV	Horizontal
6	2497.50	36.58	44.36	7.78	74.00	29.64	PK	Horizontal

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

802.11n(HT20)-ANT0:

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11n(HT20) Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Huni: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2332.03	37.22	44.11	6.89	74.00	29.89	PK	Vertical
2	2332.07	27.85	34.74	6.89	54.00	19.26	AV	Vertical
3	2360.24	30.35	37.33	6.98	54.00	16.67	AV	Vertical
4	2361.19	42.46	49.44	6.98	74.00	24.56	PK	Vertical
5	2390.00	53.71	60.79	7.08	74.00	13.21	PK	Vertical
6	2390.00	41.54	48.62	7.08	54.00	5.38	AV	Vertical

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11n(HT20) Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2329.22	35.37	42.25	6.88	74.00	31.75	PK	Horizontal
2	2329.61	27.44	34.32	6.88	54.00	19.68	AV	Horizontal
3	2362.29	27.74	34.73	6.99	54.00	19.27	AV	Horizontal
4	2362.89	36.25	43.24	6.99	74.00	30.76	PK	Horizontal
5	2390.00	35.24	42.32	7.08	74.00	31.68	PK	Horizontal
6	2390.00	27.13	34.21	7.08	54.00	19.79	AV	Horizontal

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11n(HT20) Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2483.50	52.03	59.72	7.69	74.00	14.28	PK	Vertical
2	2483.50	40.22	47.91	7.69	54.00	6.09	AV	Vertical
3	2492.17	52.00	59.75	7.75	74.00	14.25	PK	Vertical
4	2492.23	36.09	43.84	7.75	54.00	10.16	AV	Vertical
5	2497.03	35.64	43.42	7.78	54.00	10.58	AV	Vertical
6	2497.24	47.42	55.20	7.78	74.00	18.80	PK	Vertical

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11n(HT20) Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Huni: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2483.50	38.81	46.50	7.69	74.00	27.50	PK	Horizontal
2	2483.50	29.45	37.14	7.69	54.00	16.86	AV	Horizontal
3	2490.39	39.44	47.17	7.73	74.00	26.83	PK	Horizontal
4	2490.50	28.57	36.30	7.73	54.00	17.70	AV	Horizontal
5	2497.95	27.84	35.63	7.79	54.00	18.37	AV	Horizontal
6	2498.30	36.77	44.56	7.79	74.00	29.44	PK	Horizontal

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

802.11n(HT20)-ANT1:

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11n(HT20) Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2326.66	28.49	35.36	6.87	54.00	18.64	AV	Vertical
2	2326.70	38.31	45.18	6.87	74.00	28.82	PK	Vertical
3	2363.32	43.95	50.94	6.99	74.00	23.06	PK	Vertical
4	2363.64	32.67	39.66	6.99	54.00	14.34	AV	Vertical
5	2390.00	56.71	63.79	7.08	74.00	10.21	PK	Vertical
6	2390.00	45.65	52.73	7.08	54.00	1.27	AV	Vertical

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11n(HT20) Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2328.00	27.46	34.33	6.87	54.00	19.67	AV	Horizontal
2	2328.14	35.30	42.17	6.87	74.00	31.83	PK	Horizontal
3	2361.64	35.43	42.41	6.98	74.00	31.59	PK	Horizontal
4	2361.92	27.59	34.57	6.98	54.00	19.43	AV	Horizontal
5	2390.00	38.22	45.30	7.08	74.00	28.70	PK	Horizontal
6	2390.00	28.94	36.02	7.08	54.00	17.98	AV	Horizontal

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.

4. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11n(HT20) Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2483.50	38.03	45.72	7.69	54.00	8.28	AV	Vertical
2	2483.50	49.36	57.05	7.69	74.00	16.95	PK	Vertical
3	2490.46	45.79	53.52	7.73	74.00	20.48	PK	Vertical
4	2490.62	33.32	41.06	7.74	54.00	12.94	AV	Vertical
5	2496.16	45.85	53.62	7.77	74.00	20.38	PK	Vertical
6	2496.16	35.27	43.04	7.77	54.00	10.96	AV	Vertical

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11n(HT20) Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2483.50	41.68	49.37	7.69	74.00	24.63	PK	Horizontal
2	2483.50	28.97	36.66	7.69	54.00	17.34	AV	Horizontal
3	2491.52	27.25	34.99	7.74	54.00	19.01	AV	Horizontal
4	2491.54	35.23	42.97	7.74	74.00	31.03	PK	Horizontal
5	2495.50	27.45	35.22	7.77	54.00	18.78	AV	Horizontal
6	2495.56	35.69	43.46	7.77	74.00	30.54	PK	Horizontal

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

802.11ax(HE20)-MIMO:

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11ax(HE20) Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2390.00	57.47	64.55	7.08	74.00	9.45	PK	Vertical
2	2390.00	46.85	53.93	7.08	54.00	0.07	AV	Vertical

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11ax(HE20) Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2390.00	43.85	50.93	7.08	74.00	23.07	PK	Horizontal
2	2390.00	31.97	39.05	7.08	54.00	14.95	AV	Horizontal

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11ax(HE20) Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2483.50	56.21	63.90	7.69	74.00	10.10	PK	Vertical
2	2483.50	44.61	52.30	7.69	54.00	1.70	AV	Vertical
3	2492.26	36.52	44.27	7.75	54.00	9.73	AV	Vertical
4	2492.53	54.52	62.27	7.75	74.00	11.73	PK	Vertical
5	2499.50	36.62	44.42	7.80	54.00	9.58	AV	Vertical
6	2499.50	49.30	57.10	7.80	74.00	16.90	PK	Vertical

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11ax(HE20) Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2483.50	44.33	52.02	7.69	74.00	21.98	PK	Horizontal
2	2483.50	36.02	43.71	7.69	54.00	10.29	AV	Horizontal
3	2492.09	29.31	37.06	7.75	54.00	16.94	AV	Horizontal
4	2492.09	43.68	51.43	7.75	74.00	22.57	PK	Horizontal
5	2497.31	36.61	44.39	7.78	74.00	29.61	PK	Horizontal
6	2497.31	28.12	35.90	7.78	54.00	18.10	AV	Horizontal

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

802.11n(HT40)-ANT0:

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11n(HT40) Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Huni: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBuV/m]	Level [dBuV/m]	Factor [dB]	Limit [dBuV/m]	Margin [dB]	Trace	Polarity
1	2325.85	27.96	34.83	6.87	54.00	19.17	AV	Vertical
2	2325.87	36.66	43.53	6.87	74.00	30.47	PK	Vertical
3	2363.19	35.26	42.25	6.99	54.00	11.75	AV	Vertical
4	2363.52	46.59	53.58	6.99	74.00	20.42	PK	Vertical
5	2390.00	44.11	51.19	7.08	54.00	2.81	AV	Vertical
6	2390.00	55.60	62.68	7.08	74.00	11.32	PK	Vertical

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11n(HT40) Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2343.80	38.14	45.06	6.92	74.00	28.94	PK	Horizontal
2	2343.99	29.26	36.19	6.93	54.00	17.81	AV	Horizontal
3	2368.17	29.47	36.47	7.00	54.00	17.53	AV	Horizontal
4	2368.34	37.45	44.46	7.01	74.00	29.54	PK	Horizontal
5	2390.00	47.46	54.54	7.08	74.00	19.46	PK	Horizontal
6	2390.00	37.04	44.12	7.08	54.00	9.88	AV	Horizontal

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11n(HT40) Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2483.50	56.85	64.54	7.69	74.00	9.46	PK	Vertical
2	2483.50	46.14	53.83	7.69	54.00	0.17	AV	Vertical
3	2489.07	55.69	63.41	7.72	74.00	10.59	PK	Vertical
4	2489.26	45.27	53.00	7.73	54.00	1.00	AV	Vertical
5	2497.06	53.42	61.20	7.78	74.00	12.80	PK	Vertical
6	2497.11	39.06	46.84	7.78	54.00	7.16	AV	Vertical

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11n(HT40) Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2483.50	50.69	58.38	7.69	74.00	15.62	PK	Horizontal
2	2483.50	40.30	47.99	7.69	54.00	6.01	AV	Horizontal
3	2489.46	39.99	47.72	7.73	54.00	6.28	AV	Horizontal
4	2489.63	49.09	56.82	7.73	74.00	17.18	PK	Horizontal
5	2496.80	36.10	43.88	7.78	54.00	10.12	AV	Horizontal
6	2496.85	46.63	54.41	7.78	74.00	19.59	PK	Horizontal

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

802.11n(HT40)-ANT1:

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11n(HT40) Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Huni: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBuV/m]	Level [dBuV/m]	Factor [dB]	Limit [dBuV/m]	Margin [dB]	Trace	Polarity
1	2338.57	32.16	39.07	6.91	54.00	14.93	AV	Vertical
2	2338.99	43.34	50.25	6.91	74.00	23.75	PK	Vertical
3	2370.25	41.24	48.25	7.01	54.00	5.75	AV	Vertical
4	2370.25	55.05	62.06	7.01	74.00	11.94	PK	Vertical
5	2390.00	56.28	63.36	7.08	74.00	10.64	PK	Vertical
6	2390.00	46.47	53.55	7.08	54.00	0.45	AV	Vertical

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11n(HT40) Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2344.53	45.36	52.29	6.93	74.00	21.71	PK	Horizontal
2	2344.65	37.53	44.46	6.93	54.00	9.54	AV	Horizontal
3	2366.03	37.97	44.97	7.00	54.00	9.03	AV	Horizontal
4	2366.06	46.99	53.99	7.00	74.00	20.01	PK	Horizontal
5	2390.00	52.65	59.73	7.08	74.00	14.27	PK	Horizontal
6	2390.00	41.67	48.75	7.08	54.00	5.25	AV	Horizontal

Remark:

3. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.

4. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11n(HT40) Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2483.50	55.91	63.60	7.69	74.00	10.40	PK	Vertical
2	2483.50	45.07	52.76	7.69	54.00	1.24	AV	Vertical
3	2489.97	43.32	51.05	7.73	54.00	2.95	AV	Vertical
4	2490.25	54.83	62.56	7.73	74.00	11.44	PK	Vertical
5	2496.86	38.29	46.07	7.78	54.00	7.93	AV	Vertical
6	2497.05	50.78	58.56	7.78	74.00	15.44	PK	Vertical

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11n(HT40) Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2483.50	56.06	63.75	7.69	74.00	10.25	PK	Horizontal
2	2483.50	44.81	52.50	7.69	54.00	1.50	AV	Horizontal
3	2490.54	52.45	60.18	7.73	74.00	13.82	PK	Horizontal
4	2490.89	42.20	49.94	7.74	54.00	4.06	AV	Horizontal
5	2495.87	49.32	57.09	7.77	74.00	16.91	PK	Horizontal
6	2495.91	39.37	47.14	7.77	54.00	6.86	AV	Horizontal

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

802.11ax(HE40)-MIMO:

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11ax(HE40) Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Huni: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBuV/m]	Level [dBuV/m]	Factor [dB]	Limit [dBuV/m]	Margin [dB]	Trace	Polarity
1	2334.46	43.17	50.06	6.89	74.00	23.94	PK	Vertical
2	2334.68	35.15	42.04	6.89	54.00	11.96	AV	Vertical
3	2365.40	50.26	57.26	7.00	74.00	16.74	PK	Vertical
4	2365.67	40.81	47.81	7.00	54.00	6.19	AV	Vertical
5	2390.00	50.89	57.97	7.08	74.00	16.03	PK	Vertical
6	2390.00	42.87	49.95	7.08	54.00	4.05	AV	Vertical

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11ax(HE40) Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Huni: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBuV/m]	Level [dBuV/m]	Factor [dB]	Limit [dBuV/m]	Margin [dB]	Trace	Polarity
1	2341.86	41.91	48.83	6.92	74.00	25.17	PK	Horizontal
2	2341.97	30.59	37.51	6.92	54.00	16.49	AV	Horizontal
3	2367.12	43.73	50.73	7.00	74.00	23.27	PK	Horizontal
4	2367.25	33.58	40.58	7.00	54.00	13.42	AV	Horizontal
5	2390.00	54.21	61.29	7.08	74.00	12.71	PK	Horizontal
6	2390.00	46.17	53.25	7.08	54.00	0.75	AV	Horizontal

Remark:

5. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.

6. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11ax(HE40) Tx mode
Test Channel:	Highest channel	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBuV/m]	Level [dBuV/m]	Factor [dB]	Limit [dBuV/m]	Margin [dB]	Trace	Polarity
1	2483.50	49.94	57.63	7.69	74.00	16.37	PK	Vertical
2	2483.50	45.20	52.89	7.69	54.00	1.11	AV	Vertical
3	2491.26	53.85	61.59	7.74	74.00	12.41	PK	Vertical
4	2491.33	45.66	53.40	7.74	54.00	0.60	AV	Vertical
5	2496.37	52.57	60.35	7.78	74.00	13.65	PK	Vertical
6	2496.52	41.53	49.31	7.78	54.00	4.69	AV	Vertical

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	802.11ax(HE40) Tx mode
Test Channel:	Highest channel	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	2483.50	50.33	58.02	7.69	74.00	15.98	PK	Horizontal
2	2483.50	42.66	50.35	7.69	54.00	3.65	AV	Horizontal
3	2490.53	46.06	53.79	7.73	54.00	0.21	AV	Horizontal
4	2490.68	52.14	59.88	7.74	74.00	14.12	PK	Horizontal
5	2497.23	53.11	60.89	7.78	74.00	13.11	PK	Horizontal
6	2497.35	43.56	51.34	7.78	54.00	2.66	AV	Horizontal

Remark:


- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.


6.7 Spurious Emission

6.7.1 Conducted Emission Method

Test Requirement:	FCC Part 15 C Section 15.247 (d)
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph(b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
Test setup:	
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed
Measurement Data:	Refer to Appendix A - 2.4G WIFI


6.7.2 Radiated Emission Method

Test Requirement:	FCC Part 15 C Section 15.209 and 15.205				
Test Frequency Range:	9kHz to 25GHz				
Test Distance:	3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
RMS		1MHz	3MHz	Average Value	
Limit:	Frequency	Limit (dBuV/m @3m)			Remark
	30MHz-88MHz	40.0			Quasi-peak Value
	88MHz-216MHz	43.5			Quasi-peak Value
	216MHz-960MHz	46.0			Quasi-peak Value
	960MHz-1GHz	54.0			Quasi-peak Value
	Above 1GHz	54.0			Average Value
74.0			Peak Value		
Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8m(below 1GHz)/1.5m(above 1GHz) above the ground at a 3 meter chamber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.				
Test setup:	Below 1GHz  Above 1GHz				

	
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed
Remark:	1. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis is the worst case. 2. 9 kHz to 30MHz is lower than the limit 20dB, so only shows the data of above 30MHz in this report.

Measurement Data (worst case):
Below 1GHz:
Adapter(1)

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	Wi-Fi Tx mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%



Suspected Data List

NO.	Freq. [MHz]	Reading[d BuV/m]	Level [dBuV/m]	Factor [dB]	Limit [dBuV/m]	Margin [dB]	Trace	Polarity
1	181.238	50.97	32.48	-18.49	43.50	11.02	PK	Vertical
2	250.018	51.70	36.41	-15.29	46.00	9.59	PK	Vertical
3	500.109	51.67	42.19	-9.48	46.00	3.81	PK	Vertical
4	625.057	45.11	36.88	-8.23	46.00	9.12	PK	Vertical
5	750.103	45.49	38.81	-6.68	46.00	7.19	PK	Vertical
6	875.051	37.59	33.57	-4.02	46.00	12.43	PK	Vertical

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.
- The Aux Factor is a notch filter switch box loss, this item is not used.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	Wi-Fi Tx mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	180.365	39.60	21.02	-18.58	43.50	22.48	PK	Horizontal
2	250.018	56.12	40.83	-15.29	46.00	5.17	PK	Horizontal
3	313.365	47.83	34.00	-13.83	46.00	12.00	PK	Horizontal
4	624.960	48.10	39.86	-8.24	46.00	6.14	PK	Horizontal
5	750.006	48.01	41.33	-6.68	46.00	4.67	PK	Horizontal
6	875.051	35.34	31.32	-4.02	46.00	14.68	PK	Horizontal

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.
- The Aux Factor is a notch filter switch box loss, this item is not used.

Adapter(2)

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	Wi-Fi Tx mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	39.7010	50.62	33.79	-16.83	40.00	6.21	PK	Vertical
2	124.875	51.37	32.62	-18.75	43.50	10.88	PK	Vertical
3	250.018	48.19	32.90	-15.29	46.00	13.10	PK	Vertical
4	499.915	49.54	40.06	-9.48	46.00	5.94	PK	Vertical
5	625.057	47.07	38.84	-8.23	46.00	7.16	PK	Vertical
6	750.103	45.76	39.08	-6.68	46.00	6.92	PK	Vertical

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.
- The Aux Factor is a notch filter switch box loss, this item is not used.

Product Name:	Router	Product Model:	TR660
Test By:	Mike	Test mode:	Wi-Fi Tx mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24℃ Humi: 57%



Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Margin [dB]	Trace	Polarity
1	65.8936	38.43	20.42	-18.01	40.00	19.58	PK	Horizontal
2	171.440	43.51	24.67	-18.84	43.50	18.83	PK	Horizontal
3	250.018	57.23	41.94	-15.29	46.00	4.06	PK	Horizontal
4	500.012	51.15	41.67	-9.48	46.00	4.33	PK	Horizontal
5	625.057	49.34	41.11	-8.23	46.00	4.89	PK	Horizontal
6	750.103	44.22	37.54	-6.68	46.00	8.46	PK	Horizontal

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are lower than the limit 20dB and not show in test report.
- The Aux Factor is a notch filter switch box loss, this item is not used.

Above 1GHz

802.11b-ANTO						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4824.00	67.06	-9.46	57.60	74.00	16.40	Vertical
4824.00	61.21	-9.46	51.75	74.00	22.25	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4824.00	59.68	-9.46	50.22	54.00	3.78	Vertical
4824.00	53.85	-9.46	44.39	54.00	9.61	Horizontal
Test channel: Middle channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4874.00	67.05	-9.11	57.94	74.00	16.06	Vertical
4874.00	60.99	-9.11	51.88	74.00	22.12	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4874.00	59.79	-9.11	50.68	54.00	3.32	Vertical
4874.00	53.40	-9.11	44.29	54.00	9.71	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4924.00	67.14	-8.74	58.40	74.00	15.60	Vertical
4924.00	61.06	-8.74	52.32	74.00	21.68	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4924.00	60.16	-8.74	51.42	54.00	2.58	Vertical
4924.00	53.86	-8.74	45.12	54.00	8.88	Horizontal
Remark: 1. Final Level = Receiver Read level + Factor. 2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.						

802.11b-ANT1						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4824.00	68.97	-9.46	59.51	74.00	14.49	Vertical
4824.00	66.76	-9.46	57.30	74.00	16.70	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4824.00	61.80	-9.46	52.34	54.00	1.66	Vertical
4824.00	59.20	-9.46	49.74	54.00	4.26	Horizontal
Test channel: Middle channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4874.00	68.77	-9.11	59.66	74.00	14.34	Vertical
4874.00	67.11	-9.11	58.00	74.00	16.00	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4874.00	61.89	-9.11	52.78	54.00	1.22	Vertical
4874.00	59.47	-9.11	50.36	54.00	3.64	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4924.00	68.79	-8.74	60.05	74.00	13.95	Vertical
4924.00	66.80	-8.74	58.06	74.00	15.94	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4924.00	61.79	-8.74	53.05	54.00	0.95	Vertical
4924.00	59.79	-8.74	51.05	54.00	2.95	Horizontal
Remark: 3. Final Level = Receiver Read level + Factor. 4. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.						

802.11g-ANT0						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4824.00	67.05	-9.46	57.59	74.00	16.41	Vertical
4824.00	61.03	-9.46	51.57	74.00	22.43	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4824.00	60.30	-9.46	50.84	54.00	3.16	Vertical
4824.00	53.78	-9.46	44.32	54.00	9.68	Horizontal
Test channel: Middle channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4874.00	66.61	-9.11	57.50	74.00	16.50	Vertical
4874.00	61.11	-9.11	52.00	74.00	22.00	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4874.00	60.46	-9.11	51.35	54.00	2.65	Vertical
4874.00	53.31	-9.11	44.20	54.00	9.80	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4924.00	66.15	-8.74	57.41	74.00	16.59	Vertical
4924.00	60.85	-8.74	52.11	74.00	21.89	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4924.00	59.99	-8.74	51.25	54.00	2.75	Vertical
4924.00	53.58	-8.74	44.84	54.00	9.16	Horizontal
Remark: 1. Final Level = Receiver Read level + Factor. 2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.						

802.11g-ANT1						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4824.00	68.72	-9.46	59.26	74.00	14.74	Vertical
4824.00	66.86	-9.46	57.40	74.00	16.60	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4824.00	61.99	-9.46	52.53	54.00	1.47	Vertical
4824.00	60.23	-9.46	50.77	54.00	3.23	Horizontal
Test channel: Middle channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4874.00	67.95	-9.11	58.84	74.00	15.16	Vertical
4874.00	66.95	-9.11	57.84	74.00	16.16	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4874.00	61.15	-9.11	52.04	54.00	1.96	Vertical
4874.00	60.09	-9.11	50.98	54.00	3.02	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4924.00	67.77	-8.74	59.03	74.00	14.97	Vertical
4924.00	66.88	-8.74	58.14	74.00	15.86	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4924.00	61.32	-8.74	52.58	54.00	1.42	Vertical
4924.00	59.71	-8.74	50.97	54.00	3.03	Horizontal
Remark: 3. Final Level = Receiver Read level + Factor. 4. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.						

802.11n(HT20)-ANT0						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4824.00	66.47	-9.46	57.01	74.00	16.99	Vertical
4824.00	60.84	-9.46	51.38	74.00	22.62	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4824.00	59.51	-9.46	50.05	54.00	3.95	Vertical
4824.00	53.87	-9.46	44.41	54.00	9.59	Horizontal
Test channel: Middle channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4874.00	66.03	-9.11	56.92	74.00	17.08	Vertical
4874.00	61.15	-9.11	52.04	74.00	21.96	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4874.00	59.65	-9.11	50.54	54.00	3.46	Vertical
4874.00	53.48	-9.11	44.37	54.00	9.63	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4924.00	65.74	-8.74	57.00	74.00	17.00	Vertical
4924.00	61.37	-8.74	52.63	74.00	21.37	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4924.00	59.32	-8.74	50.58	54.00	3.42	Vertical
4924.00	53.45	-8.74	44.71	54.00	9.29	Horizontal
Remark: 1. Final Level = Receiver Read level + Factor. 2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.						

802.11n(HT20)-ANT1						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4824.00	68.81	-9.46	59.35	74.00	14.65	Vertical
4824.00	66.10	-9.46	56.64	74.00	17.36	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4824.00	62.39	-9.46	52.93	54.00	1.07	Vertical
4824.00	60.39	-9.46	50.93	54.00	3.07	Horizontal
Test channel: Middle channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4874.00	68.44	-9.11	59.33	74.00	14.67	Vertical
4874.00	67.36	-9.11	58.25	74.00	15.75	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4874.00	61.45	-9.11	52.34	54.00	1.66	Vertical
4874.00	60.06	-9.11	50.95	54.00	3.05	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4924.00	68.38	-8.74	59.64	74.00	14.36	Vertical
4924.00	66.87	-8.74	58.13	74.00	15.87	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4924.00	61.15	-8.74	52.41	54.00	1.59	Vertical
4924.00	59.80	-8.74	51.06	54.00	2.94	Horizontal
Remark: 3. <i>Final Level = Receiver Read level + Factor.</i> 4. <i>The emission levels of other frequencies are lower than the limit 20dB and not show in test report.</i>						

802.11n(HT40)-ANT0						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4844.00	65.31	-9.32	55.99	74.00	18.01	Vertical
4844.00	61.61	-9.32	52.29	74.00	21.71	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4844.00	59.35	-9.32	50.03	54.00	3.97	Vertical
4844.00	53.62	-9.32	44.30	54.00	9.70	Horizontal
Test channel: Middle channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4874.00	65.01	-9.11	55.90	74.00	18.10	Vertical
4874.00	61.88	-9.11	52.77	74.00	21.23	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4874.00	58.98	-9.11	49.87	54.00	4.13	Vertical
4874.00	53.20	-9.11	44.09	54.00	9.91	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4904.00	65.39	-8.90	56.49	74.00	17.51	Vertical
4904.00	61.51	-8.90	52.61	74.00	21.39	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4904.00	59.20	-8.90	50.30	54.00	3.70	Vertical
4904.00	53.15	-8.90	44.25	54.00	9.75	Horizontal
Remark: 1. Final Level = Receiver Read level + Factor. 2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.						

802.11n(HT40)-ANT1						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4844.00	67.86	-9.32	58.54	74.00	15.46	Vertical
4844.00	67.07	-9.32	57.75	74.00	16.25	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4844.00	61.52	-9.32	52.20	54.00	1.80	Vertical
4844.00	59.98	-9.32	50.66	54.00	3.34	Horizontal
Test channel: Middle channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4874.00	68.05	-9.11	58.94	74.00	15.06	Vertical
4874.00	66.89	-9.11	57.78	74.00	16.22	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4874.00	61.65	-9.11	52.54	54.00	1.46	Vertical
4874.00	59.87	-9.11	50.76	54.00	3.24	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4904.00	68.09	-8.90	59.19	74.00	14.81	Vertical
4904.00	66.47	-8.90	57.57	74.00	16.43	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4904.00	61.84	-8.90	52.94	54.00	1.06	Vertical
4904.00	60.08	-8.90	51.18	54.00	2.82	Horizontal
Remark: 3. Final Level = Receiver Read level + Factor. 4. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.						

802.11ax(HE20)-MIMO						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4824.00	65.06	-9.46	55.60	74.00	18.40	Vertical
4824.00	58.21	-9.46	48.75	74.00	25.25	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4824.00	55.68	-9.46	46.22	54.00	7.78	Vertical
4824.00	50.85	-9.46	41.39	54.00	12.61	Horizontal
Test channel: Middle channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4874.00	64.96	-9.11	55.85	74.00	18.15	Vertical
4874.00	58.36	-9.11	49.25	74.00	24.75	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4874.00	55.20	-9.11	46.09	54.00	7.91	Vertical
4874.00	50.84	-9.11	41.73	54.00	12.27	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4924.00	65.25	-8.74	56.51	74.00	17.49	Vertical
4924.00	58.80	-8.74	50.06	74.00	23.94	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4924.00	55.30	-8.74	46.56	54.00	7.44	Vertical
4924.00	51.21	-8.74	42.47	54.00	11.53	Horizontal
Remark: 5. Final Level = Receiver Read level + Factor. 6. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.						

802.11ax(HE40)-MIMO						
Test channel: Lowest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4844.00	65.10	-9.32	55.78	74.00	18.22	Vertical
4844.00	58.96	-9.32	49.64	74.00	24.36	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4844.00	55.56	-9.32	46.24	54.00	7.76	Vertical
4844.00	51.54	-9.32	42.22	54.00	11.78	Horizontal
Test channel: Middle channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4874.00	64.92	-9.11	55.81	74.00	18.19	Vertical
4874.00	58.48	-9.11	49.37	74.00	24.63	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4874.00	55.88	-9.11	46.77	54.00	7.23	Vertical
4874.00	51.18	-9.11	42.07	54.00	11.93	Horizontal
Test channel: Highest channel						
Detector: Peak Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4904.00	65.02	-8.90	56.12	74.00	17.88	Vertical
4904.00	58.01	-8.90	49.11	74.00	24.89	Horizontal
Detector: Average Value						
Frequency (MHz)	Read Level (dBuV)	Factor(dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Polarization
4904.00	55.71	-8.90	46.81	54.00	7.19	Vertical
4904.00	50.99	-8.90	42.09	54.00	11.91	Horizontal
Remark: 7. Final Level = Receiver Read level + Factor. 8. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.						