FCC TEST REPORT (BLUETOOTH)

REPORT NO.:	RF140821C27
MODEL NO.:	FGA
FCC ID:	HFS-FGA
RECEIVED:	Aug. 21, 2014
TESTED:	Aug. 27, 2014 ~ Sep. 18, 2014
ISSUED:	Sep. 24, 2014

APPLICANT:	Quanta Computer Inc.
ADDRESS:	No.211, Wen Hwa 2nd Road , Kuei Shan Hsiang Tao Yuan Shien, Taiwan

ISSUED BY:	Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
LAB ADDRESS:	No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C)
TEST LOCATION:	No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

TABLE OF CONTENTS

RELEASE CONTROL RECORD 5
1. CERTIFICATION 6
2. SUMMARY OF TEST RESULTS 7
2.1 MEASUREMENT UNCERTAINTY 8
3. GENERAL INFORMATION 9
3.1 GENERAL DESCRIPTION OF EUT 9
3.2 DESCRIPTION OF TEST MODES 11
3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL 12
3.3 DESCRIPTION OF SUPPORT UNITS 16
3.3.1 CONFIGURATION OF SYSTEM UNDER TEST 16
3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS 17
4. TEST TYPES AND RESULTS (FOR BLUETOOTH EDR) 18
4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT 18
4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT 18
4.1.2 TEST INSTRUMENTS 19
4.1.3 TEST PROCEDURES 20
4.1.4 DEVIATION FROM TEST STANDARD 20
4.1.5 TEST SETUP 21
4.1.6 EUT OPERATING CONDITIONS 22
4.1.7 TEST RESULTS 23
4.2 CONDUCTED EMISSION MEASUREMENT 27
4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT 27
4.2.2 TEST INSTRUMENTS 27
4.2.3 TEST PROCEDURES 28
4.2.4 DEVIATION FROM TEST STANDARD 28
4.2.5 TEST SETUP 29
4.2.6 EUT OPERATING CONDITIONS 29
4.2.7 TEST RESULTS 30
4.3 NUMBER OF HOPPING FREQUENCY USED 32
4.3.1 LIMIT OF HOPPING FREQUENCY USED 32
4.3.2 TEST SETUP 32
4.3.3 TEST INSTRUMENTS 32
4.3.4 TEST PROCEDURE 32
4.3.5 DEVIATION FROM TEST STANDARD 32
4.3.6 TEST RESULTS 32
4.4 DWELL TIME ON EACH CHANNEL 34
4.4.1 LIMITS OF DWELL TIME USED 34
4.4.2 TEST SETUP 34
4.4.3 TEST INSTRUMENTS 34
4.4.4 TEST PROCEDURES 34
4.4.5 DEVIATION FROM TEST STANDARD 34
4.4.6 TEST RESULTS 35
4.5 CHANNEL BANDWIDTH 38
4.5.1 LIMITS OF CHANNEL BANDWIDTH 38
4.5.2 TEST SETUP 38
4.5.3 TEST INSTRUMENTS 38
4.5.4 TEST PROCEDURE 38
4.5.5 DEVIATION FROM TEST STANDARD 38
4.5.6 EUT OPERATING CONDITION 38
4.5.7 TEST RESULTS 39
4.6 HOPPING CHANNEL SEPARATION 40
4.6.1 LIMITS OF HOPPING CHANNEL SEPARATION 40

4.6.2 TEST SETUP 40
4.6.3 TEST INSTRUMENTS 40
4.6.4 TEST PROCEDURE 40
4.6.5 DEVIATION FROM TEST STANDARD 40
4.6.6 TEST RESULTS 41
4.7 MAXIMUM OUTPUT POWER 42
4.7.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT 42
4.7.2 TEST SETUP 42
4.7.3 TEST INSTRUMENTS 42
4.7.4 TEST PROCEDURE 42
4.7.5 DEVIATION FROM TEST STANDARD 42
4.7.6 EUT OPERATING CONDITION 42
4.7.7 TEST RESULTS 43
4.8 CONDUCTED OUT OF BAND EMISSION MEASUREMENT 44
4.8.1 LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT 44
4.8.2 TEST INSTRUMENTS 44
4.8.3 TEST PROCEDURE 44
4.8.4 DEVIATION FROM TEST STANDARD 44
4.8.5 EUT OPERATING CONDITION 44
4.8.6 TEST RESULTS 44
5. TEST TYPES AND RESULTS (FOR BLUETOOTH LE 4.0) 48
5.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT 48
5.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT 48
5.1.2 TEST INSTRUMENTS 48
5.1.3 TEST PROCEDURES 49
5.1.4 DEVIATION FROM TEST STANDARD 49
5.1.5 TEST SETUP 50
5.1.6 EUT OPERATING CONDITIONS 50
5.1.7 TEST RESULTS 51
5.2 CONDUCTED EMISSION MEASUREMENT 55
5.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT 55
5.2.2 T EST INSTRUMENTS 55
5.2.3 TEST PROCEDURES 55
5.2.4 DEVIATION FROM TEST STANDARD 55
5.2.5 TEST SETUP 55
5.2.6 EUT OPERATING CONDITIONS 55
5.2.7 TEST RESULTS 56
5.3 6dB BANDWIDTH MEASUREMENT 58
5.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT 58
5.3.2 TEST SETUP 58
5.3.3 TEST INSTRUMENTS 58
5.3.4 TEST PROCEDURE 58
5.3.5 DEVIATION FROM TEST STANDARD 58
5.3.6 EUT OPERATING CONDITIONS 58
5.3.7 TEST RESULTS 59
5.4 CONDUCTED OUTPUT POWER 60
5.4.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT 60
5.4.2 TEST SETUP 60
5.4.3 INSTRUMENTS 60
5.4.4 TEST PROCEDURES 60
5.4.5 DEVIATION FROM TEST STANDARD 60
5.4.6 EUT OPERATING CONDITIONS 60
5.4.7 TEST RESULTS 60
5.5 POWER SPECTRAL DENSITY MEASUREMENT 61
5.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT 61

5.5.2 TEST SETUP 61
5.5.3 TEST INSTRUMENTS 61
5.5.4 TEST PROCEDURE. 61
5.5.5 DEVIATION FROM TEST STANDARD 61
5.5.6 EUT OPERATING CONDITION 61
5.5.7 TEST RESULTS 62
5.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT 63
5.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT 63
5.6.2 TEST SETUP 63
5.6.3 TEST INSTRUMENTS 63
5.6.4 TEST PROCEDURE 63
5.6.5 DEVIATION FROM TEST STANDARD 63
5.6.6 EUT OPERATING CONDITION 63
5.6.7 TEST RESULTS 64
6. PHOTOGRAPHS OF THE TEST CONFIGURATION 65
7. INFORMATION ON THE TESTING LABORATORIES 66
8. APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB 67

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF140821C27	Original release	Sep. 24, 2014

1. CERTIFICATION

PRODUCT:	Tablet PC
MODEL NO.:	FGA
BRAND:	QOCA/faceVsion
APPLICANT:	Quanta Computer Inc.
TESTED:	Aug. 27, 2014 ~ Sep. 18, 2014
TEST SAMPLE:	Identical Prototype
STANDARDS:	**FCC Part 15, Subpart C (Section 15.247)**
	ANSI C63.10-2009

The above equipment (model: FGA) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch,** and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Rona Chen **, DATE :** Sep. 24, 2014

Ivonne Wu / Supervisor

APPROVED BY : Sam chen **, DATE :** Sep. 24, 2014

Sam Chen / Senior Project Engineer

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C (Bluetooth EDR)			
STANDARD SECTION	**TEST TYPE AND LIMIT**	**RESULT**	**REMARK**
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -10.52dB at 0.19687MHz.
15.247(a)(1) (iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.
15.247(a)(1) (iii)	Dwell Time on Each Channel	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power	PASS	Meet the requirement of limit.
15.247(d)	Transmitter Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -15.81dB at 188.22MHz.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

NOTE: If The Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247) (Bluetooth LE 4.0)			
STANDARD SECTION	**TEST TYPE AND LIMIT**	**RESULT**	**REMARK**
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -14.02dB at 0.19297MHz.
15.205 & 15.209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -13.37dB at 43.5MHz.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.247(d)	Antenna Port Emission	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	2.93 dB
	200MHz ~1000MHz	2.95 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	Tablet PC	
MODEL NO.	FGA	
POWER SUPPLY	5.0Vdc (adapter or host equipment) 3.7Vdc (Li-ion battery)	
MODULATION TYPE	**Bluetooth EDR**	GFSK, π/4-DQPSK, 8DPSK
	Bluetooth LE 4.0	GFSK
TRANSFER RATE	**Bluetooth EDR**	1/2/3Mbps
	Bluetooth LE 4.0	1Mbps
OPERATING FREQUENCY	2402 ~ 2480MHz	
NUMBER OF CHANNEL	**Bluetooth EDR**	79
	Bluetooth LE 4.0	40
CHANNEL SPACING	**Bluetooth EDR**	1MHz
	Bluetooth LE 4.0	2MHz
OUTPUT POWER	**Bluetooth EDR**	1.795mW
	Bluetooth LE 4.0	1.435mW
ANTENNA TYPE	PCB antenna with 2.3dBi gain	
ANTENNA CONNECTOR	NA	
DATA CABLE	Refer to Note as below	
I/O PORTS	Refer to user's manual	
ACCESSORY DEVICES	Refer to Note as below	

NOTE:

1. The EUT contains following accessory devices.

ITEM	BRAND	MODEL	SPECIFICATION
Adapter	TPT	MII050200B	I/P: 100-240Vac, 50-60Hz, 300mA O/P: 5Vdc, 2000mA
Battery	ATL	3590A3	3.7Vdc, 7880mAh
USB Cable	David	AA787300	1m shielded cable w/o core
EMMC	KINGSTON	KE4CN3K6A	169PIN, 8GB
CPU	MTK	MT8125	1.2GHz, 515PIN
LCD Panel	Innolux	N101ICG-L11	10.1”
Front Camera	LITE-ON	13P2SF101	--
Rear Camera	MCNEX	MC520B-2DB1T0246	--
Main Board	DME	T9208N0856A0	--
	GOC	909G8577A	--
	TDT	Q017008SS1589-02	--
WLAN/BT Module	MTK	MT6628Q	--

2. The above EUT information is declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

Bluetooth EDR:

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

Bluetooth LE 4.0:

40 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

BLUETOOTH EDR

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where **RE≥1G:** Radiated Emission above 1GHz **RE<1G:** Radiated Emission below 1GHz
PLC: Power Line Conducted Emission **APCM:** Antenna Port Conducted Measurement

NOTE: 1. For Radiated emission test, pre-tested GFSK, π/4-DQPSK, 8DPSK modulation type and found GFSK was the worse, therefore chosen for the final test and presented in the test report.

2. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Y-plane.**

RADIATED EMISSION TEST (ABOVE 1GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	PACKET TYPE
-	0 to 78	0, 39, 78	GFSK	DH5

RADIATED EMISSION TEST (BELOW 1GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	PACKET TYPE
-	0 to 78	0	GFSK	DH5

POWER LINE CONDUCTED EMISSION TEST:

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	PACKET TYPE
-	0 to 78	0	GFSK	DH5

ANTENNA PORT CONDUCTED MEASUREMENT:

☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	PACKET TYPE
-	0 to 78	0, 39, 78	GFSK	DH5
-	0 to 78	0, 39, 78	π/4-DQPSK	DH5
-	0 to 78	0, 39, 78	8DPSK	DH5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE≥1G	25deg. C, 65%RH	120Vac, 60Hz	Anson Lin
RE<1G	25deg. C, 65%RH	120Vac, 60Hz	Anson Lin
PLC	25deg. C, 65%RH	120Vac, 60Hz	Gavin Wu
APCM	25deg. C, 65%RH	120Vac, 60Hz	Howard Kao

BLUETOOTH LE 4.0:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where **RE≥1G:** Radiated Emission above 1GHz **RE<1G:** Radiated Emission below 1GHz
PLC: Power Line Conducted Emission **APCM:** Antenna Port Conducted Measurement

NOTE: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Y-plane.**

RADIATED EMISSION TEST (ABOVE 1GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
-	0 to 39	0, 19, 39	GFSK	1.0

RADIATED EMISSION TEST (BELOW 1GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
-	0 to 39	39	GFSK	1.0

POWER LINE CONDUCTED EMISSION TEST:

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
-	0 to 39	39	GFSK	1.0

ANTENNA PORT CONDUCTED MEASUREMENT:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
-	0 to 39	0, 19, 39	GFSK	1.0

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE≥1G	25deg. C, 65%RH	120Vac, 60Hz	Anson Lin
RE<1G	25deg. C, 65%RH	120Vac, 60Hz	Anson Lin
PLC	25deg. C, 65%RH	120Vac, 60Hz	Gavin Wu
APCM	25deg. C, 65%RH	120Vac, 60Hz	Howard Kao

3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units.

3.3.1 CONFIGURATION OF SYSTEM UNDER TEST



3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)
ANSI C63.10-2009
558074 D01 DTS Meas Guidance v03r02
FCC Public Notice DA 00-705

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

4. TEST TYPES AND RESULTS (FOR BLUETOOTH EDR)

4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver Agilent	N9038A	MY51210203	Jan. 17, 2014	Jan. 16, 2015
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 21, 2013	Dec. 20, 2014
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Feb. 27. 2014	Feb. 26, 2015
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-969	Feb. 19, 2014	Feb. 18, 2015
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Dec. 18, 2013	Dec. 17, 2014
Loop Antenna	HFH2-Z2	100070	Mar. 06, 2014	Mar. 05, 2016
Preamplifier EMCI	EMC 012645	980115	Dec. 26, 2013	Dec. 25, 2014
Preamplifier EMCI	EMC 184045	980116	Jan. 13, 2014	Jan. 12, 2015
Preamplifier EMCI	EMC 330H	980112	Dec. 27, 2013	Dec. 26, 2014
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309219/4 2950114	Oct. 18, 2013	Oct. 17, 2014
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250130/4	Oct. 18, 2013	Oct. 17, 2014
RF signal cable Worken	RG-213	NA	Nov. 07, 2013	Nov. 06, 2014
Software BV ADT	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower &Turn Table Controller MF	MF-7802	NA	NA	NA
Bluetooth Tester	CBT	100980	Apr. 18, 2013	Apr. 17, 2015
Power Meter	ML2495A	1012010	Aug. 22, 2014	Aug. 21, 2015
Power Sensor	MA2411B	1315050	Aug. 22, 2014	Aug. 21, 2015

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The calibration interval of the loop antenna is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
3. The test was performed in HwaYa Chamber 10.
4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
5. The FCC Site Registration No. is 690701.
6. The IC Site Registration No. is IC 7450F-10.

4.1.3 TEST PROCEDURES

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

4.1.5 TEST SETUP

Frequency Range 30MHz ~ 1GHz



Frequency Range above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

a. Placed the EUT on a testing table.

b. Use the software to control the EUT under transmission condition continuously at specific channel frequency.

4.1.7 TEST RESULTS

ABOVE 1GHz WORST-CASE DATA

GFSK

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anson Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2374	34.43	41.55	54	-19.57	26.86	3.52	37.5	151	135	Average
2374	56.86	63.98	74	-17.14	26.86	3.52	37.5	151	135	Peak
2402	82.99	90.06			26.91	3.54	37.52	151	135	Average
2402	94.06	101.13			26.91	3.54	37.52	151	135	Peak
2488	32.94	39.44	54	-21.06	27.2	3.62	37.32	151	135	Average
2488	56.56	63.06	74	-17.44	27.2	3.62	37.32	151	135	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2354	32.94	40.12	54	-21.06	26.81	3.5	37.49	121	206	Average
2354	55.88	63.06	74	-18.12	26.81	3.5	37.49	121	206	Peak
2402	78.27	85.34			26.91	3.54	37.52	121	206	Average
2402	89.44	96.51			26.91	3.54	37.52	121	206	Peak
2496	32.91	39.34	54	-21.09	27.2	3.62	37.25	121	206	Average
2496	56.76	63.19	74	-17.24	27.2	3.62	37.25	121	206	Peak

REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
   Margin value = Emission level – Limit value
2. 2402MHz: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anson Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2380	32.35	39.47	54	-21.65	26.86	3.52	37.5	149	134	Average
2380	55.72	62.84	74	-18.28	26.86	3.52	37.5	149	134	Peak
2441	82.4	89.15			27.06	3.58	37.39	149	134	Average
2441	94.58	101.33			27.06	3.58	37.39	149	134	Peak
2488	32.92	39.42	54	-21.08	27.2	3.62	37.32	149	134	Average
2488	55.52	62.02	74	-18.48	27.2	3.62	37.32	149	134	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2332	32.16	39.43	54	-21.84	26.72	3.48	37.47	100	62	Average
2332	56.36	63.63	74	-17.64	26.72	3.48	37.47	100	62	Peak
2441	78.81	85.56			27.06	3.58	37.39	100	62	Average
2441	89.07	95.82			27.06	3.58	37.39	100	62	Peak
2498	32.9	39.33	54	-21.1	27.2	3.62	37.25	100	62	Average
2498	55.66	62.09	74	-18.34	27.2	3.62	37.25	100	62	Peak

REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
   Margin value = Emission level – Limit value
2. 2441MHz: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anson Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2322	32.16	39.43	54	-21.84	26.72	3.48	37.47	100	179	Average
2322	56.02	63.29	74	-17.98	26.72	3.48	37.47	100	179	Peak
2480	82.84	89.41			27.15	3.6	37.32	100	179	Average
2480	94.79	101.36			27.15	3.6	37.32	100	179	Peak
2492	34.84	41.27	54	-19.16	27.2	3.62	37.25	100	179	Average
2492	55.88	62.31	74	-18.12	27.2	3.62	37.25	100	179	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2346	32.2	39.42	54	-21.8	26.77	3.5	37.49	100	62	Average
2346	55.5	62.72	74	-18.5	26.77	3.5	37.49	100	62	Peak
2480	78.76	85.33			27.15	3.6	37.32	100	62	Average
2480	89.03	95.6			27.15	3.6	37.32	100	62	Peak
2492	33.77	40.2	54	-20.23	27.2	3.62	37.25	100	62	Average
2492	55.22	61.65	74	-18.78	27.2	3.62	37.25	100	62	Peak

REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
   Margin value = Emission level – Limit value
2. 2480MHz: Fundamental frequency.

BELOW 1GHz WORST-CASE DATA:

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	30MHz ~ 1GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anson Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
178.77	27.59	47	43.5	-15.91	10.92	1.49	31.82	135	218	Peak
188.22	**27.69**	**47.66**	**43.5**	**-15.81**	**10.19**	**1.54**	**31.7**	**122**	**298**	**Peak**
206.58	26.95	47.33	43.5	-16.55	9.65	1.63	31.66	140	241	Peak
501.6	20.37	31.86	46	-25.63	17.35	2.78	31.62	110	257	Peak
650	23.48	32.05	46	-22.52	20.21	3.24	32.02	133	148	Peak
791.4	25.66	31.28	46	-20.34	22.11	3.67	31.4	109	14	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
41.88	24.02	40.83	40	-15.98	13.56	0.68	31.05	120	237	Peak
55.11	22.87	40.95	40	-17.13	12.45	0.8	31.33	106	165	Peak
87.24	23.4	45.96	40	-16.6	8.25	1.01	31.82	109	25	Peak
544.3	20.89	31.45	46	-25.11	18.33	2.93	31.82	102	170	Peak
692.7	23.46	31.16	46	-22.54	20.73	3.4	31.83	120	137	Peak
781.6	26.14	31.94	46	-19.86	21.97	3.65	31.42	123	42	Peak

REMARKS: Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor

Margin value = Emission level – Limit value

4.2 CONDUCTED EMISSION MEASUREMENT

4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

NOTE: 1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.2.2 TEST INSTRUMENTS

Test Date: 2014/09/18

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCS30	100288	Apr. 24, 2014	Apr. 23, 2015
RF signal cable Woken	5D-FB	Cable-HYCO2-01	Dec. 27, 2013	Dec. 26, 2014
LISN ROHDE & SCHWARZ (EUT)	ESH2-Z5	100100	Dec. 23, 2013	Dec. 22, 2014
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100312	Jul. 10, 2014	Jul. 09, 2015
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Shielded Room 2.
3. The VCCI Site Registration No. is C-2047.

4.2.3 TEST PROCEDURES

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

4.2.5 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

Same as section 4.1.6.

4.2.7 TEST RESULTS

CONDUCTED WORST-CASE DATA：

PHASE	Line 1	6dB BANDWIDTH	9kHz

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.18906	0.28	50.83	39.77	51.11	40.05	64.08	54.08	-12.97	-14.03
2	0.25156	0.29	43.27	28.83	43.56	29.12	61.71	51.71	-18.15	-22.59
3	0.31797	0.29	39.86	28.13	40.15	28.42	59.76	49.76	-19.61	-21.34
4	0.67734	0.32	38.36	23.75	38.68	24.07	56.00	46.00	-17.32	-21.93
5	1.99609	0.36	38.48	23.19	38.84	23.55	56.00	46.00	-17.16	-22.45
6	3.27734	0.40	38.70	24.63	39.10	25.03	56.00	46.00	-16.90	-20.97

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



PHASE	Line 2	6dB BANDWIDTH	9kHz

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	0.26	34.99	14.94	35.25	15.20	66.00	56.00	-30.75	-40.80
2	**0.19687**	**0.28**	**52.94**	**41.09**	**53.22**	**41.37**	**63.74**	**53.74**	**-10.52**	**-12.37**
3	0.25938	0.29	45.32	29.87	45.61	30.16	61.45	51.45	-15.85	-21.30
4	0.32188	0.29	40.87	26.52	41.16	26.81	59.66	49.66	-18.50	-22.85
5	0.85703	0.33	39.31	22.02	39.64	22.35	56.00	46.00	-16.36	-23.65
6	3.44922	0.42	39.10	25.10	39.52	25.52	56.00	46.00	-16.48	-20.48

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



4.3 NUMBER OF HOPPING FREQUENCY USED

4.3.1 LIMIT OF HOPPING FREQUENCY USED

At least 15 channels frequencies, and should be equally spaced.

4.3.2 TEST SETUP



4.3.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.3.4 TEST PROCEDURE

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
d. Set the SA on View mode and then plot the result on SA screen.
e. Repeat above procedures until all frequencies measured were complete.

4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

4.3.6 TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer to next page for the test result. On the plot, it shows that the hopping frequencies are equally spaced.

GFSK


RBW 1 MHz
VBW 1 MHz
SWT 500 ms
[T1] MP MAXH
[T2] MP VIEW
Ref 24.3 dBm
Att 20 dB
Offset 14.3 dB
24.3
20
10
0
-10
-20
-30
-40
-50
-60
-70
-75.7
Start 2.4 GHz
4.1 MHz/
Stop 2.441 GHz


RBW 1 MHz
VBW 1 MHz
SWT 500 ms
[T1] MP MAXH
[T2] MP VIEW
Ref 24.3 dBm
Att 20 dB
Offset 14.3 dB
24.3
20
10
0
-10
-20
-30
-40
-50
-60
-70
-75.7
Start 2.441 GHz
4.25 MHz/
Stop 2.4835 GHz

4.4 DWELL TIME ON EACH CHANNEL

4.4.1 LIMITS OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.4.4 TEST PROCEDURES

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
e. Repeat above procedures until all different time-slot modes have been completed.

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 TEST RESULTS

GFSK

Mode	Average Hopping Channel	Package Transfer Time (usec)	Result (sec)	Limit (sec)
DH1	10.00	438.00	0.14	0.4
DH3	5.00	1690.00	0.27	0.4
DH5	3.20	2948.00	0.30	0.4

NOTE:

1. Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time
2. 79 channels come from the Hopping Channel number
3. Average Hopping Channel = hops/sweep time
4. t: Package Transfer Time(us)
5. Test plots of the transmitting time slot are shown as below.

DH1





DH3





DH5





π/4-DQPSK

Mode	Average Hopping Channel	Package Transfer Time (usec)	Result (sec)	Limit (sec)
DH1	10.00	428.00	0.14	0.4
DH3	5.40	1674.00	0.29	0.4
DH5	3.20	2940.00	0.30	0.4

NOTE:

1. Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time
2. 79 channels come from the Hopping Channel number
3. Average Hopping Channel = hops/sweep time
4. t: Package Transfer Time(us)
5. Test plots of the transmitting time slot are shown as below.

DH1



DH3



DH5



8DPSK

Mode	Average Hopping Channel	Package Transfer Time (usec)	Result (sec)	Limit (sec)
DH1	10.00	413.00	0.13	0.4
DH3	5.20	1738.00	0.29	0.4
DH5	3.40	2924.00	0.31	0.4

NOTE:

1. Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time
2. 79 channels come from the Hopping Channel number
3. Average Hopping Channel = hops/sweep time
4. t: Package Transfer Time(us)
5. Test plots of the transmitting time slot are shown as below.

DH1



DH3



DH5



4.5 CHANNEL BANDWIDTH

4.5.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dBbandwidth of hopping channel shell be a minimum limit for the hopping channel separation.

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.5.4 TEST PROCEDURE

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
d. Repeat above procedures until all frequencies measured were complete.

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

4.5.6 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.5.7 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	20dB BANDWIDTH (MHz)		
		GFSK	π/4-DQPSK	8DPSK
0	2402	0.943	1.28	1.24
39	2441	0.944	1.28	1.25
78	2480	0.945	1.28	1.25

SPECTRUM PLOT OF WORST VALUE

GFSK



π/4-DQPSK



8DPSK



4.6 HOPPING CHANNEL SEPARATION

4.6.1 LIMITS OF HOPPING CHANNEL SEPARATION

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

4.6.2 TEST SETUP



4.6.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.6.4 TEST PROCEDURE

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
c. By using the MaxHold function record the separation of two adjacent channels.
d. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
e. Repeat above procedures until all frequencies measured were complete.

4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

4.6.6 TEST RESULTS

CHAN.	FREQ. (MHz)	ADJACENT CHANNEL SEPARATION (MHz)			20dB BANDWIDTH (MHz)			MINIMUM LIMIT (MHz)			PASS / FAIL
		GFSK	π/4-DQPSK	8DPSK	GFSK	π/4-DQPSK	8DPSK	GFSK	π/4-DQPSK	8DPSK	
0	2402	1.00	1.00	1.01	0.943	1.28	1.24	0.629	0.853	0.827	PASS
39	2441	1.00	1.00	1.01	0.944	1.28	1.25	0.629	0.853	0.833	PASS
78	2480	1.01	1.01	1.00	0.945	1.28	1.25	0.630	0.853	0.833	PASS

NOTE:

1. The minimum limit is two-third 20dB bandwidth.

SPECTRUM PLOT OF WORST VALUE

GFSK



π/4-DQPSK



8DPSK



4.7 MAXIMUM OUTPUT POWER

4.7.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT

The Maximum Output Power Measurement is 125mW.

4.7.2 TEST SETUP



4.7.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.7.4 TEST PROCEDURE

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
c. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 3MHz RBW and 10 MHz VBW.
d. Measure the captured power within the band and recording the plot.
e. Repeat above procedures until all frequencies required were complete.

4.7.5 DEVIATION FROM TEST STANDARD

No deviation.

4.7.6 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.7.7 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	OUTPUT POWER (mW)			OUTPUT POWER (dBm)			POWER LIMIT (mW)	PASS / FAIL
		GFSK	π/4-DQPSK	8DPSK	GFSK	π/4-DQPSK	8DPSK		
0	2402	1.795	1.567	1.589	2.54	1.95	2.01	125	PASS
39	2441	1.786	1.535	1.570	2.52	1.86	1.96	125	PASS
78	2480	1.644	1.416	1.449	2.16	1.51	1.61	125	PASS

SPECTRUM PLOT OF WORST VALUE

GFSK



π/4-DQPSK



8DPSK



4.8 CONDUCTED OUT OF BAND EMISSION MEASUREMENT

4.8.1 LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100KHz RBW).

4.8.2 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.8.3 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set VBW = 300 kHz.
3. Set span to encompass the spectrum to be examined.
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

4.8.4 DEVIATION FROM TEST STANDARD

No deviation.

4.8.5 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit continuously.

4.8.6 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

GFSK

Hopping disabled_Low Channel





Hopping disabled_High Channel





Hopping enabled_Low Channel



Hopping enabled_High Channel



π/4-DQPSK

Hopping disabled_Low Channel





Hopping disabled_High Channel





Hopping enabled_Low Channel



Hopping enabled_High Channel



8DPSK

Hopping disabled_Low Channel





Hopping disabled_High Channel





Hopping enabled_Low Channel



Hopping enabled_High Channel



5. TEST TYPES AND RESULTS (FOR BLUETOOTH LE 4.0)

5.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

5.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

5.1.2 TEST INSTRUMENTS

Same as section 4.1.2.

5.1.3 TEST PROCEDURES

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
c. Height of receiving antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

5.1.4 DEVIATION FROM TEST STANDARD

No deviation.

5.1.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

5.1.6 EUT OPERATING CONDITIONS

a. Placed the EUT on a testing table.
b. Use the software to control the EUT under transmission condition continuously at specific channel frequency.

5.1.7 TEST RESULTS

ABOVE 1GHz WORST-CASE DATA

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anson Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2384	37.07	44.19	54	-16.93	26.86	3.52	37.5	105	43	Average
2384	55.92	63.04	74	-18.08	26.86	3.52	37.5	105	43	Peak
2402	91.14	98.21			26.91	3.54	37.52	105	43	Average
2402	92.98	100.05			26.91	3.54	37.52	105	43	Peak
2492	33.85	40.28	54	-20.15	27.2	3.62	37.25	105	43	Average
2492	56.25	62.68	74	-17.75	27.2	3.62	37.25	105	43	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2310	34.52	41.84	54	-19.48	26.67	3.46	37.45	100	189	Average
2310	56.14	63.46	74	-17.86	26.67	3.46	37.45	100	189	Peak
2402	87.38	94.45			26.91	3.54	37.52	100	189	Average
2402	88.32	95.39			26.91	3.54	37.52	100	189	Peak
2498	34.4	40.83	54	-19.6	27.2	3.62	37.25	100	189	Average
2498	56.69	63.12	74	-17.31	27.2	3.62	37.25	100	189	Peak

REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
   Margin value = Emission level – Limit value
2. 2402MHz: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 19	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anson Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2390	33.89	40.96	54	-20.11	26.91	3.54	37.52	102	43	Average
2390	55.68	62.75	74	-18.32	26.91	3.54	37.52	102	43	Peak
2440	91.55	98.37			27.06	3.58	37.46	102	43	Average
2440	92.74	99.56			27.06	3.58	37.46	102	43	Peak
2496	34.45	40.88	54	-19.55	27.2	3.62	37.25	102	43	Average
2496	55.87	62.3	74	-18.13	27.2	3.62	37.25	102	43	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2384	36.06	43.18	54	-17.94	26.86	3.52	37.5	118	174	Average
2384	56.3	63.42	74	-17.7	26.86	3.52	37.5	118	174	Peak
2440	87.86	94.68			27.06	3.58	37.46	118	174	Average
2440	88.88	95.7			27.06	3.58	37.46	118	174	Peak
2498	34.44	40.87	54	-19.56	27.2	3.62	37.25	118	174	Average
2498	56.13	62.56	74	-17.87	27.2	3.62	37.25	118	174	Peak

REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
   Margin value = Emission level – Limit value
2. 2441MHz: Fundamental frequency.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	FREQUENCY RANGE	1GHz ~ 25GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anson Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2312	37.9	45.22	54	-16.1	26.67	3.46	37.45	102	43	Average
2312	55.32	62.64	74	-18.68	26.67	3.46	37.45	102	43	Peak
2480	91.12	97.69			27.15	3.6	37.32	102	43	Average
2480	92.08	98.65			27.15	3.6	37.32	102	43	Peak
2484	34.26	40.83	54	-19.74	27.15	3.6	37.32	102	43	Average
2484	56.55	63.12	74	-17.45	27.15	3.6	37.32	102	43	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2332	34.5	41.77	54	-19.5	26.72	3.48	37.47	117	174	Average
2332	55.47	62.74	74	-18.53	26.72	3.48	37.47	117	174	Peak
2480	87.52	94.09			27.15	3.6	37.32	117	174	Average
2480	88.5	95.07			27.15	3.6	37.32	117	174	Peak
2494	35.96	42.39	54	-18.04	27.2	3.62	37.25	117	174	Average
2494	56.16	62.59	74	-17.84	27.2	3.62	37.25	117	174	Peak

REMARKS:

1. Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor
   Margin value = Emission level – Limit value
2. 2480MHz: Fundamental frequency.

BELOW 1GHz WORST-CASE DATA：

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	FREQUENCY RANGE	30MHz ~ 1GHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anson Lin

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
43.77	24.99	41.8	40	-15.01	13.59	0.71	31.11	127	290	Peak
55.11	23.5	41.58	40	-16.5	12.45	0.8	31.33	135	33	Peak
88.32	22.9	45.49	43.5	-20.6	8.27	1.01	31.87	126	21	Peak
351.8	31.69	47.14	46	-14.31	14.19	2.23	31.87	100	231	Peak
635.3	22.36	31.24	46	-23.64	20.03	3.2	32.11	103	121	Peak
693.4	24.37	32.04	46	-21.63	20.74	3.41	31.82	129	69	Peak
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
43.5	**26.63**	**43.44**	**40**	**-13.37**	**13.59**	**0.71**	**31.11**	**119**	**199**	**Peak**
71.85	25.35	45.91	40	-14.65	10.29	0.91	31.76	115	308	Peak
86.7	22.47	45.02	40	-17.53	8.23	1	31.78	110	48	Peak
452.6	18.6	31.56	46	-27.4	16.39	2.63	31.98	139	234	Peak
654.2	23.27	31.73	46	-22.73	20.27	3.26	31.99	121	254	Peak
794.9	26.74	32.32	46	-19.26	22.16	3.68	31.42	123	302	Peak

REMARKS: Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor

Margin value = Emission level – Limit value

5.2 CONDUCTED EMISSION MEASUREMENT

5.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

Same as section 4.2.1.

5.2.2 T EST INSTRUMENTS

Same as section 4.2.2.

5.2.3 TEST PROCEDURES

Same as section 4.2.3.

5.2.4 DEVIATION FROM TEST STANDARD

No deviation.

5.2.5 TEST SETUP

Same as section 4.2.5.

5.2.6 EUT OPERATING CONDITIONS

Same as section 4.1.6.

5.2.7 TEST RESULTS

CONDUCTED WORST-CASE DATA：

PHASE	Line 1	6dB BANDWIDTH	9kHz

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	**0.19297**	**0.28**	**49.61**	**39.54**	**49.89**	**39.82**	**63.91**	**53.91**	**-14.02**	**-14.09**
2	0.25547	0.29	41.86	27.29	42.15	27.58	61.58	51.58	-19.43	-24.00
3	0.66172	0.32	40.10	22.26	40.42	22.58	56.00	46.00	-15.58	-23.42
4	1.93359	0.36	37.17	22.39	37.53	22.75	56.00	46.00	-18.47	-23.25
5	2.17188	0.37	39.67	24.42	40.04	24.79	56.00	46.00	-15.96	-21.21
6	3.29688	0.41	39.89	24.67	40.30	25.08	56.00	46.00	-15.70	-20.92

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



PHASE	Line 2	6dB BANDWIDTH	9kHz

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.18906	0.28	47.75	37.80	48.03	38.08	64.08	54.08	-16.05	-16.00
2	0.26328	0.29	40.06	25.55	40.35	25.84	61.33	51.33	-20.98	-25.49
3	0.67344	0.32	39.76	22.11	40.08	22.43	56.00	46.00	-15.92	-23.57
4	0.86094	0.33	40.03	22.74	40.36	23.07	56.00	46.00	-15.64	-22.93
5	3.28125	0.41	38.30	25.15	38.71	25.56	56.00	46.00	-17.29	-20.44
6	4.20703	0.44	38.49	26.66	38.93	27.10	56.00	46.00	-17.07	-18.90

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



5.3 6dB BANDWIDTH MEASUREMENT

5.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5MHz.

5.3.2 TEST SETUP



5.3.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

5.3.4 TEST PROCEDURE

1. Set resolution bandwidth (RBW) = approximately 1% of the emission bandwidth
2. Set the video bandwidth (VBW) ≥ 3 x RBW, Detector = Peak.
3. Trace mode = max hold.
4. Sweep = auto couple.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.5 DEVIATION FROM TEST STANDARD

No deviation.

5.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

5.3.7 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (KHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	687.76	0.5	PASS
19	2440	689.22	0.5	PASS
39	2480	695.27	0.5	PASS

SPECTRUM PLOT OF WORST VALUE



5.4 CONDUCTED OUTPUT POWER

5.4.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400-2483.5 MHz bands: 1 Watt (30dBm).

5.4.2 TEST SETUP



5.4.3 INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

5.4.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the peak power level.

5.4.5 DEVIATION FROM TEST STANDARD

No deviation.

5.4.6 EUT OPERATING CONDITIONS

Same as section 4.3.6.

5.4.7 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
0	2402	1.435	1.57	30	PASS
19	2440	1.426	1.54	30	PASS
39	2480	1.297	1.13	30	PASS

5.5 POWER SPECTRAL DENSITY MEASUREMENT

5.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

5.5.2 TEST SETUP



5.5.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

5.5.4 TEST PROCEDURE.

a. Set the RBW = 3 kHz, VBW =10 kHz, Detector = peak.
b. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
c. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

5.5.5 DEVIATION FROM TEST STANDARD

No deviation.

5.5.6 EUT OPERATING CONDITION

Same as section 4.3.6.

5.5.7 TEST RESULTS

Channel	FREQUENCY (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS / FAIL
0	2402	-12.95	8	PASS
19	2440	-12.98	8	PASS
39	2480	-13.45	8	PASS

SPECTRUM PLOT OF WORST VALUE



5.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT

5.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

5.6.2 TEST SETUP

5.6.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

5.6.4 TEST PROCEDURE

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW ≥ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOBE

1. Set RBW = 100 kHz.
2. Set VBW ≥ 300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

5.6.5 DEVIATION FROM TEST STANDARD

No deviation.

5.6.6 EUT OPERATING CONDITION

Same as section 4.3.6.

5.6.7 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

CH 0





CH 19





CH 39





6. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

7. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.
If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:
Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab:
Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Lab:
Tel: 886-3-3183232
Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

8. APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---