Test Report No. 7191124732-EEC15/02 dated 11 Dec 2015



Note: This report is issued subject to the Testing and Certification Regulations of the TÜV SÜD Group and the General Terms and Conditions of Business of TÜV SÜD PSB Pte Ltd. In addition, this report is governed by the terms set out within this report.

Choose certainty. Add value.

TEST REPORT COVER PAGE

Product Information								
Product Name /	HANDHELD RADIO	Applicant Company Number:	109U					
Description:								
Model Number(s):	AAH56JDN9RA1AN	UPN Number:	89FT7066					
All Used IC Test Site(s)	2932I-1	SAR Test Lab Company						
Reg. #:		Number:						

Emissions Information								
	Band 1	Band 2	Band 3	Band 4	Band 5	Band	6 Band 7	Band 8
RSS # & Issue #	RSS-247							
	& Issue 1				A			
Frequency Min (MHz)	2412				-			
Frequency Max (MHz)	2462				10 A			
RF Power Min (W)	1	1.17						
Conducted / EIRP / ERP		11				1		
RF Power Max (W)	0.0263	1				1.00		
Conducted					1.1			
Field Strength Units @	105.2dBµ				196			
distance	V/m @ 3m			100				
Measured BW (kHz)	17767							
(99%, 26dB, 6dB, etc.)	(99%)							
Calculated BW (kHz)	17900							
As per TRC-43			1					
Emission Classification	17M9D1D							
(FID, GID, DID, etc.)								
Transmitter Spurious Units	1.54GHz	- 22	Sector and the sector of the					
@ distance	49.6	100	N 10 ** 10 10*	· · · · ·	1			
	dBµV/m	N. 16		1		1000		
	(Peak) @	N 6	3 U L	1 1		1		
	3m	1.				1		
	В	В	В	В	В	В	В	В
RSS # & Issue #					11			
Frequency Min (MHz)					11			
Frequency Max (MHz)					1			
RF Power Min (W)				9.1	0			
Conducted / EIRP / ERP				1				
RF Power Max (W)								
Conducted / EIRP / ERP								
Field Strength Units @								
distance								
Measured BW (KHz)								
(99%, 26dB, 6dB, etc.)								
As per TRC-43				-				
(FID, GID, DID, etc.)				-				
@ distance		A	reement	Signatura				
		A	greement	Signature				
ATTESTATION: The test me	easurements	were made i	n accordance	ce with the ab	ove-mention	ed depar	mental standard	I(s), and that
the radio equipment identifie	a in this appli	cation has b	een subject	to all the appl	icable test co	onaltions	specified in the	departmental
Applicant / A cont Norse	Lim Cha		nave been n	Applicant / A -	vant Titla.	Δ	agistant Viac Dr	aidant
Applicant / Agent Name:	Lim Che	nwee		Applicant / Ag		A	SSISTANT VICE Pro	esident
Applicant / Agent Signature:				Signature Dat	te:	1	T Dec 2015	
	Λ.II	٨٨						
	.₩							
	1							

Test Report No. 7191124732-EEC15/02 dated 11 Dec 2015



Note: This report is issued subject to the Testing and Certification Regulations of the TÜV SÜD Group and the General Terms and Conditions of Business of TÜV SÜD PSB Pte Ltd. In addition, this report is governed by the terms set out within this report.

FORMAL REPOI 4 HAN [M [RT ON TESTING IN ACCORDANCE 7 CFR FCC Parts 15B & C RSS-GEN Issue 4: 2014 RSS-247 Issue 1: 2015 OF A DHELD RADIO (2.4GHz WiFi) odel : AAH56RDN9RA1AN] FCC ID : AZ489FT7066] [IC : 109U-89FT7066]	WITH	Choose certainty. Add value.
TEST FACILITY	TÜV SÜD PSB Pte Ltd Electrical & Electronics Centre (EE No. 1 Science Park Drive, Singapo	EC), Product Services, pre 118221	
FCC REG. NO.	99142 (3m and 10m Semi-Anechoid	c Chamber, Science Park	<)
IND. CANADA REG. NO.	2932I-1 (3m and 10m Semi-Anecho	oic Chamber, Science Pa	rk)
PREPARED FOR	Motorola Solutions Malaysia Sdn E Plot 2, Technoplex Industrial Park Medan Bayan Lepas, Bayan Lepas 11900 Bayan Lepas, Pulau Penan Malaysia Tel : +604 2528543	3hd Mukim 12 Swd, s Industrial Park, g, Fax : +604 850309	9
QUOTATION NUMBER	2191028611		•
JOB NUMBER	7191124732		
TEST PERIOD	18 Aug 2015 – 22 Oct 2015		
PREPAR	ED BY	APPROVED BY	
Higher Associa	ite Engineer		



TÜV SÜD PSB Laboratory: TÜV SÜD PSB Pte. Ltd. No.1 Science Park Drive Singapore 118221

Phone : +65-6885 1333 Fax : +65-6776 8670 E-mail: testing@tuv-sud-psb.sg www.tuv-sud-psb.sg Co. Reg : 199002667R

Regional Head Office: TÜV SÜD Asia Pacific Pte. Ltd. 3 Science Park Drive, #04-01/05 The Franklin, Singapore 118223 TÜV®



TABLE OF CONTENTS

TEST SUMMARY	4
PRODUCT DESCRIPTION	7
SUPPORTING EQUIPMENT DESCRIPTION	9
EUT OPERATING CONDITIONS	10
RADIATED EMISSION TEST	11
SPECTRUM BANDWIDTH (6dB and 99% BANDWIDTH MEASUREMENT) TEST	19
MAXIMUM PEAK POWER TEST	58
RF CONDUCTED SPURIOUS EMISSIONS (NON-RESTRICTED BANDS) TEST	61
RF CONDUCTED SPURIOUS EMISSIONS (RESTRICTED BANDS) TEST	96
BAND EDGE COMPLIANCE (CONDUCTED) TEST	. 198
BAND EDGE COMPLIANCE (RADIATED) TEST	. 212
PEAK POWER SPECTRAL DENSITY TEST	. 223
ANNEX A TEST SETUP / EUT PHOTOGRAPHS / DIAGRAMS	. 245
ANNEX B USER MANUALTECHNICAL DESCRIPTION BLOCK & CIRCUIT DIAGRAMS	. 253
ANNEX C FCC, IC LABEL & POSITION	. 254
ANNEX D TEST SITE DESCRIPTION	. 256



The product was tested in accordance with the customer's specifications.

Test Results Summary

Test Standard	Description	Pass / Fail		
47 CFR FCC Part 15 and RS	S-GEN Issue 4: 2014 and RSS-247 Issue 1: 20)15		
15.207 RSS-GEN 8.8	Conducted Emissions	Not Applicable * ^{See Note 4}		
15.205, 15.209 RSS-GEN 8.9, 8.10	Radiated Emissions (Spurious Emissions inclusive Restricted Bands Requirement)	Pass		
15.247(a)(2) RSS-247 5.2(1)	Spectrum Bandwidth (6dB and 99% Bandwidth Measurement)	Pass *See Note 11		
15.247(b)(3) RSS-247 5.4(4)	Maximum Peak Power	Pass		
15.247(d) RSS-247 5.5	RF Conducted Spurious Emissions (Non- Restricted Bands)	Pass * ^{See Note 11}		
15.247(d) RSS-247 5.5	RF Conducted Spurious Emissions (Restricted Bands)	Pass *See Note 11		
15.247(d) RSS-247 5.5	Band Edge Compliance (Conducted)	Pass *See Note 11		
15.247(d) RSS-247 5.5	Band Edge Compliance (Radiated)	Pass		
15.247(e) RSS-247 5.2(2)	Peak Power Spectral Density	Pass * ^{See Note 11}		



TEST SUMMARY

Notes

1. The channels as listed below, under the different configurations were tested for 802.11b WLAN.

Transmit Channel	Frequency (GHz)	Modulation	Data Rate
Channel 1 (Lower Channel)	2.412	DBPSK	1Mbps
Channel 6 (Middle Channel)	2.437	DBPSK	1Mbps
Channel 11 (Upper Channel)	2.462	DBPSK	1Mbps
Channel 1 (Lower Channel)	2.412	DQPSK	2Mbps
Channel 6 (Middle Channel)	2.437	DQPSK	2Mbps
Channel 11 (Upper Channel)	2.462	DQPSK	2Mbps
Channel 1 (Lower Channel)	2.412	CCK	11Mbps
Channel 6 (Middle Channel)	2.437	CCK	11Mbps
Channel 11 (Upper Channel)	2.462	CCK	11Mbps

2. The channels as listed below, under the different configurations were tested for 802.11g WLAN.

Transmit Channel	Frequency (GHz)	Modulation	Data Rate
Channel 1 (Lower Channel)	2.412	BPSK	9Mbps
Channel 6 (Middle Channel)	2.437	BPSK	9Mbps
Channel 11 (Upper Channel)	2.462	BPSK	9Mbps
Channel 1 (Lower Channel)	2.412	QPSK	18Mbps
Channel 6 (Middle Channel)	2.437	QPSK	18Mbps
Channel 11 (Upper Channel)	2.462	QPSK	18Mbps
Channel 1 (Lower Channel)	2.412	16QAM	36Mbps
Channel 6 (Middle Channel)	2.437	16QAM	36Mbps
Channel 11 (Upper Channel)	2.462	16QAM	36Mbps
	NOOD .		
Channel 1 (Lower Channel)	2.412	64QAM	54Mbps
Channel 6 (Middle Channel)	2.437	64QAM	54Mbps
Channel 11 (Upper Channel)	2.462	64QAM	54Mbps

3. The channels as listed below, under the different configurations were tested for 802.11n WLAN.

Transmit Channel	Frequency (GHz)	Modulation	Data Rate
Channel 1 (Lower Channel)	2.412	BPSK	6.5Mbps
Channel 6 (Middle Channel)	2.437	BPSK	6.5Mbps
Channel 11 (Upper Channel)	2.462	BPSK	6.5Mbps
Channel 1 (Lower Channel)	2.412	QPSK	19.5Mbps
Channel 6 (Middle Channel)	2.437	QPSK	19.5Mbps
Channel 11 (Upper Channel)	2.462	QPSK	19.5Mbps
Channel 1 (Lower Channel)	2.412	16QAM	39Mbps
Channel 6 (Middle Channel)	2.437	16QAM	39Mbps
Channel 11 (Upper Channel)	2.462	16QAM	39Mbps
Channel 1 (Lower Channel)	2.412	64QAM	65Mbps
Channel 6 (Middle Channel)	2.437	64QAM	65Mbps
Channel 11 (Upper Channel)	2.462	64QAM	65Mbps



TEST SUMMARY

Notes (continued)

- 2. The EUT is a Class B device when in non-transmitting state and meets the 47 CFR FCC Part15B Class B requirements.
- 3. All test measurement procedures are according to ANSI C63.4: 2014, ANSI C63.10: 2013 and KDB 558074 D01 DTS Measurement Guidance V03R03.
- 4. The Equipment Under Test (EUT) is a battery operated device / DC operated device and contains no provision for public utility connections. The Equipment Under Test (EUT) will be powered off and not operational during the charging mode.
- 5. The EUT was tested using fully charged batteries with DC voltage of 7.45V.
- 6. RSS-102 is RSS-102 Issue 4: 2015.
- 7. The unit was also investigated for inter-modulation products between the co-located WiFi and the land mobile radios. All inter-modulation products between the co-located radios were found to be compliant to the FCC limits of 15.209 and Industry Canada RSS-GEN.
- 8. The EUT uses a -4dBi internal PIFA which connects to the RF port via a spring contact. The EUT meets the requirement of FCC 15.203.
- 9. The maximum measured RF power of the Equipment Under Test is 14.20dBm.
- 10. All tests except Maximum Peak Power and Band Edge Compliance (Radiated) were tested at the maximum power of the RF module which is higher than the supported maximum EUT RF power. The Maximum Peak Power and Band Edge Compliance (Radiated) tests were tested at the maximum RF power of the EUT.
- 11. Conducted data reuse from FCC ID : AZ489FT7065 & IC : 109U-89FT7065 (7191121792-EEC15).

Modifications

No modifications were made.



PRODUCT DESCRIPTION

Description	:	The Equipment Under Test (EUT) is a HANDHELD RADIO.
Manufacturer	:	Motorola Solutions Malaysia Sdn Bhd Plot 2, Technoplex Industrial Park Mukim 12 Swd, Medan Bayan Lepas, Bayan Lepas Industrial Park, 11900 Bayan Lepas, Pulau Penang, Malaysia
Model Number	:	AAH56JDN9RA1AN
FCC ID	:	AZ489FT7066
IC	:	109U-89FT7066
Serial Number	/	871TRTT159 (RF Radiated Radio) 871TRP0174 (RF Conducted Radio)(Data from FCC ID : AZ489FT7065 & IC : 109U-89FT7065)
Microprocessor	:	TI OMAPL138BZCEA3R
Operating / Transmitting Frequency	:	<u>Bluetooth / Bluetooth LE</u> 2.402GHz (lower channel) to 2.480GHz (upper channel) 79 channels (Bluetooth), 40 channels (Bluetooth LE)
		<u>WiFi</u> 2.412GHz (lower channel) to 2.462GHz (upper channel) 11 channels
		Land Mobile 136MHz to 174MHz / Channel Spacing 12.5kHz/25kHz
Clock / Oscillator Frequency	:	Reference Clock: 38.4MHz , LO: 806MHz - 1054MHz
Modulation	:	Bluetooth Gaussian Frequency Shift Keying (GFSK) (π/4) DQPSK 8DPSK
		WiFi Differential Binary Phase Shift Keying (DBPSK) Differential Quadrature Phase Shift Keying (DQPSK) Complementary Code Keying (CCK) Binary Phase Shift Keying (BPSK) Quadrature Phase Shift Keying (QPSK) 16-Quadrature Amplitude Modulation (16QAM) 64-Quadrature Amplitude Modulation (64QAM)
		Land Mobile Frequency Modulation (FM)
Antenna Gain	:	-4.0 dBi (PIFA Antenna)
		PRODUCT DESCRIPTION
		Motorola Solutions Malavsia Sdn Bhd Page 7 of 258

Test Report No. 7191124732-EEC15/02 dated 11 Dec 2015



(Continued)

Port / Connectors

Rated Input Power

Accessories

- : 7.4Vdc 20.7Wh 2800mAh Lithium ION battery
- : Refer to manufacturer's user manual / operating manual

: Refer to manufacturer's user manual / operating manual





SUPPORTING EQUIPMENT DESCRIPTION

Equipment Description (Including Brand Name)	Model, Serial & FCC ID Number	Cable Description (List Length, Type & Purpose)
Fujitsu Laptop	M/N: S6310	Nil
	S/N: R7100269	
	FCC ID: DoC	
Fujitsu AC Adapter	M/N: CP293662-01	1.80m unshielded power cable
	S/N: O6X00399B	
	FCC ID: DoC	
Microsoft Wheel Mouse	M/N: X08-71118	Nil
	S/N: Nil	
	FCC ID: DoC	





EUT OPERATING CONDITIONS

47 CFR FCC Part 15 and RSS-GEN Issue 4 and RSS-247 Issue 1

- 1. Radiated Emissions (Spurious Emissions inclusive Restricted Bands Requirement)
- 2. Spectrum Bandwidth (6dB Bandwidth Measurement)
- 3. Maximum Peak Power
- 4. RF Conducted Spurious Emissions Emission (Non-Restricted Bands)
- 5. RF Conducted Spurious Emissions Emission (Restricted Bands)
- 6. Band Edge Compliance (Conducted)
- 7. Band Edge Compliance (Radiated)
- 8. Peak Power Spectral Density

The EUT was exercised by operating in maximum continuous transmission in test mode, i.e transmitting at lower, middle and upper channels respectively at one time.





47 CFR FCC Part 15.205 and RSS-GEN 8.10 Restricted Bands

ľ	MHz			MHz			MHz			GHz	
0.090	-	0.110	16.42	-	16.423	399.9	-	410	4.5	-	5.15
0.495	-	0.505	16.69475	-	16.69525	608	-	614	5.35	-	5.46
2.1735	-	2.1905	16.80425	-	16.80475	960	-	1240	7.25	-	7.75
4.125	-	4.128	25.5	-	25.67	1300	-	1427	8.025	-	8.5
4.17725	-	4.17775	37.5	-	38.25	1435	-	1626.5	9.0	-	9.2
4.20725	-	4.20775	73	-	74.6	1645.5	-	1646.5	9.3	-	9.5
6.215	-	6.218	74.8	-	75.2	1660	-	1710	10.6	-	12.7
6.26775	-	6.26825	108	-	121.94	1718.8	-	1722.2	13.25	-	13.4
6.31175	-	6.31225	123	-	138	2200	-	2300	14.47	-	14.5
8.291	-	8.294	149.9	-	150.05	2310	-	2390	15.35	-	16.2
8.362	-	8.366	156.52475	1-	156.52525	2483.5		2500	17.7	-	21.4
8.37625	-	8.38675	156.7	-	156.9	2690	1	2900	22.01	-	23.12
8.41425	-	8.41475	162.0125	-	167.17	3260		3267	23.6	-	24.0
12.29	-	12.293	167.72	-	173.2	3332	-	3339	31.2	-	31.8
12.51975	-	12.52025	240	- 1	285	3345.8	-	3358	36.43	-	36.5
12.57675	-	12.57725	322		335.4	3600	-	4400	Ab	ove 3	8.6
13.36	-	13.41		1							

47 CFR FCC Part 15.209 and RSS-GEN 8.9 Radiated Emission Limits

Frequency Range (MHz)	Quasi-Peak Limit Values (dBµV/m)		
0.009 - 0.490	20 log [2400 / F (kHz)] @ 300m		
0.490 - 1.705	20 log [24000 / F (kHz)] @ 30m		
1.705 - 30.0	30.0 @ 30m		
30 - 88	40.0 @ 3m		
88 - 216	43.5 @ 3m		
216 - 960	46.0 @ 3m		
Above 960	54.0* @ 3m		
* For frequency bands 9kHz - 90kHz, 110kHz - 490kHz and above 1GHz, average detector wa			
peak limit of 20dB above the average limit does apply.			

47 CFR FCC Part 15.209, RSS-GEN 8.9 and 8.10 Radiated Emission Test Instrumentation

Instrument	Model	S/No	Cal Due Date	Cal Interval
R&S Test Receiver – ESI1	ESI40	100010	14 Jul 2016	1 year
Schaffner Bilog Antenna –(30MHz-2GHz) BL3 (Ref)	CBL6112D	2549	29 Jan 2016	1 year
ETS Horn Antenna(18GHz-40GHz)(Ref)	3116	0004-2474	02 Oct 2016	1 year
EMCO Horn Antenna(1GHz-18GHz)	3115	0003-6088	20 Apr 2016	1 year
R&S Preamplifier (1GHz -18GHz)	SCU18	102191	13 Mar 2016	1 year
Agilent Preamplifier(1GHz-26.5GHz) (PA18)	8449D	3008A02305	06 Oct 2016	1 year
Com-Power Preamplifier (1MHz-1GHz)	PAM-103	441096	13 Oct 2016	1 year
Micro-Tronics Bandstop Filter (2.4-2.5 GHz)	BRM50701	017	13 Aug 2016	1 year



47 CFR FCC Part 15.209, RSS-GEN 8.9 and 8.10 Radiated Emission Test Setup

- The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m X 1.0m X 0.8m high, non-metallic table. For >1GHz measurements, the EUT is raised 1. further to a height of 1.5m with a non-metallic foam block. The filtered power supply for the EUT and supporting equipment were tapped from the appropriate
- 2. power sockets located on the turntable.
- The relevant broadband antenna was set at the required test distance away from the EUT and 3. supporting equipment boundary.

47 CFR FCC Part 15.209, RSS-GEN 8.9 and 8.10 Radiated Emission Test Method

- The EUT was switched on and allowed to warm up to its normal operating condition. 1.
- 2. A prescan was carried out to pick the worst emission frequencies from the EUT. For EUT which is a portable device, the prescan was carried out by rotating the EUT through three orthogonal axes to determine which altitude and equipment arrangement produces such emissions.
- The test was carried out at the selected frequency points obtained from the prescan in step 2. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: 3.
 - Vertical or horizontal polarisation (whichever gave the higher emission level over a full rotation a. of the EUT) was chosen.
 - The EUT was then rotated to the direction that gave the maximum emission. b.
 - Finally, the antenna height was adjusted to the height that gave the maximum emission.
- A Quasi-peak measurement was made for that frequency point if it was less than or equal to 1GHz. For 4. frequency point in the range of 9kHz - 90kHz, 110kHz - 490kHz and above 1GHz, both Peak and Average measurements were carried out.
- 5. Steps 3 and 4 were repeated for the next frequency point, until all selected frequency points were measured.
- The frequency range covered was from the lowest radio frequency signal generated from the EUT, without going below 9kHz to 10th harmonics of the EUT fundamental frequency, using the loop antenna 6. for frequency below 30MHz, Bi-log antenna for frequencies from 30MHz up to 1GHz, and the Horn antenna above 1GHz.

Sample Calculation Example

At 300 MHz	Q-P limit (Class B) = 46.0 dB μ V/m
Log-periodic antenna factor & cable loss at 300 MHz =	18.5 dB
Q-P reading obtained directly from EMI Receiver = 40.0 (Calibrated level inclu	0 dB μ V/m ding antenna factors & cable losses)
Therefore, Q-P margin = 46.0 - 40.0 = 6.0	i.e. 6.0 dB below Q-P limit



47 CFR FCC Part 15.205, 15.209 and RSS-GEN 8.9 and 8.10 Radiated Emission Results

Test Input Power	7.4Vdc	Temperature	24°C
Test Distance	3m (≥30MHz –25GHz)	Relative Humidity	60%
	802.11b @ 2Mbps (Worst)	Atmospheric Pressure	1030mbar
		Tested By	Dylan Lin

Spurious Emissions ranging from 30MHz – 1GHz								
Frequency (MHz)	Q-P Value (dBµV/m)	Q-P Limit (dBµV/m)	Q-P Margin (dB)	Height (cm)	Azimuth (Degrees)	Pol (H/V)	Channel (Worst)	
32.8630	26.6	40.0	13.4	100	84	V	1	
192.9560	28.3	43.5	15.2	100	108	Н	1	
220.4430	29.5	46.0	16.5	100	262	Н	1	
236.1490	31.5	46.0	14.5	100	236	Н	1	
659.7090	30.8	46.0	15.2	100	245	H	1	
869.5260	31.3	46.0	14.7	100	270	Н	1	

Test Input Power	7.4Vdc	Temperature	24°C
Test Distance	3m (1GHz –25GHz)	Relative Humidity	60%
	802.11b @ 2Mbps (Worst)	Atmospheric Pressure	1030mbar
		Tested By	Dylan Lin

Spurious Emissions above 1GHz - 25GHz

Freq (GHz)	Peak Value (dBµV/m)	Peak Limit (dBµV/m)	Peak Margin (dB)	AV Value (dBµV/m) *See Note 4	AV Limit (dBμV/m)	AV Margin (dB)	Height (cm)	Azimuth (Degrees)	Pol (H/V)	Ch
1.0911	48.0	74.0	26.0		54.0	6.0	400	29	V	1
1.4757	47.8	74.0	26.2		54.0	6.2	100	355	V	1
1.6679	47.6	74.0	26.4	-	54.0	6.4	200	348	V	1
1.9918	45.9	74.0	28.1		54.0	8.1	100	244	V	1
3.3479	44.8	74.0	29.2		54.0	9.2	200	32	V	1
4.9874	44.6	74.0	29.4		54.0	9.4	200	296	V	1

Freq (GHz)	Peak Value (dBµV/m)	Peak Limit (dBµV/m)	Peak Margin (dB)	AV Value (dBµV/m) *See Note 4	AV Limit (dBμV/m)	AV Margin (dB)	Height (cm)	Azimuth (Degrees)	Pol (H/V)	Ch
1.1518	47.8	74.0	26.2		54.0	6.2	300	52	V	6
1.4251	47.0	74.0	27.0		54.0	7.0	200	207	V	6
1.5364	48.7	74.0	25.3		54.0	5.3	200	241	V	6
1.6882	47.4	74.0	26.6		54.0	6.6	200	349	V	6
3.8741	42.4	74.0	31.6		54.0	11.6	200	341	V	6
4.9773	45.0	74.0	29.0		54.0	9.0	200	23	V	6



47 CFR FCC Part 15.205, 15.209 and RSS-GEN 8.9 and 8.10 Radiated Emission Results

Freq	Peak	Peak	Peak	AV	AV	AV	Height	Azimuth	Pol	Ch
(GHz)	Value	Limit	Margin	Value	Limit	Margin	(cm)	(Degrees)	(H/V)	
	(dBµV/m)	(dBµV/m)	(dB)	(dBµV/m) *See Note 4	(dBµV/m)	(aB)				
1.1518	46.8	74.0	27.2		54.0	7.2	300	45	V	11
1.4149	46.1	74.0	27.9		54.0	7.9	100	304	Н	11
1.5364	49.6	74.0	24.4		54.0	4.4	200	358	V	11
1.6578	48.5	74.0	25.5		54.0	5.5	200	358	V	11
3.9045	42.7	74.0	31.3		54.0	11.3	200	5	V	11
5.0076	43.5	74.0	30.5		54.0	10.5	100	317	V	11





47 CFR FCC Part 15.205, 15.209 and RSS-GEN 8.9 and 8.10 Radiated Emission Results

Test Input Power	7.4Vdc	Temperature	24°C
Test Distance	3m (≥30MHz –25GHz)	Relative Humidity	60%
	802.11g @ 18Mbps (Worst)	Atmospheric Pressure	1030mbar
		Tested By	Dylan Lin

Spurious Emissions ranging from 30MHz – 1GHz								
Frequency (MHz)	Q-P Value (dBµV/m)	Q-P Limit (dBµV/m)	Q-P Margin (dB)	Height (cm)	Azimuth (Degrees)	Pol (H/V)	Channel (Worst)	
51.5970	6.6	40.0	33.4	401	319	Н	1	
55.5230	18.1	40.0	21.9	100	309	V	1	
96.7530	19.2	43.5	24.3	297	155	V	1	
132.0930	14.8	43.5	28.7	198	41	V	1	
167.4330	16.0	43.5	27.5	297	327	V	1	
228.2960	15.4	46.0	30.6	297	75	V	1	

Test Input Power	7.4Vdc	Temperature	24°C
Test Distance	3m (1GHz –25GHz)	Relative Humidity	60%
	802.11g @ 18Mbps (Worst)	Atmospheric Pressure	1030mbar
		Tested By	Dylan Lin

Spurious Emissions above 1GHz - 25GHz

Freq (GHz)	Peak Value (dBμV/m)	Peak Limit (dBµV/m)	Peak Margin (dB)	AV Value (dBµV/m) *See Note 4	AV Limit (dBμV/m)	AV Margin (dB)	Height (cm)	Azimuth (Degrees)	Pol (H/V)	Ch
1.4251	46.8	74.0	27.2	· · · ·	54.0	7.2	200	216	V	1
1.5465	49.2	74.0	24.8		54.0	4.8	200	317	V	1
1.6882	47.7	74.0	26.3		54.0	6.3	200	342	V	1
1.9918	45.6	74.0	28.4		54.0	8.4	200	292	V	1
3.3378	44.2	74.0	29.8		54.0	9.8	200	6	V	1
4.9975	43.5	74.0	30.5		54.0	10.5	100	317	V	1

Freq (GHz)	Peak Value (dBµV/m)	Peak Limit (dBµV/m)	Peak Margin (dB)	AV Value (dBμV/m) _* See Note 4	AV Limit (dBμV/m)	AV Margin (dB)	Height (cm)	Azimuth (Degrees)	Pol (H/V)	Ch
1.0911	46.2	74.0	27.8		54.0	7.8	400	20	V	6
1.1619	47.3	74.0	26.7		54.0	6.7	100	312	Н	6
1.5364	48.2	74.0	25.8		54.0	5.8	200	333	V	6
1.6679	48.8	74.0	25.2		54.0	5.2	200	6	V	6
2.0019	44.5	74.0	29.5		54.0	9.5	200	292	V	6
4.9570	43.0	74.0	31.0		54.0	11.0	200	32	V	6



47 CFR FCC Part 15.205, 15.209 and RSS-GEN 8.9 and 8.10 Radiated Emission Results

Peak									
Value (dBμV/m)	Peak Limit (dBµV/m)	Peak Margin (dB)	AV Value (dBμV/m) *See Note 4	AV Limit (dBμV/m)	AV Margin (dB)	Height (cm)	Azimuth (Degrees)	Pol (H/V)	Ch
46.9	74.0	27.1		54.0	7.1	400	35	V	11
47.3	74.0	26.7		54.0	6.7	200	308	V	11
48.1	74.0	25.9		54.0	5.9	200	323	V	11
45.7	74.0	28.3		54.0	8.3	200	282	V	11
42.3	74.0	31.7		54.0	11.7	100	0	V	11
42.4	74.0	31.6		54.0	11.6	200	23	V	11
	Value (dBµV/m) 46.9 47.3 48.1 45.7 42.3 42.4	Value (dBμV/m) Limit (dBμV/m) 46.9 74.0 47.3 74.0 48.1 74.0 45.7 74.0 42.3 74.0	Value (dBμV/m)Limit (dBμV/m)Margin (dB)46.974.027.147.374.026.748.174.025.945.774.028.342.374.031.742.474.031.6	Value (dB μ V/m)Limit (dB μ V/m)Margin (dB)Value (dB μ V/m) *See Note 446.974.027.147.374.026.748.174.025.945.774.028.342.374.031.742.474.031.6	$\begin{array}{c c c c c c c c c c c c c c c c c c c $	$\begin{array}{c c c c c c c c c c c c c c c c c c c $	$\begin{array}{c c c c c c c c c c c c c c c c c c c $	$\begin{array}{c c c c c c c c c c c c c c c c c c c $	$ \begin{array}{c c c c c c c c c c c c c c c c c c c $





47 CFR FCC Part 15.205, 15.209 and RSS-GEN 8.9 and 8.10 Radiated Emission Results

Test Input Power	7.4Vdc	Temperature	24°C
Test Distance	3m (≥30MHz –25GHz)	Relative Humidity	60%
	802.11n @ 65Mbps (Worst)	Atmospheric Pressure	1030mbar
		Tested By	Dylan Lin

Spurious Emiss	Spurious Emissions ranging from 30MHz – 1GHz									
Frequency (MHz)	Q-P Value (dBµV/m)	Q-P Limit (dBµV/m)	Q-P Margin (dB)	Height (cm)	Azimuth (Degrees)	Pol (H/V)	Channel (Worst)			
49.6330	18.8	40.0	21.2	100	326	V	1			
96.7530	19.9	43.5	23.6	199	9	V	1			
167.4330	16.2	43.5	27.3	299	317	V	1			
228.2960	14.6	46.0	31.4	401	71	V	1			
285.2320	16.8	46.0	29.2	100	100	V	1			
434.4450	25.5	46.0	20.5	401	99	н	1			

Test Input Power	7.4Vdc	Temperature	24°C
Test Distance	3m (1GHz –25GHz)	Relative Humidity	60%
	802.11n @ 65Mbps (Worst)	Atmospheric Pressure	1030mbar
		Tested By	Dylan Lin

Spurious Emissions above 1GHz - 25GHz

Freq (GHz)	Peak Value (dBµV/m)	Peak Limit (dBµV/m)	Peak Margin (dB)	AV Value (dBµV/m) *See Note 4	AV Limit (dBμV/m)	AV Margin (dB)	Height (cm)	Azimuth (Degrees)	Pol (H/V)	Ch
1.1518	46.1	74.0	27.9	· · · ·	54.0	7.9	100	68	Н	1
1.4251	46.7	74.0	27.3		54.0	7.3	100	330	V	1
1.4757	47.4	74.0	26.6		54.0	6.6	200	324	V	1
1.6882	47.6	74.0	26.4		54.0	6.4	200	350	V	1
2.0019	45.3	74.0	28.7		54.0	8.7	200	283	V	1
4.9570	42.6	74.0	31.4		54.0	11.4	200	32	V	1

Freq (GHz)	Peak Value (dBµV/m)	Peak Limit (dBµV/m)	Peak Margin (dB)	AV Value (dBμV/m) *See Note 4	AV Limit (dBμV/m)	AV Margin (dB)	Height (cm)	Azimuth (Degrees)	Pol (H/V)	Ch
1.1518	46.7	74.0	27.3		54.0	7.3	400	53	V	6
1.4757	48.3	74.0	25.7		54.0	5.7	100	346	V	6
1.5364	47.4	74.0	26.6		54.0	6.6	200	14	V	6
1.9918	43.6	74.0	30.4		54.0	10.4	300	96	V	6
3.3277	41.6	74.0	32.4		54.0	12.4	200	39	V	6
4.9570	42.9	74.0	31.1		54.0	11.1	200	31	V	6



47 CFR FCC Part 15.205, 15.209 and RSS-GEN 8.9 and 8.10 Radiated Emission Results

Freq (GHz)	Peak Value (dBµV/m)	Peak Limit (dBµV/m)	Peak Margin (dB)	AV Value (dBµV/m) *See Note 4	AV Limit (dBμV/m)	AV Margin (dB)	Height (cm)	Azimuth (Degrees)	Pol (H/V)	Ch
1.5465	47.7	74.0	26.3		54.0	6.3	300	271	V	11
1.6679	48.6	74.0	25.4		54.0	5.4	200	350	V	11
1.9918	46.6	74.0	27.4		54.0	7.4	100	300	V	11
3.2973	42.6	74.0	31.4		54.0	11.4	200	6	V	11
3.8843	42.1	74.0	31.9		54.0	11.9	200	358	V	11
4.9773	44.5	74.0	29.5		54.0	9.5	200	15	V	11

Spurious Emissions above 1GHz - 25GHz

<u>Notes</u>

- 1. All possible modes of operation were investigated. Only the worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.
- 2. Quasi-peak measurement was used for frequency measurement up to 1GHz. Average and peak measurements were used for emissions above 1GHz. The average measurement was done by averaging over a complete cycle of the pulse train, including the blanking interval as the pulse train duration does not exceed 0.1 second.
- 3. A "positive" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency. Conversely, a "negative" margin indicates a FAIL.
- 4. As the measured peak shows compliance to the average limits, as such no average measurements was carried out. The EUT is deemed to meet both requirements.
- 5. EMI receiver Resolution Bandwidth (RBW) and Video Bandwidth (VBW) settings:

30MHz - 1GHz	
RBW: 100kHz	VBW: 1MHz
<u>>1GHz</u>	
RBW: 1MHz	VBW: 3MHz

- 6. The upper frequency of radiated emission investigations was according to requirements stated in Section 15.33(a) for intentional radiators & Section 15.33(b) for unintentional radiators.
- 7. The upper frequency of radiated emission investigations was according to requirements stated in RSS-GEN 6.13.
- 8. The channel in the table refers to the transmit channel of the EUT.
- <u>Radiated Emissions Measurement Uncertainty</u> All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95%, with a coverage factor of 2, in the range 30MHz – 25GHz is ±4.0dB.



47 CFR FCC Part 15.247(a)(2) and RSS-247 5.2(1) Spectrum Bandwidth (6dB and 99% Bandwidth Measurement) Limits

The EUT shows compliance to the requirements of this section, which states that the minimum bandwidth of the EUT employing digital modulation techniques shall be at least 500kHz.

47 CFR FCC Part 15.247(a)(2) and RSS-247 5.2(1) Spectrum Bandwidth (6dB and 99% Bandwidth Measurement) Test Instrumentation

Instrument	Model	S/No	Cal Due Date	Cal Interval
Agilent Spectrum Analyzer	E4440A	MY45304764	12 Dec 2015	1 year

<u>47 CFR FCC Part 15.247(a)(2) and RSS-247 5.2(1) Spectrum Bandwidth (6dB and 99% Bandwidth Measurement) Test Setup</u>

- 1. The EUT and supporting equipment were set up as shown in the setup photo.
- 2. The power supply for the EUT was connected to a filtered mains.
- 3. The RF antenna connector was connected to the spectrum analyser via a low-loss coaxial cable.
- 4. The resolution bandwidth (RBW) and the video bandwidth (VBW) of the spectrum analyser were respectively set to the following: RBW = 100kHz VBW = 3 times RBW
- 5. All other supporting equipment were powered separately from another filtered mains.

47 CFR FCC Part 15.247(a)(2) and RSS-247 5.2(1) Spectrum Bandwidth (6dB and 99% Bandwidth Measurement) Test Method

- 1. The EUT was switched on and allowed to warm up to its normal operating condition. The EUT was then configured to operate in the test mode at lower channel.
- 2. The center frequency of the spectrum analyser was set to the transmitting frequency with the frequency span wide enough to capture the 6dB and 99% bandwidth of the transmitting frequency.
- 3. The spectrum analyser was set to max hold to capture the transmitting frequency. The signal capturing was continuous until no further changes were observed.
- 4. The peak of the transmitting frequency was detected with the marker peak function of the spectrum analyser. For 6dB bandwidth measurement, the frequencies below the 6dB peak frequency at lower (f_L) and upper (f_H) sides of the transmitting frequency were marked and measured by using the marker-delta function of the spectrum analyser. For 99% bandwidth measurement, the spectrum analyser power measurement was activated with bandwidth measurement as 99%.
- 5. For 6dB bandwidth measurement, the 6dB bandwidth of the transmitting frequency is the frequency difference between the marked lower and upper frequencies, $|f_H f_L|$. For 99% bandwidth measurement, the measured 99% bandwidth shown on the spectrum analyser was recorded.
- 6. The steps 2 to 5 were repeated with the transmitting frequency was set to middle and upper channel respectively.



47 CFR FCC Part 15.247(a)(2) and RSS-247 5.2(1) Spectrum Bandwidth (6dB and 99% Bandwidth **Measurement) Results**

Test Input Power	7.4Vdc	Temperature	24°C
		Relative Humidity	60%
		Atmospheric Pressure	1030mbar
		Tested By	Liau Lee Yin

802.11b

	Channel Frequency (GHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Modulation @ Data Rate
	_	10.125	13.369	DBPSK @ 1Mbps
1 (lower ch)	2.412	9.938	13.566	DQPSK @ 2Mbps
		9.438	13.640	CCK @ 11Mbps
		10.170	13.533	DBPSK @ 1Mbps
6 (<i>mid ch</i>)	2.437	9.960	13.555	DQPSK @ 2Mbps
		9.330	13.583	CCK @ 11Mbps
		10.170	13.594	DBPSK @ 1Mbps
11 <i>(upper ch)</i>	2.462	9.870	13.641	DQPSK @ 2Mbps
		9.300	13.656	CCK @ 11Mbps

802.11q

Channel	Channel Frequency (GHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Modulation @ Data Rate
1 <i>(lower ch)</i>	2.412	16.500	16.460	BPSK @ 9Mbps
		16.500	16.492	QPSK @ 18Mbps
		16.625	16.542	16QAM @ 36Mbps
		16.625	16.619	64QAM @ 54Mbps
6 (mid ch)	2.437	16.540	16.568	BPSK @ 9Mbps
		16.540	16.482	QPSK @ 18Mbps
		16.580	16.518	16QAM @ 36Mbps
		16.580	16.527	64QAM @ 54Mbps
11 (upper ch)	2.462	16.500	16.516	BPSK @ 9Mbps
		16.500	16.436	QPSK @ 18Mbps
		16.580	16.573	16QAM @ 36Mbps
		16.580	16.562	64QAM @ 54Mbps



47 CFR FCC Part 15.247(a)(2) and RSS-247 5.2(1) Spectrum Bandwidth (6dB and 99% Bandwidth Measurement) Results

Test Input Power	7.4Vdc	Temperature	24°C
		Relative Humidity	60%
		Atmospheric Pressure	1030mbar
		Tested By	Liau Lee Yin

802.11n

Channel	Channel Frequency (GHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Modulation @ Data Rate
1 (lower ch)	2.412	17.540	17.636	BPSK @ 6.5Mbps (MCS0)
		17.750	17.723	QPSK @ 19.5Mbps (MCS2)
		17.830	17.728	16QAM @ 39Mbps (MCS4)
		17.790	17.646	64QAM @ 65Mbps (MCS7)
6 (mid ch)	2.437	17.750	17.767	BPSK @ 6.5Mbps (MCS0)
		17.750	17.730	QPSK @ 19.5Mbps (MCS2)
		17.830	17.648	16QAM @ 39Mbps (MCS4)
		17.790	17.597	64QAM @ 65Mbps (MCS7)
11 (upper ch)	2.462	17.750	17.620	BPSK @ 6.5Mbps (MCS0)
		17.750	17.738	QPSK @ 19.5Mbps (MCS2)
		17.790	17.626	16QAM @ 39Mbps (MCS4)
		17.790	17.746	64QAM @ 65Mbps (MCS7)





Spectrum Bandwidth (6dB Bandwidth Measurement) Plots - 802.11b

Plot 2 - Channel 1 (lower ch) @ DQPSK 2Mbps





Spectrum Bandwidth (6dB Bandwidth Measurement) Plots - 802.11b





Spectrum Bandwidth (6dB Bandwidth Measurement) Plots - 802.11g



Plot 5 - Channel 1 (lower ch) @ QPSK 18Mbps





Spectrum Bandwidth (6dB Bandwidth Measurement) Plots - 802.11g

Plot 7 - Channel 1 (lower ch) @ 64QAM 54Mbps





Spectrum Bandwidth (6dB Bandwidth Measurement) Plots - 802.11n

Plot 9 - Channel 1 (lower ch) @ QPSK 19.5Mbps





Spectrum Bandwidth (6dB Bandwidth Measurement) Plots - 802.11n







Spectrum Bandwidth (6dB Bandwidth Measurement) Plots - 802.11b

Plot 13 - Channel 6 (middle ch) @ DQPSK 2Mbps





Spectrum Bandwidth (6dB Bandwidth Measurement) Plots - 802.11b





Spectrum Bandwidth (6dB Bandwidth Measurement) Plots - 802.11g

Plot 16 - Channel 6 (middle ch) @ QPSK 18Mbps





Spectrum Bandwidth (6dB Bandwidth Measurement) Plots - 802.11g







Spectrum Bandwidth (6dB Bandwidth Measurement) Plots - 802.11n

Plot 20 - Channel 6 (middle ch) @ QPSK 19.5Mbps





Spectrum Bandwidth (6dB Bandwidth Measurement) Plots - 802.11n

Plot 22 - Channel 6 (middle ch) @ 64QAM 65Mbps





Spectrum Bandwidth (6dB Bandwidth Measurement) Plots - 802.11b







Spectrum Bandwidth (6dB Bandwidth Measurement) Plots - 802.11b





Spectrum Bandwidth (6dB Bandwidth Measurement) Plots - 802.11g

Plot 27 - Channel 11 (upper ch) @ QPSK 18Mbps




Spectrum Bandwidth (6dB Bandwidth Measurement) Plots - 802.11g

Plot 29 - Channel 11 (upper ch) @ 64QAM 54Mbps





Spectrum Bandwidth (6dB Bandwidth Measurement) Plots - 802.11n

Plot 31 - Channel 11 (upper ch) @QPSK 19.5Mbps





Spectrum Bandwidth (6dB Bandwidth Measurement) Plots - 802.11n

Plot 33 - Channel 11 (upper ch) @ 64QAM 65Mbps





Spectrum Bandwidth (99% Bandwidth Measurement) Plots - 802.11b

Plot 35 - Channel 1 (lower ch) @ DQPSK 2Mbps



K Agilent 15:24:36 24 Aug 2015	Freq/Channel
Ch Freq 2.412 GHz Trig Free	Center Freq 2.41200000 GHz
Center 2.412000000 GHz	Start Freq 2.40000000 GHz
Ref 20 dBm Atten 30 dB 7.64 dBm Peak	Stop Freq 2.42400000 GHz
$\begin{array}{c c c c c c c c c c c c c c c c c c c $	CF Step 2.40000000 MHz Auto Mar
Center 2.412 00 GHz Span 24 MHz	Freq Offset
Res BW 240 kHz VBW 750 kHz Sweep 1 ms (601 pts) Occupied Bandwidth Occ BW % Pwr 99.00 % 100 C 100 dB 0 cc BW % Pwr 99.00 %	Signal Track On <u>Off</u>
13.b401 MHz X ub -20.00 ub A Transmit Freq Error -4.073 kHz x ub -20.00 ub x x dB Bandwidth 15.229 MHz*	
File Operation Status, A:\SCREN897.GIF file saved	
SÜD	

Spectrum Bandwidth (99% Bandwidth Measurement) Plots - 802.11b





Spectrum Bandwidth (99% Bandwidth Measurement) Plots - 802.11g

Plot 38 - Channel 1 (lower ch) @ QPSK 18Mbps





Spectrum Bandwidth (99% Bandwidth Measurement) Plots - 802.11g







Spectrum Bandwidth (99% Bandwidth Measurement) Plots - 802.11n

Plot 42 - Channel 1 (lower ch) @ QPSK 19.5Mbps





Spectrum Bandwidth (99% Bandwidth Measurement) Plots - 802.11n

Plot 44 - Channel 1 (lower ch) @ 64QAM 65Mbps





Spectrum Bandwidth (99% Bandwidth Measurement) Plots - 802.11b

Plot 46 - Channel 6 (middle ch) @ DQPSK 2Mbps



eq/Channel
Center Freq 43700000 GHz
Start Freq 42500000 GHz
Stop Freq 44900000 GHz
CF Step 40000000 MHz to Man
- FreqOffset .00000000 Hz
Signal Track Off

Spectrum Bandwidth (99% Bandwidth Measurement) Plots - 802.11b





Spectrum Bandwidth (99% Bandwidth Measurement) Plots - 802.11g







Spectrum Bandwidth (99% Bandwidth Measurement) Plots - 802.11g

Plot 51 - Channel 6 (middle ch) @ 64QAM 54Mbps





Spectrum Bandwidth (99% Bandwidth Measurement) Plots - 802.11n

Plot 53 - Channel 6 (middle ch) @ QPSK 19.5Mbps





Spectrum Bandwidth (99% Bandwidth Measurement) Plots - 802.11n

Plot 55 - Channel 6 (middle ch) @ 64QAM 65Mbps





Spectrum Bandwidth (99% Bandwidth Measurement) Plots - 802.11b

Plot 57 - Channel 11 (upper ch) @ DQPSK 2Mbps



Agilent 15:24:03 24 Aug 2015	Marker
Ch Freq 2.462 GHz Trig Free	Select Marker 1 <u>2</u> 3 4
Marker 2.462000000 GHz	Normal
ef 20 dBm Atten 30 dB 7.68 dBm Peak 7.68 dBm	Delta
	Delta Pair (Tracking Ref) Ref ∆
Center 2.462 00 GHz Span 24 MHz	Span Pair Span <u>Center</u>
Res BW 240 kHz VBW 750 kHz Sweep 1 ms (601 pts) Occupied Bandwidth Occ BW % Pwr 99.00 % 40 ccccc 40 ccccc 40 ccccc	Off
13.0500/MHZ Transmit Freq Error –22.280 kHz x dB Bandwidth 15.229 MHz*	More 1 of 2
Plot 58 - Channel 11 (upper ch) @ CCK 11Mbp:	S

Spectrum Bandwidth (99% Bandwidth Measurement) Plots - 802.11b





Spectrum Bandwidth (99% Bandwidth Measurement) Plots - 802.11g







Spectrum Bandwidth (99% Bandwidth Measurement) Plots - 802.11g

Plot 62 - Channel 11 (upper ch) @ 64QAM 54Mbps





Spectrum Bandwidth (99% Bandwidth Measurement) Plots - 802.11n







Spectrum Bandwidth (99% Bandwidth Measurement) Plots - 802.11n





MAXIMUM PEAK POWER TEST

47 CFR FCC Part 15.247(b)(3) and RSS-247 5.4(4) Maximum Peak Power Limits

The EUT shows compliance to the requirements of this section, which states the maximum peak power of the EUT employing digital modulation shall not exceed 1W (30dBm).

47 CFR FCC Part 15.247(b)(3) and RSS-247 5.4(4) Maximum Peak Power Test Instrumentation

Instrument	Model	S/No	Cal Due Date	Cal Interval
Boonton Electronics RF Power Meter	4532	72901	27 Aug 2016	1 year
Boonton Electronics Peak Power Sensor	56218-S/1	1417	27 Aug 2016	1 year

47 CFR FCC Part 15.247(b)(3) and RSS-247 5.4(4) Maximum Peak Power Test Setup

- 1. The EUT and supporting equipment were set up as shown in the setup photo.
- 2. The power supply for the EUT was connected to a filtered mains.
- 3. The RF antenna connector was connected to the power meter.
- 4. All other supporting equipment were powered separately from another filtered mains.

47 CFR FCC Part 15.247(b)(3) and RSS-247 5.4(4) Maximum Peak Power Test Method

- 1. The EUT was switched on and allowed to warm up to its normal operating condition. The EUT was then configured to operate in the test mode at lower channel with specified modulation and data rate.
- 2. The maximum peak power of the transmitting frequency was detected and recorded.
- 3. Repeat steps 1 to 2 with all possible modulations and data rates.
- 4. The steps 2 to 3 were repeated with the transmitting frequency was set to middle and upper respectively.



MAXIMUM PEAK POWER TEST

47 CFR FCC Part 15.247(b)(3) and RSS-247 5.4(4) Maximum Peak Power Results

Test Input Power	7.4Vdc	Temperature	24°C
Antenna Gain	-4.0 dBi	Relative Humidity	60%
		Atmospheric Pressure	1030mbar
		Tested By	Liau Lee Yin

802.11b

Channel	Channel Frequency (GHz)	Maximum Peak Power (W)	Limit (W)	Modulation @ Data Rate
		0.0222	1.0	DBPSK @ 1Mbps
1 (lower ch)	2.412	0.0263	1.0	DQPSK @ 2Mbps
		0.0240	1.0	CCK @ 11Mbps
		0.0092	1.0	DBPSK @ 1Mbps
6 <i>(mid ch)</i>	2.437	0.0089	1.0	DQPSK @ 2Mbps
	11	0.0090	1.0	CCK @ 11Mbps
		0.0203	1.0	DBPSK @ 1Mbps
11 (upper ch)	2.462	0.0198	1.0	DQPSK @ 2Mbps
		0.0200	1.0	CCK @ 11Mbps

Test Input Power	7.4Vdc	Temperature	24°C
Antenna Gain	-4.0 dBi	Relative Humidity	60%
		Atmospheric Pressure	1030mbar
		Tested By	Liau Lee Yin
000.44 ~		SLID	

802.11a

Channel	Channel Frequency (GHz)	Maximum Peak Power (W)	Limit (W)	Modulation @ Data Rate
		0.0063	1.0	BPSK @ 9Mbps
1 (lowor ch)	2 /12	0.0063	1.0	QPSK @ 18Mbps
	2.412	0.0062	1.0	16QAM @ 36Mbps
		0.0057	1.0	64QAM @ 54Mbps
	0.0020	1.0	BPSK @ 9Mbps	
6 (mid ch)	6 <i>(mid ch)</i> 2.437	0.0018	1.0	QPSK @ 18Mbps
		0.0019	1.0	16QAM @ 36Mbps
		0.0018	1.0	64QAM @ 54Mbps
		0.0016	1.0	BPSK @ 9Mbps
11 (upper ch)	2 462	0.0017	1.0	QPSK @ 18Mbps
i (upper cri)	2.402	0.0019	1.0	16QAM @ 36Mbps
		0.0018	1.0	64QAM @ 54Mbps



MAXIMUM PEAK POWER TEST

47 CFR FCC Part 15.247(b)(3) and RSS-247 5.4(4) Maximum Peak Power Results

Test Input Power	7.4Vdc	Temperature	24°C
Antenna Gain	-4.0 dBi	Relative Humidity	60%
		Atmospheric Pressure	1030mbar
		Tested By	Liau Lee Yin

802.11n

Channel	Channel Frequency (GHz)	Maximum Peak Power (W)	Limit (W)	Modulation @ Data Rate
		0.0124	1.0	BPSK @ 6.5Mbps (MCS0)
1 (lower ch)	2 /12	0.0124	1.0	QPSK @ 19.5Mbps (MCS2)
	2.412	0.0126	1.0	16QAM @ 39Mbps (MCS4)
		0.0119	1.0	64QAM @ 65Mbps (MCS7)
		0.0122	1.0	BPSK @ 6.5Mbps (MCS0)
6 (mid ch) 2.437	ch) 2.437	0.0121	1.0	QPSK @ 19.5Mbps (MCS2)
		0.0107	1.0	16QAM @ 39Mbps (MCS4)
		0.0113	1.0	64QAM @ 65Mbps (MCS7)
		0.0096	1.0	BPSK @ 6.5Mbps (MCS0)
11 <i>(upper ch)</i>	2 462	0.0106	1.0	QPSK @ 19.5Mbps (MCS2)
	2.402	0.0105	1.0	16QAM @ 39Mbps (MCS4)
		0.0096	1.0	64QAM @ 65Mbps (MCS7)

<u>Notes</u>

1. Nil.



47 CFR FCC Part 15.247(d) and RSS-247 5.5 RF Conducted Spurious Emissions (Non-Restricted Bands) Limits

The EUT shows compliance to the requirements of this section, which states in any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator (EUT) is operating, the radio frequency power that is produced by the EUT shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of desired power.

47 CFR FCC Part 15.247(d) and RSS-247 5.5 RF Conducted Spurious Emissions (Non-Restricted Bands) Test Instrumentation

Instrument	Model	S/No	Cal Due Date	Cal Interval
Agilent Spectrum Analyzer	E4440A	MY45304764	12 Dec 2015	1 year

47 CFR FCC Part 15.247(d) and RSS-247 5.5 RF Conducted Spurious Emissions (Non-Restricted Bands) Test Setup

- 1. The EUT and supporting equipment were set up as shown in the setup photo.
- 2. The power supply for the EUT was connected to a filtered mains.
- 3. The RF antenna connector was connected to the spectrum analyser via a low-loss coaxial cable.
- 4. The resolution bandwidth (RBW) and the video bandwidth (VBW) of the spectrum analyser were respectively set to 100kHz and 300kHz.
- 5. All other supporting equipment were powered separately from another filtered mains.

47 CFR FCC Part 15.247(d) and RSS-247 5.5 RF Conducted Spurious Emissions (Non-Restricted Bands) Test Method

- 1. The EUT was switched on and allowed to warm up to its normal operating condition. The EUT was then configured to operate in the test mode, with the transmitting frequency was set to lower channel with specified modulation and data rate.
- 2. The start and stop frequencies of the spectrum analyser were set to 30MHz and 10GHz.
- 3. The spectrum analyser was set to max hold to capture any spurious emissions within the span. The signal capturing was continuous until no further spurious emissions were detected.
- 4. The steps 2 to 3 were repeated with frequency span was set from 10GHz to 25GHz.
- 5. Repeat steps 1 to 4 with all possible modulations and data rates.
- 6. The steps 2 to 5 were repeated with the transmitting frequency was set to middle and upper channel respectively.



47 CFR FCC Part 15.247(d) and RSS-247 5.5 RF Conducted Spurious Emissions (Non-Restricted Bands) Results

Test Input Power	7.4Vdc	Temperature	24°C
Attached Plots	67 – 84 (802.11b)	Relative Humidity	60%
	85 – 108 (802.11g)		
	109–132 (802.11n)		
		Atmospheric Pressure	1030mbar
		Tested By	Liau Lee Yin

All spurious signals found were below the specified limit. Please refer to the attached plots.







RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11b

Plot 68 – Channel 1 (lower ch) @ DBPSK 1Mbps

atus, A:\SCREN742.GIF file save





RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11b

Plot 70 – Channel 1 (lower ch) @ DQPSK 2Mbps





RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11b

Plot 72 – Channel 1 (lower ch) @ CCK 11Mbps

atus, A:\SCREN744.GIF file saved





RF Conducted Spurious Emissions (Non-Restricted Bands) Plots – 802.11b



Plot 74 – Channel 6 (middle ch) @ DBPSK 1Mbps





RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11b



VBW 300 kHz

Stop 25.000 GHz

Sweep 1.434 s (601 pts)

-52.75 dBm

Start 10.000 GHz

#Res BW 100 kHz

More

1 of 2





RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11b

Plot 78 – Channel 6 (middle ch) @ CCK 11Mbps

atus, A:\SCREN755.GIF file saved





RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11b







RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11b







RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11b

Plot 84 – Channel 11 (upper ch) @ CCK 11Mbps





RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11g



VBW 300 kHz

atus, A:\SCREN745.GIF file save

Μ1

S3 FC A AA <u>£</u>(f):

FTun

aw

Marker

Start 10.000 GHz

#Res BW 100 kHz

-52.53 dBm

24.975000000 GHz

Pk-Pk Search

Stop 25.000 GHz

Sweep 1.434 s (601 pts)

Mkr → CF

More

1 of 2




RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11g

Plot 88 – Channel 1 (lower ch) @ QPSK 18Mbps





RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11g

Plot 90 – Channel 1 (lower ch) @ 16QAM 36Mbps





RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11g

Plot 92 – Channel 1 (lower ch) @ 64QAM 54Mbps





RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11g

Plot 94 – Channel 6 (middle ch) @ BPSK 9Mbps





RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11g



VBW 300 kHz

Start 10.000 GHz

#Res BW 100 kHz

More

1 of 2

Stop 25.000 GHz

Sweep 1.434 s (601 pts)





RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11g







RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11g

Plot 100 – Channel 6 (middle ch) @ 64QAM 54Mbps

atus, A:\SCREN760.GIF file save





RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11g

Plot 102 – Channel 11 (upper ch) @ BPSK 9Mbps





RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11g

Plot 104 – Channel 11 (upper ch) @ QPSK 18Mbps





RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11g

Plot 106 – Channel 11 (upper ch) @ 16QAM 36Mbps





RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11g

Plot 108 – Channel 11 (upper ch) @ 64QAM 54Mbps





RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11n

Plot 110 – Channel 1 (lower ch) @ BPSK 6.5Mbps

Sweep 1.434 s (601 pts)

VBW 300 kHz

atus, A:\SCREN749.GIF file save

#Res BW 100 kHz





RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11n

Plot 112 - Channel 1 (lower ch) @ QPSK 19.5Mbps





RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11n

Plot 114 – Channel 1 (lower ch) @ 16QAM 39Mbps

atus, A:\SCREN751.GIF file saved





RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11n

Plot 116 – Channel 1 *(lower ch)* @ 64QAM 65Mbps





RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11n



Plot 118 – Channel 6 (middle ch) @ BPSK 6.5Mbps





RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11n

Plot 120 – Channel 6 (middle ch) @ QPSK 19.5Mbps





RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11n



Plot 122 – Channel 6 (middle ch) @ 16QAM 39Mbps





RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11n

Plot 124 – Channel 6 (middle ch) @ 64QAM 65Mbps

Status, A:\SCREN764.GIF file save





RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11n

Plot 126 – Channel 11 (upper ch) @ BPSK 6.5Mbps





RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11n

Plot 128 – Channel 11 (upper ch) @ QPSK 19.5Mbps





RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11n

Plot 130 – Channel 11 (upper ch) @ 16QAM 39Mbps





RF Conducted Spurious Emissions (Non-Restricted Bands) Plots - 802.11g

Plot 132 – Channel 11 (upper ch) @ 64QAM 65Mbps



47 CFR FCC Part 15.205 and RSS-GEN 8.10 Restricted Bands

MHz		MHz		MHz			GHz				
0.090	-	0.110	16.42	-	16.423	399.9	-	410	4.5	-	5.15
0.495	-	0.505	16.69475	-	16.69525	608	-	614	5.35	-	5.46
2.1735	-	2.1905	16.80425	-	16.80475	960	-	1240	7.25	-	7.75
4.125	-	4.128	25.5	-	25.67	1300	-	1427	8.025	-	8.5
4.17725	-	4.17775	37.5	-	38.25	1435	-	1626.5	9.0	-	9.2
4.20725	-	4.20775	73	-	74.6	1645.5	-	1646.5	9.3	-	9.5
6.215	-	6.218	74.8	-	75.2	1660	-	1710	10.6	-	12.7
6.26775	-	6.26825	108	-	121.94	1718.8	-	1722.2	13.25	-	13.4
6.31175	-	6.31225	123	-	138	2200	-	2300	14.47	-	14.5
8.291	-	8.294	149.9	-	150.05	2310	-	2390	15.35	-	16.2
8.362	-	8.366	156.52475	1-	156.52525	2483.5	h	2500	17.7	-	21.4
8.37625	-	8.38675	156.7	-	156.9	2690	1	2900	22.01	-	23.12
8.41425	-	8.41475	162.0125	-	167.17	3260		3267	23.6	-	24.0
12.29	-	12.293	167.72	-	173.2	3332	-	3339	31.2	-	31.8
12.51975	-	12.52025	240	/	285	3345.8	-	3358	36.43	-	36.5
12.57675	-	12.57725	322	-/	335.4	3600	-	4400	Above 38.6		8.6
13.36	-	13.41		1							

47 CFR FCC Part 15.247(d) and RSS-247 5.5 RF Conducted Spurious Emissions (Restricted Bands) Limits

The EUT shows compliance to the requirements of this section, which states that emissions which fall in the restricted bands must comply with the radiated emission limits specified in the table below:

Frequency Range (MHz)	EIRP (dBm)	Radiated Emissions (dBµV/m)				
0.009 - 0.490	-6.7 – (-41.4) **	67.6 – 20logF* @ 300m **				
0.490 – 1.705	-41.4 – (-52.3) **	87.6 – 20logF* @ 30m **				
1.705 – 30	-45.7	29.5 @ 30m				
30 - 88	-55.2	40.0 @ 3m				
88 - 216	-51.7	43.5 @ 3m				
216 - 960	-49.2	46.0 @ 3m				
>960	-41.2 ***	54.0 @ 3m ***				
F is frequency in kHz.						
** Decreasing linearly with the logarith	Decreasing linearly with the logarithm of the frequency.					
*** Above 1GHz, a peak limit of 20dB a	* Above 1GHz, a peak limit of 20dB above the average limit does apply.					

<u>47 CFR FCC Part 15.247(d) and RSS-247 5.5 RF Conducted Spurious Emissions (Restricted Bands)</u> <u>Test Instrumentation</u>

Instrument	Model	S/No	Cal Due Date	Cal Interval
Agilent Spectrum Analyzer	E4440A	MY45304764	12 Dec 2015	1 year
Micro-tronics Bandstop Filter (2.4GHz)	BRM50701-02	007	13 Aug 2016	1 year



47 CFR FCC Part 15.247(d) and RSS-247 5.5 RF Conducted Spurious Emissions (Restricted Bands) Test Setup

- 1. The EUT and supporting equipment were set up as shown in the setup photo.
- 2. The power supply for the EUT was connected to a filtered mains.
- 3. The RF antenna connector was connected to the spectrum analyser via a low-loss coaxial cable.
- 4. The resolution bandwidth (RBW) of the spectrum analyser was set to the following settings. The video bandwidth (VBW) was set to at least three times of the RBW.

Frequency (MHz)	RBW (kHz)
0.009 - 0.150	0.2
0.150 – 30.0	9.0
30.0 - 1000	100.0
> 1000	1000.0

5. The detector of the spectrum analyser was set to peak detection mode.

6. All other supporting equipment were powered separately from another filtered mains.

<u>47 CFR FCC Part 15.247(d) and RSS-247 5.5 RF Conducted Spurious Emissions (Restricted Bands)</u> <u>Test Method</u>

- 1. Measurement in the range 9kHz 1000MHz
- 1.1 The EUT was switched on and allowed to warm up to its normal operating condition. The EUT was then configured to operate in the test mode, with the transmitting frequency was set to lower channel with specified modulation and data rate.
- 1.2 The start and stop frequencies of the spectrum analyser were set according to the supported RBW.
- 1.3 The spectrum analyser was set to max hold to capture any spurious emissions within the span. The signal capturing was continuous until no further spurious emissions were detected.
- 1.4 No further measurement was required if all the captured emissions complied to the limits. Else, the spectrum analyser was set to zoom to the captured emission with the detector of the spectrum analyser was set to quasi-peak. The emission level of the captured frequency was measured.
- 1.5 The step 1.4 was repeated until all the captured emissions which exceeding the limits were measured.
- 1.6 Repeat steps 1.1 to 1.5 with all possible modulations and data rates.
- 1.7 The steps 1.2 to 1.6 were repeated with the transmitting frequency was set to middle and upper channel respectively.

2. <u>Measurement above 1000MHz</u>

- 2.1 The EUT was switched on and allowed to warm up to its normal operating condition. The EUT was then configured to operate in the test mode, with the transmitting frequency was set to lower channel with specified modulation and data rate.
- 2.2 The start and stop frequencies of the spectrum analyser were set according to the supported frequency band of the set RBW with the number of points in a sweep was set to equal or greater than 2 times of the ratio of span over RBW.
- 2.3 The detector of the spectrum analyser was set to power average (RMS) mode with the sweep time was set to equal or greater than 10 times of the product of number of measurement points in a sweep and transmission symbol time.
- 2.4 The spectrum analyser was then allowed to capture any spurious emissions within a single sweep. The peak marker function of the spectrum analyser was used to locate the highest power level.
- 2.5 The steps 2.2 to 2.4 were repeated until all the required frequency bands were measured.
- 2.6 Repeat steps 2.1 to 2.5 with all possible modulations and data rates.
- 2.7 The steps 2.2 to 2.6 were repeated with the transmitting frequency was set to middle and upper channel respectively.
- 2.8 The measurements were repeated with the detector of the spectrum analyser was set to peak detecting mode. The sweep time was set to auto coupler.



47 CFR FCC Part 15.247(d) and RSS-247 5.5 RF Conducted Spurious Emissions (Restricted Bands) Results

Test Input Power	7.4Vdc	Temperature	24°C
Attached Plots	133 – 186 (802.11b)	Relative Humidity	60%
	187 – 258 (802.11g)		
	259 – 330 (802.11n)		
		Atmospheric Pressure	1030mbar
		Tested By	Chang Wai Kit

All spurious signals found were below the specified limit. Please refer to the attached plots.







RF Conducted Spurious Emissions (Restricted) Plots - 802.11b

Plot 134 – Channel 1 (lower ch) @ DBPSK 1Mbps





RF Conducted Spurious Emissions (Restricted) Plots - 802.11b

Plot 136 – Channel 1 (lower ch) @ DBPSK 1Mbps





RF Conducted Spurious Emissions (Restricted) Plots - 802.11b

Plot 138 - Channel 1 (lower ch) @ DBPSK 1Mbps





RF Conducted Spurious Emissions (Restricted) Plots - 802.11b

Plot 140 – Channel 1 (lower ch) @ DQPSK 2Mbps





RF Conducted Spurious Emissions (Restricted) Plots - 802.11b

Plot 142 - Channel 1 (lower ch) @ DQPSK 2Mbps





RF Conducted Spurious Emissions (Restricted) Plots – 802.11b







RF Conducted Spurious Emissions (Restricted) Plots – 802.11b

Plot 146 – Channel 1 (lower ch) @ CCK 11Mbps

Sweep 345.1 ms (8192 pts)

VBW 27 kHz

atus, C:/TMPIMAGE.GIF file saved

#Res BW 9.1 kHz





RF Conducted Spurious Emissions (Restricted) Plots - 802.11b

Plot 148 – Channel 1 (lower ch) @ CCK 11Mbps





RF Conducted Spurious Emissions (Restricted) Plots - 802.11b

Plot 150 – Channel 1 (lower ch) @ CCK 11Mbps





RF Conducted Spurious Emissions (Restricted) Plots - 802.11b



VBW 27 kHz

Span 29.85 MHz

Sweep 345.1 ms (8192 pts)

Center 15.075 MHz

#Res BW 9.1 kHz




Plot 154 – Channel 6 (middle ch) @ DBPSK 1Mbps





Plot 156 – Channel 6 (middle ch) @ DBPSK 1Mbps







Plot 158 – Channel 6 (middle ch) @ DQPSK 2Mbps





RF Conducted Spurious Emissions (Restricted) Plots - 802.11b

Plot 160 – Channel 6 (middle ch) @ DQPSK 2Mbps





Plot 162 – Channel 6 (middle ch) @ DQPSK 2Mbps







Plot 164 – Channel 6 (middle ch) @ CCK 11Mbps





RF Conducted Spurious Emissions (Restricted) Plots - 802.11b

Plot 166 – Channel 6 (middle ch) @ CCK 11Mbps











RF Conducted Spurious Emissions (Restricted) Plots - 802.11b



Sweep 345.1 ms (8192 pts)

VBW 27 kHz

#Res BW 9.1 kHz





RF Conducted Spurious Emissions (Restricted) Plots - 802.11b

Plot 172 – Channel 11 (upper ch) @ DBPSK 1Mbps





Plot 174 – Channel 11 (upper ch) @ DBPSK 1Mbps





RF Conducted Spurious Emissions (Restricted) Plots - 802.11b



VBW 27 kHz

#Res BW 9.1 kHz

Span 29.85 MHz

Sweep 345.1 ms (8192 pts)





Plot 178 – Channel 11 (upper ch) @ DQPSK 2Mbps











Plot 182 – Channel 11 (upper ch) @ CCK 11Mbps



















Plot 188 – Channel 1 (lower ch) @ BPSK 9Mbps











Plot 192 - Channel 1 (lower ch) @ BPSK 9Mbps





























RF Conducted Spurious Emissions (Restricted) Plots - 802.11g

Plot 202 – Channel 1 (lower ch) @ 16QAM 36Mbps













Plot 206 - Channel 1 (lower ch) @ 64QAM 54Mbps

















🔆 Agilent 14:20	:00 21 Sep 2015			R	Т	Freq/Channel
Ref -9 dBm #Peak PASS	#Atten 6 dB			Mkr1 7. -84.2%	70 kHz 3 dBm	Center Freq 15.0750000 MHz
Log 10 dB/ Offst				DC C	oupled	Start Freq 150.000000 kHz
						Stop Freq 30.0000000 MHz
LgAv						CF Step 2.98500000 MHz <u>Auto</u> Man
M1 S2 S3 FC A AA 🔆						FreqOffset 0.00000000 Hz
£(f): <mark>Ինդուստեր</mark> FTun ^{Ինդ} ինթյու _ն Տաթ	in Marine In a little population of a strategic policy of a strate	an terillinen linitik Navadi teringan	(1996) a free mind y fachte Niger alle de State print de State	a dan sa ang sa	ng Norsen Versigeren	Signal Track On <u>Off</u>
Center 15.075 MW #Res BW 9.1 kHz	l I Hz VI	3W 27 kHz	Sweep 34	Span 29.8 5.1 ms (8192	5 MHz 2 pts)	
File Operation S	Status, C:/TMPI	IAGE.GIF fi	le saved			
PI	ot 212 – Cha	nnel 6 <i>(m</i>	iddle ch)	@ BPSK	9Mbj	os





RF Conducted Spurious Emissions (Restricted) Plots - 802.11g

Plot 214 – Channel 6 (middle ch) @ BPSK 9Mbps





RF Conducted Spurious Emissions (Restricted) Plots - 802.11g

Plot 216 – Channel 6 (middle ch) @ BPSK 9Mbps







Plot 218 – Channel 6 (middle ch) @ QPSK 18Mbps





RF Conducted Spurious Emissions (Restricted) Plots - 802.11g

Plot 220 – Channel 6 (middle ch) @QPSK 18Mbps













Plot 224 – Channel 6 (middle ch) @ 16QAM 36Mbps




Plot 226 – Channel 6 (middle ch) @ 16QAM 36Mbps













Plot 230 - Channel 6 (middle ch) @ 64QAM 54Mbps





RF Conducted Spurious Emissions (Restricted) Plots - 802.11g

Plot 232 – Channel 6 (middle ch) @ 64QAM 54Mbps

















Plot 238 – Channel 11 (upper ch) @ BPSK 9Mbps





RF Conducted Spurious Emissions (Restricted) Plots - 802.11g

Plot 240 – Channel 11 (upper ch) @ BPSK 9Mbps





RF Conducted Spurious Emissions (Restricted) Plots - 802.11g



VBW 27 kHz

Span 29.85 MHz

Sweep 345.1 ms (8192 pts)

Center 15.075 MHz

#Res BW 9.1 kHz





RF Conducted Spurious Emissions (Restricted) Plots - 802.11g

Plot 244 – Channel 11 (upper ch) @ QPSK 18Mbps

















RF Conducted Spurious Emissions (Restricted) Plots - 802.11g

Plot 250 - Channel 11 (upper ch) @ 16QAM 36Mbps





Plot 252 – Channel 11 (upper ch) @ 16QAM 36Mbps





RF Conducted Spurious Emissions (Restricted) Plots - 802.11g

Plot 254 – Channel 11 (upper ch) @ 64QAM 54Mbps























RF Conducted Spurious Emissions (Restricted) Plots - 802.11n

Plot 262 – Channel 1 (lower ch) @ BPSK 6.5Mbps





RF Conducted Spurious Emissions (Restricted) Plots - 802.11n

Plot 264 – Channel 1 (lower ch) @ BPSK 6.5Mbps





Plot 266 - Channel 1 (lower ch) @ QPSK 19.5Mbps











RF Conducted Spurious Emissions (Restricted) Plots - 802.11n

Plot 270 – Channel 1 (lower ch) @ QPSK 19.5Mbps





Plot 272 - Channel 1 (lower ch) @ 16QAM 39Mbps











RF Conducted Spurious Emissions (Restricted) Plots - 802.11n

Plot 276 - Channel 1 (lower ch) @ 16QAM 39Mbps





RF Conducted Spurious Emissions (Restricted) Plots - 802.11n

Plot 278 – Channel 1 (lower ch) @ 64QAM 65Mbps











RF Conducted Spurious Emissions (Restricted) Plots - 802.11n

Plot 282 – Channel 1 (lower ch) @ 64QAM 65Mbps





RF Conducted Spurious Emissions (Restricted) Plots - 802.11n

Plot 284 – Channel 6 (middle ch) @ BPSK 6.5Mbps

Sweep 345.1 ms (8192 pts)

VBW 27 kHz

atus, C:/TMPIMAGE.GIF file saved





Plot 286 – Channel 6 (middle ch) @ BPSK 6.5Mbps





RF Conducted Spurious Emissions (Restricted) Plots - 802.11n

Plot 288 – Channel 6 (middle ch) @ BPSK 6.5Mbps







Plot 290 – Channel 6 (middle ch) @ QPSK 19.5Mbps





RF Conducted Spurious Emissions (Restricted) Plots - 802.11n

Plot 292 – Channel 6 (middle ch) @QPSK 19.5Mbps













Plot 296 – Channel 6 (middle ch) @ 16QAM 39Mbps
















RF Conducted Spurious Emissions (Restricted) Plots - 802.11n



Status, C:/TMPIMAGE.GIF file save

















Plot 308 – Channel 11 (upper ch) @ BPSK 6.5Mbps











RF Conducted Spurious Emissions (Restricted) Plots - 802.11n

Plot 312 – Channel 11 (upper ch) @ BPSK 6.5Mbps





Plot 314 – Channel 11 (upper ch) @ QPSK 19.5Mbps











Plot 318 – Channel 11 (upper ch) @ QPSK 19.5Mbps

















Plot 324 – Channel 11 (upper ch) @ 16QAM 39Mbps

















RF Conducted Spurious Emissions (Restricted) Plots – 802.11n

Plot 330 – Channel 11 (upper ch) @ 64QAM 65Mbps



47 CFR FCC Part 15.247(d) and RSS-247 5.5 Band Edge Compliance (Conducted) Limits

The EUT shows compliance to the requirements of this section, which states in any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator (EUT) is operating, the radio frequency power that is produced by the EUT shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of desired power.

47 CFR FCC Part 15.247(d) and RSS-247 5.5 Band Edge Compliance (Conducted) Test Instrumentation

Instrument	Model	S/No	Cal Due Date	Cal Interval
Agilent Spectrum Analyzer	E4440A	MY45304764	12 Dec 2015	1 year

47 CFR FCC Part 15.247(d) and RSS-247 5.5 Band Edge Compliance (Conducted) Test Setup

- 1. The EUT and supporting equipment were set up as shown in the setup photo.
- 2. The power supply for the EUT was connected to a filtered mains.
- 3. The RF antenna connector was connected to the spectrum analyser via a low-loss coaxial cable.
- 4. The resolution bandwidth (RBW) and the video bandwidth (VBW) of the spectrum analyser were respectively set to 100kHz and 300kHz.
- 5. All other supporting equipment were powered separately from another filtered mains.

47 CFR FCC Part 15.247(d) and RSS-247 5.5 Band Edge Compliance (Conducted) Test Method

- 1. The EUT was switched on and allowed to warm up to its normal operating condition. The EUT was then configured to operate in the test mode with specified modulation and data rate.
- 2. The frequency span of the spectrum analyser was set to wide enough to capture the lower band edge of the transmission band, 2.400GHz and any spurious emissions at the band edge.
- 3. The spectrum analyser was set to max hold to capture any spurious emissions within the span. The signal capturing was continuous until no further spurious emissions were detected.
- 4. Repeat steps 1 to 3 with all possible modulations and data rates.
- 5. The steps 2 to 4 were repeated with the frequency span of the spectrum analyser was set to wide enough to capture the upper band edge frequency of the transmission band, 2.4835GHz and the any spurious emissions at the band-edge.



47 CFR FCC Part 15.247(d) and RSS-247 5.5 Band Edge Compliance (Conducted) Results

Test Input Power	7.4Vdc	Temperature	24°C
Attached Plots	331 – 336 (802.11b) 337 – 344 (802.11g) 345 – 352 (802.11n)	Relative Humidity	60%
		Atmospheric Pressure	1030mbar
		Tested By	Liau Lee Yin

No significant signal was found and they were below the specified limit.







Band Edge Compliance (Conducted) Plots - 802.11b







Band Edge Compliance (Conducted) Plots - 802.11b





Band Edge Compliance (Conducted) Plots – 802.11b



Plot 335 – Upper Band Edge at 2.4835GHz @ DQPSK 2Mbps





Band Edge Compliance (Conducted) Plots – 802.11b





Band Edge Compliance (Conducted) Plots - 802.11g

Plot 338 – Lower Band Edge at 2.4000GHz @ QPSK 18Mbps





Band Edge Compliance (Conducted) Plots - 802.11g



ration Status, A:\SCREN819.GIF file save





Band Edge Compliance (Conducted) Plots - 802.11g



Plot 342 – Upper Band Edge at 2.4835GHz @ QPSK 18Mbps





Band Edge Compliance (Conducted) Plots – 802.11g



Plot 344 – Upper Band Edge at 2.4835GHz @ 64QAM 54Mbps





Band Edge Compliance (Conducted) Plots – 802.11n



Plot 346 – Lower Band Edge at 2.4000GHz @ QPSK 19.5Mbps





Band Edge Compliance (Conducted) Plots - 802.11n

M1 Span Pair \$3 FC Span Center AA Ĥ £(f): Marker Off FTun 2.400000000 GHz ŝwр -34.93 dBm More Start 2.310 00 GHz Stop 2.425 00 GHz 1 of 2 #Res BW 100 kHz #VBW 300 kHz Sweep 11 ms (601 pts) ation Status, A:\SCREN823.GIF file save







Band Edge Compliance (Conducted) Plots - 802.11n



Plot 350 – Upper Band Edge at 2.4835GHz @ QPSK 19.5Mbps





Band Edge Compliance (Conducted) Plots - 802.11n



Plot 352 – Upper Band Edge at 2.4835GHz @ 64QAM 65Mbps



47 CFR FCC Part 15.247(d) and RSS-247 5.5 Band Edge Compliance (Radiated) Limits

The EUT shows compliance to the requirements of this section, which states in any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator (EUT) is operating, the radio frequency power that is produced by the EUT shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of desired power. In addition, radiated emissions which fall in the restricted bands shall comply to the radiated emission limits specified in 15.209.

47 CFR FCC Part 15.247(d) and RSS-247 5.5 Band Edge Compliance (Radiated) Test Instrumentation

Instrument	Model	S/No	Cal Due Date	Cal Interval
R&S Test Receiver – ESI1	ESI40	100010	14 Jul 2016	1 year
EMCO Horn Antenna(1GHz-18GHz)	3115	0003-6088	20 Apr 2016	1 year
R&S Preamplifier (1GHz -18GHz)	SCU18	102191	13 Mar 2016	1 year

47 CFR FCC Part 15.247(d) and RSS-247 5.5 Band Edge Compliance (Radiated) Test Setup

- 1. The EUT and supporting equipment were set up as shown in the setup photo.
- 2. The power supply for the EUT was connected to a filtered mains.
- 3. The resolution bandwidth (RBW) and the video bandwidth (VBW) of the spectrum analyser were respectively set to 100kHz and 300kHz to show compliance of spurious at band edges are at least 20dB below the carriers. For restricted band spurious at band edges, peak and average measurement plots were taken using the following setting:

.

- a. Peak Plot:
 - RBW = 1MHz, VBW = 3MHz
- b. Average Plot
 - RBW = 1MHz, VBW = 30Hz
- 4. All other supporting equipment were powered separately from another filtered mains.

47 CFR FCC Part 15.247(d) and RSS-247 5.5 Band Edge Compliance (Radiated) Test Method

- 1. The EUT was switched on and allowed to warm up to its normal operating condition. The EUT was then configured to operate in the test mode with specified modulation and data rate.
- 2. The frequency span of the spectrum analyser was set to wide enough to capture the lower band edge of the transmission band, 2.400GHz and any spurious emissions at the band edge.
- 3. The spectrum analyser was set to max hold to capture any spurious emissions within the span. The signal capturing was continuous until no further spurious emissions were detected. For the average measurement, it was done via a video average mode with a reduced VBW.
- 4. Repeat steps 1 to 3 with all possible modulations and data rates.
- 5. The steps 2 to 4 were repeated with the frequency span of the spectrum analyser was set to wide enough to capture the upper band edge frequency of the transmission band, 2.4835GHz and the any spurious emissions at the band-edge.



47 CFR FCC Part 15.247(d) and RSS-247 5.5 Band Edge Compliance (Radiated) Results

Test Input Power	7.4Vdc	Temperature	24°C
Attached Plots	353 – 358 (802.11b) 359 – 364 (802.11g) 365 – 370 (802.11n)	Relative Humidity	60%
		Atmospheric Pressure	1030mbar
		Tested By	Dylan Lin

No significant signal was found and they were below the specified limit.







Band Edge Compliance (Radiated) Plots (20dB Delta from Carrier at Band Edge) - 802.11b

Plot 354 – Upper Band Edge at 2.4835GHz @ CCK 11Mbps

Motorola Solutions Malaysia Sdn Bhd Handheld Radio [Model : AAH56JDN9RA1AN] [FCC ID : AZ489FT7066 & IC : 109U-89FT7066]





Band Edge Compliance (Radiated) Plots (Restricted Band) - 802.11b



Motorola Solutions Malaysia Sdn Bhd Handheld Radio [Model : AAH56JDN9RA1AN] [FCC ID : AZ489FT7066 & IC : 109U-89FT7066]





Band Edge Compliance (Radiated) Plots (Restricted Band) – 802.11b






Band Edge Compliance (Radiated) Plots (20dB Delta from Carrier at Band Edge) - 802.11g

Plot 360 – Upper Band Edge at 2.4835GHz @ 64QAM 54Mbps





Band Edge Compliance (Radiated) Plots (Restricted Band) – 802.11g







Band Edge Compliance (Radiated) Plots (Restricted Band) - 802.11g







Band Edge Compliance (Radiated) Plots (20dB Delta from Carrier at Band Edge) - 802.11n

Plot 366 – Upper Band Edge at 2.4835GHz @ 64QAM 65Mbps





Band Edge Compliance (Radiated) Plots (Restricted Band) – 802.11n







Band Edge Compliance (Radiated) Plots (Restricted Band) - 802.11n





47 CFR FCC Part 15.247(e) and RSS-247 5.2(2) Peak Power Spectral Density Limits

The EUT shows compliance to the requirements of this section, which states the peak power spectral density conducted from the intentional radiator (EUT) to the antenna shall not be greater than 8dBm (6.3mW) in any 3kHz band during any time interval of continuous transmission.

47 CFR FCC Part 15.247(e) and RSS-247 5.2(2) Peak Power Spectral Density Test Instrumentation

Instrument	Model	S/No	Cal Due Date	Cal Interval
Agilent Spectrum Analyzer	E4440A	MY45304764	12 Dec 2015	1 year

47 CFR FCC Part 15.247(e) and RSS-247 5.2(2) Peak Power Spectral Density Test Setup

- 1. The EUT and supporting equipment were set up as shown in the setup photo.
- 2. The power supply for the EUT was connected to a filtered mains.
- 3. The RF antenna connector was connected to the spectrum via a low-loss coaxial cable.
- 4. The resolution bandwidth (RBW), video bandwidth (VBW) and span of the spectrum analyser were set to the following:
 - RBW = 3kHz
 - VBW = 9kHz
 - Span = 1.5 times the channel bandwidth
 - Sweep time = auto couple
- 5. All other supporting equipment were powered separately from another filtered mains.

47 CFR FCC Part 15.247(e) and RSS-247 5.2(2) Peak Power Spectral Density Test Method

- 1. The EUT was switched on and allowed to warm up to its normal operating condition. The EUT was then configured to operate in the test mode at lower channel with specified modulation and data rate.
- 2. The peak of the transmitting frequency was detected with the marker peak function of the spectrum analyser.
- 3. The peak power density of the transmitting frequency was plotted and recorded.
- 4. Repeat steps 1 to 3 with all possible modulations and data rates.
- 5. The steps 2 to 4 were repeated with the transmitting frequency was set to middle and upper channel respectively.



47 CFR FCC Part 15.247(e) and RSS-247 5.2(2) Peak Power Spectral Density Results

Test Input Power	7.4Vdc	Temperature	24°C
		Relative Humidity	60%
		Atmospheric Pressure	1030mbar
		Tested By	Liau Lee Yin

802.11b

Channel	Channel Frequency (GHz)	Peak Power Spectral Density (mW)	Limit (mW)	Modulation @ Data Rate
		0.1540	6.3	DBPSK @ 1Mbps
1 (lower ch)	2.412	0.3850	6.3	DQPSK @ 2Mbps
		0.3392	6.3	CCK @ 11Mbps
		0.1754	6.3	DBPSK @ 1Mbps
6 (mid ch)	2.437	0.9285	6.3	DQPSK @ 2Mbps
		0.3204	6.3	CCK @ 11Mbps
11 (upper ch)	1	0.1456	6.3	DBPSK @ 1Mbps
	2.462	0.8937	6.3	DQPSK @ 2Mbps
		0.2633	6.3	CCK @ 11Mbps

802.11a

Channel	Channel Frequency (GHz)	Peak Power Spectral Density (mW)	Limit (mW)	Modulation @ Data Rate
1 (lower ch)		0.1320	6.3	BPSK @ 9Mbps
	2 /12	0.1113	6.3	QPSK @ 18Mbps
	2.412	0.2904	6.3	16QAM @ 36Mbps
		0.1061	6.3	64QAM @ 54Mbps
6 (mid ch)	2 427	0.0965	6.3	BPSK @ 9Mbps
		0.0985	6.3	QPSK @ 18Mbps
	2.437	0.1121	6.3	16QAM @ 36Mbps
	1	0.0970	6.3	64QAM @ 54Mbps
11 <i>(upper ch)</i>		0.1112	6.3	BPSK @ 9Mbps
	2 462	0.0934	6.3	QPSK @ 18Mbps
	2.402	0.1130 6.3 16QAM @ 3	16QAM @ 36Mbps	
		0.1037	6.3	64QAM @ 54Mbps



47 CFR FCC Part 15.247(e) and RSS-247 5.2(2) Peak Power Spectral Density Results

Test Input Power	7.4Vdc	Temperature	24°C
		Relative Humidity	60%
		Atmospheric Pressure	1030mbar
		Tested By	Liau Lee Yin

802.11n

Channel	Channel Frequency (GHz)	Peak Power Spectral Density (mW)	Limit (mW)	Modulation @ Data Rate
1 (lower ch)		0.1190	6.3	BPSK @ 6.5Mbps (MCS0)
	0.440	0.1020 6.3 QPSK @ 19.5M 0.1029 6.3 16QAM @ 39M	QPSK @ 19.5Mbps (MCS2)	
	2.412		16QAM @ 39Mbps (MCS4)	
		0.0928	6.3	64QAM @ 65Mbps (MCS7)
6 (mid ch)		0.1007	6.3	BPSK @ 6.5Mbps (MCS0)
	2 427	0.0861	6.3	QPSK @ 19.5Mbps (MCS2)
	2.437	0.0879	'9 6.3 16QAM @ 39Mbp	16QAM @ 39Mbps (MCS4)
		0.1028	6.3	64QAM @ 65Mbps (MCS7)
11 <i>(upper ch)</i>		0.0919	6.3	BPSK @ 6.5Mbps (MCS0)
	2.462	0.0908	6.3	QPSK @ 19.5Mbps (MCS2)
	2.402	0.0820	6.3	BPSK @ 6.5Mbps (MCS0) QPSK @ 19.5Mbps (MCS2) 16QAM @ 39Mbps (MCS4) 64QAM @ 65Mbps (MCS7) BPSK @ 6.5Mbps (MCS0) QPSK @ 19.5Mbps (MCS2) 16QAM @ 65Mbps (MCS7) BPSK @ 6.5Mbps (MCS0) QPSK @ 19.5Mbps (MCS2) 16QAM @ 39Mbps (MCS2)
		0.0768	6.3	64QAM @ 65Mbps (MCS7)





Peak Power Spectral Density Plots - 802.11b

#Res BW 3 kHz

Plot 372 – Channel 1 (lower ch) @ DQPSK 2Mbps

Sweep 1.687 s (401 pts)

#VBW 10 kHz

File Operation Status, A:\SCREN847.GIF file saved

1 of 2





Peak Power Spectral Density Plots - 802.11b





Peak Power Spectral Density Plots – 802.11g



Plot 375 - Channel 1 (lower ch) @ QPSK 18Mbps





Peak Power Spectral Density Plots – 802.11g

Plot 377 – Channel 1 (lower ch) @ 64QAM 54Mbps





Peak Power Spectral Density Plots - 802.11n



Plot 379 – Channel 1 (lower ch) @ QPSK 19.5Mbps





Peak Power Spectral Density Plots – 802.11n

Plot 381 – Channel 1 (lower ch) @ 64QAM 65Mbps





Peak Power Spectral Density Plots – 802.11b



Plot 383 – Channel 6 (middle ch) @ DQPSK 2Mbps





Peak Power Spectral Density Plots – 802.11b



Min Search

Pk-Pk Search

Mkr → CF

More

1 of 2

mpl

Span 25 MHz

Sweep 2.636 s (401 pts)



Peak Power Spectral Density Plots - 802.11g

DI 6.299 mW

_gAv

\$3 Ĥ **£**(f):

Tun

wp

S2 FC AA Μ1

Marker

Center 2.437 000 0 GHz

#Res BW 3 kHz

98.45 µW

2.437000000 GHz



#VBW 10 kHz





Peak Power Spectral Density Plots – 802.11g

Plot 388 – Channel 6 (middle ch) @ 64QAM 54Mbps





Peak Power Spectral Density Plots – 802.11n

M1 S2

S3 FC A AA €(f):

Tun

wp

Marker

Center 2.437 000 0 GHz

#Res BW 3 kHz

86.06 µW

2.437000000 GHz

File Operation Status, A:\SCREN867.6IF file saved Plot 390 – Channel 6 (middle ch) @ QPSK 19.5Mbps

#VBW 10 kHz

inni

Span 27 MHz

Sweep 2.847 s (401 pts)

Pk-Pk Search

Mkr → CF

More

1 of 2





Peak Power Spectral Density Plots – 802.11n

Plot 392 – Channel 6 (middle ch) @ 64QAM 65Mbps





Peak Power Spectral Density Plots – 802.11b



Plot 394 – Channel 11 (upper ch) @ DQPSK 2Mbps





Peak Power Spectral Density Plots - 802.11b





Peak Power Spectral Density Plots – 802.11g

Plot 397 – Channel 11 (upper ch) @ QPSK 18Mbps





Peak Power Spectral Density Plots – 802.11g

Plot 399 – Channel 11 (upper ch) @ 64QAM 54Mbps





Peak Power Spectral Density Plots – 802.11n

Center 2.462 000 0 GHz

#Res BW 3 kHz

File Operation Status, A:\SCREN881.GIF file saved Plot 401 – Channel 11 (upper ch) @ QPSK 19.5Mbps

#VBW 10 kHz

More

1 of 2

Span 27 MHz

Sweep 2.847 s (401 pts)





Peak Power Spectral Density Plots – 802.11n





Please note that this Report is issued under the following terms :

- 1. This report applies to the sample of the specific product/equipment given at the time of its testing/calibration. The results are not used to indicate or imply that they are applicable to other similar items. In addition, such results must not be used to indicate or imply that TÜV SÜD PSB approves, recommends or endorses the manufacturer, supplier or user of such product/equipment, or that TÜV SÜD PSB in any way "guarantees" the later performance of the product/equipment. Unless otherwise stated in this report, no tests were conducted to determine long term effects of using the specific product/equipment.
- The sample/s mentioned in this report is/are submitted/supplied/manufactured by the Client. TÜV SÜD PSB therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture, consignment or any information supplied.
- 3. Nothing in this report shall be interpreted to mean that TÜV SÜD PSB has verified or ascertained any endorsement or marks from any other testing authority or bodies that may be found on that sample.
- 4. This report shall not be reproduced wholly or in parts and no reference shall be made by the Client to TÜV SÜD PSB or to the report or results furnished by TÜV SÜD PSB in any advertisements or sales promotion.
- 5. Unless otherwise stated, the tests were carried out in TÜV SÜD PSB Pte Ltd, No.1 Science Park Drive Singapore 118221.



July 2011



ANNEX A

TEST SETUP / EUT PHOTOGRAPHS / DIAGRAMS



TEST SETUP (30MHz to 1GHz)



Radiated Emissions Test Setup (Front View)



Radiated Emissions Test Setup (Rear View)



TEST SETUP (Above 1GHz)



Radiated Emissions Test Setup (Front View)



Radiated Emissions Test Setup (Rear View)



TEST SETUP



Spectrum Bandwidth (6dB Bandwidth Measurement) Test Setup



Maximum Peak Power Test Setup



TEST SETUP



RF Conducted Spurious Emissions (Non-Restricted Bands) Test Setup



RF Conducted Spurious Emissions (Restricted Bands) Test Setup



TEST SETUP



Band Edge Compliance (Conducted) Test Setup



Band Edge Compliance (Radiated) Test Setup



TEST SETUP





EUT PHOTOGRAPHS



Rear View


ANNEX B USER MANUALTECHNICAL DESCRIPTION BLOCK & CIRCUIT DIAGRAMS

ANNEX B

USER MANUAL TECHNICAL DESCRIPTION BLOCK & CIRCUIT DIAGRAMS (Please refer to manufacturer for details)



ANNEX C FCC, IC LABEL & POSITION





ANNEX C FCC, IC LABEL & POSITION

Labelling requirements per Section 2.925, 15.19 and RSS-GEN 2.1

The label shown will be permanently affixed at a conspicuous location on the device and be readily visible to the user at the time of purchase.



Physical Location of FCC and IC Label on EUT

Motorola Solutions Malaysia Sdn Bhd Handheld Radio [Model : AAH56JDN9RA1AN] [FCC ID : AZ489FT7066 & IC : 109U-89FT7066]



ANNEX D TEST SITE DESCRIPTION





ANNEX D TEST SITE DESCRIPTION

Radiated Emission Test Site Description

The Radiated Emission test facility consists of a RF-shielded enclosure (Model: 04" x 07") manufactured by Lindgren whose dimensions are shown below. The exterior of the chamber is made of rigid steel panels while the interior is covered with RF absorbing panels on the 4 walls and ceiling. The steel-clad ground place is covered with vinyl flooring.

The turntable is mounted flushed with the chamber floor and is driven by a pneumatic motor, which is capable of supporting 4,000 kg.

The boresight antenna mast is driven by a pneumatic motor with heights variation from 1m- 4m for both vertical and horizontal polarity and with tilt capability.

Both turntable and antenna mast in the chamber are controlled by the controller stationed outside the chamber.

The physical layout of the chamber is show below:





ANNEX D TEST SITE DESCRIPTION

Conducted Emission Test Site Description

The Conducted Emission facility consists of an RF-shielded enclosure measuring 4.3m x 3.7m x 2.45m manufactured by Universal Shielding Corporation. The Conducted Emission data were taken using two LISNs.

The physical layout of the test site is show below:

	LISN	1.5m x 1.0m Non-conductive Table.	
	4.3m		
•		3.7m	-
	7		