

# Product Specification



Numbering	20230823002
Expiration date	2023/8/23

The name of the customer	Dongguan Hankai Electronics Co., Ltd
Products	A11 coil
Hui Yu Ya material number	TD-HBY20230823002-50 OPEN DOUBLE GROOVE L=18MM
Customer part number	101.20.05640

[ ☐√ new edition , ☐ version revision ] [ This template contains a total of 3 parts of the table of contents ] [ RoHS Compliant Parts ]

Weave	Examine	From it
Xiao Shufang	Peng Yong	Zhu Hui

**Anfuhui Electronics Co., Ltd**

This acknowledgement shall be signed and sealed within 30 days by the customer, and the expiration shall be deemed to be the execution of this acknowledgement.

【Customer Quasi】 day

Form: ☐ to the fullest ☐ ☐ but to it

From it	Examine	Retest	Examine


bright

\_\_\_\_\_

## Product Specification

The name of the customer	Dongguan Hankai Electronics Co., Ltd	Customer part number	101.20.05640
Hui Yu Ya material number	TD-HBY20230823002-50 OPEN DOUBLE GROOVE L=18MM	numbering	20230823002
Distribution/Revision			
Version	Expiration date	Changeler/also	Permit
01	2023/8/23	Issued by Xinge	
Weave		Examine	
Xiao Shufang		Peng Yong	
		From it	
		Zhu Hui	

# Product Specification

The name of the customer	Dongguan Hankai Electronics Co., Ltd	Customer part number	101.20.05640		
Hui Yu Ya material number	TD-HBY20230823002-50 OPEN DOUBLE GROOVE L=18MM	Numbering	20230823002	Version	002
◆ Dimensions			(bits, mm).		
			One	50.0 ±1	
			B	42.0 ±1.5	
			C	20.5 ±0.5	
			D	5 References ±0.5	
			and	10.0 References	
			F	3 ±1	
			G	2.5 Max	
			H	18.0 ±1.5	
			I	1.0 ±0.1 (sheet thickness).	
			(2) Number of coils, 10TS		
			(3) Beginning and end line handover: No		
			(4) The coil is wrapped with 8mm wide temperature tape		
			(5) The coil and magnetic sheet are pasted in the center		
			(6) Magnetic sheet back 48.5 with white round adhesive		
◆ Electricity					
parameter	Grid also	Try it	Tester		
Level L0	6.3 ±10%μH	100KHz/1V	■TH1816B		
Q	> 80 minutes	100KHz/1V	■TH1816B		
DCR	<45 mΩ	@ 25° Celsius	■CH-502BC Liu		
◆ Temperature rating					
Operating temperature	-40℃ ~ 125℃				
◆ Material list					
Serial number	Name of article	Grid	Vendor	Remark	
1	Magnetic sheets	50*5.3*1.0*10T open double slots	PC95 mammothzinc		
2	Copper wire	0.08 * 105 pips	Apropylene copper wire wrapping		
3	Warm tape	8 mm	Eco-friendly tape		
4	Tin	107 less	Thousand Islands Environmental Tin		
5	Glue	Yellow gum	Eco-friendly glue		
6	Glue	One side round white glue			
Weave		Examine		From it	

Xiao Shufang	Peng Yong	Zhu Hui