



SAR EVALUATION REPORT

IEEE Std 1528-2013

For
PHONE

FCC ID: A4RGUR25
Model Name: GUR25, G1B60

Report Number: 15107843 -S6V3
Issue Date: 5/14/2024

Prepared for
Google LLC
1600 Amphitheatre Parkway
Mountain View, CA 94043 U.S.A.

Prepared by
UL VERIFICATION SERVICES INC.
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 319-4000
FAX: (510) 661-0888



Revision History

Rev.	Date	Revisions	Revised By
V1	5/9/2024	Initial Issue	--
V2	5/14/2024	Section 1: Updated Highest SAR values	Coltyce Sanders
V3	5/14/2024	Updated section 1 and 7.1 data re-use description.	Devin Chang

Table of Contents

1.	Attestation of Test Results	4
2.	Test Specification, Methods and Procedures.....	5
3.	Facilities and Accreditation	6
4.	Measurement System & Test Equipment.....	7
4.1.	SAR Measurement System.....	7
4.2.	SAR Scan Procedures.....	8
4.3.	Test Equipment.....	10
5.	Measurement Uncertainty.....	11
6.	Dielectric Property Measurements & System Check	12
6.1.	Dielectric Property Measurements	12
6.2.	System Check.....	14
7.	Test Rationale.....	15
7.1.	Purpose	15
7.2.	Data Reuse Approach.....	15
8.	Measured and Reported (Scaled) SAR Results.....	15
Appendixes	16	
Appendix A:	SAR Setup Photos	16
Appendix B:	SAR System Check Plots	16
Appendix C:	SAR Highest Test Plots.....	16
Appendix D:	Tissue Ingredients.....	16
Appendix E:	Probe Certificates.....	16
Appendix F:	Dipole Certificates	16

1. Attestation of Test Results

Applicant Name	Google LLC								
FCC ID	A4RGUR25								
Model Name	GUR25, G1B60								
Applicable Standards	Published RF exposure KDB procedures. IEEE Std 1528-2013								
Difference in Model Name	Model G1B60 is electrically identical to Model GUR25. Two model numbers are allocated for marketing and logistic purposes. Model GUR25 was used for all final testing.								
Exposure Category	SAR Limits (W/Kg)								
	Peak spatial-average (1g of tissue)				Extremities (hands, wrists, ankles, etc.) (10g of tissue)				
General population / Uncontrolled exposure	1.6				4				
RF Exposure Conditions	Equipment Class - Highest Reported SAR (W/kg)								
		TNB	PCE	CBE	DTS	NII	6CD	DSS	DXX
Worst Case from A4RG2YBB	1g	0.986	0.984	0.599	0.820	0.540	0.395	0.275	N/A
	10g	2.335	2.469	N/A	N/A	1.181	0.350	N/A	0.080
Variant Models A4RGUR25	1g	0.824	0.865	0.383	0.518	0.468	0.312	0.192	N/A
	10g	2.03	1.338	N/A	N/A	1.340	0.511	N/A	0.080
Date Tested	5/6/2024 to 5/9/2024								
Test Results	Pass								
This application for certification is leveraging the data reuse procedure from TCB workshop April 2021; RF Exposure Procedures (Remarks on Test Reductions via Data Referencing for Closely Related Products) based on reference FCC ID: A4RG2YBB (UL report# 5107843-S1) to cover variants FCC ID: A4RGUR25. The major difference between the reference model and the variant models is that support for some LTE/5GNR FR1 bands is disabled via software and mmWave module is removed in the variant models. All other circuitry and features are identical. UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested can demonstrate compliance with the requirements as documented in this report. This report contains data provided by the customer which can impact the validity of results. UL Verification Services Inc. is only responsible for the validity of results after the integration of the data provided by the customer. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not considered unless noted otherwise. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by A2LA, NIST, or any agency of the U.S. Government, or any agency of the U.S. government.									
Approved & Released By:					Prepared By:				
									
Devin Chang Senior Laboratory Engineer UL Verification Services Inc.					Coltyce Sanders Staff Laboratory Engineer UL Verification Services Inc.				

2. Test Specification, Methods and Procedures

The tests documented in this report were performed in accordance with FCC 47 CFR § 2.1093, IEEE Std 1528-2013, the following FCC Published RF exposure [KDB](#) procedures:

- 248227 D01 802.11 Wi-Fi SAR v02r02
- 447498 D01 General RF Exposure Guidance v06
- 447498 D03 Supplement C Cross-Reference v01
- 648474 D04 Handset SAR v01r03
- 865664 D01 SAR measurement 100 MHz to 6 GHz v01r04
- 865664 D02 RF Exposure Reporting v01r02
- 941225 D01 3G SAR Procedures v03r01
- 941225 D05 SAR for LTE Devices v02r05
- 941225 D05A LTE Rel.10 KDB Inquiry Sheet v01r02
- 941225 D06 Hotspot Mode v02r01

In addition to the above, the following information was used:

- **TCB workshop** October 2014; RF Exposure Procedures (Other LTE Considerations)
- **TCB workshop** April 2015; RF Exposure Procedures (Overlapping LTE Bands)
- **TCB workshop** October 2015; RF Exposure Procedures (KDB 941225 D05A)
- **TCB workshop** April 2016; RF Exposure Procedures (LTE Carrier Aggregation for DL)
- **TCB workshop** October 2016; RF Exposure Procedures (LTE Carrier Aggregation for UL)
- **TCB workshop** October 2016; RF Exposure Procedures (Bluetooth Duty Factor)
- **TCB workshop** October 2016; RF Exposure Procedures (DUT Holder Perturbations)
- **TCB workshop** May 2017; RF Exposure Procedures (Broadband Liquid Above 3 GHz)
- **TCB workshop** May 2017; RF Exposure Procedures (LTE Band 41 Power Class 2)
- **TCB workshop** November 2017; RF Exposure Procedures (LTE UL/DL Carrier Aggregation SAR)
- **TCB workshop** April 2018; RF Exposure Procedures (LTE DL CA SAR Test Exclusion)
- **TCB workshop** October 2018; RF Exposure Procedures (LTE Inter-Band Uplink Carrier Aggregation – Interim Procedures)
- **TCB workshop** April 2019; RF Exposure Procedures (802.11ax SAR Testing)
- **TCB workshop** November 2019; RF Exposure Policy Updates (5G NR FR1 NSA EN-DCUE SAR Evaluations)
- **TCB workshop** April 2021; RF Exposure Procedures (Remarks on Test Reductions via Data Referencing for Closely Related Products)
- **TCB Workshop** April 2022; RF Exposure Procedures (Sum-Peak Location Separation Ratio)

PD

- 388624 D02 Pre-Approval Guidance List v18r03 (APPENDIX OVER6G)
- SPEAG DASY8 System Handbook; part 4 DASY8 Module mmWave
- SPEAG DASY8 Application Note: SAR, APD & PD at 6 – 10 GHz (Version 5), April 2022
- IEC TR 63170: 2018
- **TCB workshop** November 2017; RF Exposure Procedures (Power Density Evaluation)
- **TCB workshop** October 2018; RF Exposure Procedures (Millimeter Wave Assessment)
- **TCB workshop** April 2019; RF Exposure Procedures (Millimeter Wave RF Exposure Evaluation)
- **TCB workshop** November 2019; RF Exposure Procedures (Millimeter Wave Scan Requirements)
- **TCB workshop** October 2020; RF Exposure Procedures (U NII 6-7 GHz RF Exposure)
- **TCB workshop** October 2022; RF Exposure Policies and Procedures (f-above-6 GHz Portable Devices)

3. Facilities and Accreditation

The test sites and measurement facilities used to collect data are located at

47266 Benicia Street
SAR Labs 1 to 16

UL Verification Services Inc. is accredited by A2LA, Certificate Number 0751.05


The Test Lab Conformity Assessment Body Identifier (CABID)

Location	CABID	Company Number
47173 Benicia Street, Fremont, CA, 94538 UNITED STATES	US0104	2324A
47266 Benicia Street, Fremont, CA, 94538 UNITED STATES		

4. Measurement System & Test Equipment

4.1. SAR Measurement System

The DASY system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running Win10 and the DASY6/8¹ software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder, and other accessories according to the targeted measurement.

¹ DASY6/8 software used: DASY6.16.2 or DASY8.16.2 and older generations.

4.2. SAR Scan Procedures

Step 1: Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. The minimum distance of probe sensors to surface is 2.1 mm. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

Step 2: Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum locations even in relatively coarse grids. When an Area Scan has measured all reachable points, it computes the field maximal found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEC/IEEE 62209-1528, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan). If only one Zoom Scan follows the Area Scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of Zoom Scans has to be increased accordingly.

Area Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$	≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

Step 3: Zoom Scan

Zoom Scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The Zoom Scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the Zoom Scan evaluates the averaged SAR for 1 g and 10 g and displays these values next to the job's label.

Zoom Scan Parameters extracted from KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <u>reported</u> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

Step 4: Power drift measurement

The Power Drift Measurement measures the field at the same location as the most recent power reference measurement within the same procedure, and with the same settings. The Power Drift Measurement gives the field difference in dB from the reading conducted within the last Power Reference Measurement. This allows a user to monitor the power drift of the device under test within a batch process. The measurement procedure is the same as Step 1.

4.3. Test Equipment

The measuring equipment used to perform the tests documented in this report has been calibrated in accordance with the manufacturers' recommendations and is traceable to recognized national standards.

Dielectric Property Measurements

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
Vector Network Analyzer	ROHDE & SCHWARZ	ZNLE6	101274-mn	2/28/2025
Dielectric Probe kit	SPEAG	DAK-3.5	1087	11/1/2024
Dielectric Probe kit	SPEAG	DAK-12	1128	1/16/2025
Shorting Block	SPEAG	DAK-1.2/3.5 Short	SM DAK 200 DA	11/1/2024
Shorting Block	SPEAG	DAK-12 Short	SM DAK 220 AC	1/16/2025
Thermometer	Fisher Scientific	Traceable	122529162	1/31/2025

Lab Equipment

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
E-Field Probe (SAR Lab 1)	SPEAG	EX3DV4	3989	1/9/2024
E-Field Probe (SAR Lab 2)	SPEAG	EX3DV4	7585	4/16/2025
Data Acquisition Electronics (SAR Lab 1)	SPEAG	DAE4	1433	2/8/2025
Data Acquisition Electronics (SAR Lab 2)	SPEAG	DAE4	1258	3/12/2025
Thermometer	TRACEABLE	6530CC	181175331	1/31/2025
System Validation Dipole*	SPEAG	D1950V2	1136	4/14/2025
System Validation Dipole	SPEAG	D2300V2	1058	10/13/2024
System Validation Dipole*	SPEAG	D2450V2	748	2/8/2025
System Validation Dipole	SPEAG	D2600V2	1006	10/13/2024
System Validation Dipole*	SPEAG	D3500V2	1060	2/7/2025
System Validation Dipole	SPEAG	D5GHzV2	1168	11/15/2024
System Validation Dipole*	SPEAG	D6.5GHzV2	1033	3/15/2025
System Validation Dipole*	SPEAG	CLA13	1008	1/12/2025

Note(s):

*Dipole Calibration Date has been extended past 1 year. Impedance measurements have been performed to validate Dipole performance. Refer to Appendix K for Dipole Impedance measurements.

System Check

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
Signal Genarator	R&S	SMB 100A	180968-gX	2/16/2025
Power Meter	Keysight	N1912A	MY551960004	1/23/2025
Power Sensor	Agilent	N1921A	MY522600009	1/23/2025
Power Sensor	Agilent	N1921A	MY522700022	1/23/2025
Bi-directional coupler	Werlatone	C8060-102	2148	N/A
Directional coupler	Anatech Electronics	AMOR5-100DC869	4	N/A
Low Frequency Amplifier	Mini Circuits	ZHL-42W	QA1240001	N/A
DC Power Supply	Sorensen	XT 15-4	1802A01877	N/A
Signal Genarator	R&S	SMB 100A	180970-zC	2/14/2025
Power Meter	HP	437B	3125U09516	1/23/2025
Power Sensor	HP	8481A	2237A31744	1/24/2025
Power Sensor	R&S	NRP18A	100995-hs	2/22/2025
Directional coupler	Mini Circuits	ZUDC10-83-S+	2026	N/A
Signal Genarator	R&S	SMB 100A	180969-yC	2/21/2025
Power Meter	HP	437B	3125U11364	1/23/2025
Power Meter	Keysight	N1912A	MY50001018	2/5/2025
Power Sensor	HP	8481A	3318A92374	1/31/2025
Power Sensor	Agilent	N1921A	MY53260001	1/31/2025
Bi-directional coupler	Werlatone	C8060-102	4736	N/A

Other

Name of Equipment	Manufacturer	Type/Model	Serial No.	Cal. Due Date
Power Meter	Keysight	N1911A	MY55196007	1/31/2025
Power Sensor	Agilent	N1921A	MY53020038	1/31/2025
Wideband Radio Communication Tester	R&S	CMW500	171873-pw	2/28/2025
Wideband Radio Communication Tester	R&S	CMW500	164541-Ci	2/28/2025
Wideband Radio Communication Tester	Agilent	UXM	245173	2/28/2025
Spectrum Analyzer	Agilent	E4446A	MY45300064	2/28/2025

5. Measurement Uncertainty

Per KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be $\leq 30\%$, for a confidence interval of $k = 2$. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. Therefore, the measurement uncertainty is not required.

6. Dielectric Property Measurements & System Check

6.1. Dielectric Property Measurements

The temperature of the tissue-equivalent medium used during measurement must also be within 18°C to 25°C and within $\pm 2^\circ\text{C}$ of the temperature when the tissue parameters are characterized.

The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements. The parameters should be re-measured after each 3 – 4 days of use; or earlier if the dielectric parameters can become out of tolerance; for example, when the parameters are marginal at the beginning of the measurement series.

Tissue dielectric parameters were measured at the low, middle and high frequency of each operating frequency range of the test device.

The dielectric constant (ϵ_r) and conductivity (σ) of typical tissue-equivalent media recipes are expected to be within $\pm 5\%$ of the required target values; but for SAR measurement systems that have implemented the SAR error compensation algorithms documented in IEEE Std 1528-2013, to automatically compensate the measured SAR results for deviations between the measured and required tissue dielectric parameters, the tolerance for ϵ_r and σ may be relaxed to $\pm 10\%$. This is limited to frequencies $\leq 3\text{ GHz}$.

Tissue Dielectric Parameters

FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz

Target Frequency (MHz)	Head		Body	
	ϵ_r	σ (S/m)	ϵ_r	σ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800 – 2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
3000	38.5	2.40	52.0	2.73
5000	36.2	4.45	49.3	5.07
5100	36.1	4.55	49.1	5.18
5200	36.0	4.66	49.0	5.30
5300	35.9	4.76	48.9	5.42
5400	35.8	4.86	48.7	5.53
5500	35.6	4.96	48.6	5.65
5600	35.5	5.07	48.5	5.77
5700	35.4	5.17	48.3	5.88
5800	35.3	5.27	48.2	6.00

Dielectric Property Measurements

SAR Lab	Date	Band (MHz)	Tissue Type	Frequency (MHz)	Relative Permittivity (ϵ_r)			Conductivity (σ)		
					Measured	Target	Delta	Measured	Target	Delta
1	5/6/2024	1950	Head	1950	39.95	40.00	-0.12%	1.38	1.40	-1.71%
				1920	39.98	40.00	-0.05%	1.36	1.40	-2.79%
				2020	39.92	39.96	-0.11%	1.42	1.42	0.03%
1	5/6/2024	2300	Head	2300	39.50	39.47	0.07%	1.61	1.66	-3.41%
				2350	39.43	39.38	0.12%	1.64	1.71	-3.73%
				2400	39.35	39.30	0.14%	1.68	1.75	-4.32%
1	5/6/2024	2600	Head	2600	39.11	39.01	0.25%	1.83	1.96	-6.74%
				2495	39.23	39.14	0.22%	1.74	1.85	-5.82%
				2690	38.96	38.90	0.16%	1.90	2.06	-7.60%
1	5/6/2024	3700	Head	3700	40.50	37.70	7.42%	2.88	3.12	-7.74%
				3500	40.80	37.93	7.57%	2.69	2.91	-7.51%
				3800	40.35	37.59	7.35%	2.97	3.22	-7.63%
2	5/6/2024	6500	Head	6500	35.02	34.50	1.51%	6.21	6.07	2.31%
				6000	36.07	35.10	2.76%	5.65	5.48	3.05%
				7200	33.70	33.70	0.00%	7.16	6.89	3.86%
2	5/6/2024	5250	Head	5250	37.40	35.93	4.08%	4.78	4.70	1.72%
				5150	37.55	36.05	4.17%	4.63	4.60	0.68%
				5350	37.28	35.82	4.08%	4.92	4.80	2.32%
2	5/6/2024	5850	Head	5850	36.20	35.30	2.55%	5.49	5.32	3.10%
				5900	36.10	35.20	2.56%	5.55	5.38	3.12%
				5925	36.10	35.20	2.56%	5.59	5.40	3.54%
2	5/6/2024	2450	Head	2450	39.78	39.20	1.48%	1.80	1.80	-0.28%
				2400	39.86	39.30	1.43%	1.76	1.75	0.36%
				2500	39.73	39.14	1.52%	1.83	1.85	-1.24%
2	5/7/2024	13	Head	13	54.21	55.00	-1.44%	0.72	0.75	-4.60%
				12	54.22	55.00	-1.42%	0.72	0.75	-4.60%
				14	54.15	55.00	-1.55%	0.72	0.75	-4.59%

6.2. System Check

SAR system verification is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device. The same SAR probe(s) and tissue-equivalent media combinations used with each specific SAR system for system verification must be used for device testing. When multiple probe calibration points are required to cover substantially large transmission bands, independent system verifications are required for each probe calibration point. A system verification must be performed before each series of SAR measurements using the same probe calibration point and tissue-equivalent medium. Additional system verification should be considered according to the conditions of the tissue-equivalent medium and measured tissue dielectric parameters, typically every three to four days when the liquid parameters are re-measured or sooner when marginal liquid parameters are used at the beginning of a series of measurements.

System Performance Check Measurement Conditions:

- The measurements were performed in the flat section of the TWIN SAM or ELI phantom, shell thickness: 2.0 $\pm$ 0.2 mm (bottom plate) filled with Body or Head simulating liquid of the following parameters.
- The depth of tissue-equivalent liquid in a phantom must be $\geq$ 15.0 cm for SAR measurements $\leq$ 3 GHz and $\geq$ 10.0 cm for measurements $>$ 3 GHz.
- The DASY system with an E-Field Probe was used for the measurements.
- The dipole was mounted on the small tripod so that the dipole feed point was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 10 mm (above 1 GHz) and 15 mm (below 1 GHz) from dipole center to the simulating liquid surface.
- The coarse grid with a grid spacing of 15 mm was aligned with the dipole.
For 5 GHz band - The coarse grid with a grid spacing of 10 mm was aligned with the dipole.
- Special 7x7x7 (below 3 GHz) and/or 8x8x7 (above 3 GHz) fine cube was chosen for the cube.
- Distance between probe sensors and phantom surface was set to 3 mm.
For 5 GHz band - Distance between probe sensors and phantom surface was set to 2.5 mm
- The dipole input power (forward power) was 100 mW.
- The results are normalized to 1 W input power.

System Check Results

The 1-g and 10-g SAR measured with a reference dipole, using the required tissue-equivalent medium at the test frequency, must be within $\pm 10\%$ of the manufacturer calibrated dipole SAR target. Refer to Appendix B for the SAR System Check Plots.

SAR Lab	Date	Tissue Type	Dipole Type & Serial Number	Dipole Cal. Due Date	Measured results for 1-g SAR				Measured results for 10-g SAR				Plot No.									
					Zoom Scan at 100 mW	Normalize to 1 W	Target (Ref. Value)	Delta ±10%	Zoom Scan at 100 mW	Normalize to 1 W	Target (Ref. Value)	Delta ±10%										
1	5/7/2024	Head	D1950V3 SN: 1136	4/14/2024	4.12	41.2	40.2	2.5%	2.15	21.5	20.9	2.9%	1									
1	5/7/2024	Head	D2300V2 SN: 1058	10/13/2024	4.57	45.7	48.5	-5.8%	2.21	22.1	23.6	-6.4%	2									
1	5/7/2024	Head	D2600V2 SN: 1006	10/13/2024	5.05	50.5	56.1	-10.0%	2.29	22.9	25.4	-9.8%	3									
1	5/7/2024	Head	D3500V2 SN: 1060	2/7/2024	5.96	59.6	65.7	-9.3%	2.29	22.9	24.9	-8.0%	4									
2	5/6/2024	Head	D5GHzV2 SN: 1168 (5.25 GHz)	11/15/2024	8.03	80.3	77.0	4.3%	2.29	22.9	22.3	2.7%	5									
2	5/6/2024	Head	D5GHzV2 SN: 1168 (5.85 GHz)	11/15/2024	8.22	82.2	80.1	2.6%	2.31	23.1	22.8	1.3%	6									
2	5/6/2024	Head	D2450V2 SN: 748	2/8/2024	4.89	48.9	51.7	-5.4%	2.28	22.8	24.2	-5.8%	7									
2	5/7/2024	Head	CLA13 SN: 1008	1/12/2024	0.059	0.59	0.54	8.5%	0.037	0.37	0.34	9.5%	8									
SAR Lab	Date	Tissue Type	Dipole Type & Serial Number	Dipole Cal. Due Date	Input Power (dBm)	Measured results for 1-g SAR				Measured results for 8-g SAR				Measured results for 10-g SAR				Measured results for APD 4cm² SAR				Plot No.
						Zoom Scan	Normalize to 1 W	Target (Ref. Value)	Delta ±10%	Zoom Scan at 100 mW	Normalize to 1 W	Target (Ref. Value)	Delta ±10%	Zoom Scan at 100 mW	Normalize to 1 W	Target (Ref. Value)	Delta ±10%	Zoom Scan at 100 mW	Normalize to 1 W	Target (Ref. Value)	Delta ±10%	
2	5/6/2024	Head	D6.5GHzV2 SN: 1033	3/15/2024	20.00	29.8	298.0	288.0	3.5%	6.61	66.1	64.7	2.2%	5.42	54.2	53.1	2.1%	132	1320	1300	1.5%	

7. Test Rationale

7.1. Purpose

This application for certification is leveraging the data reuse procedure from TCB workshop April 2021; RF Exposure Procedures (Remarks on Test Reductions via Data Referencing for Closely Related Products) based on reference FCC ID: A4RG2YBB (UL report# 5107843-S1) to cover variants FCC ID: A4RGUR25. The major difference between the reference model and the variant models is that support for some LTE/5GNR FR1 bands is disabled via software and mmWave module is removed in the variant models. All other circuitry and features are identical.

7.2. Data Reuse Approach

Full RF exposure testing was performed on the reference model. The configurations with the highest SAR results for each equipment class were identified. These configurations were tested on the variant models.

The variation in SAR results was well within the uncertainty budget of the SAR test equipment. The variant SAR results and worst-case reference model SAR results are summarized in § 1.

8. Measured and Reported (Scaled) SAR Results

															A4RGUR25		Delta %	Plot No.
Equipment Class	Technology	Band	Antenna	RF Exposure Condition	Mode	Power Mode(s)	Dist (mm)	Test Position	Channel	Freq. (MHz)	RB	Duty Cycle (%)	Max Output Pwr (dBm)	Meas. (dBm)	1-g Meas. (W/kg)	1-g Scaled (W/kg)	1g	Plot No.
TNB	NTN	S-band	ANT 1	Body-worn	BPSK	Index 5	10	Back	Low	2000.1	N/A	79.92%	23.0	22.1	0.649	0.824	-16.5%	1
DTS	WLAN	2.4GHz	ANT 3 (Chain 0)	Head	802.11b	Index 1	0	Right Cheek	11	2462.0	N/A	100.0%	15.5	14.8	0.441	0.518	-36.8%	2
NI	WLAN	5.3GHz	ANT 3 (Chain 0)	Head	802.11n MIMO (HT40)	Index 1	0	Right Cheek	54	5270.0	N/A	96.67%	13.5	11.6	0.292	0.468	-13.4%	3
DSS	Bluetooth	2.4G	ANT 3 (Chain 0)	Body & Hotspot	GFSK	Index 2	10	Back	78	2480.0	N/A	76.40%	15.0	14.1	0.143	0.192	-30.2%	4
PCE	LTE	7	ANT 0	Body-worn	QPSK	Index 5	10	Back	20850	2510.0	1,49	N/A	21.5	20.6	0.703	0.865	-12.1%	5
CBE	FR1	n48	ANT 1	Body-worn	OFDM 11/2 BPSK	Index 5	10	Back	642888	3643.32	50,28	N/A	22.4	21.4	0.304	0.383	-36.1%	6

															A4RGUR25		Delta %	Plot No.
Equipment Class	Technology	Band	Antenna	RF Exposure Condition	Mode	Power Mode(s)	Dist (mm)	Test Position	Channel	Freq. (MHz)	RB	Duty Cycle (%)	Max Output Pwr (dBm)	Meas. (dBm)	10-g Meas. (W/kg)	10-g Scaled (W/kg)	10g	Plot No.
TNB	NTN	S-band	ANT 1	Extremity	BPSK	Index 5	0	Edge Top	Low	2000.1	N/A	79.92%	23.0	22.1	1.60	2.03	-13.0%	7
NI	WLAN	5.9GHz	ANT 3 (Chain 0)	Extremity	802.11n MIMO (HT40)	Index 3	0	Edge Left	167	5835.0	N/A	96.67%	20.0	18.5	0.917	1.340	13.5%	8
PCE	LTE	30	ANT 0	Extremity	QPSK	Index 5	0	Edge Bottom	27710	2310.0	1,49	N/A	21.6	20.3	0.992	1.338	-45.8%	9

											A4RGUR25		Delta %	Plot No.
Equipment Class	Technology	Band	Antenna	RF Exposure Condition	Mode	Dist (mm)	Test Position	Channel	Freq. (MHz)		10-g Meas. (W/kg)	10-g Scaled (W/kg)	10g	Plot No.
DXX	NFC	ISO 15693	Primary	Extremity	Type A	0	Back	0	13.56		0.080		0.0%	10

															A4RGUR25		Delta %	Plot No.			
Equipment Class	Technology	Band	Antenna	RF Exposure Condition	Mode	Power Mode(s)	Dist (mm)	Test Position	Channel	Freq. (MHz)	Duty Cycle (%)	Max Output Pwr (dBm)	Meas. (dBm)		1-g Meas. (W/kg)	1-g Scaled (W/kg)	APD Meas. (W/m²)	APD Scaled (W/m²)	1g	APD	Plot No.
6CD	WLAN	6GHz	ANT 3 (Chain 0)	Head	802.11ax (HE160)	Index 1	0	Right Cheek	15	6025.0	94.16%	12.0	10.2		0.194	0.312	1.38	2.22	-21.1%	-22.0%	11

															A4RGUR25		Delta %	Plot No.			
Equipment Class	Technology	Band	Antenna	RF Exposure Condition	Mode	Power Mode(s)	Dist (mm)	Test Position	Channel	Freq. (MHz)	Duty Cycle (%)	Max Output Pwr (dBm)	Meas. (dBm)		10-g Meas. (W/kg)	10-g Scaled (W/kg)	APD Meas. (W/m²)	APD Scaled (W/m²)	10g	APD	Plot No.
6CD	WLAN	6GHz	ANT 3 (Chain 0)	Extremity	802.11ax (HE160)	Index 3	0	Edge Left	207	6985.0	94.16%	15.0	13.4		0.333	0.511	7.78	11.94	46.1%	43.8%	12

Appendixes

Refer to separated files for the following appendixes.

Appendix A: SAR Setup Photos

Appendix B: SAR System Check Plots

Appendix C: SAR Highest Test Plots

Appendix D: Tissue Ingredients

Appendix E: Probe Certificates

Appendix F: Dipole Certificates