



FCC PART 15.247

TEST REPORT

For

Shenzhen Teslong Technology Co., Ltd.

2nd Floor, Block 4, Jinhua Industrial Park, East of Donghuan 2 avenue, Longhua, Shenzhen, China

FCC ID: 2AXAVSA39W2101

Report Type: Original Report	Product Type: Digital Oscope
Report Number: SZ4210319-07490E-00	
Report Date: 2021-07-21	
Jacob Kong	
Reviewed By: RF Engineer	<i>Jacob Kong</i>
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY.....	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	6
EUT EXERCISE SOFTWARE	6
DUTY CYCLE	7
SUPPORT EQUIPMENT LIST AND DETAILS	7
EXTERNAL I/O CABLE.....	7
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
TEST EQUIPMENT LIST	9
FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE	10
APPLICABLE STANDARD	10
FCC §15.203 - ANTENNA REQUIREMENT.....	11
APPLICABLE STANDARD	11
ANTENNA CONNECTOR CONSTRUCTION	11
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	12
APPLICABLE STANDARD	12
EUT SETUP	12
EMI TEST RECEIVER SETUP.....	12
TEST PROCEDURE	12
CORRECTED FACTOR & MARGIN CALCULATION	13
TEST DATA	13
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	16
APPLICABLE STANDARD	16
EUT SETUP	16
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	17
TEST PROCEDURE	17
CORRECTED AMPLITUDE & MARGIN CALCULATION	17
TEST DATA	17
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	27
APPLICABLE STANDARD	27
TEST PROCEDURE	27
TEST DATA	27
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	28
APPLICABLE STANDARD	28
TEST PROCEDURE	28
TEST DATA	28

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	29
APPLICABLE STANDARD	29
TEST PROCEDURE	29
TEST DATA	29
FCC §15.247(e) - POWER SPECTRAL DENSITY	30
APPLICABLE STANDARD	30
TEST PROCEDURE	30
TEST DATA	30
APPENDIX Wi-Fi.....	31
APPENDIX A: DTS BANDWIDTH	31
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH	38
APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER	45
APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY	46
APPENDIX E: BAND EDGE MEASUREMENTS.....	53
APPENDIX F: DUTY CYCLE	57

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	Digital Oscope
Tested Model	SA39W
Frequency Range	Wi-Fi: 2412-2472MHz
Maximum Conducted Peak Power	Wi-Fi: 12.35(802.11b), 14.88dBm(802.11g) 13.33dBm(802.11n-HT20), 12.46dBm(802.11n-HT40)
Modulation Technique	Wi-Fi: DSSS, OFDM
Antenna Specification*	1.5dBi(It is provided by the applicant)
Voltage Range	DC3.7Vbattery or DC5V from USB port
Date of Test	2021-04-22 to 2021-07-16
Sample number	SZ4210319-07490E-RF -S_10G (Assigned by BACL, Shenzhen)
Received date	2021-03-19
Sample/EUT Status	Good condition
Adapter information	N/A

Objective

This report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters. Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF Output Power with Power meter		±0.73dB
RF conducted test with spectrum		±1.6dB
AC Power Lines Conducted Emissions		±1.95dB
Emissions, Radiated	Below 1GHz	±4.75dB
	Above 1GHz	±4.88dB
Temperature		±1 °C
Humidity		±6%
Supply voltages		±0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 802.11b, 802.11g and 802.11n-HT20 mode, 13 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	12	2467
6	2437	13	2472
7	2442	/	/

For 802.11b, 802.11g, 802.11n-HT20 mode, EUT was tested with Channel 1, 7 and 13

For 802.11n-HT40 mode, 9 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2422	6	2447
2	2427	7	2452
3	2432	8	2457
4	2437	9	2462
5	2442	/	/

EUT was tested with Channel 1, 5 and 9.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

“Wifi Test Toolv1.4.1.exe” software was use to the EUT tested

The device was tested with the worst case was performed as below:

Mode	Data rate	Power level*		
		Low channel	Middle channel	High channel
802.11b	1 Mbps	6	7	10
802.11g	6 Mbps	2	2	2
802.11n-HT20	MCS0	2	2	2
802.11n-HT40	MCS0	2	2	1

The software and power level was provided by the applicant.

Duty cycle


Test Result Compliant. Please refer to the Appendix .

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
BULL	Socket	GN-212	A37209315081183
YEZZ	Adapter	YW1000US	Unknown

External I/O Cable

Cable Description	Length (m)	From Port	To
Un-Shielded Detachable USB Cable	1.0	Adapter	EUT

Block Diagram of Test Setup

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b) (1)& §2.1093	RF Exposure	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2020/08/04	2021/08/03
Rohde & Schwarz	LISN	ENV216	101613	2020/08/04	2021/08/03
Rohde & Schwarz	Transient Limitor	ESH3Z2	DE25985	2020/11/29	2021/11/28
Unknown	CE Cable	CE Cable	UF A210B-1-0720-504504	2020/11/29	2021/11/28
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
Radiated Emission Test					
R&S	EMI Test Receiver	ESR3	102455	2020/08/04	2021/08/03
Sonoma instrument	Pre-amplifier	310 N	186238	2020/08/04	2021/08/03
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2020/12/22	2023/12/21
Unknown	Cable 2	RF Cable 2	F-03-EM197	2020/11/29	2021/11/28
Unknown	Cable	Chamber Cable 1	F-03-EM236	2020/11/29	2021/11/28
Rohde & Schwarz	Auto test software	EMC 32	V9.10	NCR	NCR
Rohde & Schwarz	Spectrum Analyzer	FSV40-N	102259	2020/08/04	2021/08/03
COM-POWER	Pre-amplifier	PA-122	181919	2020/11/29	2021/11/28
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2020/11/28	2021/11/27
Sunol Sciences	Horn Antenna	3115	9107-3694	2021/01/15	2024/01/14
Insulated Wire Inc.	RF Cable	SPS-2503-3150	02222010	2020/11/29	2021/11/28
Unknown	RF Cable	W1101-EQ1 OUT	F-19-EM005	2020/11/29	2021/11/28
SNSD	Band Reject filter	BSF2402-2480MN-0898-001	2.4G filter	2021/04/20	2022/04/20
Ducommun Technologies	Horn antenna	ARH-4223-02	1007726-021304	2020/12/06	2023/12/05
RF Conducted Test					
Tonscend Corporation	RF control Unit	JS0806-2	19D8060154	2020/08/04	2021/08/03
Rohde & Schwarz	Signal and Spectrum Analyzer	FSV40	101473	2020/08/04	2021/08/03
Unknown	RF Cable	Unknown	Unknown	2020/11/29	2021/11/28

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.

2. Power and distance are rounded to the nearest mW and mm before calculation.

3. The result is rounded to one decimal place for comparison.

4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

Measurement Result

For worst case:

Mode	Frequency (MHz)	Max Tune-up Conducted Power (dBm)	Max Tune-up Conducted Power (mW)	Calculated Distance (mm)	Calculated value	Threshold (1-g SAR)	SAR Test Exclusion
Wi-Fi	2472	9.5	8.91	5	2.8	3.0	Yes

Result: No SAR test is required

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
 - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one internal antenna arrangement, which was permanently attached and the antenna gain is 1.5 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$


Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	65 %
ATM Pressure:	101.0 kPa

The testing was performed by Haiguo Li on 2021-04-22.


EUT operation mode: Charging&Transmitting

AC 120V/60 Hz, Line**Final Result 1**

Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.470890	41.1	9.000	L1	19.8	15.4	56.5
0.541810	45.9	9.000	L1	19.8	10.1	56.0
0.542010	46.0	9.000	L1	19.8	10.0	56.0
0.600910	36.5	9.000	L1	19.8	19.5	56.0
0.904470	36.8	9.000	L1	19.8	19.2	56.0
1.002850	34.5	9.000	L1	19.9	21.5	56.0

Final Result 2

Frequency (MHz)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.470890	32.2	9.000	L1	19.8	14.3	46.5
0.541810	37.0	9.000	L1	19.8	9.0	46.0
0.542010	37.2	9.000	L1	19.8	8.8	46.0
0.600910	26.5	9.000	L1	19.8	19.5	46.0
0.904470	28.4	9.000	L1	19.8	17.6	46.0
1.002850	25.2	9.000	L1	19.9	20.8	46.0

AC 120V/60 Hz, Neutral**Final Result 1**

Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.474890	45.4	9.000	N	19.8	11.0	56.4
0.541990	50.3	9.000	N	19.8	5.7	56.0
0.545750	51.5	9.000	N	19.8	4.5	56.0
0.608910	40.4	9.000	N	19.8	15.6	56.0
0.904350	41.3	9.000	N	19.7	14.7	56.0
1.554450	38.1	9.000	N	19.8	17.9	56.0

Final Result 2

Frequency (MHz)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.478000	35.8	9.000	N	19.8	10.6	46.4
0.482000	30.4	9.000	N	19.8	15.9	46.3
0.550000	40.8	9.000	N	19.8	5.2	46.0
0.618000	31.8	9.000	N	19.8	14.2	46.0
0.910000	31.5	9.000	N	19.7	14.5	46.0
1.574000	24.0	9.000	N	19.8	22.0	46.0


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	> 1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$


Test Data

Environmental Conditions

Temperature:	26.1~27 °C
Relative Humidity:	44~58 %
ATM Pressure:	101 kPa

The testing was performed by Zero Yan on 2021-06-01 for below 1GHz and Bruce Lin from 2021-06-09 to 2021-07-16 for above 1GHz.

EUT operation mode: Charging&Transmitting

30 MHz~1 GHz:**Final_Result**

Frequency (MHz)	QuasiPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
168.024375	39.17	43.50	4.33	242.0	H	75.0	-12.0
336.006250	40.64	46.00	5.36	114.0	H	77.0	-9.2
371.978250	41.44	46.00	4.56	114.0	H	86.0	-8.2
432.061750	41.23	46.00	4.77	109.0	H	67.0	-6.2
599.993125	44.50	46.00	1.50	183.0	H	81.0	-4.5

Critical_Freqs

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
131.971250	37.11	43.50	6.39	300.0	H	13.0	-10.4

1 GHz-25 GHz (Wi-Fi):**802.11b Mode:**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2412 MHz)									
2389.59	28.53	PK	68	1.4	H	31.87	60.40	74	13.60
2389.59	14.62	Ave.	68	1.4	H	31.87	46.49	54	7.51
2494.40	29.03	PK	334	1.4	H	32.13	61.16	74	12.84
2494.40	14.71	Ave.	334	1.4	H	32.13	46.84	54	7.16
4824.00	49.1	PK	44	1.5	H	6.28	55.38	74	18.62
4824.00	44.11	Ave.	44	1.5	H	6.28	50.39	54	3.61
Middle Channel (2442MHz)									
4884.00	48.48	PK	68	1.2	H	6.76	55.24	74	18.76
4884.00	42.84	Ave.	68	1.2	H	6.76	49.60	54	4.40
High channel (2472 MHz)									
2351.51	29.75	PK	333	2.5	H	31.77	61.52	74	12.48
2351.51	14.49	Ave.	333	2.5	H	31.77	46.26	54	7.74
2496.84	29.16	PK	106	1.3	H	32.13	61.29	74	12.71
2496.84	15.01	Ave.	106	1.3	H	32.13	47.14	54	6.86
4944.00	48.27	PK	157	1.7	H	6.76	55.03	74	18.97
4944.00	45.06	Ave.	157	1.7	H	6.76	51.82	54	2.18

802.11g Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2412 MHz)									
2389.97	29.03	PK	107	2.4	H	31.87	60.90	74	13.10
2389.97	14.59	Ave.	107	2.4	H	31.87	46.46	54	7.54
2483.51	29.29	PK	107	1.6	H	32.13	61.42	74	12.58
2483.51	14.64	Ave.	107	1.6	H	32.13	46.77	54	7.23
4824.00	52.26	PK	159	1.7	H	6.28	58.54	74	15.46
4824.00	35.64	Ave.	159	1.7	H	6.28	41.92	54	12.08
7236.00	41.87	PK	109	2.5	H	11.93	53.80	74	20.20
7236.00	26.69	Ave.	109	2.5	H	11.93	38.62	54	15.38
Middle Channel (2442 MHz)									
4884.00	50.76	PK	318	1.2	H	6.76	57.52	74	16.48
4884.00	35.22	Ave.	318	1.2	H	6.76	41.98	54	12.02
7326.00	41.47	PK	242	1.3	H	11.66	53.13	74	20.87
7326.00	26.64	Ave.	242	1.3	H	11.66	38.30	54	15.70
High Channel (2472 MHz)									
2389.74	29.13	PK	149	1.2	H	31.87	61.00	74	13.00
2389.74	14.77	Ave.	149	1.2	H	31.87	46.64	54	7.36
2483.59	33.33	PK	173	1.0	H	32.13	65.46	74	8.54
2483.59	18.83	Ave.	173	1.0	H	32.13	50.96	54	3.04
4944.00	49.14	PK	213	1.0	H	6.76	55.90	74	18.10
4944.00	34.29	Ave.	213	1.0	H	6.76	41.05	54	12.95
7416.00	41.68	PK	93	1.5	H	12.39	54.07	74	19.93
7416.00	26.74	Ave.	93	1.5	H	12.39	39.13	54	14.87



802.11n-HT20 Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2412 MHz)									
2389.83	29.05	PK	179	1.7	H	31.87	60.92	74	13.08
2389.83	14.71	Ave.	179	1.7	H	31.87	46.58	54	7.42
2483.68	29.45	PK	211	2.1	H	32.13	61.58	74	12.42
2483.68	14.56	Ave.	211	2.1	H	32.13	46.69	54	7.31
4824.00	49.86	PK	233	2.5	H	6.28	56.14	74	17.86
4824.00	33.12	Ave.	233	2.5	H	6.28	39.40	54	14.60
7236.00	42.15	PK	165	1.4	H	11.93	54.08	74	19.92
7236.00	27.14	Ave.	165	1.4	H	11.93	39.07	54	14.93
Middle Channel (2442 MHz)									
4884.00	49.27	PK	255	1.6	H	6.76	56.03	74	17.97
4884.00	32.86	Ave.	255	1.6	H	6.76	39.62	54	14.38
7326.00	42.17	PK	82	2.4	H	11.66	53.83	74	20.17
7326.00	27.53	Ave.	82	2.4	H	11.66	39.19	54	14.81
High Channel (2472 MHz)									
2389.41	29.89	PK	350	1.5	H	31.87	61.76	74	12.24
2389.41	14.65	Ave.	350	1.5	H	31.87	46.52	54	7.48
2493.32	33.13	PK	218	1.1	H	32.13	65.26	74	8.74
2493.32	21.19	Ave.	218	1.1	H	32.13	53.32	54	0.68
4944.00	48.87	PK	81	2.3	H	6.76	55.63	74	18.37
4944.00	32.52	Ave.	81	2.3	H	6.76	39.28	54	14.72
7416.00	42.47	PK	193	1.8	H	12.39	54.86	74	19.14
7416.00	27.88	Ave.	193	1.8	H	12.39	40.27	54	13.73


802.11n-HT40 Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2422 MHz)									
2389.70	29.61	PK	291	1.7	H	31.87	61.48	74	12.52
2389.70	14.74	Ave.	291	1.7	H	31.87	46.61	54	7.39
2483.91	29.40	PK	304	2.4	H	32.13	61.53	74	12.47
2483.91	14.71	Ave.	304	2.4	H	32.13	46.84	54	7.16
4844.00	48.78	PK	103	1.5	H	6.28	55.06	74	18.94
4844.00	32.91	Ave.	103	1.5	H	6.28	39.19	54	14.81
Middle Channel (2442 MHz)									
4884.00	49.15	PK	303	1.4	H	6.76	55.91	74	18.09
4884.00	32.74	Ave.	303	1.4	H	6.76	39.50	54	14.50
High Channel (2462 MHz)									
2389.27	28.92	PK	279	2.1	H	31.87	60.79	74	13.21
2389.27	14.68	Ave.	279	2.1	H	31.87	46.55	54	7.45
2484.37	30.65	PK	330	1.5	H	32.13	62.78	74	11.22
2484.37	16.58	Ave.	330	1.5	H	32.13	48.71	54	5.29
4924.00	48.75	PK	126	1.4	H	6.76	55.51	74	18.49
4924.00	32.55	Ave.	126	1.4	H	6.76	39.31	54	14.69


Pre-scan with 802.11b Mode, high channel
Horizontal



Vertical




Date: 9.JUN.2021 13:21:21




Date: 9.JUN.2021 14:06:03

Average Horizontal





Date: 9.JUN.2021 13:15:36



Date: 9.JUN.2021 14:01:19

Vertical




FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

Temperature:	27 °C
Relative Humidity:	57 %
ATM Pressure:	101.0 kPa

The testing was performed by Bravos Zhao on 2021-07-06.

EUT operation mode: Transmitting

Test Result Compliant. Please refer to the Appendix Wi-Fi.


FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	24.6~27 °C
Relative Humidity:	51~57 %
ATM Pressure:	100.3~101.0 kPa

The testing was performed by Bravos Zhao on 2021-07-06 and 2021-07-16.

EUT operation mode: Transmitting


Test Result Compliant. Please refer to the Appendix Wi-Fi.

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

**Test Data****Environmental Conditions**

Temperature:	24.6~27 °C
Relative Humidity:	51~57 %
ATM Pressure:	100.3~101.0 kPa

The testing was performed by Bravos Zhao on 2021-07-06.

EUT operation mode: Transmitting

Test Result Compliant. Please refer to the Appendix Wi-Fi.


FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to: $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
3. Set the VBW $\geq 3 \times \text{RBW}$.
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Data

Environmental Conditions

Temperature:	24.6~27 °C
Relative Humidity:	51~57 %
ATM Pressure:	100.3~101.0 kPa

The testing was performed by Bravos Zhao on 2021-07-06 and 2021-07-16.

EUT operation mode: Transmitting

Test Result Compliant. Please refer to the Appendix Wi-Fi.


APPENDIX Wi-Fi

Appendix A: DTS Bandwidth


Test Result

TestMode	Antenna	Channel	DTS BW [MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	9.120	0.5	PASS
		2442	9.120	0.5	PASS
		2472	9.120	0.5	PASS
11G	Ant1	2412	15.800	0.5	PASS
		2442	15.240	0.5	PASS
		2472	15.200	0.5	PASS
11N20SISO	Ant1	2412	15.560	0.5	PASS
		2442	15.240	0.5	PASS
		2472	15.200	0.5	PASS
11N40SISO	Ant1	2422	35.280	0.5	PASS
		2442	35.280	0.5	PASS
		2462	35.280	0.5	PASS

Test Graphs




11B_Ant1_2442




Date: 6.JUL.2021 16:40:31

11B_Ant1_2472




Date: 6.JUL.2021 16:42:20

11G_Ant1_2412




Date: 6.JUL.2021 16:49:01

11G_Ant1_2442




Date: 6.JUL.2021 16:46:54

11G Ant1 2472




Date: 6.JUL.2021 16:44:55

11N20SISO Ant1 2412




Date: 6.JUL.2021 16:51:15

11N20SISO Ant1 2442





Date: 6.JUL.2021 16:54:14

11N20SISO Ant1 2472



Date: 6.JUL.2021 16:55:53






Appendix B: Occupied Channel Bandwidth


Test Result

TestMode	Antenna	Channel	OCB [MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	14.346	---	PASS
		2442	14.306	---	PASS
		2472	14.226	---	PASS
11G	Ant1	2412	17.622	---	PASS
		2442	17.862	---	PASS
		2472	17.702	---	PASS
11N20SISO	Ant1	2412	18.581	---	PASS
		2442	18.741	---	PASS
		2472	18.342	---	PASS
11N40SISO	Ant1	2422	37.882	---	PASS
		2442	37.802	---	PASS
		2462	37.802	---	PASS


Test Graphs




11B_Ant1_2442



11B_Ant1_2472




11G_Ant1_2412




Date: 6.JUL.2021 16:49:11

11G_Ant1_2442




Date: 6.JUL.2021 16:47:04

11G Ant1 2472




Date: 6.JUL.2021 16:45:05

11N20SISO Ant1 2412




Date: 6.JUL.2021 16:51:25

11N20SISO Ant1 2442




Date: 6.JUL.2021 16:54:24

11N20SISO Ant1 2472




Date: 6.JUL.2021 16:56:03

11N40SISO Ant1 2422




Date: 6.JUL.2021 16:50:17

11N40SISO Ant1 2442



Date: 6.JUL.2021 17:01:29



Appendix C: Maximum conducted output power**Test Result (PK)**


TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	2412	9.47	≤30	PASS
		2442	10.19	≤30	PASS
		2472	12.35	≤30	PASS
11G	Ant1	2412	13.11	≤30	PASS
		2442	13.86	≤30	PASS
		2472	14.88	≤30	PASS
11N20SISO	Ant1	2412	12.67	≤30	PASS
		2442	13.33	≤30	PASS
		2472	13.26	≤30	PASS
11N40SISO	Ant1	2422	12.46	≤30	PASS
		2442	12.42	≤30	PASS
		2462	10.63	≤30	PASS

Test Result (AV)


TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	2412	7.47	≤30	PASS
		2442	8.13	≤30	PASS
		2472	9.40	≤30	PASS
11G	Ant1	2412	8.07	≤30	PASS
		2442	8.88	≤30	PASS
		2472	8.94	≤30	PASS
11N20SISO	Ant1	2412	8.04	≤30	PASS
		2442	8.77	≤30	PASS
		2472	8.85	≤30	PASS
11N40SISO	Ant1	2422	8.92	≤30	PASS
		2442	9.23	≤30	PASS
		2462	7.09	≤30	PASS

Appendix D: Maximum power spectral density**Test Result**

TestMode	Antenna	Channel	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-16.36	≤8	PASS
		2442	-15.58	≤8	PASS
		2472	-13.66	≤8	PASS
11G	Ant1	2412	-16.64	≤8	PASS
		2442	-16.19	≤8	PASS
		2472	-16.38	≤8	PASS
11N20SISO	Ant1	2412	-16.86	≤8	PASS
		2442	-16.21	≤8	PASS
		2472	-16.16	≤8	PASS
11N40SISO	Ant1	2422	-19.65	≤8	PASS
		2442	-19.12	≤8	PASS
		2462	-20.63	≤8	PASS


Test Graphs

11B_Ant1_2442




Date: 6.JUL.2021 16:40:47

11B_Ant1_2472




Date: 6.JUL.2021 16:42:35

11G_Ant1_2412




Date: 16.JUL.2021 10:01:15

11G_Ant1_2442




Date: 16.JUL.2021 10:01:57

11G Ant1 2472




Date: 16.JUL.2021 10:02:44

11N20SISO Ant1 2412




Date: 16.JUL.2021 10:03:50

11N20SISO Ant1 2442




Date: 16.JUL.2021 10:04:41

11N20SISO Ant1 2472




Date: 16.JUL.2021 10:05:29

11N40SISO Ant1 2422




Date: 16.JUL.2021 10:06:33

11N40SISO Ant1 2442




Date: 16.JUL.2021 10:07:11




Appendix E: Band edge measurements

Test Graphs




11G Ant1 Low 2412




Date: 6.JUL.2021 16:49:25

11G Ant1 High 2472




Date: 6.JUL.2021 16:45:19

11N20SISO_Ant1_Low_2412




Date: 6.JUL.2021 16:51:39

11N20SISO_Ant1_High_2472



Date: 6.JUL.2021 16:56:17




Appendix F: Duty Cycle

Test Result

TestMode	Antenna	Channel	TransmissionDuration [ms]	Transmission Period [ms]	Duty Cycle [%]
11B	Ant1	2442	30.00	30.00	100.00
11G	Ant1	2442	1.39	1.41	98.58
11N20SISO	Ant1	2442	1.30	1.32	98.48
11N40SISO	Ant1	2442	30.00	30.00	100.00

Test Graphs





***** END OF REPORT *****