



Test Report - FCC Part 1.1310/ MPE

Applicant: goTenna Inc.

Signature: _____

A handwritten signature in black ink, appearing to read "Tim Royer".

Sr. EMC Engineer
EMC-003838-NE



Name & Title: Tim Royer, EMC Engineer

Date of Signature 9/30/2024

Signature: _____

A handwritten signature in black ink, appearing to read "Kristoffer Costa".

Name & Title: Kristoffer Costa, EMC Technician

Date of Signature 9/30/2024

This test report relates only to the items tested as identified and is not valid for any subsequent changes or modifications made to the equipment under test.

Table of Contents

1.	APPLICANT INFORMATION.....	3
2.	LOCATION OF TESTING.....	3
2.1	TEST LABORATORY.....	3
3.	TEST SAMPLE(S) (EUT/DUT).....	3
3.1	DESCRIPTION OF THE EUT.....	4
4.	TEST METHODS & APPLICABLE REGULATORY LIMITS.....	5
4.1	TEST METHODS/STANDARDS/GUIDANCE:.....	5
4.1.1	<i>FCC Limits for Maximum Permissible Exposure (MPE)</i>	5
4.2	EQUATIONS.....	6
5.	RF EXPOSURE RESULTS	7
6.	HISTORY OF TEST REPORT CHANGES.....	8

1. Applicant Information

Applicant: goTenna Inc.
Address: 101 Hudson Street
Suite 1701
New Jersey, 07302, United States

2. Location of Testing

2.1 Test Laboratory

Timco Engineering Inc. is a subsidiary of Industrial Inspection & Analysis, Inc. ("IIA"). Testing was performed at IIA's permanent laboratory located at 13146 NW 86th Drive, Suite 400, Alachua, Florida 32615.

FCC test firm # 578780
FCC Designation # US1070
FCC site registration is under A2LA certificate # 0955.01
ISED Canada test site registration # 2056A
EU Notified Body # 1177
For all designations see A2LA scope # 0955.01

3. Test Sample(s) (EUT/DUT)

The test sample was received: 9/20/2024

Dates of Testing: 9/24/2024 – 9/27/2024

3.1 Description of the EUT

A description as well as unambiguous identification of the EUT(s) tested. Where more than one sample is required for technical reasons (such as the use of connected units for the purpose of conducted output power testing where the product units will have integral antennas), each specific test shall identify which unit was tested.

Identification	
FCC ID:	2ABVK373373
Brief Description	Mesh networking module
Model(s) #	900-00222
Firmware version	N/A
Software version	N/A
Serial Number	N/A

Technical Characteristics	
Frequency Range	142 MHz- 173.3 MHz
RF O/P Power (Max.)	5W
Modulation	FM
Bandwidth & Emission Class	F1D
Number of Channels	N/A
Duty Cycle	N/A
Antenna Connector	SMA
Voltage Rating (AC or Batt.)	12VDC

Antenna Characteristics			
Antenna	Frequency Range	Mode / BW	Antenna Gain
1	142 MHz- 173.3 MHz	n/a	6 dBi

- Note: Information such as antenna gain, firmware/software numbers are provided by manufacturer and cannot be validated by the test lab.

4. Test methods & Applicable Regulatory Limits

4.1 Test methods/Standards/Guidance:

The following guidance FCC KDB 447498 D01 General RF Exposure Guidance v06 was used for RF exposure evaluation as per FCC Part 1.1310 and FCC Part 2.1091 and part 2.1093. Full test results are available in this report.

4.1.1 FCC Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging Time (minutes)
A Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6

4.2 Equations

POWER DENSITY

$$E(V/m) = \text{SQRT} (30 * P * G) / d$$

$$Pd(W/m^2) = E^2 / 377$$

$$S = \text{EIRP} / (4 * \text{Pi} * D^2)$$

Where:

S = Power density, in mW/cm²

EIRP = Equivalent Isotropic Radiated Power, in mW

D = Separation distance in cm

Power density is converted from units of mW/cm² to units of W/m² by multiplying by 10.

DISTANCE

$$D = \text{SQRT} (\text{EIRP} / (4 * \text{Pi} * S))$$

Where:

D = Separation distance in cm

EIRP = Equivalent Isotropic Radiated Power, in mW

S = Power density in mW/cm²

SOURCE-BASED DUTY CYCLE (When applicable (for example, multi-slot mobile phone applications) A duty cycle factor may be applied.)

$$\text{Source-based time-average EIRP} = (\text{DC} / 100) * \text{EIRP}$$

Where:

DC = Duty Cycle in % as applicable.

EIRP = Equivalent Isotropic radiated Power, in mW

5. RF Exposure Results

MPE

Frequency Band	Evaluation Distance (cm)	Max Power + Tolerance (dBm)	Antenna Gain (dBi)	Duty Cycle (%)	EIRP (W)	Power Density	Limit for Controlled Exposure	Distance Required to meet Uncontrolled Exposure Limit (cm)
150-174 MHz	20	36.97	6.00	25%	4.9755	0.99 mW/cm ²	1 mW/cm ²	20.00

RESULT: Pass at DISTANCE 20 cm

6. History of Test Report Changes

Test Report #	Revision #	Description	Date of Issue
TR_16261-24_FCC 1.1310/ MPE_	1	Initial release	9/30/2024
	2	Updated sec 3.1	10/31/2021
	3	Updated pages 4 & 7	2/7/2025
	4	Updated pages 5 & 7	2/11/2025

END OF TEST REPORT
