

# **FCC Test Report**

Report No.: AGC07434230602FE10

FCC ID	:	2ARXB-B1B
PRODUCT DESIGNATION	:	Label Printer
BRAND NAME	:	NIIMBOT
MODEL NAME	:	NIIMBOT B1, B1, B1 Pro, B1 SE, NIIMBOT B1_X
APPLICANT	:	Wuhan Jingchen Intelligent Identification Technology Co., Ltd.
DATE OF ISSUE	:	Jun. 14, 2023
STANDARD(S)	:	FCC Part 15 Subpart C §15.225
<b>REPORT VERSION</b>	:	V 1.0







## **REPORT REVISE RECORD**

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Jun. 14, 2023	Valid	Initial Release



## **TABLE OF CONTENTS**

1. GENERAL INFORMATION	5
2. PRODUCT INFORMATION	6
2.1 PRODUCT TECHNICAL DESCRIPTION	6
2.2 TEST FREQUENCY LIST	6
2.3 RELATED SUBMITTAL(S) / GRANT (S)	7
2.4 TEST METHODOLOGY	7
2.5 SPECIAL ACCESSORIES	7
2.6 EQUIPMENT MODIFICATIONS	7
2.7 ANTENNA REQUIREMENT	7
3. TEST ENVIRONMENT	8
3.1 ADDRESS OF THE TEST LABORATORY	8
3.2 TEST FACILITY	8
3.3 ENVIRONMENTAL CONDITIONS	9
3.4 MEASUREMENT UNCERTAINTY	9
3.5 LIST OF EQUIPMENTS USED	
4.SYSTEM TEST CONFIGURATION	11
4.1 EUT CONFIGURATION	11
4.2 EUT EXERCISE	11
4.3 CONFIGURATION OF TESTED SYSTEM	11
4.4 EQUIPMENT USED IN TESTED SYSTEM	11
4.5 SUMMARY OF TEST RESULTS	
5. DESCRIPTION OF TEST MODES	
6. FIELD STRENGTH OF FUNDAMENTAL	14
6.1 PROVISIONS APPLICABLE	
6.2 MEASUREMENT PROCEDURE	
6.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)	
6.4 MEASUREMENT RESULTS	
7. RADIATED EMISSION	
7.1 LIMITS OF RADIATED EMISSION TEST	
7.2 MEASUREMENT PROCEDURE	
7.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)	21
7.4 MEASUREMENT RESULT	
8. 20 dB BANDWIDTH	
8.1 PROVISIONS APPLICABLE	



8.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)	24
8.4 MEASUREMENT RESULTS	25
9. FREQUENCY STABILITY	26
9.1 PROVISIONS APPLICABLE	
9.2 MEASUREMENT PROCEDURE	
9.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)	
9.4 MEASUREMENT RESULTS	27
10. AC POWER LINE CONDUCTED EMISSION TEST	28
10.1 LIMITS OF LINE CONDUCTED EMISSION TEST	28
10.2 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)	
10.3 PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	29
10.4 FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	29
10.5 MEASUREMENT RESULTS	30
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	32
APPENDIX B: PHOTOGRAPHS OF TEST EUT	32




# **1. GENERAL INFORMATION**

Wuhan Jingchen Intelligent Identification Technology Co., Ltd.		
Creative Workshop No. 5, Creative World, Yezhihu West Road, Hongshan District, Wuhan, China		
Wuhan Jingchen Intelligent Identification Technology Co., Ltd.		
Creative Workshop No. 5, Creative World, Yezhihu West Road, Hongshan District, Wuhan, China		
Huangpi branch of Wuhan Jingchen Intelligent Identification Technology Co., Ltd.		
3rd Floor, Building 1 Workshop, Building 1 Spare Warehouse, Linkong Economic Demonstration Industrial Park, Hengdian Street, Huangpi District, Wuhan, China		
Label Printer		
NIIMBOT		
NIIMBOT B1		
B1, B1 Pro, B1 SE, NIIMBOT B1_X		
All the same except for the model name		
Jun. 02, 2023		
Jun. 02, 2023 to Jun. 13, 2023		
No any deviation from the test method		
Pass		
AGCTR-ER-FCC-NFCV1.0		

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC Part 15.225.

けんご Prepared By CiCi Li Jun. 14, 2023 (Project Engineer) vin Lin Reviewed By Calvin Liu Jun. 14, 2023 (Reviewer) ax 2ra Approved By Max Zhang Jun. 14, 2023 (Authorized Officer)





# **2. PRODUCT INFORMATION**

## 2.1 PRODUCT TECHNICAL DESCRIPTION

Hardware Version	B1-Main-YC3121-L-YC5018-B		
Software Version	V5.07		
Operation Frequency	13.56MHz		
Modulation Type	ASK		
Number of channels	1		
Field Strength of Fundamental	63.25dBuV/m		
Antenna Designation	Coil Antenna		
Antenna Gain	0dBi		
Power Supply	DC 7.4V by battery or DC 5V by adapter		
Note: The EUT has two batteries. One battery is JL-B201-1500mAh, and the other battery is BL-2S1P18650.			
All the parameters of the two batteries are the same except for the manufacturers. Two batteries have been			
evaluated, only the test data of battery (JL-B201-1500mAh) has been recorded in this report.			

#### 2.2 TEST FREQUENCY LIST

Frequency Band	Channel Number	Frequency
13.110~14.010 MHz	01	13.56 MHz



# 2.3 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: 2ARXB-B1B** filing to comply with Part 2, Part 15 of the Federal Communication Commission rules.

## 2.4 TEST METHODOLOGY

The tests were performed according to following standards:

No.	Identity	Document Title	
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations	
2	FCC 47 CFR Part 15	Radio Frequency Devices	
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices	

#### **2.5 SPECIAL ACCESSORIES**

Not available for this EUT intended for grant.

#### 2.6 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

#### 2.7 ANTENNA REQUIREMENT

#### **Standard Requirement**

#### 15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antennathat uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a brokenantenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

#### EUT Antenna:

The non-detachable antenna inside the device cannot be replaced by the user at will. The gain of the antenna is 0dBi.



# **3. TEST ENVIRONMENT**

# 3.1 ADDRESS OF THE TEST LABORATORY

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

## **3.2 TEST FACILITY**

The test facility is recognized, certified, or accredited by the following organizations:

## CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

## A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

#### FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

#### IC-Registration No.: 24842(CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



# **3.3 ENVIRONMENTAL CONDITIONS**

	NORMAL CONDITIONS	EXTREME CONDITIONS			
Temperature range (°C)	15 - 35	-20 - 50			
Relative humidty range	20 % - 75 %	20 % - 75 %			
Pressure range (kPa) 86 - 106 86 - 106					
Power supply DC 7.4V LV:DC 6.66V HV:8.14V					
Note: The Extreme Temperature and Extreme Voltages declared by the manufacturer.					

## **3.4 MEASUREMENT UNCERTAINTY**

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard

uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 2.9 \text{ dB}$
Uncertainty of Radiated Emission below 150kHz	$U_c = \pm 4.2 \text{ dB}$
Uncertainty of Radiated Emission below 30MHz	$U_c = \pm 3.8 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.8 \text{ dB}$
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$
Uncertainty of spurious emissions, conducted	$U_{c} = \pm 2.7 \%$
Uncertainty of Occupied Channel Bandwidth	U <sub>c</sub> = ±2 %



#### 3.5 LIST OF EQUIPMENTS USED

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Test Receiver	R&S	ESPI	101206	Aug. 04, 2022	Aug. 03, 2023
Artificial power network	R&S	ESH2-Z5	100086	Jun. 08, 2022	Jun. 07, 2023
Artificial power network	R&S	ESH2-Z5	100086	Jun. 03, 2023	Jun. 02, 2024
Test Software	R&S	V1.71	N/A	N/A	N/A
Test Receiver	R&S	ESCI	10096	Feb. 18, 2023	Feb. 17, 2024
Signal Analyzer	Aglient	N9020A	MY52090123	Aug. 04, 2022	Aug. 03, 2023
2.4GHz Filter	EM Electronics	N/A	N/A	Mar. 18, 2022	Mar. 19, 2024
Attenuator	ZHINAN	E-002	N/A	Aug. 04, 2022	Aug. 03, 2024
Horn Antenna	SCHWARZBEC	BBHA9170	768	Oct. 31, 2021	Oct. 30, 2023
Active Loop Antenna (9K-30Mhz)	ZHINAN	ZN30900C	18051	Mar. 12, 2022	Mar. 11, 2024
Double-Ridged Waveguide Horn	ETS	3117	00154520	Sep. 06, 2021	Sep. 05, 2023
Preamplifer	ETS	3117-PA	00246148	Aug. 04, 2022	Aug. 03, 2024
Wideband Antenna	SCHWARZBECK	VULB9168	VULB9168-494	Jan. 05, 2023	Jan. 04, 2024
Test software	FARA	V.RA-03A	N/A	N/A	N/A



# **4.SYSTEM TEST CONFIGURATION**

# **4.1 EUT CONFIGURATION**


The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

# 4.2 EUT EXERCISE

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

# **4.3 CONFIGURATION OF TESTED SYSTEM**

Radiated Emission Configure:



Conducted Emission Configure:

EUT	AE

# 4.4 EQUIPMENT USED IN TESTED SYSTEM

The Following Peripheral Devices And Interface Cables Were Connected During The Measurement:

ltem	Equipment	Model No.	Identifier	Note
1	Adapter	HW-050200C01	DC 5V	Accessories

☑ Test Accessories Come From The Manufacturer

ltem	Equipment	Model No.	Identifier	Note
1	Label Printer	NIIMBOT B1	2ARXB-B1B	EUT
2	Charger line	N/A	0.8m unshielded	Accessories



#### **4.5 SUMMARY OF TEST RESULTS**

Item	FCC Rules	Description Of Test	Result
1	§15.203	Antenna Equipment	Pass
2	15.225(a)(b)(c)	Field Strength of Fundamental	Pass
3	§15.209	Radiated Emission	Pass
4	§15.215(c)	20dB Bandwidth	Pass
5	§15.205(a)	Restricted Bands of Operation	Pass
6	§15.225(e)	Frequency Stability	Pass
7	§15.207	AC Power Line Conducted Emission	Pass



# 5. DESCRIPTION OF TEST MODES

	Summary table of Test Cases
Test Item	Data Rate / Modulation
iest item	NFC/ ASK
Radiated&Conducted Test Cases	Mode 1: NFC TX_13.56 MHz
AC Conducted Emission	Mode 1: NFC Normal Operation + adapter power supply TX_13.56 MHz
Note: 1. Only the result of the wo 2. The battery is full-charge	rst case was recorded in the report, if no other cases.

The battery is full-charged during the test.

2. 3. For Radiated Emission, 3axis were chosen for testing for each applicable mode.

4. For Conducted Test method, a temporary antenna connector is provided by the manufacture.



# 6. FIELD STRENGTH OF FUNDAMENTAL

# 6.1 PROVISIONS APPLICABLE

Rules and specifications		FCC CFR 47 Part	15 section 15.225	
Description	Compliance v	vith the spectrum ma	sk is tested with RBV	V set to 9kHz.
Freq. of Emission (MHz)	Field Strength (µV/m) at 30m	Field Strength (dBµV/m) at 30m	Field Strength (dBµV/m) at 10m	Field Strength (dBµV/m) at 3m
1.705~13.110	30	29.5	48.58	69.5
13.110~13.410	106	40.5	59.58	80.5
13.410~13.553	334	50.5	69.58	90.5
13.553~13.567	15848	84.0	103.08	124.0
13.567~13.710	334	50.5	69.58	90.5
13.710~14.010	106	40.5	59.58	80.5
14.010~30.000	30	29.5	48.58	69.5

## **6.2 MEASUREMENT PROCEDURE**

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the



pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.

- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

The following table is the setting of spectrum analyzer and receiver.


Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz
	1MHz/3MHz for Peak, 1MHz/3MHz for Average

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP




#### 6.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)

RADIATED EMISSION TEST SETUP 9KHz-30MHz




## RADIATED EMISSION TEST SETUP 30MHz-1000MHz






#### **6.4 MEASUREMENT RESULTS**



#### **RESULT: PASS**





EUT	Label Printer		Model Na	ne	NIIMBO	T B1
Temperature	23.9°C		Relative H	umidity	68.5%	
Pressure	985hPa		Test Volta	ge	Normal	/oltage
Test Mode	Mode 1		Antenna		Side	
132.0 dBuV/m		1			Limit: Margin:	_
72						
ertresservations starting and the model of	and courses approximation	And the second	nuthernetectuleneres-ent	-		nateri kundu
12.0	12.96 13.16	13.36 13.56	13.76 13.3	36 14.16		14.56 MHz
	Readii req. Leve	ng Correct	Measure- ment	Limit	Over	
M	lHz dBu∨	dB	dBuV/m	dB/m	dB	Detector
1 * 12.9	060 10.8	24.59	35.40	69.50	-34.10	peak
2 13.5	640 35.80	24.64	60.44	124.0	-63.56	peak
3 14.2	118 10.43	3 24.69	35.12	69.50	-34.38	peak

# **RESULT: PASS**



# 7. RADIATED EMISSION

## 7.1 LIMITS OF RADIATED EMISSION TEST

According to 15.35, on any frequency or frequencies below or equal to 1000 MHz, the limits Shown are based on measuring equipment employing a CISPR quasi-peak detector function and related measurement bandwidths, unless otherwise specified the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test.

The field strength of any emissions which appear outside of 13.110 ~14.010MHz band shall not exceed

the general radiated emissions limits.

Frequency	Distance	Field Streng	ths Limit
(MHz)	Meters	μ <b>V/m</b>	dB(µV)/m
0.009 ~ 0.490	300	2400/F(kHz)	
0.490 ~ 1.705	30	24000/F(kHz)	
1.705 ~ 30	30	30	
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/ 54.0 dB(μV)/m	. ,

15.209 Limit in the below table has to be followed:

Remark: (1) Emission level dB  $\mu$  V = 20 log Emission level  $\mu$  V/m.


(2) The smaller limit shall apply at the cross point between two frequency bands.

(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

# 7.2 MEASUREMENT PROCEDURE

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.





- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz
Start ~Stop Trequency	1MHz/3MHz for Peak, 1MHz/3MHz for Average


The following table is the setting of spectrum analyzer and receiver.

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP




#### 7.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)

RADIATED EMISSION TEST SETUP 9KHz-30MHz



## RADIATED EMISSION TEST SETUP 30MHz-1000MHz





#### 7.4 MEASUREMENT RESULT

#### **RADIATED EMISSION BELOW 30MHz**

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.

											Hz ~10					
EUT			I	_abe	l Pri	nter				Мо	del Nar	ne	1	NIIMBC	DT B1	
Temperature	е		2	23.9	ŶĊ					Rela	ative H	umidity	6	68.5%		
Pressure			ę	985h	Pa					Tes	t Volta	ge	1	Normal	Voltage	
Test Mode			I	Mode	ə 1					Ant	enna		ŀ	Horizon	ital	
66.9 d	lBuV/m	1	_	_										Limit:		
27											<	2×	34	Margin 5	6x	
-13	~				~	M		nun	ml	M	, ll			. In ten		
-13	· · ·			60		0			₩7)	m	300	400	500	600 700	1000.0	10
			50 Fre		R	o eadi		™ Min Corre Fact		Measme	sure-	400		600 700	) 1000.0	10
30.000				eq.	R	eadi	el	Corre		Mea	sure- ent				Detecto	
30.000			Fre	eq. Iz	R	eadi Leve	el V	Corre Fact		Measme	sure- ent //m	Limit	(	Over		r
30.000 No.	Mk		Fre MH	eq. Iz 99	R	eadi Leve dBu\	≥l ∨ 8	Corre Fact	Hz) ect or	Mea: me dBu\	sure- ent //m 54	Limit dB/m	(	Over dB	Detecto	r
30.000 No.	Mk	257	Fre MH 7.94	eq. Iz 99 32	R	eadi Leve dBu\ 27.6	el V 8 5	Corre Fact dB 14.8	++2) ect or 9	Meas me dBu\ 42.4	sure- ent //m 54 34	Limit dB/m 46.00	-	Over dB 3.46	Detecto	r
30.000 No. 1 2 3	Mk	257 435	Fre MH 7.94 5.78 7.51	eq. 12 99 32 67		eadi Leve dBu\ 27.6	8 5 9	Corre Fact dB 14.8 24.1	Hz) ect or 9	Meas me dBu\ 42.	sure- ent //m 54 34 80	Limit dB/m 46.00 46.00		Over dB 3.46 4.66	Detecto peak peak	r
30.000 No. 1 2 3 4	Mk * !	257 435 487	Fre MH 7.94 5.78 7.51 5.91	eq. 99 32 67 66		eadi Leve dBu\ 27.6 17.1 18.8	8 5 8 8 8	Corre Fact dB 14.8 24.1 21.9	Hz) ect or 9 11 7	Mea: me dBu\ 42. 41. 40.	sure- ent 54 34 80 55	Limit dB/m 46.00 46.00 46.00	-	Over dB 3.46 4.66 5.20	Detecto peak peak peak	r

# RADIATED EMISSION FROM 30MHz ~1000MHz

# **RESULT: PASS**



EUT		Label P	rinter		Model Nar	ne	NIIMBO	T B1
Temperature	e	23.9°C			Relative H		68.5%	
Pressure	<u> </u>	985hPa			Test Voltag		Normal	Voltage
Test Mode		Mode 1			Antenna		Vertical	
66.9 dl	lBu¥/m						Linit:	
27						Î	s 	nul M
13			hann	mont				
-13 30.000	40 50	60 70 1	80	(MH2)	300	400	500 600 700	1000.000
30.000			Reading Level			400	500 600 700 Over	1000.000
30.000	Mk. F	F	Reading	(MHz) Correct	300 Measure-			1000.000 Detector
30.000	. Mk. F	Freq.	Reading Level	(MHz) Correct Factor	300 Measure- ment	Limit	Over	
30.000 No.	Mk. F	Freq. MHz 1166	Reading Level dBuV	(MHz) Correct Factor dB	300 Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
<u>30.000</u> No.	Mk. F 1 80.7 342.0	Freq. MHz 1166	Reading Level dBuV 10.10	(MHz) Correct Factor dB 16.88	300 Measure- ment dBuV/m 26.98	Limit dB/m 40.00	Over dB -13.02	Detector peak
30.000 No.	Mk. F 80.7 342.0 * 385.0	Freq. MHz 1166 0167	Reading Level dBuV 10.10 11.76	(MH₂) Correct Factor dB 16.88 19.76	300 Measure- ment dBuV/m 26.98 31.52	Limit dB/m 40.00 46.00	Over dB -13.02 -14.48	Detector peak peak
30.000 No. 1 2 3	Mk. F 80.7 342.0 * 385.0 398.0	Freq. MHz 1166 0167 6666 6000	Reading Level dBuV 10.10 11.76 20.21	(мнz) Correct Factor dB 16.88 19.76 21.63	300 Measure- ment dBuV/m 26.98 31.52 41.84	Limit dB/m 40.00 46.00 46.00	Over dB -13.02 -14.48 -4.16	Detector peak peak peak

#### **RESULT: PASS**

Note: 1. Factor=Antenna Factor + Cable loss, Over=Measurement-Limit.



# 8. 20 dB BANDWIDTH

#### **8.1 PROVISIONS APPLICABLE**


Intentional radiators must be designed to ensure that the 20dB and 99% emission bandwidth in the specific band 13.553~13.567MHz.

#### 8.2 MEASUREMENT PROCEDURE

Set the parameters of SPA as below:

- 1. The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max hold mode.
- 2. Centre frequency = Operation Frequency
- 3. The resolution bandwidth of 10 kHz and the video bandwidth of 30 kHz were used.
- 4. Span: 100kHz, Sweep time: Auto
- 5. Set the EUT to continue transmitting mode. Allow the trace to stabilize. Use the "N dB down" function of SPA to define the bandwidth.
- 6. Measured the spectrum width with power higher than 20dB below carrier.
- 7. Measured the 99% OBW.
- 8. Record the plots and Reported.

#### 8.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)



Spectrum Analyzer



# **8.4 MEASUREMENT RESULTS**

	Tes	t Data of Occupied Bandwi	dth and -20dB Bandwic	ith	
Test Mode	Test Channel (MHz)	99% Occupied Bandwidth (kHz)	-20dB Bandwidth (kHz)	Limits (MHz)	Pass or Fail
NFC_ASK	13.56	32.646	27.02	N/A	Pass

# Test Graphs of Occupied Bandwidth&-20dB Bandwidth

Agilent Spectrum Analyzer - Occupied BW [₩ R RF 50 Ω AC ] Center Freq 13.560000 M 10 dB/div Ref -10.00 dB	#IFGain:Low #	SENSE:INT Center Freq: 13.560000 MHz Tig: Free Run Avg H Atten: 10 dB	ALIGNAUTO  04:38:31 F Radio Std old>10/10 Radio Dev		Trace/Detector
-20.0 -30.0 -40.0					Clear Write
-50.0 -60.0 -70.0					Average
-80.0 -90.0 -100					Max Hold
Center 13.56 MHz #Res BW 10 kHz Occupied Bandwidt	h	#VBW 30 kHz Total Power		n 100 kHz 1.267 ms	Min Hold
	2.646 kHz	2			Detector
Transmit Freq Error	1.238 kH	Z OBW Power	99.00 %		Average▶ <u>Auto</u> Man
x dB Bandwidth	27.02 kH:	z x dB	-20.00 dB		
MSG			STATUS		



# 9. FREQUENCY STABILITY


## 9.1 PROVISIONS APPLICABLE

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

# 9.2 MEASUREMENT PROCEDURE

- 1. The spectrum analyzer connected via a receive antenna placed near the EUT.
- 2. EUT have transmitted signal and fixed channelize.
- 3. Set the spectrum analyzer span to view the entire emissions bandwidth.
- 4. Set RBW = 1 kHz, VBW = 3 kHz with peak detector and maxhold settings.
- 5. The fc is declaring of channel frequency. Then the frequency error formula is  $(fc-f)/fc \times 10^6$  ppm and the limit is less than ±100ppm.
- 6. Extreme temperature rule is -20°C~50°C.

# 9.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)





# 9.4 MEASUREMENT RESULTS

Operating frequency: 13.56MHz

#### Voltage vs. Frequency Stability (Test Temperature: 20°C)

Voltage(V)	Measurement Frequency (MHz)	Max. Deviation (ppm)	Limit(ppm)	Conclusion
7.4	13.56027			
6.29	13.56065	+47.94	±100	PASS
8.51	13.56057			

#### Temperature vs. Frequency Stability (Test Voltage: 7.4V)

Temperature	Measurement Frequency (MHz)	Max. Deviation (ppm)	Limit(ppm)	Conclusion
<b>-20</b> ℃	13.56051			
<b>-10</b> ℃	13.56042			
<b>0</b> °C	13.56058			
<b>10</b> ℃	13.56074	+69.32		PASS
<b>20</b> ℃	13.56083	+09.32	±100	PASS
<b>30</b> ℃	13.56094			
<b>40</b> ℃	13.56062			
<b>50</b> ℃	13.56038			

# **10. AC POWER LINE CONDUCTED EMISSION TEST**


# **10.1 LIMITS OF LINE CONDUCTED EMISSION TEST**

Framerou	Maximum RF	Line Voltage
Frequency	Q.P. (dBµV)	Average (dBµV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Note: 1. The lower limit shall apply at the transition frequency.

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

# 10.2 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)





# **10.3 PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST**

- The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 500hm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.


Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

# **10.4 FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST**

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.



#### **10.5 MEASUREMENT RESULTS**



## MEASUREMENT RESULT: "agc\_fin"


2023/6/7 23:27 Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.150000 0.194000 0.506000 0.982000 1.002000 1.358000	39.70 35.10 39.30 30.30 30.00 30.20	6.2 6.2 6.3 6.3 5.4	66 64 56 56 56	26.3 28.8 16.7 25.7 26.0 25.8	QP QP QP QP QP QP	L1 L1 L1 L1 L1 L1	GND GND GND GND GND GND

#### MEASUREMENT RESULT: "agc fin2"

2023/6/7 23:27 Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.506000	35.10	6.2	46	10.9	AV	L1	GND
0.530000	31.00	6.2	46	15.0	AV	L1	GND
0.582000	27.40	6.2	46	18.6	AV	L1	GND
0.606000	25.90	6.2	46	20.1	AV	L1	GND
0.982000	25.20	6.3	46	20.8	AV	L1	GND
1.234000	24.90	5.7	46	21.1	AV	L1	GND

#### **RESULT: PASS**





# MEASUREMENT RESULT: "agc\_fin"

2023/6/7 23:24 Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.502000 0.982000 1.006000 1.206000 1.354000 1.382000	42.20 32.80 35.10 33.40 32.80 33.30	6.2 6.3 5.7 5.4 5.4	56 56 56 56 56	13.8 23.2 20.9 22.6 23.2 22.7	QP QP QP QP QP QP	N N N N N	GND GND GND GND GND GND

#### MEASUREMENT RESULT: "agc\_fin2"

2023/6/7 Frequen M		4 Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.1500	00	32.40	6.2	56	23.6	AV	N	GND
0.4540	00	25.20	6.2	47	21.6	AV	N	GND
0.5060	00	35.30	6.2	46	10.7	AV	N	GND
0.5300	00	32.20	6.2	46	13.8	AV	N	GND
0.5820	00	26.00	6.2	46	20.0	AV	N	GND
0.6020	00	26.00	6.2	46	20.0	AV	N	GND

#### **RESULT: PASS**



Report No.: AGC07434230602FE10 Page 32 of 32

# APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Refer to the Report No.: AGC07434230602AP02

# APPENDIX B: PHOTOGRAPHS OF TEST EUT

Refer to the Report No.: AGC07434230602AP03

-----END OF REPORT-----



# Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").

2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.

7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.