



FCC and IC Radio Test Report

Equipment : Cisco Aironet 700 Series Access Point
Brand Name : CISCO
Model No. : AIR-CAP702I-A-K9, AIR-SAP702I-A-K9,
AIR-CAP702I-N-K9, AIR-SAP702I-N-K9,
AIR-CAP702I-Z-K9, AIR-SAP702I-Z-K9
FCC ID : LDK102085
IC : 2461B-102085
Standard : 47 CFR FCC Part 15.247
IC RSS-210 Issue 8 and RSS-Gen Issue 3
Frequency Range : 5725 MHz – 5850 MHz
Equipment Class : DTS
Applicant : CISCO System, Inc.
170 West Tasman Drive San Jose, CA
95134-1706
Manufacturer : Wistron NeWeb Corporation
20 Park Avenue II, Hsinchu Science Park,
Hsinchu 308, Taiwan, R.O.C.

The product sample received on Oct. 05, 2012 and completely tested on Apr. 12, 2013. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2009 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.


Reviewed by: Jordan Hsiao



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Accessories	7
1.3	Support Equipment.....	7
1.4	Testing Applied Standards	7
1.5	Testing Location Information	7
1.6	Measurement Uncertainty	8
2	TEST CONFIGURATION OF EUT	9
2.1	The Worst Case Modulation Configuration	9
2.2	Test Channel Frequencies Configuration.....	9
2.3	The Worst Case Power Setting Parameter	10
2.4	Target Maximum Channel Power	10
2.5	EUT Operation during Test	10
2.6	The Worst Case Measurement Configuration.....	11
2.7	Test Setup Diagram	13
3	TRANSMITTER TEST RESULT	15
3.1	AC Power-line Conducted Emissions	15
3.2	6dB Bandwidth	18
3.3	26dB Bandwidth	27
3.4	RF Output Power.....	36
3.5	Power Spectral Density	51
3.6	Transmitter Conducted Unwanted Emissions.....	66
3.7	Transmitter Radiated Unwanted Emissions	78
4	TEST EQUIPMENT AND CALIBRATION DATA	145
APPENDIX A. TEST PHOTOS.....		A1 ~ A5
APPENDIX B. MAXIMUM PERMISSIBLE EXPOSURE.....		B1 ~ B4
APPENDIX C. CO-LOCATION.....		C1 ~ C3

Summary of Test Result

Conformance Test Specifications						
Report Clause	FCC Std. Clause	IC Std. Clause	Description	Measured	Limit	Result
1.1.2	15.203	-	Antenna Requirement	Antenna connector mechanism complied	FCC 15.203	Complied
3.1	15.207	RSS-Gen 7.2.4	AC Power-line Conducted Emissions	[dBuV]: 21.169MHz 38.62 (Margin 11.38dB) - AV 40.70 (Margin 19.30dB) - QP	FCC 15.207 / RSS-Gen 7.2.4	Complied
3.2	15.247(a)	RSS-210 A8.2	6dB Bandwidth	6dB Bandwidth Unit [MHz] 20M: 17.76 / 40M: 36.48	≥500kHz	Complied
3.3	15.247	RSS-210	26dB Bandwidth	Bandwidth [MHz] 20M:26.41 / 40M:49.12	Information only	Complied
3.4	15.247(b)	RSS-210 A8.4	RF Output Power (Maximum Conducted Output Power)	Power [dBm] 20M:20.64 / 40M:20.73	Power [dBm]:30	Complied
3.5	15.247(d)	RSS-210 A8.2	Power Spectral Density	PSD [dBm/3kHz] 20M: -4.28 / 40M:-7.74	PSD [dBm/3kHz]:8	Complied
3.6	15.247(c)	RSS-210 A8.5	Transmitter Conducted Unwanted Emissions	38.75 (Margin 8.75dB)	Non-Restricted Bands: > 30 dBc	Complied
3.7	15.247(c)	RSS-210 A8.5	Transmitter Radiated Unwanted Emissions	Restricted Bands [dBuV/m at 3m]: 41.09MHz 36.65 (Margin 3.35dB) - QP	Restricted Bands: FCC 15.209 / RSS-Gen 7.2.5	Complied

Revision History

[illegible]

1 General Description

1.1 Information

1.1.1 RF General Information

RF General Information				
Frequency Range (MHz)	Operating Mode	Ch. Freq. (MHz)	Channel Number	Co-location
5725-5850	Non HT-20, 6 to 54Mbps	5745-5825	149-165 [5]	Yes
5725-5850	Non HT-20, Beam Forming, 6 to 54Mbps	5745-5825	149-165 [5]	Yes
5725-5850	HT-20, M0 to M15	5745-5825	149-165 [5]	Yes
5725-5850	HT-20, STBC, M0 to M7	5745-5825	149-165 [5]	Yes
5725-5850	HT-20, Beam Forming, M0 to M7	5745-5825	149-165 [5]	Yes
5725-5850	HT-20, Beam Forming, M8 to M15	5745-5825	149-165 [5]	Yes
5725-5850	HT-40, M0 to M15	5755-5795	151-159 [2]	Yes
5725-5850	HT-40, STBC, M0 to M7	5755-5795	151-159 [2]	Yes
5725-5850	HT-40, Beam Forming, M0 to M7	5755-5795	151-159 [2]	Yes
5725-5850	HT-40, Beam Forming, M8 to M15	5755-5795	151-159 [2]	Yes

Note 1: RF output power specifies that Maximum Conducted Output Power.
 Note 2: Non HT-20 / HT-20 / HT-40 uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.
 Note 3: Co-location, Co-location is generally defined as simultaneously transmitting (co-transmitting) antennas within 20 cm of each other. (EUT has simultaneously co-transmitting that operating 2.4GHz and 5GHz.)

1.1.2 Antenna Information

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	WNC	WNC	PIFA Antenna	I-PEX	5
2	WNC	WNC	PIFA Antenna	I-PEX	5


1.1.3 EUT Description

Operating Mode	Non HT-20 6 to 54Mbps		Non HT-20 BF 6 to 54Mbps		HT-20 M0 to M15		HT-20 STBC M0 to M7		HT-20BF M0 to M7		HT-20 BF M8 to M15	
Tx	1	2	1	2	1	2	1	2	1	2	1	2
Single (Tx)	V	-	-	-	V	-	-	-	-	-	-	-
Two (Tx)	V	V	V	V	V	V	V	V	V	V	V	V

Note: BF: Beam Forming

Operating Mode	HT-40 M0 to M15		HT-40 STBC M0 to M7		HT-40 BF M0 to M7		HT-40 BF M8 to M15	
Tx	1	2	1	2	1	2	1	2
Single (Tx)	V	-	-	-	-	-	-	-
Two (Tx)	V	V	V	V	V	V	V	V

Note: BF: Beam Forming



1.1.4 Type of EUT

Identify EUT	
EUT Serial Number	N/A
Presentation of Equipment	<input type="checkbox"/> Production ; <input checked="" type="checkbox"/> Pre-Production ; <input type="checkbox"/> Prototype
The EUT has six model names. All the models are identical; the different model names served as marketing strategy.	
Type of EUT	
<input checked="" type="checkbox"/>	Stand-alone
<input type="checkbox"/>	Combined (EUT where the radio part is fully integrated within another device) Combined Equipment - Brand Name / Model No.: ...
<input type="checkbox"/>	Plug-in radio (EUT intended for a variety of host systems) Host System - Brand Name / Model No.: ...
<input type="checkbox"/>	Other:

1.1.5 EUT Operational Condition

EUT Power Type	From Power Adapter / POE
-----------------------	--------------------------

1.2 Accessories

Accessories					
No.	Equipment Name	Brand Name	Model Name	Rating	Remark
1	AC Adapter	CISCO	AA25480L	INPUT: 100-240V ~ 600mA, 50/60Hz OUTPUT: 48V, 380mA	With power cable
2	AC Adapter	CISCO	EADP-18MB B	INPUT: 100-240V ~ 0.5A, 50-60Hz OUTPUT: 48V, 0.38A	With power cable

1.3 Support Equipment

Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
1	Notebook	DELL	M1330	E2KWM3945ABG
2	Notebook	DELL	E6220	E2KWM3945ABG
3	Notebook	DELL	E6220	E2KWM3945ABG
4	Notebook	DELL	E6400	E2KWM3945ABG
5	POE	CISCO	DPSN-35FB A	N/A
6	POE	CISCO	POE30U-560(G)	N/A
7	POE Switch	MOTOROLA	RFS-4010	N/A

1.4 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ◆ 47 CFR FCC Part 15
- ◆ ANSI C63.10-2009
- ◆ FCC KDB 558074
- ◆ FCC KDB 662911
- ◆ FCC KDB 412172

1.5 Testing Location Information

Testing Location			
<input type="checkbox"/>	HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055	
<input checked="" type="checkbox"/>	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085	
Test Condition		Test Site No.	Test Engineer
RF Conducted		TH01-CB	Satoshi Yang
AC Conduction		CO01-CB	Sollo Luo
Radiated Emission		03CH01-CB	Satoshi Yang
		Test Environment	
		24°C / 60%	
		24°C / 64%	
		24°C / 60%	

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Measurement Uncertainty			
Test Item		Uncertainty	Limit
AC power-line conducted emissions		±2.26 dB	N/A
Emission bandwidth, 6dB bandwidth		±1.42 %	N/A
RF output power, conducted		±0.63 dB	N/A
Power density, conducted		±0.81 dB	N/A
Unwanted emissions, conducted	30 – 1000 MHz	±0.51 dB	N/A
	1 – 18 GHz	±0.67 dB	N/A
	18 – 40 GHz	±0.83 dB	N/A
	40 – 200 GHz	N/A	N/A
All emissions, radiated	30 – 1000 MHz	±2.56 dB	N/A
	1 – 18 GHz	±3.59 dB	N/A
	18 – 40 GHz	±3.82 dB	N/A
	40 – 200 GHz	N/A	N/A
Temperature		±0.8 °C	N/A
Humidity		±3 %	N/A
DC and low frequency voltages		±3 %	N/A
Time		±1.42 %	N/A
Duty Cycle		±1.42 %	N/A

2 Test Configuration of EUT

2.1 The Worst Case Modulation Configuration

Worst Modulation Used for Conformance Testing	
Operating Mode	Worst Data Rate / MCS
Non HT-20, 6 to 54Mbps	6Mbps
Non HT-20, Beam Forming, 6 to 54Mbps	6Mbps
HT-20, M0 to M15	6.5Mbps (M0)
HT-20, STBC, M0 to M7	6.5Mbps (M0)
HT-20, Beam Forming, M0 to M7	6.5Mbps (M0)
HT-20, Beam Forming, M8 to M15	13Mbps (M8)
HT-40, M0 to M15	13.5Mbps (M0)
HT-40, STBC, M0 to M7	13.5Mbps (M0)
HT-40, Beam Forming, M0 to M7	13.5Mbps (M0)
HT-40, Beam Forming, M8 to M15	27Mbps (M8)
Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput). Then EUT support HT20 and HT40. Worst modulation mode of Guard Interval (GI) is 400ns.	
Note 2: Modulation modes consist below configuration: M: Modulation and Coding Scheme	
Note 3: RF output power specifies that Maximum Conducted Output Power.	

2.2 Test Channel Frequencies Configuration

Test Channel Frequencies Configuration	
Operating Mode	Test Channel Frequencies (MHz)
Non HT-20, 6 to 54Mbps	5745, 5785, 5825
Non HT-20, Beam Forming, 6 to 54Mbps	
HT-20, M0 to M15	
HT-20, STBC, M0 to M7	
HT-20, Beam Forming, M0 to M7	
HT-20, Beam Forming, M8 to M15	
HT-40, M0 to M15	5755, 5795
HT-40, STBC, M0 to M7	
HT-40, Beam Forming, M0 to M7	
HT-40, Beam Forming, M8 to M15	

2.3 The Worst Case Power Setting Parameter

The Worst Case Power Setting Parameter						
Test Software Version	ART 2 GUI:2.3					
Operating Mode	N _{TX}	Test Frequency (MHz)				
		NCB: 20MHz			NCB: 40MHz	
		5745	5785	5825	5755	5795
Non HT-20, 6 to 54Mbps	2	16.5	17	17.5	-	-
Non HT-20, Beam Forming, 6 to 54Mbps	2	16.5	17	17.5	-	-
HT-20, M0 to M15 / HT-20, STBC, M0 to M7	2	17	17	17.5	-	-
HT-20, Beam Forming, M0 to M7	2	17	17	17.5	-	-
HT-20, Beam Forming, M8 to M15	2	17	17	17.5	-	-
HT-40, M0 to M15 / HT-40, STBC, M0 to M7	2	-	-	-	17	17.5
HT-40, Beam Forming, M0 to M7	2	-	-	-	17	17.5
HT-40, Beam Forming, M8 to M15	2	-	-	-	17	17.5

2.4 Target Maximum Channel Power

Target Maximum Channel Power (dBm)				
Operating Mode	N _{TX}	Frequency (MHz)		
		5745	5785	5825
		5755	5795	
Non HT-20, 6 to 54Mbps	2	20.39	20.60	20.51
Non HT-20, Beam Forming, 6 to 54Mbps	2	20.39	20.60	20.51
HT-20, M0 to M15 / HT-20, STBC, M0 to M7	2	20.46	20.64	20.28
HT-20, Beam Forming, M0 to M7	2	20.46	20.64	20.28
HT-20, Beam Forming, M8 to M15	2	20.46	20.52	20.45
HT-40, M0 to M15 / HT-40, STBC, M0 to M7	2	20.53	20.73	
HT-40, Beam Forming, M0 to M7	2	20.53	20.73	
HT-40, Beam Forming, M8 to M15	2	20.30	20.60	

2.5 EUT Operation during Test

During the test, "ART 2 GUI:2.3" under WIN XP was executed the test program to control the EUT continuously transmit RF signal.


2.6 The Worst Case Measurement Configuration


The Worst Case Mode for Following Conformance Tests	
Tests Item	AC power-line conducted emissions
Test Condition	AC power-line conducted measurement for line and neutral Test Voltage: 120Vac / 60Hz
Test Mode	Normal Link
1	EUT with AC Adapter 1 (CISCO AA25480L)
2	EUT with AC Adapter 2 (CISCO EADP-18MB B)
For test mode 2 is the worst case and it was record in this test report.	

The Worst Case Mode for Following Conformance Tests	
Tests Item	6 dB Bandwidth 26 dB Bandwidth RF Output Power Power Spectral Density Transmitter Conducted Bandedge Emissions Transmitter Conducted Unwanted Emissions
Test Condition	Conducted measurement at transmit chains
Operating Mode	Non HT-20 / Non HT-20, Beam Forming / HT-20 / HT-20, STBC / HT-20, Beam Forming / HT-40 / HT-40, STBC / HT-40, Beam Forming

The Worst Case Mode for Following Conformance Tests	
Tests Item	Transmitter Radiated Unwanted Emissions
Test Condition	Radiated measurement
Test Mode < 1GHz	Normal Link
1	Stand-up of EUT with AC Adapter 1 (CISCO AA25480L)
2	Laying-flat of EUT with AC Adapter 1 (CISCO AA25480L)
Mode 1 has been evaluated to be the worst case, thus measurement will follow this same test mode.	
3	Stand-up of EUT with AC Adapter 2 (CISCO EADP-18MB B)
4	Stand-up of EUT with POE 1 (CISCO DPSN-35FB A)
5	Stand-up of EUT with POE 2 (CISCO POE30U-560(G))
6	Stand-up of EUT with POE Switch (MOTOROLA RFS-4010)
For test mode 4 is the worst case and it was record in this test report.	
Operating Mode	Non HT-20 / Non HT-20, Beam Forming / HT-20 / HT-20, STBC / HT-20, Beam Forming / HT-40 / HT-40, STBC / HT-40, Beam Forming
Test Mode > 1GHz	Continuously transmit RF signal
1	Stand-up of EUT
2	Laying-flat of EUT
For test mode 2 is the worst case and it was record in this test report.	

2.7 Test Setup Diagram



Test Setup Diagram - Radiated Test
Test Mode 4
Stand-up of EUT with POE 1 (CISCO DPSN-35FB A)


Item	Connection	Shield	Length	Remark
1	RS-232 Cable	No	1.5m	-
2	RJ-45 Cable	No	10m	-
3	RJ-45 Cable	No	1.5m	-

3 Transmitter Test Result

3.1 AC Power-line Conducted Emissions

3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.


3.1.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/>	Refer as ANSI C63.10-2009, clause 6.2 for AC power-line conducted emissions.

3.1.4 Test Setup




3.1.5 Test Result of AC Power-line Conducted Emissions



AC Power-line Conducted Emissions Result

Test Mode	2	Power Phase	Line
Operating Function	Normal Link		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.15403	23.07	-32.71	55.78	22.71	0.16	0.20	LINE	AVERAGE
2	0.15403	36.02	-29.76	65.78	35.66	0.16	0.20	LINE	QP
3	0.83337	22.47	-23.53	46.00	22.11	0.16	0.20	LINE	AVERAGE
4	0.83337	28.81	-27.19	56.00	28.45	0.16	0.20	LINE	QP
5	1.991	20.87	-35.13	56.00	20.48	0.19	0.20	LINE	QP
6	1.991	16.05	-29.95	46.00	15.66	0.19	0.20	LINE	AVERAGE
7	11.438	31.31	-18.69	50.00	30.55	0.36	0.40	LINE	AVERAGE
8	11.438	36.85	-23.15	60.00	36.09	0.36	0.40	LINE	QP
9	15.552	32.98	-17.02	50.00	32.16	0.42	0.40	LINE	AVERAGE
10	15.552	38.45	-21.55	60.00	37.63	0.42	0.40	LINE	QP
11	21.169	40.70	-19.30	60.00	39.70	0.50	0.50	LINE	QP
12	21.169	38.62	-11.38	50.00	37.62	0.50	0.50	LINE	AVERAGE

Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)

3.2 6dB Bandwidth

3.2.1 6dB Bandwidth Limit

6dB Bandwidth Limit
Systems using digital modulation techniques:
6 dB bandwidth \geq 500 kHz.


3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures

Test Method
<input checked="" type="checkbox"/> For the emission bandwidth shall be measured using one of the options below:
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 7.1 Option 1 for 6 dB bandwidth measurement.
<input type="checkbox"/> Refer as FCC KDB 558074, clause 7.2 Option 2 for 6 dB bandwidth measurement.
<input type="checkbox"/> Refer as ANSI C63.10, clause 6.9.1 for occupied bandwidth testing.

3.2.4 Test Setup



3.2.5 Test Result of Emission Bandwidth


Freq. (MHz)	Operating Mode	Data Rate (Mbps)	99% BW (MHz)	6dB BW (MHz)	Limit (kHz)	Margin (MHz)
5745	Non HT-20, Beam Forming, 6 to 54Mbps	6	16.56	16.4	>500	15.9
	HT-20, Beam Forming, M0 to M7	M0	17.84	17.6	>500	17.1
	HT-20, Beam Forming, M8 to M15	M8	17.84	17.76	>500	17.26
5785	Non HT-20, Beam Forming, 6 to 54Mbps	6	16.56	16.4	>500	15.9
	HT-20, Beam Forming, M0 to M7	M0	17.84	17.6	>500	17.1
	HT-20, Beam Forming, M8 to M15	M8	17.84	17.68	>500	17.18
5825	Non HT-20, Beam Forming, 6 to 54Mbps	6	16.64	16.32	>500	15.82
	HT-20, Beam Forming, M0 to M7	M0	17.84	17.68	>500	17.18
	HT-20, Beam Forming, M8 to M15	M8	17.84	17.6	>500	17.1
5755	HT-40, Beam Forming, M0 to M7	M0	36.48	36.48	>500	35.98
	HT-40, Beam Forming, M8 to M15	M8	36.48	36.48	>500	35.98
5795	HT-40, Beam Forming, M0 to M7	M0	36.32	35.84	>500	35.34
	HT-40, Beam Forming, M8 to M15	M8	36.48	36.48	>500	35.98



Date: 18.OCT.2012 21:34:02


Date: 18.OCT.2012 21:37:03

6 dB and 99% Bandwidth Plot on 5745 MHz, HT-20, Beam Forming, M8




Date: 18.OCT.2012 21:40:01

6 dB and 99% Bandwidth Plot on 5785 MHz, Non HT-20, Beam Forming, 6Mbps




Date: 18.OCT.2012 21:34:28

6 dB and 99% Bandwidth Plot on 5785 MHz, HT-20, Beam Forming, M0




Date: 18.OCT.2012 21:36:27

6 dB and 99% Bandwidth Plot on 5785 MHz, HT-20, Beam Forming, M8




Date: 18.OCT.2012 21:39:12

6 dB and 99% Bandwidth Plot on 5825 MHz, Non HT-20, Beam Forming, 6Mbps




Date: 18.OCT.2012 21:35:12

6 dB and 99% Bandwidth Plot on 5825 MHz, HT-20, Beam Forming, M0




Date: 18.OCT.2012 21:38:07

6 dB and 99% Bandwidth Plot on 5825 MHz, HT-20, Beam Forming, M8




Date: 18.OCT.2012 21:38:39

6 dB and 99% Bandwidth Plot on 5755 MHz, HT-40, Beam Forming, M0




Date: 18.OCT.2012 21:42:09

6 dB and 99% Bandwidth Plot on 5755 MHz, HT-40, Beam Forming, M8




Date: 18.OCT.2012 21:43:45

6 dB and 99% Bandwidth Plot on 5795 MHz, HT-40, Beam Forming, M0



Date: 18.OCT.2012 21:42:38

6 dB and 99% Bandwidth Plot on 5795 MHz, HT-40, Beam Forming, M8



Date: 18.OCT.2012 21:43:14

3.3 26dB Bandwidth


3.3.1 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.3.2 Test Procedures

Test Method	
For the emission bandwidth shall be measured using below:	
Center Frequency	: Frequency from table below
Span	: 2 x Nominal Bandwidth (e.g. 40MHz for a 20MHz channel)
Reference Level	: 20 dBm
Attenuation	: 10 dB
Sweep Time	: 5 s
Resolution Bandwidth	: 1%-3% of 26 dB Bandwidth
Video Bandwidth	: \geq Resolution Bandwidth
X dB Bandwidth	: 26 dB
Detector	: Peak
Trace	: Single


3.3.3 Test Setup




3.3.4 Test Result of Emission Bandwidth

Freq. (MHz)	Operating Mode	Data Rate (Mbps)	99% BW (MHz)	26dB BW (MHz)
5745	Non HT-20, 6 to 54Mbps	6	17.2	23.76
	Non HT-20, Beam Forming, 6 to 54Mbps	6	17.2	23.76
	HT-20, Beam Forming, M0 to M7	M0	18.72	25.68
	HT-20, Beam Forming, M8 to M15	M8	18.4	25.2
5785	Non HT-20, 6 to 54Mbps	6	17.04	23.76
	Non HT-20, Beam Forming, 6 to 54Mbps	6	17.04	23.76
	HT-20, Beam Forming, M0 to M7	M0	18.8	26.4
	HT-20, Beam Forming, M8 to M15	M8	18.48	24.88
5825	Non HT-20, 6 to 54Mbps	6	17.28	23.52
	Non HT-20, Beam Forming, 6 to 54Mbps	6	17.28	23.52
	HT-20, Beam Forming, M0 to M7	M0	18.88	26.08
	HT-20, Beam Forming, M8 to M15	M8	18.4	24.96
5755	HT-40, STBC, M0 to M7	M0	36.96	48.64
	HT-40, Beam Forming, M0 to M7	M0	36.96	48.64
	HT-40, Beam Forming, M8 to M15	M8	36.8	47.36
5795	HT-40, STBC, M0 to M7	M0	37.12	49.12
	HT-40, Beam Forming, M0 to M7	M0	37.12	49.12
	HT-40, Beam Forming, M8 to M15	M8	36.64	46.72

26 dB and 99% Bandwidth Plot on 5745 MHz, Non HT-20 / Non HT-20, Beam Forming, 6Mbps



26 dB and 99% Bandwidth Plot on 5745 MHz, HT-20, Beam Forming, M0





Ref 20 dBm Att 30 dB RBW 300 kHz Delta 1 [T1] n:24.d6
 VSW 3 MHz SWT 20 ms 23.440000000 MHz

20 Offset 1.5 dB

Marker 1 [T1]

Center 5.825 GHz 4 MHz/ Span 40 MHz

Date: 18.OCT.2012 18:24:23

Ref 20 dBm Att 30 dB SWT 20 ms RBW 300 kHz Delta 1 [T1] n:09 dB VBW 3 MHz 26.93000000 MHz

20 Offset 1.5 dB

Marker 1 [T1] 5.825 GHz

Temp 1 [T1] 0.00

Temp 2 [T1] 0.00

0.07 dBm


-15.28 dBm

F1 F2


Center 5.825 GHz 4 MHz/ Span 400 MHz

Date: 18.OCT.2012 18:32:24


26 dB and 99% Bandwidth Plot on 5755 MHz, HT-40, Beam Forming, M8



26 dB and 99% Bandwidth Plot on 5795 MHz, HT-40, STBC / HT-40, Beam Forming, M0



26 dB and 99% Bandwidth Plot on 5795 MHz, HT-40, Beam Forming, M8



3.4 RF Output Power

3.4.1 RF Output Power Limit

RF Output Power Limit	
Maximum Conducted Output Power Limit	
<input checked="" type="checkbox"/> 2400-2483.5 MHz Band:	
<input checked="" type="checkbox"/>	If $G_{TX} \leq 6$ dBi, then $P_{Out} \leq 30$ dBm (1 W)
<input checked="" type="checkbox"/>	Point-to-multipoint systems (P to M): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$ dBm
<input type="checkbox"/>	Point-to-point systems (P to P): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
<input type="checkbox"/>	Smart antenna system (SAS):
<input type="checkbox"/>	Single beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
<input type="checkbox"/>	Overlap beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
<input type="checkbox"/>	Aggregate power on all beams: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3 + 8$ dB dBm
P_{Out} = maximum conducted output power in dBm, G_{TX} = the maximum transmitting antenna directional gain in dBi.	


3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.4.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/> Maximum Conducted Output Power	
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 8.2.1 Option 1 (spectral trace averaging).
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.2.2 Option 2 (slow sweep speed).
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.2.3 Option 3 (average power meter).
<input checked="" type="checkbox"/> For conducted measurement.	
<input checked="" type="checkbox"/>	The EUT supports multiple transmit chains using options given below: Refer as FCC KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them.

3.4.4 Test Setup



3.4.5 Test Result of Maximum Conducted Output Power

Freq. (MHz)	Operating Mode	N _{TX}	Correlated Antenna Gain (dBi)	Tx1 Output Power (dBm)	Tx2 Output Power (dBm)	Total Tx Channel Power (dBm)	Limit (dBm)	Margin (dB)
5745	Non HT-20, 6 to 54Mbps	2	5.00	17.66	17.07	20.39	30.00	9.61
	Non HT-20, Beam Forming, 6 to 54Mbps	2	8.01	17.66	17.07	20.39	27.99	7.60
	HT-20, M0 to M15	2	5.00	17.83	17.03	20.46	30.00	9.54
	HT-20, STBC, M0 to M7	2	5.00	17.83	17.03	20.46	30.00	9.54
	HT-20, Beam Forming, M0 to M7	2	8.01	17.83	17.03	20.46	27.99	7.53
	HT-20, Beam Forming, M8 to M15	2	5.00	17.84	17.01	20.46	30.00	9.54
5785	Non HT-20, 6 to 54Mbps	2	5.00	17.92	17.23	20.60	30.00	9.40
	Non HT-20, Beam Forming, 6 to 54Mbps	2	8.01	17.92	17.23	20.60	27.99	7.39
	HT-20, M0 to M15	2	5.00	17.96	17.28	20.64	30.00	9.36
	HT-20, STBC, M0 to M7	2	5.00	17.96	17.28	20.64	30.00	9.36
	HT-20, Beam Forming, M0 to M7	2	8.01	17.96	17.28	20.64	27.99	7.35
	HT-20, Beam Forming, M8 to M15	2	5.00	17.95	17.01	20.52	30.00	9.48
5825	Non HT-20, 6 to 54Mbps	2	5.00	18.00	16.94	20.51	30.00	9.49
	Non HT-20, Beam Forming, 6 to 54Mbps	2	8.01	18.00	16.94	20.51	27.99	7.48
	HT-20, M0 to M15	2	5.00	17.52	17.00	20.28	30.00	9.72
	HT-20, STBC, M0 to M7	2	5.00	17.52	17.00	20.28	30.00	9.72
	HT-20, Beam Forming, M0 to M7	2	8.01	17.52	17.00	20.28	27.99	7.71
	HT-20, Beam Forming, M8 to M15	2	5.00	17.79	17.05	20.45	30.00	9.55
5755	HT-40, M0 to M15	2	5.00	17.91	17.1	20.53	30.00	9.47
	HT-40, STBC, M0 to M7	2	5.00	17.91	17.1	20.53	30.00	9.47
	HT-40, Beam Forming, M0 to M7	2	8.01	17.91	17.1	20.53	27.99	7.46
	HT-40, Beam Forming, M8 to M15	2	5.00	17.64	16.9	20.30	30.00	9.70
5795	HT-40, M0 to M15	2	5.00	18.26	17.1	20.73	30.00	9.27
	HT-40, STBC, M0 to M7	2	5.00	18.26	17.1	20.73	30.00	9.27
	HT-40, Beam Forming, M0 to M7	2	8.01	18.26	17.1	20.73	27.99	7.26
	HT-40, Beam Forming, M8 to M15	2	5.00	18.10	17.00	20.60	30.00	9.40

Note 1: For all transmitter outputs with equal antenna gains, directional gain is to be computed as follows:

Any transmit signals are correlated, Directional Gain = $G_{ANT} + 10 \log(N_{TX})$

All transmit signals are completely uncorrelated, Directional Gain = G_{ANT}

Note 2: For all transmitter outputs with unequal antenna gains, directional gain is to be computed as follows:

Any transmit signals are correlated, Directional Gain = $10 \log[(10^{G_{1/20}} + \dots + 10^{G_{N/20}})^2 / N_{TX}]$

All transmit signals are completely uncorrelated, Directional Gain = $10 \log[(10^{G_{1/10}} + \dots + 10^{G_{N/10}}) / N_{TX}]$

Note 3: For Spatial Multiplexing, Directional Gain (DG) = $G_{ANT} + 10 \log(N_{TX}/N_{SS})$,

where N_{ss} is the number of independent spatial streams data.

Note 4: For CDD transmissions, directional gain is calculated as power measurements:


Directional Gain (DG) = $G_{ANT} + \text{Array Gain}$, where Array Gain is as follows:

Array Gain = 0 dB (i.e., no array gain) for $N_{TX} \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{TX}


Maximum Conducted Output Power Plot on 5745 MHz, Non HT-20 / Non HT-20, Beam Forming, 6 Mbps

Tx1



Date: 18.OCT.2012 19:03:24


Tx2



Date: 18.OCT.2012 19:02:35


Maximum Conducted Output Power Plot on 5745 MHz, HT-20 / HT-20, STBC / HT-20, Beam Forming, M0

Tx1



Date: 18.OCT.2012 19:20:20


Tx2



Date: 18.OCT.2012 19:19:18


Maximum Conducted Output Power Plot on 5745 MHz, HT-20, Beam Forming, M8

Tx1



Date: 18.OCT.2012 19:23:46


Tx2



Date: 18.OCT.2012 19:24:46


**Maximum Conducted Output Power Plot on 5785 MHz,
Non HT-20 / Non HT-20, Beam Forming, 6 Mbps**

Tx1




Date: 18.OCT.2012 19:04:21


Tx2



Date: 18.OCT.2012 19:05:38

**Maximum Conducted Output Power Plot on 5785 MHz,
HT-20 / HT-20, STBC / HT-20, Beam Forming, M0**
Tx1



Date: 18.OCT.2012 19:16:05

Tx2


Date: 18.OCT.2012 19:15:18


Maximum Conducted Output Power Plot on 5785 MHz, HT-20, Beam Forming, M8

Tx1



Date: 18.OCT.2012 19:26:22


Tx2



Date: 18.OCT.2012 19:25:50


**Maximum Conducted Output Power Plot on 5825 MHz,
Non HT-20 / Non HT-20, Beam Forming, 6 Mbps**

Tx1



Date: 18.OCT.2012 20:21:59


Tx2



Date: 18.OCT.2012 20:21:23


Maximum Conducted Output Power Plot on 5825 MHz, HT-20 / HT-20, STBC / HT-20, Beam Forming, M0

Tx1



Date: 18.OCT.2012 19:13:36


Tx2



Date: 18.OCT.2012 19:14:19


Maximum Conducted Output Power Plot on 5825 MHz, HT-20, Beam Forming, M8

Tx1



Date: 18.OCT.2012 19:28:58


Tx2



Date: 18.OCT.2012 19:28:10


Maximum Conducted Output Power Plot on 5755 MHz, HT-40 / HT-40, STBC / HT-40, Beam Forming, M0

Tx1



Date: 18.OCT.2012 19:58:12


Tx2



Date: 18.OCT.2012 19:57:06


Maximum Conducted Output Power Plot on 5755 MHz, HT-40, Beam Forming, M8

Tx1



Date: 18.OCT.2012 20:05:00


Tx2



Date: 18.OCT.2012 20:08:49


Maximum Conducted Output Power Plot on 5795 MHz, HT-40 / HT-40, STBC / HT-40, Beam Forming, M0

Tx1



Date: 18.OCT.2012 20:01:23


Tx2



Date: 18.OCT.2012 20:02:08


Maximum Conducted Output Power Plot on 5795 MHz, HT-40, Beam Forming, M8

Tx1



Date: 18.OCT.2012 20:04:15

Tx2



Date: 18.OCT-2012 20:03:40

3.5 Power Spectral Density

3.5.1 Power Spectral Density Limit

Power Spectral Density Limit
Power Spectral Density (PSD) ≤ 8 dBm/3kHz


3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.5.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/>	Power spectral density procedures that the same method as used to determine the conducted output power shall be used to determine the power spectral density. In addition, the use of a peak PSD procedure will always result in a "worst-case" measured level for comparison to the limit. Therefore, whenever the DTS bandwidth exceeds 500 kHz, it is acceptable to utilize the peak PSD procedure to demonstrate compliance to the PSD limit, regardless of how the fundamental output power was measured. For the power spectral density shall be measured using below options:
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 9.1 Option 1 - (RBW \geq 3kHz; sweep=auto, detector=peak).
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 9.2 Option 2 - (RBW \geq 3kHz; sweep=auto, average=100).
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 9.3 Option 3 - (RBW \geq 3kHz; slow sweep speed).
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 9.4 Option 2 (average PSD; BWCF=-15.2dB).
<input type="checkbox"/>	RBW>3kHz, add the bandwidth correction factor (BWCF) adjusting in PSD per 3kHz.
<input checked="" type="checkbox"/>	For conducted measurement.
<input checked="" type="checkbox"/>	The EUT supports multiple transmit chains using options given below:
<input type="checkbox"/>	Option 1: Measure and sum the spectra across the outputs. Refer as FCC KDB 662911, In-band power spectral density (PSD). Sample all transmit ports simultaneously using a spectrum analyzer for each transmit port. Where the trace bin-by-bin of each transmit port summing can be performed. (i.e., in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the N _{TX} output to obtain the value for the first frequency bin of the summed spectrum.). Add up the amplitude (power) values for the different transmit chains and use this as the new data trace.
<input checked="" type="checkbox"/>	Option 2: Measure and add 10 log(N) dB, where N is the number of transmit chains. Refer as FCC KDB 662911, In-band power spectral density (PSD). Performed at each transmit chains and each transmit chains shall be compared with the limit have been reduced with 10 log(N). Or each transmit chains shall be add 10 log(N) to compared with the limit.

3.5.4 Test Setup



3.5.5 Test Result of Power Spectral Density


Freq. (MHz)	Operating Mode	Data Rate (Mbps)	Tx1 PSD Antenna (dBm/3kHz)	Tx2 PSD Antenna (dBm/3kHz)	1Port Limit (dBm/3kHz)	1Port Margin (dB)	Total Tx PSD Antenna (dBm/3kHz)	Total Port Limit (dBm/3kHz)	Margin (dB)
5745	Non HT-20, 6 to 54Mbps	6	-8.32	-9.31	4.99	13.31	-5.78	8.00	13.78
	Non HT-20, Beam Forming, 6 to 54Mbps	6	-8.32	-9.31	2.98	11.30	-5.78	5.99	11.77
	HT-20, M0 to M15 / HT-20, STBC, M0 to M7	M0	-7.7	-9.09	4.99	12.69	-5.33	8.00	13.33
	HT-20, Beam Forming, M0 to M7	M0	-7.7	-9.09	2.98	10.68	-5.33	5.99	11.32
	HT-20, Beam Forming, M8 to M15	M8	-8.83	-9.84	4.99	13.82	-6.30	8.00	14.30
5785	Non HT-20, 6 to 54Mbps	6	-7.85	-9.33	4.99	12.84	-5.52	8.00	13.52
	Non HT-20, Beam Forming, 6 to 54Mbps	6	-7.85	-9.33	2.98	10.83	-5.52	5.99	11.51
	HT-20, M0 to M15 / HT-20, STBC, M0 to M7	M0	-8.89	-9.17	4.99	13.88	-6.02	8.00	14.02
	HT-20, Beam Forming, M0 to M7	M0	-8.89	-9.17	2.98	11.87	-6.02	5.99	12.01
	HT-20, Beam Forming, M8 to M15	M8	-8.68	-9.07	4.99	13.67	-5.86	8.00	13.86
5825	Non HT-20, 6 to 54Mbps	6	-6.28	-8.6	4.99	11.27	-4.28	8.00	12.28
	Non HT-20, Beam Forming, 6 to 54Mbps	6	-6.28	-8.6	2.98	9.26	-4.28	5.99	10.27
	HT-20, M0 to M15 / HT-20, STBC, M0 to M7	M0	-6.99	-8.3	4.99	11.98	-4.59	8.00	12.59
	HT-20, Beam Forming, M0 to M7	M0	-6.99	-8.3	2.98	9.97	-4.59	5.99	10.58
	HT-20, Beam Forming, M8 to M15	M8	-7.56	-9.18	4.99	12.55	-5.28	8.00	13.28
5755	HT-40, M0 to M15 / HT-40, STBC, M0 to M7	M0	-9.44	-12.69	4.99	14.43	-7.76	8.00	15.76
	HT-40, Beam Forming, M0 to M7	M0	-9.44	-12.69	2.98	12.42	-7.76	5.99	13.75
	HT-40, Beam Forming, M8 to M15	M8	-10.6	-12.65	4.99	15.59	-8.49	8.00	16.49
5795	HT-40, M0 to M15 / HT-40, STBC, M0 to M7	M0	-9.46	-12.58	4.99	14.45	-7.74	8.00	15.74
	HT-40, Beam Forming, M0 to M7	M0	-9.46	-12.58	2.98	12.44	-7.74	5.99	13.73
	HT-40, Beam Forming, M8 to M15	M8	-11.98	-12.53	4.99	16.97	-9.24	8.00	17.24

Note 1: PSD [dBm/3kHz] = each transmit chains PSD [dBm/3kHz] + $10\log N_{TX}$

Note 2: Power spectral density plots w/o [$10\log N_{TX}$] factor


Power Spectral Density Plot on 5745 MHz, Non HT-20 / Non HT-20, Beam Forming, 6Mbps

Tx1



Date: 24.OCT.2012 21:54:11


Tx2



Date: 24.OCT.2012 22:04:53


Power Spectral Density Plot on 5745 MHz, HT-20 / HT-20, STBC / HT-20, Beam Forming, M0

Tx1



Date: 24.OCT.2012 21:55:16


Tx2



Date: 24.OCT.2012 22:05:30


Power Spectral Density Plot on 5745 MHz, HT-20, Beam Forming, M8

Tx1



Date: 24.OCT.2012 21:55:48


Tx2



Date: 24.OCT.2012 22:06:57


Power Spectral Density Plot on 5785 MHz, Non HT-20 / Non HT-20, Beam Forming, 6Mbps

Tx1




Date: 24.OCT.2012 21:58:45


Tx2



Date: 24.OCT.2012 22:08:03

Power Spectral Density Plot on 5785 MHz, HT-20 / HT-20, STBC / HT-20, Beam Forming, M0
Tx1



Date: 24.OCT.2012 21:57:02

Tx2


Date: 24.OCT.2012 22:08:25


Power Spectral Density Plot on 5785 MHz, HT-20, Beam Forming, M8

Tx1



Date: 24.OCT.2012 21:57:57


Tx2



Date: 24.OCT.2012 22:08:47


Power Spectral Density Plot on 5825 MHz, Non HT-20 / Non HT-20, Beam Forming, 6Mbps

Tx1



Date: 24.OCT.2012 21:59:42


Tx2



Date: 24.OCT.2012 22:03:37


Power Spectral Density Plot on 5825 MHz, HT-20 / HT-20, STBC / HT-20, Beam Forming, M0

Tx1



Date: 24.OCT.2012 22:00:19


Tx2



Date: 24.OCT.2012 22:02:56


Power Spectral Density Plot on 5825 MHz, HT-20, Beam Forming, M8

Tx1



Date: 24.OCT.2012 22:00:56


Tx2



Date: 24.OCT.2012 22:02:01


Power Spectral Density Plot on 5755 MHz, HT-40 / HT-40, STBC / HT-40, Beam Forming, M0

Tx1



Date: 24.OCT.2012 22:20:07


Tx2



Date: 24.OCT.2012 22:21:45


Power Spectral Density Plot on 5755 MHz, HT-40, Beam Forming, M8

Tx1



Date: 24.OCT.2012 22:20:46


Tx2



Date: 24.OCT.2012 22:22:57


Power Spectral Density Plot on 5795 MHz, HT-40 / HT-40, STBC / HT-40, Beam Forming, M0

Tx1



Date: 24.OCT.2012 22:17:29


Tx2



Date: 24.OCT.2012 22:24:15


Power Spectral Density Plot on 5795 MHz, HT-40, Beam Forming, M8

Tx1



Date: 24.OCT.2012 22:16:46

Tx2



Date: 24.OCT.2012 22:24:58

3.6 Transmitter Conducted Unwanted Emissions

3.6.1 Transmitter Conducted Unwanted Emissions Limit

Un-restricted Band Emissions Limit	
RF output power procedure	Limit (dBc)
Peak output power procedure	20
Average output power procedure	30
<p>Note 1: If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.</p> <p>Note 2: If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.</p>	


3.6.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.6.3 Test Procedures


Test Method	
<input checked="" type="checkbox"/>	For the transmitter unwanted emissions shall be measured using following options below:
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 10.1 for unwanted emissions into non-restricted bands.
<input checked="" type="checkbox"/>	For conducted measurement, refer as FCC KDB 558074, clause 10.2.2.
<input checked="" type="checkbox"/>	For conducted unwanted emissions into non-restricted bands (relative emission limits). Devices with multiple transmit chains: Refer as FCC KDB 662911, when testing out-of-band and spurious emissions against relative emission limits, tests may be performed on each output individually without summing or adding 10 log(N) if the measurements are made relative to the in-band emissions on the individual outputs.

3.6.4 Test Setup




3.6.5 Transmitter Conducted Unwanted Emissions


Freq. (MHz)	Operating Mode	Data Rate (Mbps)	Conducted Spur Delta (dB)	Limit (dBc)	Margin (dB)
5745	Non HT-20, 6 to 54Mbps	6	42.5	30	12.5
	Non HT-20, Beam Forming, 6 to 54Mbps	6	42.5	30	12.5
	HT-20, M0 to M15 / HT-20, STBC, M0 to M7	M0	43.13	30	13.13
	HT-20, Beam Forming, M0 to M7	M0	43.13	30	13.13
	HT-20, Beam Forming, M8 to M15	M8	42.37	30	12.37
5785	Non HT-20, 6 to 54Mbps	6	41.91	30	11.91
	Non HT-20, Beam Forming, 6 to 54Mbps	6	41.91	30	11.91
	HT-20, M0 to M15 / HT-20, STBC, M0 to M7	M0	42.22	30	12.22
	HT-20, Beam Forming, M0 to M7	M0	42.22	30	12.22
	HT-20, Beam Forming, M8 to M15	M8	42.41	30	12.41
5825	Non HT-20, 6 to 54Mbps	6	42.12	30	12.12
	Non HT-20, Beam Forming, 6 to 54Mbps	6	42.12	30	12.12
	HT-20, M0 to M15 / HT-20, STBC, M0 to M7	M0	41.88	30	11.88
	HT-20, Beam Forming, M0 to M7	M0	41.88	30	11.88
	HT-20, Beam Forming, M8 to M15	M8	42.35	30	12.35
5755	HT-40, M0 to M15 / HT-40, STBC, M0 to M7	M0	38.75	30	8.75
	HT-40, Beam Forming, M0 to M7	M0	38.75	30	8.75
	HT-40, Beam Forming, M8 to M15	M8	40.93	30	10.93
5795	HT-40, M0 to M15 / HT-40, STBC, M0 to M7	M0	39.93	30	9.93
	HT-40, Beam Forming, M0 to M7	M0	39.93	30	9.93
	HT-40, Beam Forming, M8 to M15	M8	39.71	30	9.71

**Transmitter Conducted Unwanted Emissions Plot on
Non HT-20 / Non HT-20, Beam Forming, 6Mbps / Reference Level**



Date: 18.OCT.2012 21:58:46

**Transmitter Conducted Unwanted Emissions Plot on
HT-20 / HT-20, STBC / HT-20, Beam Forming, M0 / Reference Level**


Date: 18.OCT.2012 21:56:38


Transmitter Conducted Unwanted Emissions Plot on HT-20, Beam Forming, M8 / Reference Level


Date: 18.OCT.2012 21:58:02



**Transmitter Conducted Unwanted Emissions Plot on
HT-40 / HT-40, STBC / HT-40, Beam Forming, M0 / Reference Level**




Date: 18.OCT.2012 21:54:24


Transmitter Conducted Unwanted Emissions Plot on HT-40, Beam Forming, M8 / Reference Level




Date: 18.OCT.2012 21:53:15

**Transmitter Conducted Unwanted Emissions Plot on 5745 MHz,
Non HT-20 / Non HT-20, Beam Forming, 6Mbps**

**Transmitter Conducted Unwanted Emissions Plot on 5745 MHz,
HT-20 / HT-20, STBC / HT-20, Beam Forming, M0**




**Transmitter Conducted Unwanted Emissions Plot on 5745 MHz,
HT-20, Beam Forming, M8**

**Transmitter Conducted Unwanted Emissions Plot on 5785 MHz,
Non HT-20 / Non HT-20, Beam Forming, 6Mbps**




**Transmitter Conducted Unwanted Emissions Plot on 5785 MHz,
HT-20 / HT-20, STBC / HT-20, Beam Forming, M0**




Date: 18.OCT.2012 22:35:05

**Transmitter Conducted Unwanted Emissions Plot on 5785 MHz,
HT-20, Beam Forming, M8**



Date: 18.OCT.2012 22:33:36

**Transmitter Conducted Unwanted Emissions Plot on 5825 MHz,
Non HT-20 / Non HT-20, Beam Forming, 6Mbps**

**Transmitter Conducted Unwanted Emissions Plot on 5825 MHz,
HT-20 / HT-20, STBC / HT-20, Beam Forming, M0**


**Transmitter Conducted Unwanted Emissions Plot on 5825 MHz,
HT-20, Beam Forming, M8**

**Transmitter Conducted Unwanted Emissions Plot on 5755 MHz,
HT-40 / HT-40, STBC / HT-40, Beam Forming, M0**


**Transmitter Conducted Unwanted Emissions Plot on 5755 MHz,
HT-40, Beam Forming, M8**

**Transmitter Conducted Unwanted Emissions Plot on 5795 MHz,
HT-40 / HT-40, STBC / HT-40, Beam Forming, M0**


**Transmitter Conducted Unwanted Emissions Plot on 5795 MHz,
HT-40, Beam Forming, M8**



Date: 18.OCT.2012 23:03:21

3.7 Transmitter Radiated Unwanted Emissions

3.7.1 Transmitter Radiated Unwanted Emissions Limit

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.


3.7.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.7.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/>	Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).
<input checked="" type="checkbox"/>	Measurements in the frequency range above 1GHz -40GHz are typically made at a closer distance 3m, because the instrumentation noise floor is typically close to the radiated emission limit.
<input checked="" type="checkbox"/>	The average emission levels shall be measured in [duty cycle \geq 98 or duty factor].
<input checked="" type="checkbox"/>	For the transmitter unwanted emissions shall be measured using following options below:
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 10.1 for unwanted emissions into non-restricted bands.
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 10.2 for unwanted emissions into restricted bands.
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 10.2.3.3 and 8.2.1 Option 1 (spectral trace averaging)
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 10.2.3.3 and 8.2.1 Option 2 (slow sweep speed).
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 4.2.3.2.3 (Reduced VBW) – Duty cycle \geq 98%.
<input type="checkbox"/>	Refer as ANSI C63.10, clause 4.2.3.2.4 average value of pulsed emissions.
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 10.2.3.2 and 8.1.1 measurement procedure peak limit.
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 10.2.3.1 measurement procedure Quasi-Peak limit.
<input checked="" type="checkbox"/>	For cabinet radiation radiated measurement, refer as FCC KDB 558074, clause 10.2.1.
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.4 for radiated emissions from below 30 MHz.
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.5 for radiated emissions from 30 MHz to 1000 MHz.
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.5 for radiated emissions from above 1 GHz.


3.7.4 Test Setup



3.7.5 Transmitter Radiated Unwanted Emissions (Below 30MHz)


All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

3.7.6 Transmitter Radiated Unwanted Emissions (Below 1GHz)



Transmitter Radiated Unwanted Emissions (Below 1GHz)

Test Mode	4	Polarization	Horizontal
Operating Function	Normal Link		



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	30.97	22.61	40.00	-17.39	31.69	0.50	18.22	27.80	Peak	100	0	HORIZONTAL
2	77.53	20.55	40.00	-19.45	40.21	1.00	7.03	27.69	Peak	100	0	HORIZONTAL
3	166.77	23.34	43.50	-20.16	36.54	1.53	12.54	27.27	Peak	100	0	HORIZONTAL
4	321.97	29.56	46.00	-16.44	40.51	2.14	13.96	27.05	Peak	100	0	HORIZONTAL
5	357.86	27.37	46.00	-18.63	37.52	2.22	14.93	27.30	Peak	100	0	HORIZONTAL
6	800.18	39.69	46.00	-6.31	44.22	3.30	19.77	27.60	Peak	100	0	HORIZONTAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

3.7.7 Transmitter Radiated Unwanted Emissions (Above 1GHz)

Transmitter Radiated Unwanted Emissions Result – Average


Freq. (MHz)	Operating Mode	Data Rate (Mbps)	Spurious Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)
5745	Non HT-20, 6 to 54Mbps	6	43.48	54	10.52
	Non HT-20, Beam Forming, 6 to 54Mbps	6	43.48	54	10.52
	HT-20, M0 to M15 / HT-20, STBC, M0 to M7	M0	43.48	54	10.52
	HT-20, Beam Forming, M0 to M7	M0	43.48	54	10.52
	HT-20, Beam Forming, M8 to M15	M8	43.48	54	10.52
5785	Non HT-20, 6 to 54Mbps	6	43.32	54	10.68
	Non HT-20, Beam Forming, 6 to 54Mbps	6	43.32	54	10.68
	HT-20, M0 to M15 / HT-20, STBC, M0 to M7	M0	43.32	54	10.68
	HT-20, Beam Forming, M0 to M7	M0	43.32	54	10.68
	HT-20, Beam Forming, M8 to M15	M8	43.32	54	10.68
5825	Non HT-20, 6 to 54Mbps	6	43.56	54	10.44
	Non HT-20, Beam Forming, 6 to 54Mbps	6	43.56	54	10.44
	HT-20, M0 to M15 / HT-20, STBC, M0 to M7	M0	43.56	54	10.44
	HT-20, Beam Forming, M0 to M7	M0	43.56	54	10.44
	HT-20, Beam Forming, M8 to M15	M8	43.56	54	10.44
5755	HT-40, M0 to M15 / HT-40, STBC, M0 to M7	M0	43.37	54	10.63
	HT-40, Beam Forming, M0 to M7	M0	43.37	54	10.63
	HT-40, Beam Forming, M8 to M15	M8	43.37	54	10.63
5795	HT-40, M0 to M15 / HT-40, STBC, M0 to M7	M0	43.31	54	10.69
	HT-40, Beam Forming, M0 to M7	M0	43.31	54	10.69
	HT-40, Beam Forming, M8 to M15	M8	43.31	54	10.69

Transmitter Radiated Unwanted Emissions Result – Peak

Freq. (MHz)	Operating Mode	Data Rate (Mbps)	Spurious Emission (dBuV/m)	Limit (dBuV/m)	Margin (dB)
5745	Non HT-20, 6 to 54Mbps	6	56.27	74	17.73
	Non HT-20, Beam Forming, 6 to 54Mbps	6	56.27	74	17.73
	HT-20, M0 to M15 / HT-20, STBC, M0 to M7	M0	56.27	74	17.73
	HT-20, Beam Forming, M0 to M7	M0	56.27	74	17.73
	HT-20, Beam Forming, M8 to M15	M8	56.27	74	17.73
5785	Non HT-20, 6 to 54Mbps	6	56.2	74	17.8
	Non HT-20, Beam Forming, 6 to 54Mbps	6	56.2	74	17.8
	HT-20, M0 to M15 / HT-20, STBC, M0 to M7	M0	56.2	74	17.8
	HT-20, Beam Forming, M0 to M7	M0	56.2	74	17.8
	HT-20, Beam Forming, M8 to M15	M8	56.2	74	17.8
5825	Non HT-20, 6 to 54Mbps	6	56.2	74	17.8
	Non HT-20, Beam Forming, 6 to 54Mbps	6	56.2	74	17.8
	HT-20, M0 to M15 / HT-20, STBC, M0 to M7	M0	56.2	74	17.8
	HT-20, Beam Forming, M0 to M7	M0	56.2	74	17.8
	HT-20, Beam Forming, M8 to M15	M8	56.2	74	17.8
5755	HT-40, M0 to M15 / HT-40, STBC, M0 to M7	M0	55.69	74	18.31
	HT-40, Beam Forming, M0 to M7	M0	55.69	74	18.31
	HT-40, Beam Forming, M8 to M15	M8	55.69	74	18.31
5795	HT-40, M0 to M15 / HT-40, STBC, M0 to M7	M0	56.17	74	17.83
	HT-40, Beam Forming, M0 to M7	M0	56.17	74	17.83
	HT-40, Beam Forming, M8 to M15	M8	56.17	74	17.83

Transmitter Radiated Unwanted Emissions Worst Plots (Above 1GHz)
Only test maximum power of operating mode for low, middle, high channel.
Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-20 - Average		
Test Freq. (MHZ)	5745	Polarization	Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg
1	5736.00	54.44	54.00	0.44	50.35	4.40	34.89	35.20	Average	100	0 VERTICAL
2	11392.00	43.48	54.00	-10.52	31.73	7.27	39.50	35.02	Average	100	77 VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-20 - Average		
Test Freq. (MHZ)	5745	Polarization	Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	Remark	cm	deg	Pol/Phase
1	5736.00	43.31	54.00	-10.69	39.22	4.40	34.89	35.20	Average	100	0	HORIZONTAL
2	11638.00	43.37	54.00	-10.63	31.76	7.24	39.44	35.07	Average	100	211	HORIZONTAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)


Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-20 - Average		
Test Freq. (MHZ)	5745	Polarization	Vertical




	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	22980.00	49.53	60.00	-10.47	31.61	14.77	38.66	35.51	Average	100	18 VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-20 - Average		
Test Freq. (MHZ)	5745	Polarization	Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	
1	22980.00	49.65	60.00	-10.35	31.73	14.77	38.66	35.51	Average	100	157	HORIZONTAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-20 - Average		
Test Freq. (MHZ)	5745	Polarization	Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	28725.00	43.08	60.00	-16.92	33.59	11.22	39.74	41.47	Average	100	206 VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-20 - Average		
Test Freq. (MHZ)	5745	Polarization	Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	Remark	cm	deg	
1	28725.00	41.99	60.00	-18.01	32.50	11.22	39.74	41.47	Average	100	101	HORIZONTAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-20 - Peak		
Test Freq. (MHZ)	5745	Polarization	Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	
1	5736.00	62.82	74.00	-11.18	58.73	4.40	34.89	35.20	Peak	100	0	VERTICAL
2	11416.00	55.65	74.00	-18.35	43.92	7.27	39.50	35.04	Peak	100	77	VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-20 - Peak		
Test Freq. (MHZ)	5745	Polarization	Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	
1	5736.00	52.20	74.00	-21.80	48.11	4.40	34.89	35.20	Peak	100	0	HORIZONTAL
2	11662.00	56.27	74.00	-17.73	44.68	7.22	39.44	35.07	Peak	100	211	HORIZONTAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)


Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-20 - Peak		
Test Freq. (MHZ)	5745	Polarization	Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	22980.00	62.01	80.00	-17.99	44.09	14.77	38.66	35.51	Peak	100	18 VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)


Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-20 - Peak		
Test Freq. (MHZ)	5745	Polarization	Horizontal




Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	Pol/Phase
MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	cm	deg	
1	22980.00	61.21	80.00	-18.79	43.29	14.77	38.66	35.51	Peak	100 157 HORIZONTAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-20 - Peak		
Test Freq. (MHZ)	5745	Polarization	Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	Remark	cm	deg	
1	28725.00	55.04	80.00	-24.96	45.55	11.22	39.74	41.47	Peak	100	206	VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-20 - Peak		
Test Freq. (MHZ)	5745	Polarization	Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	Pol/Phase
1	28725.00	53.95	80.00	-26.05	44.46	11.22	39.74	41.47	100	101	HORIZONTAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-20 - Average		
Test Freq. (MHZ)	5785	Polarization	Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	Remark	cm	deg	
1	5785.00	51.09	54.00	-2.91	46.94	4.42	34.93	35.20	Average	100	0	VERTICAL
2	11668.00	43.08	54.00	-10.92	31.49	7.22	39.44	35.07	Average	100	10	VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-20 - Average		
Test Freq. (MHZ)	5785	Polarization	Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
				dB	dBuV	dB	dB/m	dB			Pol/Phase
1	5785.00	41.32	54.00	-12.68	37.17	4.42	34.93	35.20	Average	100	360 HORIZONTAL
2	11668.00	43.32	54.00	-10.68	31.73	7.22	39.44	35.07	Average	100	55 HORIZONTAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-20 - Average		
Test Freq. (MHZ)	5785	Polarization	Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	23140.00	49.79	60.00	-10.21	31.47	14.90	38.70	35.28	Average	100	315	VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)


Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-20 - Average		
Test Freq. (MHZ)	5785	Polarization	Horizontal




	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	23140.00	49.78	60.00	-10.22	31.46	14.90	38.70	35.28	Average	100	208	HORIZONTAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-20 - Average		
Test Freq. (MHZ)	5785	Polarization	Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	28925.00	42.46	60.00	-17.54	33.43	11.31	39.85	42.13	Average	100	93	VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-20 - Average		
Test Freq. (MHZ)	5785	Polarization	Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	28925.00	42.34	60.00	-17.66	33.31	11.31	39.85	42.13	Average	100	177	HORIZONTAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)
Operating Mode HT-20 - Peak

Test Freq. (MHZ) 5785

Polarization

Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	Remark	cm	deg	Pol/Phase
1	5785.00	60.78	74.00	-13.22	56.63	4.42	34.93	35.20	Peak	100	0	VERTICAL
2	11644.00	56.20	74.00	-17.80	44.59	7.24	39.44	35.07	Peak	100	10	VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-20 - Peak		
Test Freq. (MHZ)	5785	Polarization	Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	5785.00	51.36	74.00	-22.64	47.21	4.42	34.93	35.20	Peak	100	360	HORIZONTAL
2	11693.00	55.65	74.00	-18.35	44.09	7.20	39.42	35.06	Peak	100	55	HORIZONTAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-20 - Peak		
Test Freq. (MHZ)	5785	Polarization	Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	Remark	cm	deg	Pol/Phase
1	23140.00	61.60	80.00	-18.40	43.28	14.90	38.70	35.28	Peak	100	315	VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)
Operating Mode HT-20 - Peak

Test Freq. (MHZ) 5785

Polarization

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	23140.00	60.20	80.00	-19.80	41.88	14.90	38.70	35.28	Peak	100	208 HORIZONTAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)
Operating Mode HT-20 - Peak

Test Freq. (MHZ) 5785

Polarization

Vertical



	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	28925.00	53.92	80.00	-26.08	44.89	11.31	39.85	42.13 Peak	100	93	VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-20 - Peak		
Test Freq. (MHZ)	5785	Polarization	Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg
1	28925.00	53.83	80.00	-26.17	44.80	11.31	39.85	42.13	Peak	100	177

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	Non HT-20 - Average		
Test Freq. (MHZ)	5825	Polarization	Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	Pol/Phase
1	5834.00	45.40	54.00	-8.60	41.20	4.43	34.97	35.20	100	0	VERTICAL
2	11675.00	43.56	54.00	-10.44	31.99	7.20	39.43	35.06	100	89	VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	Non HT-20 - Average		
Test Freq. (MHZ)	5825	Polarization	Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	Remark	cm	deg	Pol/Phase
1	5825.00	37.99	54.00	-16.01	33.80	4.42	34.97	35.20	Average	100	360	HORIZONTAL
2	11650.00	43.36	54.00	-10.64	31.77	7.22	39.44	35.07	Average	100	332	HORIZONTAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

**Transmitter Radiated Unwanted Emissions (Above 1GHz)**

Operating Mode	Non HT-20 - Average		
Test Freq. (MHZ)	5825	Polarization	Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg
1	23300.00	50.56	60.00	-9.44	31.77	15.05	38.70	34.96	Average	100	10 VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)


Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	Non HT-20 - Average		
Test Freq. (MHZ)	5825	Polarization	Horizontal




Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark		A/Pos	T/Pos	Pol/Phase
MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		cm	deg	
1 23300.00	50.37	60.00	-9.63	31.58	15.05	38.70	34.96	Average	100	182	HORIZONTAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	Non HT-20 - Average		
Test Freq. (MHZ)	5825	Polarization	Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	Pol/Phase
1	29125.00	43.02	60.00	-16.98	33.93	11.38	39.93	42.22	Average	100	195 VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	Non HT-20 - Average		
Test Freq. (MHZ)	5825	Polarization	Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	29125.00	42.80	60.00	-17.20	33.71	11.38	39.93	42.22	Average	100	270	HORIZONTAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	Non HT-20 - Peak		
Test Freq. (MHZ)	5825	Polarization	Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	5810.00	55.82	74.00	-18.18	51.65	4.42	34.95	35.20	Peak	100	0	VERTICAL
2	11699.00	55.41	74.00	-18.59	43.87	7.18	39.42	35.06	Peak	100	89	VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	Non HT-20 - Peak		
Test Freq. (MHZ)	5825	Polarization	Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	Remark	cm	deg	Pol/Phase
1	5825.00	49.35	74.00	-24.65	45.16	4.42	34.97	35.20	Peak	100	360	HORIZONTAL
2	11650.00	56.20	74.00	-17.80	44.61	7.22	39.44	35.07	Peak	100	332	HORIZONTAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)
Operating Mode Non HT-20 - Peak

Test Freq. (MHZ) 5825

Polarization

Vertical



Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1 23300.00	60.57	80.00	-19.43	41.78	15.05	38.70	34.96	Peak	100	10	VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)


Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	Non HT-20 - Peak		
Test Freq. (MHZ)	5825	Polarization	Horizontal




Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1 23300.00	60.83	80.00	-19.17	42.04	15.05	38.70	34.96	Peak	100	182	HORIZONTAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	Non HT-20 - Peak		
Test Freq. (MHZ)	5825	Polarization	Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBUV/m	dBUV/m	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
				dB	dBUV	dB	dB/m	dB			Pol/Phase
1	29125.00	54.09	80.00	-25.91	45.00	11.38	39.93	42.22	Peak	100	195 VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	Non HT-20 - Peak		
Test Freq. (MHZ)	5825	Polarization	Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	29125.00	53.94	80.00	-26.06	44.85	11.38	39.93	42.22	Peak	100	270	HORIZONTAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-40 - Average		
Test Freq. (MHZ)	5755	Polarization	Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	
1	5769.00	48.99	54.00	-5.01	44.87	4.41	34.91	35.20	Average	100	0	VERTICAL
2	11680.00	43.37	54.00	-10.63	31.80	7.20	39.43	35.06	Average	100	332	VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-40 - Average		
Test Freq. (MHZ)	5755	Polarization	Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamplifier	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5755.00	39.06	54.00	-14.94	34.96	4.40	34.90	35.20	Average	100	360	HORIZONTAL
2	11646.00	43.15	54.00	-10.85	31.54	7.24	39.44	35.07	Average	100	258	HORIZONTAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-40 - Average		
Test Freq. (MHZ)	5755	Polarization	Vertical



	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	23020.00	49.85	60.00	-10.15	31.84	14.77	38.70	35.46	Average	100	168 VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-40 - Average		
Test Freq. (MHZ)	5755	Polarization	Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	Pol/Phase
1	23020.00	49.94	60.00	-10.06	31.93	14.77	38.70	35.46	100	108	HORIZONTAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)
Operating Mode HT-40 - Average

Test Freq. (MHZ) 5755

Polarization

Vertical



Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Loss	Factor	Factor	Remark	A/Pos	T/Pos	Pol/Phase
MHz	dBUV/m	dBUV/m	dB	dBUV	dB	dB/m	dB				cm	deg	
1	28775.00	42.30	60.00	-17.70	32.92	11.24	39.76	41.62	Average		100	1	VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-40 - Average		
Test Freq. (MHZ)	5755	Polarization	Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	28775.00	42.32	60.00	-17.68	32.94	11.24	39.76	41.62	Average	100	103 HORIZONTAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-40 - Peak		
Test Freq. (MHZ)	5755	Polarization	Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	5735.00	59.43	74.00	-14.57	55.34	4.40	34.89	35.20	Peak	100	0	VERTICAL
2	11646.00	55.37	74.00	-18.63	43.76	7.24	39.44	35.07	Peak	100	332	VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-40 - Peak		
Test Freq. (MHZ)	5755	Polarization	Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	Pol/Phase
1	5755.00	50.87	74.00	-23.13	46.77	4.40	34.90	35.20 Peak	100	360	HORIZONTAL
2	11714.00	55.69	74.00	-18.31	44.15	7.18	39.42	35.06 Peak	100	258	HORIZONTAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-40 - Peak		
Test Freq. (MHZ)	5755	Polarization	Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	
1	23020.00	60.69	80.00	-19.31	42.68	14.77	38.70	35.46	Peak	100	168	VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-40 - Peak		
Test Freq. (MHZ)	5755	Polarization	Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg
1	23020.00	61.24	80.00	-18.76	43.23	14.77	38.70	35.46	Peak	100	108 HORIZONTAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-40 - Peak		
Test Freq. (MHZ)	5755	Polarization	Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	Remark	cm	deg	
1	28775.00	54.46	80.00	-25.54	45.08	11.24	39.76	41.62	Peak	100	1	VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-40 - Peak		
Test Freq. (MHZ)	5755	Polarization	Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	Remark	cm	deg	
1	28775.00	53.90	80.00	-26.10	44.52	11.24	39.76	41.62	Peak	100	103	HORIZONTAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-40 - Average		
Test Freq. (MHZ)	5795	Polarization	Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
			dBuV/m	dB	dBuV	dB	dB/m	dB				
1	5786.00	48.36	54.00	-5.64	44.21	4.42	34.93	35.20	Average	100	360	VERTICAL
2	11692.00	43.31	54.00	-10.69	31.75	7.20	39.42	35.06	Average	100	147	VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-40 - Average		
Test Freq. (MHZ)	5795	Polarization	Horizontal



	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5795.00	40.12	54.00	-13.88	35.96	4.42	34.94	35.20	Average	100	0	HORIZONTAL
2	11641.00	43.10	54.00	-10.90	31.49	7.24	39.44	35.07	Average	100	32	HORIZONTAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)


Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-40 - Average		
Test Freq. (MHZ)	5795	Polarization	Vertical




	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
1	23180.00	49.71	60.00	-10.29	31.27	14.92	38.70	35.18	Average	100	0 VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-40 - Average		
Test Freq. (MHZ)	5795	Polarization	Horizontal




Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	Pol/Phase
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	Remark	cm	deg	
1 23180.00	49.88	60.00	-10.12	31.44	14.92	38.70	35.18	Average	110	16	HORIZONTAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-40 - Average		
Test Freq. (MHZ)	5795	Polarization	Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	
1	28775.00	42.30	60.00	-17.70	32.92	11.24	39.76	41.62	Average	100	1	VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-40 - Average		
Test Freq. (MHZ)	5795	Polarization	Horizontal



	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	28775.00	42.32	60.00	-17.68	32.94	11.24	39.76	41.62	Average	100	103	HORIZONTAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-40 - Peak		
Test Freq. (MHZ)	5795	Polarization	Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	
1	5786.00	58.42	74.00	-15.58	54.27	4.42	34.93	35.20	Peak	100	360	VERTICAL
2	11590.00	55.64	74.00	-18.36	43.96	7.29	39.47	35.08	Peak	100	147	VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-40 - Peak		
Test Freq. (MHZ)	5795	Polarization	Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	Remark	cm	deg	Pol/Phase
1	5795.00	48.31	74.00	-25.69	44.15	4.42	34.94	35.20	Peak	100	0	HORIZONTAL
2	11624.00	56.17	74.00	-17.83	44.55	7.24	39.45	35.07	Peak	100	32	HORIZONTAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)
Operating Mode HT-40 - Peak

Test Freq. (MHZ) 5795

Polarization

Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg
1	23180.00	60.58	80.00	-19.42	42.14	14.92	38.70	35.18	Peak	100	0 VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-40 - Peak		
Test Freq. (MHZ)	5795	Polarization	Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
1	23180.00	60.92	80.00	-19.08	42.48	14.92	38.70	35.18	Peak	110	16 HORIZONTAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)


Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-40 - Peak		
Test Freq. (MHZ)	5795	Polarization	Vertical



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	Remark	cm	deg	Pol/Phase
1	28775.00	54.46	80.00	-25.54	45.08	11.24	39.76	41.62	Peak	100	1	VERTICAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Transmitter Radiated Unwanted Emissions (Above 1GHz)

Operating Mode	HT-40 - Peak		
Test Freq. (MHZ)	5795	Polarization	Horizontal



	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBUV/m	dBUV/m	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	28775.00	53.90	80.00	-26.10	44.52	11.24	39.76	41.62	Peak	100	103	HORIZONTAL

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

4 Test Equipment and Calibration Data

Instrument	Manufacturer	Model No.	Serial No.	Spec.	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100377	9kHz ~ 2.75GHz	Oct. 23, 2012	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Nov. 14, 2011	Conduction (CO01-CB)
V- LISN	Schwarzbeck	NSLK 8127	8127-478	9K ~ 30MHz	Jun. 22, 2012	Conduction (CO01-CB)
PULSE LIMITER	R&S	ESH3-Z2	100430	9K~30MHz	Feb. 03, 2012	Conduction (CO01-CB)
Signal analyzer	R&S	FSV40	100979	9KHz~40GHz	Oct. 08, 2012	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	Jun. 05, 2012	Conducted (TH01-CB)
RF Power Divider	HP	11636A	00306	2GHz ~ 18GHz	N.C.R	Conducted (TH01-CB)
RF Power Splitter	Anaren	44100	1839	2GHz ~ 18GHz	N.C.R	Conducted (TH01-CB)
RF Power Splitter	Anaren	42100	17930	2GHz ~ 18GHz	N.C.R	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz – 26.5 GHz	Nov. 17, 2011	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz – 26.5 GHz	Nov. 17, 2011	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz – 26.5 GHz	Nov. 17, 2011	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz – 26.5 GHz	Nov. 17, 2011	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz – 26.5 GHz	Nov. 17, 2011	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	Jan. 11, 2012	Radiation (03CH01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	Jan. 10, 2013	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 27, 2012	Radiation (03CH01-CB)
Horn Antenna	SCHWARZBEAK	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Nov. 23, 2012	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 27, 2012	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Nov. 23, 2012	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26.5GHz ~ 40GHz	Jul. 31, 2012	Radiation (03CH01-CB)

**FCC and IC Radio Test Report****Report No. : FR281405-03AB**

Instrument	Manufacturer	Model No.	Serial No.	Spec.	Calibration Date	Remark
Spectrum analyzer	R&S	FSP40	100056	9KHz~40GHz	Nov. 02, 2012	Radiation (03CH01-CB)
EMI Test Receiver	R&S	ESCS 30	100355	9KHz ~ 2.75GHz	Mar. 20, 2012	Radiation (03CH01-CB)
EMI Test Receiver	R&S	ESCS 30	100355	9KHz ~ 2.75GHz	Mar. 19, 2013	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9 kHz - 30 MHz	Oct. 29, 2012	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N.C.R	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO2000	N/A	1 m - 4 m	N.C.R	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-1	N/A	1 GHz – 26.5 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-2	N/A	1 GHz – 26.5 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 18, 2012	Radiation (03CH01-CB)

Note: Calibration Interval of instruments listed above is one year.
N.C.R. means Non-Calibration required.