



- NOTES
- UNIT WEIGHT 3.5 KG ± 0.1 KG (7.72 LBS ± 0.22 LBS). INCL. CONFIG. MODULE
 - ⊙ DENOTES APPROXIMATE CENTER OF GRAVITY.
 - DARKEN PORTION INDICATES SOLID PART OF POLARIZING KEYWAY.
 - THE 405035A/405035A-THD INSTALLATION IS IN ACCORDANCE WITH ARINC 404A 3/8 SHORT ATR EXCEPT FOR: TOLERANCES MARKED WITH *, COOLING AIRHOLES ARE PLACED OUTSIDE RECOMMENDED AREA AND THE CONFIGURATION MODULE HARDWARE EXCEEDS THE UNIT REAR CASE PROJECTION OUTLINE AS NOTED ON DRAWING.
 - DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN BRACKETS ARE INCHES.
 - UNIT MATERIAL: ALUMINIUM.
 - UNIT FINISH: PAINT EPOXYESTER PRIMER + BLACK INFRASOL TOPCOAT
 - DO NOT BLOCK COOLING AIR HOLES. FORCED COOLING IS NOT RECOMMENDED. COOLING AIR HOLES ARE PLACED IDENTICALLY ON TOP AND BOTTOM SIDE OF UNIT.
 - NOTES AND DIMENSIONS NOT BALLOONED ARE FOR REFERENCE ONLY

		THESE COMMODITIES, TECHNOLOGY OR SOFTWARE ARE CONTROLLED IN ACCORDANCE WITH THE UNITED STATES EXPORT ADMINISTRATION REGULATIONS. WHEN EXPORTED FROM THE UNITED STATES, DIVERSION CONTRARY TO U.S. LAW IS PROHIBITED.		NAME DATE		COBHAM Comant Industries, Inc. Fullerton, CA	
		UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MM (INCHES) TOLERANCES: ANGLES ±0.5°		DRAWN 6/15/22			
		INCHES		CHECKED 6/15/22		TITLE OUTLINE DRAWING SDU 405035A/405035A-THD AERO HSD	
		mm		ENG APPR. 07/12/22			
NEXT ASSY		.XX ±0.02		Q.A. 07/13/22		SIZE C	
USED ON		.X ±0.5		MATERIAL: SEE NOTE 6			
THE INFORMATION CONTAINED IN THIS DRAWING IS THE PROPERTY OF COBHAM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT WRITTEN PERMISSION OF COBHAM IS PROHIBITED.		.XXX ±0.008		FINISH: SEE NOTE 7		CAGE CODE 51351	
		.XXXX ±0.004		DO NOT SCALE DRAWING			
						TYPED SIGNATURES INDICATE APPROVAL. HANDWRITTEN SIGNATURE APPROVAL OF THIS DOCUMENT IS ON FILE AT COMANT INDUSTRIES, INC., FULLERTON, CALIFORNIA	
						SCALE: N/A	
						WEIGHT: SEE NOTE 1	
						SHEET: 1 OF 1	