

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

Product Description	Wireless Mouse and Pad Combo
Model Name	SA-MPMS-NPRYL
Series Model	SA-MPMS-NPNB, SA-MPMS, SA-MPMS-XXX, SA-MPMSP-PNK, SA-MPMSP-LAV, SA-MPMSP, SA-MPMSP-XXX, SA-MPMD-BLU, SA-MPMD, SA-MPMD-XXX, SA-MPMC-BLU, SA-MPMC, SA-MPMC-XXX
FCC ID	2AANZMPMS

2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

3. CALCULATION

2.4GHz:

$$P_t = -6.641 \text{ dBm} = 0.22 \text{ mW}$$

The value of the Maximum output power P_t is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation $\text{SAR} = (0.22 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.402 \text{ GHz}}] = 0.068 < 3.0$ for

4. CONCLUSION

The SAR evaluation is not required.