说明书为折叠式 尺寸: 540*120MM 材质: 100g双胶纸 (彩色)

版本: V1.0 类型: 环保

版本	修改内容	日期
Ver: 1.0	首次发行。	2022/02/21

设计	审核	审批
Tony-W		
2022/02/21		

540.00 mm

HelloBaby®

User Manual

2.4GHz Digital Wireless Video Baby Monitor





Model: HB6339

The pictures are for reference only, please subject to practicality

service@hellobabv.net.cn

and hear your baby sleeping or playing in their room anytime

1. SAFETY INSTRUCTIOINS

Choking hazard: This product contains small parts, please be careful when unpack and

near water.

DO NOT: Use the appliance if the cord or plug is damaged. If your baby monitor is not

DO NOT: Use the appliance if the cord or plus is dimaged. If your bady monitor is not operating properly he has suffered any damping, contact Velocitems' service center to properly dependent of the control of the c

Power source: This unit should only be used with the AC power adapter package (rate 5V DC 1A).

Damage requiring service: This unit should be serviced by qualified per . Objects have fallen or liquid has been spilled into the product; . The units have been exposed to rain;

2. WARRANTY TERMS

and materials. If you have warranty or support issues, please contact our after-sales serv

*So use your parents unit and camera unit together, you have to establish a ratio link between them, and the range will be affected by environmental conditions.

*Any large metal object, like a refrigerator, a mirror, a filling cabinet, metallic doors reinforced concrete between the buylon ad parent unit may block the radio signal.

*The signal strength may also be reduced by other solid structures, like walls, or by one electrical equagment, such as 17, computers, cordisors or mobile phones, however, and the such consideration of t

or electrical equipment, such as TV, computers, cordless or mobile phones, fluorescen lights or dimmer switches.

*Use of other 2.4GHz product, such as wireless networks (Wi-Fi routers), Bluetooth systems, or microwave ovens, may cause interference with this product, so keep the bit monitor away at least 5ft (1.5m) from such products, or turn them off if they cause

- 5.1 TUNN ON THE BAY UNIT:

 1. Insert the CD (page of the power adapter into the DC jack in the rear of the Baby Unit;

 2. Insert the tother and of the power adapter into a suitable electrical outlet;

 2. TUNN ON THE PART UNIT:


 2. TUNN ON THE PART UNIT:

 1. Insert the DC plug of the power adapter into a tuble deet rical outlet;

 2. TUNN ON THE GO of the power adapter into a vitable electrical outlet;


 2. TUNN ON THE GO of the power adapter into a vitable electrical outlet;


2



5.3 INFRARED NIGHT VISION (AUTOMATIC)







6





7.2 UP ▲ KEY

7.5 RIGHT ► KEY

7.7 DIGITAL ZOOM and hold the 💇 key around 2 seconds to operate zoom in/ out;

Press and hold the the key around 2 seconds to operate zoom in/out;

7.8 New Way file

Press and hold Seavy to enter two way talk mode. A microphone scon ★ will be
displayed in the corner of the LOS sercen. Release the key to stop.

Note: When you are in the two-way talk mode, the parent unit speaker is muted.

4

△WARNING



Strangulation Hazard: Children have STRANGLED in cords. Keep this cord out of the reach of children (more than 3 ft (0.9 m) away). Do not remove this tag

AVERTISSEMENT

DANGER D'ÉTRANGLEMENT: Des enfants se sont ÉTRANGLÉS avec des cordons électriques. Garde le cordonélectrique hors de la portée des enfants (à plus de 0,9m/3 pi du lit d'enfant). Ne pas enjever



Note: Camera icon with """ means it is well registered. You should select and pair with the

camera icon without ** sign.

8.1.1 ADO CAME.

1. Press the MENU @ key then the menu will pop up;
2. Press the Mey or ** key until the camera icon ∰ is highlighted, then press ★ key or

* key to select your desired camera;
3. Press OK@ yev on cent into us-hemon;

Press ▲ key or ▼ key to select ADD CAM
 then press OK key;
 When the icon ... displayed on the LCD screen, press the PAIR buttor

camera;
6. Once paired, "\sum * appears on the LCD screen.
7 If falls, repeat the above steps.

7. If falls, repeat the a powe steps.
8.1.2 PELETE CAMERA
1. Press the MENU

key and the menu will pop up;
2. Press the

key or

key until the camera icon

is highlighted, then press

key or

2. Press the ◀ vey or F vey until ■ a injunigates.
3. Press the Æ vey or ¥ key to select the desired volume level from level 1 = 5.
(The default volume level setting is level 2 and level D is OFF.)
3. TIMPERATURE UNIT SETTING
1. Press the ② key and the menu will pop up;
2. Press the ④ vey or ▶ key until the temperature icon □ is highlighted;

5. Press the ^Tave to Est.

Next The disorder properture range is 0°10° ℃.

1. Press A / Y key to select ^Tall then @for alers esting.

2. Press A / Y key to select ^Tall then @for alers esting.

2. Press A / Y key to select ^Tall then @for alers esting.

6. Press A / Y key to select ^Tall then which the ^Tall then which the ^Tall then which the Then th

4. Press ▲ / ▼ keys to adjust the Lo limit then press @ to confirm.

To skip the settling edit, press ⊇ Ney to exit to last menu level.

More the High temperature alarm range 1.20 40 ℃, and the low temperature alarm range is 0.19 ℃. The High temperature alarm default settling is 35 ℃, and the low temperature alarm default settling is 35 ℃, and the low temperature alarm default settling is 35 ℃, and the low settlings, the temperature alarm conflaint settling is 45 ℃, and the low settlings, the temperature is done to make the temperature is done to make the default settling is 30 ℃, and the low pressure is the temperature is done to make the low the temperature is done to make the low the low the low pressure is done to the low temperature is done to the low the low temperature is done to the low

default setting is OFF.

of the parent unit is off.

The speaker of the parent unit only goes on if the baby makes loud sounds (e.g.

Frequency	2403.5MHz~2475.5MHz
Power Adaptor	Parent Unit: Input: 100-240VAC 50/60Hz Output: 5V DC 1A Camera Unit: Input: 100-240VAC 50/60Hz Output: 5V DC 1A
Operating Range	Up to 1000ft (300m) outdoor (line of sight) Up to 165ft (50m) indoor
Display	3.2" Diagonal TFT LCD
Battery (Parent Unit)	Li-ion 3.7V 950mAh (3.515Wh)
Battery Life	Up to 6 hours
Maximum power	<19d8m
Operation environment	Operation Temperature: +32F~+104F (0°C~40°C) Battery Charging Temperature: +50F~+104F (10°C~40°C)
environment	Relative Humidity : 15%-85%

No reception on the monitor	* The power adapters may not be properly connected; * Confirm that the camera and monitor are ON; * Camera may be far away from the monitor; * Camera and monitor may not be properly paired; follow PAIRING instruction
Interference or poor reception	 Move the monitor close to the camera; The camera or monitor may be placed too close to many metal objects; Other electronic devices may be interfering with the signal; The battery power may be too low;
Audio feedback (high pitched noise)	The camera and monitor may be placed too closed; The volume on the monitor may be set too high;
Frozen Picture on Screen	 Repower the baby unit (plug out the adapter, then plug it into the socket again); Press the RESET key at the back of parent unit;

* Never use cleaning agents or solvents.

Improper or incorrect use of batteries may cause corrosion or battery leakage, which could cause personal injury or damage to property. Use only the types of the batteries which are indicated in this manual. CAUTION: Risk of Fire and Burns. Do Not Open, Crush, Heat Above 45 degree C or inciner

Disposal of a battery into fire or a hot over, or mechanically crushing or cutting of a batte

that can result in an explosion; Leaving a battery in an extremely high temperature surrounding environment that can result in an explosion or the leakage of flammable liquid or gas; A battery subjected to extremely low air pressure that may result in an explosion or the

leakage of flammable liquid or gas. The battery shall not be exposed to excessive heat such as sunshine, fire or the like:

SAI Statement for Monitor's Specific Absorption for late (SAI) information: This Monitor meets the government's requirements for apposing to raise given. The Specific Absorption late (SAI) information: This Monitor meets the government's requirements of the design of the design of the specific control of the specific

Informations sur le débit d'aborption spécifique (DAS): Catte Monitaur produ au exigence de la gouvernement en matière d'exposition aux ondes radio. Le lignes directories sont basées sur des normes élaborées par des organisations considérations de la granditation de la commentation de la commen

de 1,6 W / kg en moyenne sur un gramme de tissu. Types d'appareils: la Moniteur a de 1,5 M / 1,9 em moyemes our un gramme dei tissz. Typissé d'appareils Lis Moniteura geolgement et de taste d'arm groppert a cette limité ADI, Cet appareil a les ties pour des copierations trypiques pourfeis soit et le corp saive été dus de la Moniteura groef à l'Omiteur de confesion de la compartie d

FU Declaration of Conformity (DOC)

 Model: H66339
 Tel: 1-516-681-3729

 Agd: 22 Hazelwood Drive, Jericho, NY 11753
 Tel: 1-516-681-3729

 Authorized UK Representative(UK): Safestore we host
 Tel: 44(0)740-570-279

 Add: 30 progress road leigh no seas 5959/LV
 Tel: 44(0)740-570-279

Risk Group 1 WARNING IR emitted from this product. Do not stare at operating Jamp Product tested against ENS2471