



Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V05

Report Template Revision Date: 2021-11-03

RF Exposure Evaluation Report

Report No.: CQASZ20240701214E-05
Applicant: Shenzhen Jiteng Network Technology Co., Ltd
Address of Applicant: Floor 7, Building B, Boton Science and Technology Park, Chaguang Road, Xili Street Nanshan District, Shenzhen, China
Equipment Under Test (EUT):
EUT Name: Mini PC
Model No.: Air12 Lite, Air***Lite (*Representing numbers 0-9, letters A-Z, a-z, "-" or spaces)
Test Model No.: Air12 Lite
Brand Name: GEEKOM
FCC ID: 2AY4C-GAL01
Standards: 47 CFR Part 1.1307
47 CFR Part 1.1310
447498 D04 Interim General RF Exposure Guidance v01
Date of Receipt: 2024-07-01
Date of Test: 2024-07-01 to 2024-11-25
Date of Issue: 2024-11-25
Test Result: **PASS***

*In the configuration tested, the EUT complied with the standards specified above

Tested By: Lewis Zhou
(Lewis Zhou)

Reviewed By: Timo Lei
(Timo Lei)

Approved By: Alex
(Alex Wang)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20240701214E-05	Rev.01	Initial report	2024-11-25

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
.....	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 GENERAL DESCRIPTION OF BT CLASSIC	4
3.4 GENERAL DESCRIPTION OF 2.4G WIFI CLASSIC	5
3.5 GENERAL DESCRIPTION OF 5G WIFI CLASSIC	5
4 MPE EVALUATION	7
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	7
4.1.1 Limits	7
4.1.2 Test Procedure	7
4.1.3 EUT RF Exposure	8

3 General Information

3.1 Client Information

Applicant:	Shenzhen Jiteng Network Technology Co., Ltd
Address of Applicant:	Floor 7, Building B, Boton Science and Technology Park, Chaguang Road, Xili Street Nanshan District, Shenzhen, China
Manufacturer:	Shenzhen Jiteng Network Technology Co., Ltd
Address of Manufacturer:	Floor 7, Building B, Boton Science and Technology Park, Chaguang Road, Xili Street Nanshan District, Shenzhen, China
Factory:	Guangdong Enok Communication Co., Ltd.
Address of Factory:	No.62, Lixiang Road, Dalang Town, Dongguan City, Guangdong Province, P.R. China

3.2 General Description of EUT

Product Name:	Mini PC
Model No.:	Air12 Lite, Air***Lite (*Representing numbers 0-9, letters A-Z, a-z, "-" or spaces)
Test Model No.:	Air12 Lite
Trade Mark:	GEEKOM
Software Version:	Windows 11
Hardware Version:	NUCAN03_MB_DDR4_V20
EUT Power Supply:	Power supply adapter
	Model:HKA06519034-6K Input:100-240V~50/60Hz 1.5A Output:19V 3.42V 64.98W
	Model:BSY065T1903423 D Input:100-240V~50/60Hz 1.5A Output:19V 3.42V 64.98W

3.3 General Description of BT Classic

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	Bluetooth Spec 5.2
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channel:	79
Transfer Rate:	1Mbps/2Mbps/3Mbps
Hopping Channel Type:	Adaptive Frequency Hopping systems
Sample Type:	☒ Mobile ☐ Portable
Antenna Type:	PIFA antenna
Antenna Gain:	1.32 dBi

3.4 General Description of 2.4G WIFI Classic

Operation Frequency:	2412MHz~2462MHz
Type of Modulation:	802.11b: DSSS(CCK/QPSK/BPSK) 802.11g: OFDM(BPSK/QPSK/16QAM/64QAM) 802.11n (HT20)(HT40): OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11ax(HE20)(HE40) :OFDMA(1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Number of Channel:	IEEE 802.11b/g, IEEE 802.11n HT20 ax HE20: 11 Channels IEEE 802.11n HT40 ax HE 40: 7 Channels
Channel Separation:	5MHz
Transfer Rate:	802.11b: 1M/2M/5.5M/11M bps 802.11g: 6M/9M/12M/18M/24M/36M/48M/54M bps 802.11n(HT20)(HT40): 7.2M/14.4M/21.7M/28.9M/43.3M/57.8M/65M/72.2M bps 802.11ax(HE20)(HE40): 8.6M/17.2M/25.8M/34.4M/51.6M/68.8M/77.4M/86M/103.2M/114.7M/129M/143.4Mbps
Sample Type:	☒ Mobile ☐ Portable
Antenna Type:	PIFA antenna
Antenna Gain:	Ant1:1.32dBi, Ant2:2.25dBi Ant1+Ant2:4.8dBi

3.5 General Description of 5G WIFI Classic

Type of Modulation:	OFDM
Number of Channel:	IEEE 802.11a/n/ac/ax(20M): 5150MHz ~5250MHz/ 4 channel IEEE 802.11n/ac/ax(40M): 5150MHz ~5250MHz/ 2 channel IEEE 802.11ac/ax(80M): 5150MHz ~5250MHz/ 1 channel IEEE 802.11a/n/ac/ax(20M): 5725MHz ~5850MHz/ 5 channel IEEE 802.11n/ac/ax(40M): 5725MHz ~5850MHz/ 2 channel IEEE 802.11ac/ax(80M): 5725MHz ~5850MHz/ 1 channel
Channel Separation:	5MHz
Operation Frequency:	IEEE 802.11a/n/ac/ax(20M): 5150MHz ~5250 MHz IEEE802.11n/ac/ax(40M): 5150MHz ~5250 MHz IEEE802.11ac/ax(80M): 5150MHz ~5250 MHz IEEE 802.11a/n/ac/ax(20M): 5725MHz ~5850 MHz IEEE802.11n/ac/ax(40M): 5725MHz ~5850 MHz IEEE802.11ac/ax(80M): 5725MHz ~5850 MHz
Sample Type:	☒ Mobile ☐ Portable
Antenna Type:	PIFA antenna
Antenna Gain:	Ant1:2.06dBi@5GHz: Wi-Fi: U-NII-1, 3.38dBi@5GHz: Wi-Fi: U-NII-3 Ant2:3dBi@5GHz: Wi-Fi: U-NII-1, 3dBi@5GHz: Wi-Fi: U-NII-3

	Ant1+Ant2: 5.55dBi@5GHz: Wi-Fi: U-NII-1, 6.2dBi@5GHz: Wi-Fi: U-NII-3
--	---

Note:

The above parameters will directly affect the test results. The information is provided by the applicant.

4 MPE Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

The table applies to any RF source (i.e., single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least $\lambda/2\pi$. The thresholds are based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator. For mobile devices that are not exempt per Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than ERP_{20cm} in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave Dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure

1) For BT Classic

Measurement Data

GFSK mode			
Test channel	Max.Peak Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)
2402MHz	4.83	1.85	6.68
Tune-up			
Tune up tolerance (dBm)		Maximum tune-up Power	
		(dBm)	(mW)
6.5±1		7.5	5.62

$\pi/4$ DQPSK mode			
Test channel	Max.Peak Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)
2402MHz	4.77	1.85	6.62
Tune-up			
Tune up tolerance (dBm)		Maximum tune-up Power	
		(dBm)	(mW)
6.5±1		7.5	5.62

8DPSK mode			
Test channel	Max.Peak Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)
2402MHz	4.94	1.85	6.79
Tune-up			
Tune up tolerance (dBm)		Maximum tune-up Power	
		(dBm)	(mW)
6.5±1		7.5	5.62

Note: 1) Refer to report No. CQASZ20240701214E-01 for EUT test Max Conducted Peak Output Power value.

2) EUT's module is more than 20cm away from the human body.

2) For BLE

Measurement Data

GFSK(1Mbps) mode			
Test channel	Max.Peak Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)
2480MHz	6.17	1.85	8.02
Tune-up			
Tune up tolerance (dBm)		Maximum tune-up Power	
		(dBm)	(mW)
8.0±1		9	7.94
GFSK(2Mbps) mode			
Test channel	Max.Peak Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)
2480MHz	6.3	1.85	8.15
Tune-up			
Tune up tolerance (dBm)		Maximum tune-up Power	
		(dBm)	(mW)
8.0±1		9	7.94

The ERP of this product is less than 3060mW

Note: 1) Refer to report No. CQASZ20240701214E-02 for EUT test Max Conducted Peak Output Power value.
2) EUT's module is more than 20cm away from the human body.

3) For 2.4G WIFI Classic

Measurement Data

11b mode			
Test channel	Max.Peak Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)
2462MHz	14.19	1.85	16.04
Tune-up			
Tune up tolerance (dBm)		Maximum tune-up Power	
		(dBm)	(mW)
16.0±1		17	50.12

11g mode			
Test channel	Max.Peak Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)
2462MHz	11.66	1.98	13.64
Tune-up			
Tune up tolerance (dBm)		Maximum tune-up Power	
		(dBm)	(mW)
13.5±1		14.5	28.18

11n20 mode			
Test channel	Max.Peak Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)
2462MHz	14.12	4.93	19.05
Tune-up			
Tune up tolerance (dBm)		Maximum tune-up Power	
		(dBm)	(mW)
19.0±1		20	100.00

11n40 mode			
Test channel	Max.Peak Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)
2452MHz	14.15	4.93	19.08
Tune-up			
Tune up tolerance (dBm)		Maximum tune-up Power	
		(dBm)	(mW)
19.0±1		20	100.00

11ax20 mode			
Test channel	Max.Peak Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)
2412MHz	14.83	4.93	19.76
Tune-up			
Tune up tolerance (dBm)		Maximum tune-up Power	
		(dBm)	(mW)
19.5±1		20.5	112.20

11ax 40 mode			
Test channel	Max.Peak Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)
2452MHz	14.9	4.93	19.83
Tune-up			
Tune up tolerance (dBm)		Maximum tune-up Power	
		(dBm)	(mW)
19.5±1		20.5	112.20

Note: 1) Refer to report No. CQASZ20240701214E-03 for EUT test Max Conducted AV Output Power value.
 2) EUT's module is more than 20cm away from the human body.

3) For 5G WIFI Classic

11a mode			
Test channel	Max.Peak Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)
5825MHz	12.29	1.84	14.13
Tune-up			
Tune up tolerance (dBm)		Maximum tune-up Power	
		(dBm)	(mW)
14.0±1		15.0	31.62

11n20 mode			
Test channel	Max.Peak Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)
5825MHz	13.84	4.88	18.72
Tune-up			
Tune up tolerance (dBm)		Maximum tune-up Power	
		(dBm)	(mW)
18.5±1		19.5	89.13

11n40 mode			
Test channel	Max.Peak Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)
5230MHz	13.14	4.84	17.98
Tune-up			
Tune up tolerance (dBm)		Maximum tune-up Power	
		(dBm)	(mW)
18.0±1		19	79.43

11ac20 mode			
Test channel	Max.Peak Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)
5240MHz	13.17	4.84	18.01
Tune-up			
Tune up tolerance (dBm)		Maximum tune-up Power	
		(dBm)	(mW)
18.0±1		19	79.43

11ac40 mode			
Test channel	Max.Peak Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)
5755MHz	13.81	4.88	18.69
Tune-up			
Tune up tolerance (dBm)		Maximum tune-up Power	
		(dBm)	(mW)
18.5±1		19.5	89.13

11ac80 mode			
Test channel	Max.Peak Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)
5775MHz	14.06	4.88	18.94
Tune-up			
Tune up tolerance (dBm)		Maximum tune-up Power	
		(dBm)	(mW)
19.0±1		20	100.00

11ax20 mode			
Test channel	Max.Peak Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)
5785MHz	18.03	4.88	22.91
Tune-up			
Tune up tolerance (dBm)		Maximum tune-up Power	
		(dBm)	(mW)
23.0±1		24	251.19

11ax40 mode			
Test channel	Max.Peak Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)
5755MHz	18.54	4.88	23.42
Tune-up			
Tune up tolerance (dBm)		Maximum tune-up Power	
		(dBm)	(mW)
23.5±1		24.5	281.84

11ax80 mode			
Test channel	Max.Peak Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)
5210MHz	14.16	4.84	19
Tune-up			
Tune up tolerance (dBm)		Maximum tune-up Power	
		(dBm)	(mW)
19±1		20	100.00

Note: 1) Refer to report No. CQASZ20240701214E-04 for EUT test Max Conducted AV Output Power value.
 2) EUT's module is more than 20cm away from the human body.

*** END OF REPORT ***