


FCC RF Exposure

Applicant : PEAG, LLC dba JLab Audio
Address : 5927 LANDAU CT, Carlsbad, CA 92008, United States
Product Name : Wireless Speaker
Brand Mark : 
Model : JLab GO Party
Series model : N/A
FCC ID : 2AHYV-GOSP
Report Number : BLA-EMC-202501-A4103
Date of Receipt : Jan. 10, 2025
Date of Test : Jan. 10, 2025 to Jan. 20, 2025
47 CFR Part 15, Part1.1307
Test Standard : 47 CFR Part 15, Part2.1093
KDB447498D04 General RF Exposure Guidance v01
Test Result : Pass

Compiled by: Mark Chen

Review by: Sweels

Approved by:

Issued Date: Feb. 10, 2025



BlueAsia of Technical Services(Shenzhen) Co.,Ltd.

Address: Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District,
Shenzhen, Guangdong Province, China



The test report is effective only with both signature and specialized stamp and The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full. The results described in this report do not represent the quality or characteristics of the sampled batch, nor do they represent any similar or identical products that are not explicitly stated.

Table of Contents

| | |
|---|----------|
| 1 General information | 4 |
| 1.1 General information | 4 |
| 1.2 General description of EUT | 4 |
| 2 RF Exposure Compliance Requirement | 5 |
| 2.1 Standard Requirement | 5 |
| 2.2 Limits | 5 |
| 2.3 Result | 6 |

Revise Record

| Version No. | Date | Description |
|-------------|---------------|-------------|
| 01 | Feb. 10, 2025 | Original |
| | | |
| | | |
| | | |

1 General information

1.1 General information

| | |
|--------------|---|
| Applicant | PEAG, LLC dba JLab Audio |
| Address | 5927 LANDAU CT, Carlsbad, CA 92008, United States |
| Manufacturer | GuangDong Simpreal Intelligent Technology Co., Ltd |
| Address | Room 2408, JiaHong ZhenXing DaSha, DongGuan Avenue #13, DongCheng District, DongGuan City, GuangDong Province, P.R. China |
| Factory | GuangDong Simpreal Intelligent Technology Co., Ltd |
| Address | Room 2408, JiaHong ZhenXing DaSha, DongGuan Avenue #13, DongCheng District, DongGuan City, GuangDong Province, P.R. China |

1.2 General description of EUT

| | |
|----------------------|---|
| Product name | Wireless Speaker |
| Model no. | JLab GO Party |
| Operation Frequency: | BT/BLE:2402MHz-2480MHz |
| Modulation Type: | BLE:GFSK BT:GFSK, $\pi/4$ DQPSK, 8DPSK |
| Number of Channels: | BLE:40 BT:79 |
| Antenna Type: | PCB Antenna |
| Antenna Gain: | -0.58dBi (Provided by customer) |
| Power supply: | Battery DC 3.7V |
| Test Voltage: | DC 3.7V |
| Hardware Version | N/A |
| Software Version | N/A |

2 RF Exposure Compliance Requirement

2.1 Standard Requirement

According to 447498 D04 Interim General RF Exposure Guidance v01

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

2.2 Limits

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B. 2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).

Example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

| Frequency (MHz) | Distance (mm) | | | | | | | | | | |
|-----------------|---------------|----|----|----|-----|-----|-----|-----|-----|-----|-----|
| | | 5 | 10 | 15 | 20 | 25 | 30 | 35 | 40 | 45 | 50 |
| | 300 | 39 | 65 | 88 | 110 | 129 | 148 | 166 | 184 | 201 | 217 |
| | 450 | 22 | 44 | 67 | 89 | 112 | 135 | 158 | 180 | 203 | 226 |
| | 835 | 9 | 25 | 44 | 66 | 90 | 116 | 145 | 175 | 207 | 240 |
| | 1900 | 3 | 12 | 26 | 44 | 66 | 92 | 122 | 157 | 195 | 236 |
| | 2450 | 3 | 10 | 22 | 38 | 59 | 83 | 111 | 143 | 179 | 219 |
| | 3600 | 2 | 8 | 18 | 32 | 49 | 71 | 96 | 125 | 158 | 195 |
| | 5800 | 1 | 6 | 14 | 25 | 40 | 58 | 80 | 106 | 136 | 169 |

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B. 1})$$

2.3 Result

$$\text{EIRP} = p_t \times g_t = (E \times d)^{2/30}$$

Where:

p_t = transmitter output power in watts,

g_t = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m,

d = measurement distance in meters (m)

$$\text{Spot} = (E \times d)^{2/30} \times g_t$$

Separation distance = 0.5cm

Ant gain = -0.58dBi

For BLE 2M(Worst):

Max Output power = 3.042dBm @ 2442MHz

EIRP = 3.042dBm-0.58dBi=2.462dBm, because conducted Max Output power >EIRP

So, ERP = 3.042-2.15=0.892dBm=1.228mW < 2.751 mW

For BT Classic(8DPSK):

Max Output power = 4.596dBm @ 2441MHz

EIRP = 4.596dBm-0.58dBi=4.016dBm, because conducted Max Output power >EIRP

So, ERP = 4.596dBm-2.15=2.446dBm=1.756mW < 2.752 mW

Comply with RF exposure exemption limit.

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, the result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.