



# FCC SAR TEST REPORT

Report No.: STS2105068H01

Issued for

4G NET INC

3000 NW 72 AVENUE MIAMI Florida United States 33122

Product Name:	Mobile phone
Brand Name:	UNIQCELL
Model Name:	A1
Series Model:	A2, A3, A3Pro
FCC ID:	2AWCN-A1
Test Standard:	ANSI/IEEE Std. C95.1
	FCC 47 CFR Part 2 ( 2.1093)
	IEEE 1528: 2013
Max. Report SAR (1g):	Head: 1.097 W/kg
	Body: 0.935 W/kg

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, All Test Data Presented in this report is only applicable to presented Test sample.



## Test Report Certification

**Applicant's name** ..... : 4G NET INC

**Address** ..... : 3000 NW 72 AVENUE MIAMI Florida United States 33122

**Manufacturer's Name** ..... : METELL TECHNOLOGY CO.,LIMITED

**Address** ..... : 7 / F, Building B, Tefa Industrial Park, Guangming District,  
Shenzhen, China

### Product description

**Product name** ..... : Mobile phone

**Brand name** ..... : UNIQCELL

**Model name** ..... : A1

**Series Model**..... : A2, A3, A3Pro

**Standards**..... : ANSI/IEEE Std. C95.1-1992  
FCC 47 CFR Part 2 ( 2.1093)  
IEEE 1528: 2013

The device was tested by Shenzhen STS Test Services Co., Ltd. in accordance with the measurement methods and procedures specified in KDB 865664 The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

**Date of Test**..... :

**Date (s) of performance of tests**..... : 17 May 2021 ~ 18 May 2021

**Date of Issue**..... : 04 June 2021

**Test Result**..... : **Pass**

**Testing Engineer** :

*Luffy He*

(Luffy He)

**Technical Manager** :

*Sean She*

(Sean she)

**Authorized Signatory** :

*Vita Li*

(Vita Li)





## Table of Contents

<b>1. General Information</b>	<b>5</b>
1.1 EUT Description	5
1.2 Test Environment	6
1.3 Test Factory	6
<b>2. Test Standards and Limits</b>	<b>7</b>
<b>3. SAR Measurement System</b>	<b>8</b>
3.1 Definition of Specific Absorption Rate (SAR)	8
3.2 SAR System	8
<b>4. Tissue Simulating Liquids</b>	<b>11</b>
4.1 Simulating Liquids Parameter Check	11
<b>5. SAR System Validation</b>	<b>13</b>
5.1 Validation System	13
5.2 Validation Result	13
<b>6. SAR Evaluation Procedures</b>	<b>14</b>
<b>7. EUT Antenna Location Sketch</b>	<b>15</b>
7.1 SAR test exclusion consider table	17
<b>8. EUT Test Position</b>	<b>20</b>
8.1 Define Two Imaginary Lines on the Handset	20
8.2 Hotspot mode exposure position condition	21
<b>9. Uncertainty</b>	<b>22</b>
9.1 Measurement Uncertainty	22
9.2 System validation Uncertainty	23
<b>10. Conducted Power Measurement</b>	<b>24</b>
10.1 Test Result	24
<b>11. EUT and Test Setup Photo</b>	<b>26</b>
11.1 EUT Photo	26
11.2 Setup Photo	32
<b>12. SAR Result Summary</b>	<b>43</b>
12.1 Head SAR	43
12.2 Body-worn SAR	44
12.3 repeated SAR measurement	45
<b>13. Equipment List</b>	<b>48</b>
<b>Appendix A. System Validation Plots</b>	<b>49</b>
<b>Appendix B. SAR Test Plots</b>	<b>53</b>
<b>Appendix C. Probe Calibration and Dipole Calibration Report</b>	<b>61</b>

**Revision History**

Rev.	Issue Date	Report No.	Effect Page	Contents
00	04 June 2021	STS2105068H01	ALL	Initial Issue





## 1. General Information

Environmental evaluation measurements of specific absorption rate (SAR) distributions in emulated human head and body tissues exposed to radio frequency (RF) radiation from wireless portable devices for compliance with the rules and regulations of the U.S. Federal Communications Commission (FCC).

### 1.1 EUT Description

Product Name	Mobile phone			
Brand Name	UNIQCELL			
Model Name	A1			
Series Model	A2, A3, A3Pro			
Model Difference	In addition to the different model names, A2 and A1 have different memory/GSM antenna/BT antenna/cameras /display sizes; A3 and A3Pro and A1 only have different model names			
Battery	Rated Voltage:3.7V Charge Limit Voltage:4.2V Capacity: 1000mAh			
Device Category	Portable			
Product stage	Production unit			
RF Exposure Environment	General Population / Uncontrolled			
IMEI	358688000000159			
Hardware Version	H3995_MB_V2.0			
Software Version	SUPERCON50_6464_11B_PCB01_gprs_MT6250_S00.K16_S02.bin			
Frequency Range	GSM 850: 824 MHz ~ 849 MHz PCS1900: 1850 MHz ~ 1910 MHz Bluetooth: 2402 MHz to 2480 MHz			
Max. Reported SAR(1g): (Limit:1.6W/kg)	Test Model: A1			
	Band	Mode	Head (W/kg)	Body Worn (W/kg)
	PCE	GSM 850	1.097	0.894
	PCE	GSM 1900	0.329	0.290
	DSS	Bluetooth <sup>Note</sup>	0.067	0.067
	Test Model: A2			
	Band	Mode	Head (W/kg)	Body Worn (W/kg)
	PCE	GSM 850	0.776	0.935
	PCE	GSM 1900	0.632	0.472
	DSS	Bluetooth <sup>Note</sup>	0.067	0.067
1-g Sum SAR	Test Model: A1		1.164	0.961
	Test Model: A2		0.843	1.002
FCC Equipment Class	Licensed Portable Transmitter Held to Ear (PCE) Part 15 Spread Spectrum Transmitter (DSS)			
Operating Mode:	GSM: GSM Voice; GPRS/EGPRS Class 12 Bluetooth: GFSK + $\pi$ /4DQPSK+8DPSK			
Antenna Specification:	GSM: PIFA Antenna Bluetooth: Monopole Antenna			
SIM Card	Support dual-SIM, dual standby, the multiple SIM card with two lines cannot transmitting at the same time			
Hotspot Mode	Not Support			
DTM Mode	Not Support			

**Note:**

1. Bluetooth SAR was estimated
2. The dual SIM card mobile has 2 SIM slots and supports dual SIM dual standby. The WWAN radio transmission will be enabled by either one SIM at a time (Single active)
3. After pre-scan two SIM cards power, we found test result of the SIM1 was the worse, so we chose SIM1 card to perform all tests.
4. The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power

## 1.2 Test Environment

Ambient conditions in the SAR laboratory:

Items	Required
Temperature (°C)	18-25
Humidity (%RH)	30-70

## 1.3 Test Factory

ShenZhen STS Test Services Co.,Ltd.

A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration No.: 625569

IC Registration No.: 12108A

A2LA Certificate No.: 4338.01



## 2. Test Standards and Limits

No.	Identity	Document Title
1	47 CFR Part 2	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	ANSI/IEEE Std. C95.1-1992	IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz
3	IEEE Std. 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
4	FCC KDB 447498 D01 v06	Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies
5	FCC KDB 865664 D01 v01r04	SAR Measurement 100 MHz to 6 GHz
6	FCC KDB 865664 D02 v01r02	RF Exposure Reporting
7	FCC KDB 941225 D01 v03r01	SAR Measurement Procedures for 3G Devices
8	FCC KDB 941225 D05 v02r05	SAR for LTE Devices
9	FCC KDB 941225 D06 v02r01	Hotspot Mode SAR
10	FCC KDB 648474 D04 v01r03	SAR Evaluation Considerations for Wireless Handsets
11	FCC KDB 248227 D01 Wi-Fi SAR v02r02	SAR Considerations for 802.11 Devices

### (A). Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

### (B). Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

NOTE: Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

#### **Population/Uncontrolled Environments:**

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

#### **Occupational/Controlled Environments:**

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

#### **NOTE**

#### **GENERAL POPULATION/UNCONTROLLED EXPOSURE**

#### **PARTIAL BODY LIMIT**

**1.6 W/kg**



### 3. SAR Measurement System

#### 3.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density ( $\rho$ ). The equation description is as below:

$$SAR = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma E^2}{\rho}$$

Where:  $\sigma$  is the conductivity of the tissue,  
 $\rho$  is the mass density of the tissue and E is the RMS electrical field strength.

#### 3.2 SAR System

MVG SAR System Diagram:



COMOSAR is a system that is able to determine the SAR distribution inside a phantom of human being according to different standards. The COMOSAR system consists of the following items:

- Main computer to control all the system
- 6 axis robot
- Data acquisition system
- Miniature E-field probe
- Phone holder
- Head simulating tissue



The following figure shows the system.



The EUT under test operating at the maximum power level is placed in the phone holder, under the phantom, which is filled with head simulating liquid. The E-Field probe measures the electric field inside the phantom. The Open SAR software computes the results to give a SAR value in a 1g or 10g mass.

### 3.2.1 Probe

For the measurements the Specific Dosimetric E-Field Probe SN 07/21 EPGO352 with following specifications is used

- Probe Length: 330 mm
- Length of Individual Dipoles: 2 mm
- Maximum external diameter: 8 mm
- Probe Tip External Diameter: 2.5 mm
- Distance between dipole/probe extremity: 1 mm
- Dynamic range: 0.01-100 W/kg
- Probe linearity: 3%
- Axial Isotropy: < 0.10 dB
- Spherical Isotropy: < 0.10 dB
- Calibration range: 450 MHz to 6 GHz for head & body simulating liquid.
- Angle between probe axis (evaluation axis) and surface normal line: less than 30°



Figure 1-MVG COMOSAR Dosimetric E field Dipole

### 3.2.2 Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.


SN 32/14 SAM115



SN 32/14 SAM116



### 3.2.3 Device Holder



The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5 mm distance, a positioning uncertainty of  $\pm 0.5$  mm would produce a SAR uncertainty of  $\pm 20$  %. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.

#### 4. Tissue Simulating Liquids



## 4. Tissue Simulating Liquids

### 4.1 Simulating Liquids Parameter Check

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations described in Reference [12] and extrapolated according to the head parameters specified in P1528.

#### Head Tissue

Frequency (MHz)	cellulose %	DGBE %	HEC %	NaCl %	Preventol %	Sugar %	X100 %	Water %	Conductivity $\sigma$	Permittivity $\epsilon_r$
750	0.2	/	/	1.4	0.2	57.0	/	41.1	0.89	41.9
835	0.2	/	/	1.4	0.2	57.9	/	40.3	0.90	41.5
900	0.2	/	/	1.4	0.2	57.9	/	40.3	0.97	41.5
1800	/	44.5	/	0.3	/	/	30.45	55.2	1.4	40.0
1900	/	44.5	/	0.3	/	/	30.45	55.2	1.4	40.0
2000	/	44.5	/	0.3	/	/	/	55.2	1.4	40.0
2450	/	44.9	/	0.1	/	/	/	55.0	1.80	39.2
2600	/	45.0	/	0.1	/	/	/	54.9	1.96	39.0

#### Body Tissue

Frequency (MHz)	cellulose %	DGBE %	HEC %	NaCl %	Preventol %	Sugar %	X100 %	Water %	Conductivity $\sigma$	Permittivity $\epsilon_r$
750	0.2	/	/	0.9	0.1	47.2	/	51.7	0.96	55.5
835	0.2	/	/	0.9	0.1	48.2	/	50.8	0.97	55.2
900	0.2	/	/	0.9	0.1	48.2	/	50.8	1.05	55.0
1800	/	29.4	/	0.4	/	/	30.45	70.2	1.52	53.3
1900	/	29.4	/	0.4	/	/	30.45	70.2	1.52	53.3
2000	/	29.4	/	0.4	/	/	/	70.2	1.52	53.3
2450	/	31.3	/	0.1	/	/	/	68.6	1.95	52.7
2600	/	31.7	/	0.1	/	/	/	68.2	2.16	52.3

Tissue dielectric parameters for head and body phantoms				
Frequency	$\epsilon_r$		$\sigma$ S/m	
	Head	Body	Head	Body
300	45.3	58.2	0.87	0.92
450	43.5	56.7	0.87	0.94
900	41.5	55.0	0.97	1.05
1450	40.5	54.0	1.20	1.30
1800	40.0	53.3	1.40	1.52
2450	39.2	52.7	1.80	1.95
3000	38.5	52.0	2.40	2.73
5800	35.3	48.2	5.27	6.00


**LIQUID MEASUREMENT RESULTS**

Date	Ambient		Simulating Liquid		Parameters	Target	Measured	Deviation %	Limited %
	Temp. [°C]	Humidity %	Frequency	Temp. [°C]					
2021-05-17	22.1	51	824.2 MHz	21.8	Permittivity	41.55	43.12	3.79	±5
					Conductivity	0.9	0.87	-3.60	±5
2021-05-17	22.1	51	835 MHz	21.8	Permittivity	41.5	41.14	-0.86	±5
					Conductivity	0.9	0.90	0.00	±5
2021-05-17	22.1	51	836.6 MHz	21.8	Permittivity	41.5	40.41	-2.63	±5
					Conductivity	0.9	0.91	0.57	±5
2021-05-17	22.1	51	848.8 MHz	21.8	Permittivity	41.5	42.26	1.83	±5
					Conductivity	0.91	0.91	0.00	±5
2021-05-18	22.8	58	1900 MHz	22.5	Permittivity	40	39.91	-0.22	±5
					Conductivity	1.4	1.40	-0.11	±5



## 5.1 Validation System

The system check verifies that the system operates within its specifications. It's performed daily or before every SAR measurement. The system check uses normal SAR measurement in the flat section of the phantom with a matched dipole at a specified distance. The system validation setup is shown as below.



Comparing to the original SAR value provided by MVG, the validation data should be within its specification of 10 %.

Freq.(MHz)	Power(mW)	Tested Value (W/Kg)	Normalized SAR (W/kg/W)	Target (W/Kg/W)	Tolerance(%)	Date
835	100	0.963	9.63	9.56	0.73	2021-05-17
1900	100	4.048	40.48	39.70	1.96	2021-05-18

1. The tolerance limit of System validation  $\pm 10\%$ .
2. The dipole input power (forward power) was 100 mW.
3. The results are normalized to 1 W input power.



## 6. SAR Evaluation Procedures

The procedure for assessing the average SAR value consists of the following steps:

The following steps are used for each test position

- Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- Measurement of the SAR distribution with a grid of 8 to 16mm \* 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- Around this point, a cube of 30 \* 30 \* 30 mm or 32 \* 32 \* 32 mm is assessed by measuring 5 or 8 \* 5 or 8\*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

➤ Area Scan& Zoom Scan

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01 quoted below.


When the 1-g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.



## 7. EUT Antenna Location Sketch


It is a Mobile phone, support GSM/BT mode.

Test Model: A1





Test Model: A2



Note 1: The antenna information refer the manufacturer provide report, applicable only to the tested sample identified in the report.



### 7.1 SAR test exclusion consider table

The WWAN/BT SAR evaluation of Maximum power (dBm) summing tolerance.

Test Model: A1

Exposure Position	Wireless Interface	GSM850	PCS1900	BT
	Calculated Frequency	824.2	1850.2	2402
	Maximum Turn-up power (dBm)	31.50	26.50	2
	Maximum rated power(mW)	1412.54	446.68	1.58
Back Side	Separation distance (mm)	5	5	5
	exclusion threshold(mW)	16.52	11.03	9.68
	Testing required?	YES	YES	NO
Front Side	Separation distance (mm)	5	5	5
	exclusion threshold(mW)	16.52	11.03	9.68
	Testing required?	YES	YES	NO
Left Edge	Separation distance (mm)	5	5	40
	exclusion threshold(mW)	16.52	11.03	77.43
	Testing required?	YES	YES	NO
Right Edge	Separation distance (mm)	5	5	5
	exclusion threshold(mW)	16.52	11.03	212.13
	Testing required?	YES	YES	NO
Top Edge	Separation distance (mm)	90	90	72
	exclusion threshold(mW)	385.01	510.28	316.78
	Testing required?	YES	NO	NO
Bottom Edge	Separation distance (mm)	5	5	18
	exclusion threshold(mW)	16.52	11.03	763.68
	Testing required?	YES	YES	NO



Test Model: A2

Exposure Position	Wireless Interface	GSM850	PCS1900	BT
	Calculated Frequency	824.2	1850.2	2402
	Maximum Turn-up power (dBm)	31.50	26.50	2
	Maximum rated power(mW)	1412.54	446.68	1.58
Back Side	Separation distance (mm)	5	5	5
	exclusion threshold(mW)	16.52	11.03	9.68
	Testing required?	YES	YES	NO
Front Side	Separation distance (mm)	5	5	5
	exclusion threshold(mW)	16.52	11.03	9.68
	Testing required?	YES	YES	NO
Left Edge	Separation distance (mm)	5	5	45
	exclusion threshold(mW)	16.52	11.03	87.11
	Testing required?	YES	YES	NO
Right Edge	Separation distance (mm)	5	5	8
	exclusion threshold(mW)	16.52	11.03	339.41
	Testing required?	YES	YES	NO
Top Edge	Separation distance (mm)	92	92	78
	exclusion threshold(mW)	396.00	530.28	376.78
	Testing required?	YES	NO	NO
Bottom Edge	Separation distance (mm)	5	5	20
	exclusion threshold(mW)	16.52	11.03	670.82
	Testing required?	YES	YES	NO

**Note:**

1. maximum power is the source-based time-average power and represents the maximum RF output power among production units.
2. per KDB 447498 D01, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
3. per KDB 447498 D01, standalone SAR test exclusion threshold is applied; if the distance of the antenna to the user is <25mm, 25mm is user to determine SAR exclusion threshold
4. per KDB 447498 D01, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distance  $\leq 50\text{mm}$  are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, } f(\text{GHz}) \text{ is the RF channel transmit}$$



frequency in GHz. Power and distance are rounded to the nearest mW and mm before calculation. The result is rounded to one decimal place for comparison

For <50mm distance, we just calculate mW of the exclusion threshold value(3.0)to do compare

5. per KDB 447498 D01, at 100 MHz to 6GHz and for test separation distances >50mm, the SAR test exclusion threshold is determined according to the following
- a)[threshold at 50mm in step 1]+(test separation distance -50mm)\*(f (MHz)/150)]mW, at 100 MHz to 1500 MHz
  - b) [threshold at 50mm in step1]+( test separation distance -50mm) \*10]mW at > 1500MHz and ≤ 6GHz



## 8. EUT Test Position


This EUT was tested in Right Cheek, Right Titled, Left Cheek, Left Titled, Front Face and Rear Face.

### 8.1 Define Two Imaginary Lines on the Handset

(1) The vertical centerline passes through two points on the front side of the handset the midpoint of the width  $w_t$  of the handset at the level of the acoustic output, and the midpoint of the width  $w_b$  of the handset.

(2) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.


(3) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.



#### Cheek Position


1) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.

2) To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost




### Title Position

- (1) To position the device in the “cheek” position described above.
- (2) While maintaining the device in the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until with the ear is lost.




### Body-worn Position Conditions:

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB Publication 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. When the same wireless transmission configuration is used for testing body-worn accessory and hotspot mode SAR, respectively, in voice and data mode, SAR results for the most conservative *test separation distance* configuration may be used to support both SAR conditions. When the *reported* SAR for a body-worn accessory, measured without a headset connected to the handset, is  $> 1.2 \text{ W/kg}$ , the highest *reported* SAR configuration for that wireless mode and frequency band should be repeated for the body-worn accessory with a headset attached to the handset.



## 8.2 Hotspot mode exposure position condition

For handsets that support hotspot mode operations, with wireless router capabilities and various web browsing function, the relevant hand and body exposure condition are tested according to the hotspot SAR procedures in KDB 941225. A test separation distance of 10 mm is required between the phantom and all surface and edges with a transmitting antenna located within 25 mm from that surface or edge. When form factor of a handset is smaller than 9cm x 5cm, a test separation distance of 5mm (instead of 10mm) is required for testing hotspot mode. When the separate distance required for body-worn accessory testing is larger than or equal to that tested for hotspot mode, in the same wireless mode and for the same surface of the phone, the hotspot mode SAR data may be used to support body-worn accessory SAR compliance for that particular configuration (surface).







## 9. Uncertainty

### 9.1 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in IEEE 1528: 2013. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

Uncertainty Component	Tol (+/- %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+/-%)	10g Ui (+/-%)	$v_i$
<b>Measurement System</b>								
Probe calibration	5.831	N	1	1	1	5.83	5.83	$\infty$
Axial Isotropy	0.695	R	$\sqrt{3}$	$\sqrt{0.5}$	$\sqrt{0.5}$	0.28	0.28	$\infty$
Hemispherical Isotropy	1.045	R	$\sqrt{3}$	$\sqrt{0.5}$	$\sqrt{0.5}$	0.43	0.43	$\infty$
Boundary effect	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	$\infty$
Linearity	0.685	R	$\sqrt{3}$	1	1	0.40	0.40	$\infty$
System detection limits	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	$\infty$
Modulation response	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	$\infty$
Readout Electronics	0.021	N	1	1	1	0.021	0.021	$\infty$
Response Time	0	R	$\sqrt{3}$	1	1	0	0	$\infty$
Integration Time	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	$\infty$
RF ambient conditions-Noise	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	$\infty$
RF ambient conditions-reflections	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	$\infty$
Probe positioner mechanical tolerance	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	$\infty$
Probe positioning with respect to phantom shell	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	$\infty$
Post-processing	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	$\infty$
<b>Test sample Related</b>								
Test sample positioning	2.6	N	1	1	1	2.6	2.6	$\infty$
Device holder uncertainty	3	N	1	1	1	3	3	$\infty$
SAR drift measurement	5	R	$\sqrt{3}$	1	1	2.89	2.89	$\infty$
SAR scaling	5	R	$\sqrt{3}$	1	1	2.89	2.89	$\infty$
<b>Phantom and tissue parameters</b>								
Phantom uncertainty (shape and thickness uncertainty)	4	R	$\sqrt{3}$	1	1	2.31	2.31	$\infty$
Uncertainty in SAR correction for deviations in permittivity and conductivity	1.9	N	1	1	0.84	1.90	1.60	$\infty$
Liquid conductivity (temperature uncertainty)	2.5	R	$\sqrt{3}$	0.78	0.71	1.13	1.02	$\infty$
Liquid conductivity (measured)	4	N	1	0.78	0.71	3.12	2.84	M
Liquid permittivity (temperature uncertainty)	2.5	R	$\sqrt{3}$	0.23	0.26	0.33	0.38	$\infty$
Liquid permittivity (measured)	5	N	1	0.23	0.26	1.15	1.30	M
Combined Standard Uncertainty		RSS				9.79	9.59	
Expanded Uncertainty (95% Confidence interval)		K=2				19.58	19.18	





## 9.2 System validation Uncertainty

Uncertainty Component	Tol (+-%)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	vi
<b>Measurement System</b>								
Probe calibration	5.831	N	1	1	1	5.83	5.83	∞
Axial Isotropy	0.695	R	$\sqrt{3}$	1	1	0.40	0.40	∞
Hemispherical Isotropy	1.045	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Boundary effect	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	0.685	R	$\sqrt{3}$	1	1	0.40	0.40	∞
System detection limits	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	3.0	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Readout Electronics	0.021	N	1	1	1	0.021	0.021	∞
Response Time	0.0	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Integration Time	1.4	R	$\sqrt{3}$	0	0	0.00	0.00	∞
RF ambient conditions-Noise	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient conditions-reflections	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner mechanical tolerance	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to phantom shell	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Post-Processing	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	∞
<b>System validation source</b>								
Deviation of experimental dipole from numerical dipole	5.0	N	1	1	1	5.00	5.00	∞
Input power and SAR drift measurement	5.0	R	$\sqrt{3}$	1	1	2.89	2.89	∞
Other source contribution Uncertainty	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	∞
<b>Phantom and set-up</b>								
Phantom uncertainty (shape and thickness uncertainty)	4.0	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	1.9	N	1	1	0.84	1.90	1.60	∞
Liquid conductivity (temperature uncertainty)	2.5	R	$\sqrt{3}$	0.78	0.71	1.13	1.02	∞
Liquid conductivity (measured)	4	N	1	0.78	0.71	3.12	2.84	M
Liquid permittivity (temperature uncertainty)	2.5	R	$\sqrt{3}$	0.23	0.26	0.33	0.38	∞
Liquid permittivity (measured)	5	N	1	0.23	0.26	1.15	1.30	M
Combined Standard Uncertainty		RSS				9.718	9.517	
Expanded Uncertainty (95% Confidence interval)		K=2				19.44	19.04	



## 10. Conducted Power Measurement

### 10.1 Test Result

Burst Average Power (dBm)						
Band	GSM 850			PCS 1900		
Channel	128	190	251	512	661	810
Frequency (MHz)	824.2	836.6	848.8	1850.2	1880.0	1909.8
GSM(GMSK, 1-Slot)	31.32	31.08	30.73	26.05	24.45	22.81
GPRS (GMSK, 1-Slot)	31.20	30.97	30.62	26.04	24.37	22.70
GPRS (GMSK, 2-Slot)	30.78	30.51	30.21	25.63	23.97	22.29
GPRS (GMSK, 3-Slot)	30.35	30.11	29.76	25.22	23.51	21.87
GPRS (GMSK, 4-Slot)	29.87	29.64	29.32	24.82	23.02	21.43
Remark: GPRS, CS4 coding scheme. EGPRS, MCS5 coding scheme. Multi-Slot Class 8, Support Max 4 downlink, 1 uplink, 5 working link Multi-Slot Class 10, Support Max 4 downlink, 2 uplink, 5 working link Multi-Slot Class 12, Support Max 4 downlink, 4 uplink, 5 working link						

Fram- Average Power(dBm)						
Band	GSM 850			PCS 1900		
Channel	128	190	251	512	661	810
Frequency (MHz)	824.2	836.6	848.8	1850.2	1880.0	1909.8
GSM(GMSK, 1-Slot)	22.29	22.05	21.70	17.02	15.42	13.78
GPRS (GMSK, 1-Slot)	22.17	21.94	21.59	17.01	15.34	13.67
GPRS (GMSK, 2-Slot)	24.76	24.49	24.19	19.61	17.95	16.27
GPRS (GMSK, 3-Slot)	26.09	25.85	25.50	20.96	19.25	17.61
GPRS (GMSK, 4-Slot)	26.86	26.63	26.31	21.81	20.01	18.42
Remark : 1. SAR testing was performed on the maximum frame-averaged power mode. 2. The frame-averaged power is linearly proportion to the slot number configured and it is linearly scaled the maximum Burst - averaged power based on time slots. The calculated method is shown as below: Frame-averaged power = Burst averaged power (1 TX Slot) – 9.03 dB Frame-averaged power = Burst averaged power (2 TX Slots) – 6.02 dB Frame-averaged power = Burst averaged power (3 TX Slots) - 4.26 dB Frame-averaged power = Burst averaged power (4 TX Slots) – 3.01 dB						

**Bluetooth**

Mode	Channel Number	Frequency (MHz)	Average Power (dBm)
GFSK(1Mbps)	0	2402	1.37
	39	2441	1.18
	78	2480	0.69
$\pi/4$ -DQPSK(2Mbps)	0	2402	-1.71
	39	2441	-1.85
	78	2480	-2.33
8DPSK(3Mbps)	0	2402	-1.22
	39	2441	-1.78
	78	2480	-2.25



## 11. EUT and Test Setup Photo

### 11.1 EUT Photo

Test Model: A1

Front side



Back side







Top side




Bottom side






Left side



Right side





Test Model: A2

Front side




Back side








Top side



Bottom side





Left side



Right side






## 11.2 Setup Photo


Test Model: A1  
Right Touch



Right Tilt



Left Touch




Left Tilt



Body Front side(separation distance is 10mm)



Body Back side(separation distance is 10mm)



Body Left side(separation distance is 10mm)



Body Right side(separation distance is 10mm)





Body Bottom side(separation distance is 10mm)




Body Top side(separation distance is 10mm)






Test Model: A2

Right Touch



Right Tilt



Left Touch



Left Tilt



Body Front side(separation distance is 10mm)




Body Back side(separation distance is 10mm)





Body Left side(separation distance is 10mm)



Body Right side(separation distance is 10mm)



Body Bottom side(separation distance is 10mm)




Body Top side(separation distance is 10mm)





Liquid depth (15 cm)





## 12. SAR Result Summary

### 12.1 Head SAR

#### Test Model: A1

Band	Mode	Test Position	Ch.	Result 1g (W/Kg)	Power Drift(%)	Max.Turn-up Power(dBm)	Meas.Output Power(dBm)	Scaled SAR (W/Kg)	Meas. No.
GSM 850	GPRS Data-4 Slot	Right Cheek	128	0.771	1.13	30.00	29.87	0.794	/
		Right Tilt	128	0.352	0.97	30.00	29.87	0.363	/
		Left Cheek	128	1.065	-3.83	30.00	29.87	<b>1.097</b>	1
		Left Cheek	190	0.911	1.28	30.00	29.64	0.990	/
		Left Cheek	251	0.897	-1.12	29.50	29.32	0.935	/
		Left Tilt	128	0.505	0.01	30.00	29.87	0.520	/
GSM1900	GPRS Data-4 Slot	Right Cheek	512	0.316	0.98	25.00	24.82	<b>0.329</b>	3
		Right Tilt	512	0.151	-2.70	25.00	24.82	0.157	/
		Left Cheek	512	0.227	2.71	25.00	24.82	0.237	/
		Left Tilt	512	0.114	3.87	25.00	24.82	0.119	/

#### Test Model: A2

Band	Mode	Test Position	Ch.	Result 1g (W/Kg)	Power Drift(%)	Max.Turn-up Power(dBm)	Meas.Output Power(dBm)	Scaled SAR (W/Kg)	Meas. No.
GSM 850	GPRS Data-4 Slot	Right Cheek	128	0.633	3.85	30.00	29.87	0.652	/
		Right Tilt	128	0.311	1.83	30.00	29.87	0.320	/
		Left Cheek	128	0.753	3.82	30.00	29.87	<b>0.776</b>	5
		Left Cheek	190	0.636	3.95	30.00	29.64	0.691	/
		Left Cheek	251	0.621	-2.37	29.50	29.32	0.647	/
		Left Tilt	128	0.364	3.38	30.00	29.87	0.375	/
GSM1900	GPRS Data-4 Slot	Right Cheek	512	0.606	-0.41	25.00	24.82	<b>0.632</b>	7
		Right Tilt	512	0.302	-2.13	25.00	24.82	0.315	/
		Left Cheek	512	0.523	-2.34	25.00	24.82	0.545	/
		Left Tilt	512	0.261	-1.56	25.00	24.82	0.272	/

Note:

- Per KDB 447498 D01, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
  - Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
  - For WWAN: Scaled SAR(W/kg)= Measured SAR(W/kg)\*Tune-up Scaling Factor
- Per KDB865664 D01, Repeated measurement is not required when the original highest measured SAR is <0.80 W/kg



**12.2 Body-worn SAR****Test Model: A1**

Band	Mode	Test Position	Ch.	Result 1g (W/Kg)	Power Drift(%)	Max.Turn-up Power(dBm)	Meas.Output Power(dBm)	Scaled SAR (W/Kg)	Meas. No.
GSM 850	GPRS Data-4 Slot	Front Side	128	0.719	-3.03	30.00	29.87	0.741	/
		Back Side	128	0.868	-1.31	30.00	29.87	<b>0.894</b>	2
		Back Side	190	0.801	-2.91	30.00	29.64	0.870	/
		Back Side	251	0.786	1.03	29.50	29.32	0.819	/
		Left Edge	128	0.212	1.87	30.00	29.87	0.218	/
		Right Edge	128	0.203	3.94	30.00	29.87	0.209	/
		Top Edge	128	0.125	0.14	30.00	29.87	0.129	/
		Bottom Edge	128	0.104	1.69	30.00	29.87	0.107	/
GSM1900	GPRS Data-4 Slot	Front Side	512	0.161	-3.12	25.00	24.82	0.168	/
		Back Side	512	0.278	3.84	25.00	24.82	<b>0.290</b>	4
		Left Edge	512	0.098	-3.48	25.00	24.82	0.102	/
		Right Edge	512	0.077	3.55	25.00	24.82	0.080	/
		Bottom Edge	512	0.141	-2.46	25.00	24.82	0.147	/

**Test Model: A2**

Band	Mode	Test Position	Ch.	Result 1g (W/Kg)	Power Drift(%)	Max.Turn-up Power(dBm)	Meas.Output Power(dBm)	Scaled SAR (W/Kg)	Meas. No.
GSM 850	GPRS Data-4 Slot	Front Side	128	0.587	-1.97	30.00	29.87	0.605	/
		Back Side	128	0.907	-2.65	30.00	29.87	<b>0.935</b>	6
		Back Side	190	0.842	1.87	30.00	29.64	0.915	/
		Back Side	251	0.814	-3.52	29.50	29.32	0.848	/
		Left Edge	128	0.508	0.92	30.00	29.87	0.523	/
		Right Edge	128	0.451	3.12	30.00	29.87	0.465	/
		Top Edge	128	0.212	0.85	30.00	29.87	0.218	/
		Bottom Edge	128	0.056	-0.84	30.00	29.87	0.058	/
GSM1900	GPRS Data-4 Slot	Front Side	512	0.203	0.56	25.00	24.82	0.212	/
		Back Side	512	0.453	3.39	25.00	24.82	<b>0.472</b>	8
		Left Edge	512	0.234	-1.93	25.00	24.82	0.244	/
		Right Edge	512	0.300	-1.61	25.00	24.82	0.313	/
		Front Side	128	0.587	-1.97	30.00	29.87	0.605	/

**Note:**

- The test separation of all above table is 10mm.
- Per KDB 447498 D01, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
  - Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
  - For WWAN: Scaled SAR(W/kg)= Measured SAR(W/kg)\*Tune-up Scaling Factor
- When the user enables the personal Wireless router functions for the handsets, actual operations include simultaneous transmission of both the Wi-Fi transmitting frequency and thus cannot be evaluated for SAR under actual use conditions. The "Portable Hotspot" feature on the handset was NOT activated, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal.



### Repeated SAR Test Model: A1

Band	Mode	Test Position	Ch.	Result 1g (W/Kg)	Power Drift(%)	Max.Turn-up Power(dBm)	Meas.Output Power(dBm)	Scaled SAR (W/Kg)	Meas. No.
GSM 850	GPRS Data-4 Slot	Left Cheek	128	1.048	0.45	30	29.87	1.080	/
		Back Side	128	0.834	0.30	30	29.87	0.859	/

### Test Model: A2

Band	Mode	Test Position	Ch.	Result 1g (W/Kg)	Power Drift(%)	Max.Turn-up Power(dBm)	Meas.Output Power(dBm)	Scaled SAR (W/Kg)	Meas. No.
GSM 850	GPRS Data-4 Slot	Back Side	128	0.867	4	30	29.87	0.893	/

## 12.3 repeated SAR measurement

### Test Model: A1

Band	Mode	Test Position	Ch.	Original Measured SAR 1g(mW/g)	1 st Repeated SAR 1g	Ratio	Original Measured SAR 1g(mW/g)	2nd Repeated SAR 1g	Ratio
GSM 850	GPRS Data-4 Slot	Left Cheek	128	1.065	1.048	1.016	-	-	-
		Back Side	128	0.868	0.834	1.041	-	-	-

### Test Model: A2

Band	Mode	Test Position	Ch.	Original Measured SAR 1g(mW/g)	1 st Repeated SAR 1g	Ratio	Original Measured SAR 1g(mW/g)	2nd Repeated SAR 1g	Ratio
GSM 850	GPRS Data-4 Slot	Back Side	128	0.907	0.867	1.046	-	-	-

#### Note:

1. Per KDB 865664 D01,for each frequency band ,repeated SAR measurement is required only when the measured SAR is  $\geq 0.8\text{W/Kg}$ .
2. Per KDB 865664 D01,if the ratio of largest to smallest SAR for the original and first repeated measurement is  $\leq 1.2$  and the measured SAR  $< 1.45\text{W/Kg}$ , only one repeated measurement is required.
3. Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is  $> 1.20$  or when the original or repeated measurement is  $\geq 1.45\text{W/Kg}$
4. The ratio is the difference in percentage between original and repeated measured SAR.

**Simultaneous Multi-band Transmission Evaluation:**

Application Simultaneous Transmission information:

Position	Simultaneous State
Head	1. GSM + Bluetooth
Body	1. GSM + Bluetooth

## NOTE:

1. For simultaneous transmission at head and body exposure position, 2 transmitters simultaneous transmission was the worst state.
2. Based upon KDB 447498 D01, BT SAR is excluded as below table.
3. If the test separation distance is <5mm, 5mm is used for excluded SAR calculation.
4. For minimum test separation distance  $\leq 50\text{mm}$ , Bluetooth standalone SAR is excluded according to  $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f} (\text{GHz}) / x] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR
5. The reported SAR summation is calculated based on the same configuration and test position.
6. KDB 447498 / 4.3.2 (2) when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:
  - a)  $(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot [\sqrt{f} (\text{GHz}) / x] \text{ W/kg}$  for test separation distances  $\leq 50 \text{ mm}$ ;  
Where  $x = 7.5$  for 1-g SAR, and  $x = 18.75$  for 10-g SAR.
  - b)  $0.4\text{W/Kg}$  for 1-g SAR and  $1.0\text{W/Kg}$  for 10-g SAR, when the separation distance is  $>50\text{mm}$ .

Estimated SAR		Maximum Power		Antenna to user(mm)	Frequency(GHz)	Stand Alone SAR(1g) [W/kg]
		dBm	mW			
BT	Head	2	1.585	$\leq 5$	2.48	0.067
	Body			$\leq 5$	2.48	0.067



Test Model: A1

Simultaneous Mode	Position	Mode	Max. 1-g SAR (W/kg)	1-g Sum SAR (W/kg)
GSM + Bluetooth	Head	GSM	1.097	1.164
		Bluetooth	0.067	
	Body	GSM	0.894	0.961
		Bluetooth	0.067	

Test Model: A2

Simultaneous Mode	Position	Mode	Max. 1-g SAR (W/kg)	1-g Sum SAR (W/kg)
GSM + Bluetooth	Head	GSM	0.776	0.843
		Bluetooth	0.067	
	Body	GSM	0.935	1.002
		Bluetooth	0.067	

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna.

When the sum of SAR 1g of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR-1g 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR 1g is greater than the SAR limit (SAR-1g 1.6 W/kg), SAR test exclusion is determined by the SPLSR.



### 13. Equipment List

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
835MHz Dipole	MVG	SID835	SN 30/14 DIP0G835-332	2020.07.14	2023.07.13
1900MHz Dipole	MVG	SID1900	SN 30/14 DIP1G900-333	2020.07.14	2023.07.13
E-Field Probe	MVG	SSE2	SN 07/21 EPGO352	2021.03.01	2022.02.28
Dielectric Probe Kit	MVG	SCLMP	SN 32/14 OCPG67	2020.11.24	2021.11.23
Antenna	MVG	ANTA3	SN 07/13 ZNTA52	N/A	N/A
Phantom1	MVG	SAM	SN 32/14 SAM115	N/A	N/A
Phantom2	MVG	SAM	SN 32/14 SAM116	N/A	N/A
Phone holder	MVG	N/A	SN 32/14 MSH97	N/A	N/A
Laptop holder	MVG	N/A	SN 32/14 LSH29	N/A	N/A
Attenuator	Agilent	99899	DC-18GHz	N/A	N/A
Directional coupler	Narda	4226-20	3305	N/A	N/A
Network Analyzer	Agilent	8753ES	US38432810	2020.10.12	2021.10.11
Multi Meter	Keithley	Multi Meter 2000	4050073	2020.10.10	2021.10.09
Signal Generator	Agilent	N5182A	MY50140530	2020.10.10	2021.10.09
Wireless Communication Test Set	Agilent	8960-E5515C	MY48360751	2020.10.10	2021.10.09
Wireless Communication Test Set	R&S	CMW500	117239	2020.10.10	2021.10.09
Power Amplifier	DESAY	ZHL-42W	9638	2020.10.12	2021.10.11
Power Meter	R&S	NRP	100510	2020.10.10	2021.10.09
Power Meter	Agilent	E4419B	QB43312265	2020.10.10	2021.10.09
Power Sensor	R&S	NRP-Z11	101919	2020.10.10	2021.10.09
Power Sensor	HP	E9300A	US39210170	2020.10.10	2021.10.09
Temperature hygrometer	SuWei	SW-108	N/A	2020.10.12	2021.10.11
Thermograph	Elitech	RC-4	S/N EF7176501537	2020.10.12	2021.10.11

Note:

Per KDB 865664 D01, Dipole SAR Validation Verification, STS LAB has adopted 3 years calibration intervals. On annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:

1. There is no physical damage on the dipole
2. System validation with specific dipole is within 10% of calibrated value Return-loss in within 20% of calibrated measurement



## Appendix A. System Validation Plots

### System Performance Check Data (835MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2021-05-17

### Experimental conditions




Phantom	Validation plane
Device Position	-
Band	835MHz
Channels	-
Signal	CW
Frequency (MHz)	835MHz
Relative permittivity	41.14
Conductivity (S/m)	0.90
Probe	SN 07/21 EPGO352
ConvF:	1.57
Crest factor:	1:1



Maximum location: X=-7.00, Y=-1.00

SAR 10g (W/Kg)	0.627311
SAR 1g (W/Kg)	0.963852

## Z Axis Scan





**System Performance Check Data (1900MHz)**

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2021-05-18




**Experimental conditions.**

Phantom	Validation plane
Device Position	-
Band	1900MHz
Channels	-
Signal	CW
Frequency (MHz)	1900MHz
Relative permittivity	39.91
Conductivity (S/m)	1.40
Probe	SN 07/21 EPGO352
ConvF:	1.78
Crest factor:	1:1

**Maximum location: X=3.00, Y=-2.00**

SAR 10g (W/Kg)	2.033710
SAR 1g (W/Kg)	4.048127

## Z Axis Scan



## Appendix B. SAR Test Plots


Plot 1: DUT: Mobile phone; EUT Model: A1

Test Date	2021-05-17
Probe	SN 07/21 EPG0352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Left head
Device Position	Cheek
Band	GPRS 850
Channels	Low
Signal	Duty Cycle: 2.00 (Crest factor: 2.0)
Frequency (MHz)	824.2
Relative permittivity (real part)	41.50
Conductivity (S/m)	0.90

Maximum location: X=-40.00, Y=-24.00

SAR Peak: 1.74 W/kg

SAR 10g (W/Kg)	0.648117
SAR 1g (W/Kg)	1.065012




## Plot 2: DUT: Mobile phone; EUT Model: A1

Test Date	2021-05-17
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	GPRS 850
Channels	Low
Signal	Duty Cycle: 2.00 (Crest factor: 2.0)
Frequency (MHz)	824.2
Relative permittivity (real part)	42.40
Conductivity (S/m)	0.89

Maximum location: X=-8.00, Y=23.00

SAR Peak: 1.42 W/kg

SAR 10g (W/Kg)	0.591512
SAR 1g (W/Kg)	0.868154




**Plot 3: DUT: Mobile phone; EUT Model: A1**

Test Date	2021-05-18
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Left head
Device Position	Cheek
Band	GPRS 1900
Channels	Low
Signal	Duty Cycle: 2.00 (Crest factor: 2.0)
Frequency (MHz)	1850.2
Relative permittivity (real part)	40.05
Conductivity (S/m)	1.37

Maximum location: X=-57.00, Y=-32.00

SAR Peak: 0.50 W/kg

SAR 10g (W/Kg)	0.187793
SAR 1g (W/Kg)	0.315610






**Plot 4: DUT: Mobile phone; EUT Model: A1**

Test Date	2021-05-18
Probe	SN 07/21 EPG0352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back side
Band	GPRS 1900
Channels	Low
Signal	Duty Cycle: 2.00 (Crest factor: 2.0)
Frequency (MHz)	1850.2
Relative permittivity (real part)	40.05
Conductivity (S/m)	1.37

Maximum location: X=0.00, Y=1.00

SAR Peak: 0.46 W/kg

SAR 10g (W/Kg)	0.171761
SAR 1g (W/Kg)	0.278141




### Plot 5: DUT: Mobile phone; EUT Model: A2

Test Date	2021-05-17
Probe	SN 07/21 EPG0352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	GPRS 850
Channels	Low
Signal	Duty Cycle: 2.00 (Crest factor: 2.0)
Frequency (MHz)	824.2
Relative permittivity (real part)	41.50
Conductivity (S/m)	0.90

Maximum location: X=-46.00, Y=-24.00

SAR Peak: 1.03 W/kg

SAR 10g (W/Kg)	0.502871
SAR 1g (W/Kg)	0.752578






# Plot 6: DUT: Mobile phone; EUT Model: A2

Test Date	2021-05-17
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	GPRS 850
Channels	Low
Signal	Duty Cycle: 2.00 (Crest factor: 2.0)
Frequency (MHz)	824.2
Relative permittivity (real part)	42.40
Conductivity (S/m)	0.89

Maximum location: X=0.00, Y=9.00

SAR Peak: 1.23 W/kg

SAR 10g (W/Kg)	0.634979
SAR 1g (W/Kg)	0.907454




**Plot 7: DUT: Mobile phone; EUT Model: A2**

Test Date	2021-05-18
Probe	SN 07/21 EPGO352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	GPRS 1900
Channels	Low
Signal	Duty Cycle: 2.00 (Crest factor: 2.0)
Frequency (MHz)	1850.2
Relative permittivity (real part)	40.05
Conductivity (S/m)	1.37

Maximum location: X=-65.00, Y=-47.00

SAR Peak: 0.94 W/kg

SAR 10g (W/Kg)	0.365138
SAR 1g (W/Kg)	0.606494






### Plot 8: DUT: Mobile phone; EUT Model: A2

Test Date	2021-05-18
Probe	SN 07/21 EPG0352
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back side
Band	GPRS 1900
Channels	Low
Signal	Duty Cycle: 2.00 (Crest factor: 2.0)
Frequency (MHz)	1850.2
Relative permittivity (real part)	40.05
Conductivity (S/m)	1.37

Maximum location: X=-8.00, Y=0.00

SAR Peak: 0.70 W/kg

SAR 10g (W/Kg)	0.259526
SAR 1g (W/Kg)	0.453118





## Appendix C. Probe Calibration and Dipole Calibration Report

Refer the appendix Calibration Report.

※※※※END OF THE REPORT※※※※

