

**FCC ID:2ASBQ-G65ODD22**

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

### B.3 MPE-based Exemption

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

TABLE B.1—THRESHOLDS FOR SINGLE RF SOURCES  
SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION

| RF Source Frequency |   |           | Minimum Distance   |   |                    | Threshold ERP                |
|---------------------|---|-----------|--------------------|---|--------------------|------------------------------|
| $f_L$ MHz           |   | $f_H$ MHz | $\lambda_L / 2\pi$ |   | $\lambda_H / 2\pi$ | W                            |
| 0.3                 | – | 1.34      | 159 m              | – | 35.6 m             | 1,920 R <sup>2</sup>         |
| 1.34                | – | 30        | 35.6 m             | – | 1.6 m              | 3,450 R <sup>2</sup> / $f^2$ |
| 30                  | – | 300       | 1.6 m              | – | 159 mm             | 3.83 R <sup>2</sup>          |
| 300                 | – | 1,500     | 159 mm             | – | 31.8 mm            | 0.0128 R <sup>2</sup> / $f$  |
| 1,500               | – | 100,000   | 31.8 mm            | – | 0.5 mm             | 19.2R <sup>2</sup>           |

Subscripts L and H are low and high;  $\lambda$  is wavelength.  
 From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.

### 1.1 Friis transmission formula: $P_d = 3450 R^2 / f^2$

RF Exposure Information: The radiated output power of this device meets the limits of FCC/IC radio frequency exposure limits. This device should be operated with a minimum separation distance of 20cm (8 inches) between the equipment and a person's body. the 13.56 MHz does not effect the overall RF Exposure and there was no need to evaluate for these bands.

### 1.2 Measurement Result

RFID 13.56MHz, Antenna Gain: 0dBi

| Mode     | Emission Level(dBu V/m) | ERP (dBm) | Limits (dBm ) |
|----------|-------------------------|-----------|---------------|
| 13.56MHz | 66.43                   | -28.8     | 28.76         |

Note: Refer to report No. ENS2211230013W00101R and ENS2211230013W00102R.

Limits:  $3450 * 0.2^2 / 13.56^2 = 0.751 \text{ W} = 28.76 \text{ dBm}$