

TEST REPORT

Applicant: Fujian LANDI Commercial Equipment Co.,Ltd.

FCC: Building 17, Section A, Software Park, No. 89 Software Road, Gulou District, Fuzhou Municipality, Fujian Province, China

Address: IC: Building 17, Section A, Software Park, No. 89 Software Road, Gulou District, Fuzhou Municipality, Fujian Province, P.R. 350003 China

Product Name: Mobile Terminal

FCC ID: 2AG6N-M20

IC: 23725-M20

HVIN: M20S1, M20S0, M20SES1, M20SES0

Standard(s): 47 CFR Part 15, Subpart E(15.407)
RSS-247 Issue 3, August 2023
RSS-Gen, Issue 5, February 2021 Amendment 2
ANSI C63.10-2013
KDB 789033 D02 General U-NII Test Procedures New Rules v02r01

Report Number: XMDN240206-08120E-RF-00D

Report Date: 2024/5/25

The above device has been tested and found compliant with the requirement of the relative standards by Bay Area Compliance Laboratories Corp. (Dongguan).



Reviewed By: Gavin Xu

Title: RF Engineer



Approved By: Ivan Cao

Title: EMC Manager

Bay Area Compliance Laboratories Corp. (Dongguan)
No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China

Tel: +86-769-86858888

Fax: +86-769-86858891

www.baclcorp.com.cn

Note: The information marked ▲ is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report cannot be reproduced except in full, without prior written approval of the Company. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0. This report may contain data that are not covered by the accreditation scope and shall be marked with ★. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

CONTENTS

DOCUMENT REVISION HISTORY	4
1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
1.2 ACCESSORY INFORMATION	6
1.3 ANTENNA INFORMATION DETAIL▲	6
1.4 EQUIPMENT MODIFICATIONS	6
2. SUMMARY OF TEST RESULTS	7
3. DESCRIPTION OF TEST CONFIGURATION	8
3.1 OPERATION FREQUENCY DETAIL	8
3.2 EUT OPERATION CONDITION	9
3.3 SUPPORT EQUIPMENT LIST AND DETAILS	9
3.4 SUPPORT CABLE LIST AND DETAILS	9
3.5 BLOCK DIAGRAM OF TEST SETUP	10
3.6 TEST FACILITY	11
3.7 MEASUREMENT UNCERTAINTY	11
4. REQUIREMENTS AND TEST PROCEDURES	12
4.1 AC LINE CONDUCTED EMISSIONS	12
4.1.1 Applicable Standard	12
4.1.2 EUT Setup	14
4.1.3 EMI Test Receiver Setup	14
4.1.4 Test Procedure	15
4.1.5 Corrected Amplitude & Margin Calculation	15
4.1.6 Test Result	15
4.2 RADIATION SPURIOUS EMISSIONS	16
4.2.1 Applicable Standard	16
4.2.2 EUT Setup	18
4.2.3 EMI Test Receiver & Spectrum Analyzer Setup	19
4.2.4 Test Procedure	20
4.2.5 Corrected Result & Margin Calculation	20
4.2.6 Test Result	20
4.3 26DB ATTENUATED BELOW THE CHANNEL POWER	21
4.3.1 Applicable Standard	21
4.3.2 EUT Setup	21
4.3.3 Test Procedure	21
4.3.4 Test Result	21
4.4 EMISSION BANDWIDTH	22
4.4.1 Applicable Standard	22
4.4.2 EUT Setup	23
4.4.3 Test Procedure	23
4.4.4 Test Result	24
4.5 MAXIMUM CONDUCTED OUTPUT POWER	25

4.5.1 Applicable Standard	25
4.5.2 EUT Setup	26
4.5.3 Test Procedure	26
4.5.4 Test Result	26
4.6 MAXIMUM POWER SPECTRAL DENSITY	27
4.6.1 Applicable Standard	27
4.6.2 EUT Setup	28
4.6.3 Test Procedure	28
4.6.4 Test Result	28
4.7 DUTY CYCLE	29
4.7.1 EUT Setup	29
4.7.2 Test Procedure	29
4.7.3 Judgment	29
4.8 ANTENNA REQUIREMENT	30
4.8.1 Applicable Standard	30
4.8.2 Judgment	30
4.9 ADDITIONAL REQUIREMENT	31
4.9.1 Applicable Standard	31
4.9.2 Judgment	32
5. Test DATA AND RESULTS	33
5.1 AC LINE CONDUCTED EMISSIONS	33
5.2 RADIATION SPURIOUS EMISSIONS	36
5.3 26dB ATTENUATED BELOW THE CHANNEL POWER	83
5.4 EMISSION BANDWIDTH	86
5.5 99% OCCUPIED BANDWIDTH	95
5.6 MAXIMUM CONDUCTED OUTPUT POWER	105
5.7 MAXIMUM POWER SPECTRAL DENSITY	107
5.8 DUTY CYCLE	116
APPENDIX A - EUT PHOTOGRAPHS	118
APPENDIX B - TEST SETUP PHOTOGRAPHS	119

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	XMDN240206-08120E-RF-00D	Original Report	2024/5/25

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	Mobile Terminal
EUT Model:	M20
Multiple Models:	M20SE
Operation Frequency:	5150-5250 MHz: 5180-5240 MHz (802.11a/n ht20/ac vht20) 5190-5230 MHz(802.11n ht40/ac vht40) 5210 MHz(802.11ac vht80) 5250-5350MHz: 5260-5320 MHz (802.11a/n ht20/ac vht20) 5270-5310 MHz(802.11n ht40/ac vht40) 5290 MHz(802.11ac vht80) 5470-5725MHz: 5500-5720 MHz (802.11a/n ht20/ac vht20) 5510-5710 MHz(802.11n ht40/ac vht40) 5530-5690MHz(802.11ac vht80) 5725-5850MHz 5745-5825 MHz (802.11a/n ht20/ac vht20) 5755-5795 MHz(802.11n ht40/ac vht40) 5775 MHz(802.11ac vht80)
Maximum Average Output Power (Conducted):	15.42 dBm(5150-5250 MHz) 15.46 dBm(5250-5350 MHz) 15.73 dBm(5470-5725 MHz) 16.28 dBm(5725-5850 MHz)
Maximum Average Output Power (EIRP):	18.57 dBm(5150-5250 MHz) 18.9 dBm(5250-5350 MHz) 18.8 dBm(5470-5725 MHz)
Modulation Type:	802.11a/n/ac:OFDM-BPSK, QPSK, 16QAM, 64QAM,256QAM
Rated Input Voltage:	DC 7.7V from battery or DC 5V from Adapter or Charging Base
Serial Number:	Radiated spurious emission and AC line conducted emission tests: 2HPA-3(HVIN: M20S1) 2HPA-5(HVIN: M20SES1) RF Conducted test: 2HPA-1(HVIN: M20S1)
EUT Received Date:	2024/2/7
EUT Received Status:	Good
Note 1: 5600-5650 MHz was disabled by software in Canada Market.	
Note 2: The Multiple models are electrically identical with the test model .Each model of device have two configurations, the difference see the below table and the declaration letter for more detail, which was provided by manufacturer.	

Configurations:

Configuration	HVIN	Model	Configuration Description
1	M20S1	M20	With Printer, with Scanning camera, wired loop NFC Antenna, M20 Housing and antennas
2	M20S0	M20	With Printer, without Scanning camera, wired loop NFC Antenna, M20 Housing and antennas
3	M20SES1	M20SE	Without Printer, with Scanning camera, FPC loop NFC Antenna, M20SE Housing and antennas
4	M20SES0	M20SE	Without Printer, without Scanning camera, FPC loop NFC Antenna, M20SE Housing and antennas

1.2 Accessory Information

Accessory Description	Manufacturer	Model	Parameters
Adapter 1	Something High Electric (Xiamen) Company Inc.	P12GUSB050200	Input: 100-240Vac~50/60Hz 0.3A Output: 5.0Vdc,2.0A
Adapter 2	SHENZHEN KEYU POWER SUPPLY TECHNOLOGY CO., LTD	KA1602-0502000DEU	Input: 100-240Vac~50/60Hz 0.35A Output: 5.0Vdc 2.0A,10W
Battery 1	HuiZhou Ganfeng LiEnergy Battery Technology Co.,LTD.	526265-2S (2ICP6/62/65)	DC 7.7V 3550mAh/27.34Wh
Battery 2	SCUD(Fujian)Electronics Co.,LTD	526266-2S (2ICP6/62/66)	DC 7.7V 3620mAh/27.87Wh

1.3 Antenna Information Detail ▲

Model	Manufacturer	Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain
M20	Fuzhou zhongtianxun communication technology Co., Ltd	FPC	50	5150~5250MHz	2.53 dBi
				5250~5350MHz	2.53 dBi
				5470~5725MHz	1.50 dBi
				5725~5850MHz	1.21 dBi
M20SE	Fuzhou zhongtianxun communication technology Co., Ltd	FPC	50	5150~5250MHz	3.15 dBi
				5250~5350MHz	3.44 dBi
				5470~5725MHz	3.07 dBi
				5725~5850MHz	2.39 dBi
The design of compliance with §15.203:					
☒ Unit uses a permanently attached antenna.					
☐ Unit uses a unique coupling to the intentional radiator.					
☐ Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.					

1.4 Equipment Modifications

No modifications are made to the EUT during all test items.

2. SUMMARY OF TEST RESULTS

Standard(s) Section	Test Items	Result
§15.207(a) RSS-Gen Clause 8.8	AC line conducted emissions	Compliant
FCC§15.205& §15.209 &§15.407(b) RSS-247 Clause 6.2	Undesirable Emission& Restricted Bands	Compliant
RSS-247 Clause 6.2.1.2	26dB attenuated below the channel power	Compliant
FCC§15.407(a) (e) RSS-247 Clause 6.2 RSS-Gen Clause 6.7	Emission Bandwidth	Compliant
FCC§15.407(a) RSS-247 Clause 6.2	Maximum Conducted Output Power	Compliant
FCC§15.407 (a) RSS-247 Clause 6.2	Power Spectral Density	Compliant
§15.203 RSS-GEN Clause 6.8	Antenna Requirement	Compliant
RSS-247 Clause 6.4	Additional requirements	Compliant
Note 1: For AC line conducted emissions, the maximum output power mode and channel was tested. Note 2: For Radiated Spurious Emissions 9kHz~ 1GHz, the maximum output power mode and channel was tested. Note 3: For Radiated spurious emission, according to the test result for NFC report, Configuration 1+Adapter 1+ Battery 1 was the worst for model M20, Configuration 3+Adapter 1+ Battery 1 was the worst for model M20SE, therefore, test was performed with them for this report. Note 4: AC line conducted emissions, according to the test result for NFC report, Configuration 1+Adapter 1+ Battery 1 was the worst, therefore, test was performed with this mode for this report.		

3. DESCRIPTION OF TEST CONFIGURATION

3.1 Operation Frequency Detail

For 802.11a/n ht20/ac vht20:

5150-5250MHz Band		5250-5350 MHz Band		5470-5725 MHz Band		5725-5850MHz Band	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	52	5260	100	5500	149	5745
40	5200	56	5280	104	5520	153	5765
44	5220	60	5300	108	5540	157	5785
48	5240	64	5320	112	5560	161	5805
/	/	/	/	116	5580	165	5825
/	/	/	/	120**	5600	/	/
/	/	/	/	124**	5620	/	/
/	/	/	/	128**	5640	/	/
/	/	/	/	132	5660	/	/
/	/	/	/	136	5680	/	/
/	/	/	/	140	5700	/	/
/	/	/	/	143*	5720	/	/

For 802.11n ht40/ac vh40:

5150-5250MHz Band		5250-5350 MHz Band		5470-5725 MHz Band		5725-5850MHz Band	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	54	5270	102	5510	151	5755
46	5230	62	5310	110	5550	159	5795
/	/	/	/	118**	5590	/	/
/	/	/	/	126**	5630	/	/
/	/	/	/	134	5670	/	/
/	/	/	/	142*	5710	/	/

For 802.11ac vht80:

5150-5250MHz Band		5250-5350 MHz Band		5470-5725 MHz Band		5725-5850MHz Band	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
42	5210	58	5290	106	5530	155	5775
/	/	/	/	122**	5610	/	/
/	/	/	/	138*	5690	/	/

Note

*: Additional channels cross the band 5470-5725MHz and 5725-5850 MHz, Conducted output power/ Power Spectral Density/bandwidth test with the additional channel to compliance with stricter limit of the two bands(5470-5725MHz more stricter).

** : Those channels in 5600-5650 MHz are disabled by software in Canada Market.

3.2 EUT Operation Condition

The system was configured for testing in Engineering Mode, which was provided by the manufacturer. The EUT configuration is below:

EUT Exercise Software:		QRCT4			
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer▲:					
5150-5250 MHz Band:					
Test Modes	Data Rate	Power Level Setting			
		Low Channel	Middle Channel	High Channel	
802.11a	6Mbps	13	13	13.	
802.11n ht20	MCS0	17	17	17	
802.11n ht40	MCS0	13	/	13	
802.11ac vht80	MCS0	/	15	/	
5250-5350 MHz Band:					
Test Modes	Data Rate	Power Level Setting			
		Low Channel	Middle Channel	High Channel	
802.11a	6Mbps	13	13	13.	
802.11n ht20	MCS0	17	17	17	
802.11n ht40	MCS0	13	/	13	
802.11ac vht80	MCS0	/	15	/	
5470-5725 MHz Band:					
Test Modes	Data Rate	Power Level Setting			
		Low Channel	Middle Channel	High Channel	Cross Channel
802.11a	6Mbps	13	12	11	11
802.11n ht20	MCS0	18	17	14	14
802.11n ht40	MCS0	13	13	11	11
802.11ac vht80	MCS0	15	/	13	13
5725-5850 MHz Band:					
Test Modes	Data Rate	Power Level Setting			
		Low Channel	Middle Channel	High Channel	
802.11a	6Mbps	10	9	9	
802.11n ht20	MCS0	13	13	13	
802.11n ht40	MCS0	10	/	9	
802.11ac vht80	MCS0	/	11	/	
Note:					
1.The above are the worst-case data rates, which are determined for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations.					
2. The system support 802.11a/n ht20/n ht40/ac vht20/ac vht40/ ac vht80, the vht20/vht40 were reduced since the identical parameters with 802.11n ht20 /n ht40.					

3.3 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

3.4 Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	No	No	1.0	Adapter	EUT

3.5 Block Diagram of Test Setup

AC power line conducted emissions:



Radiated Spurious Emissions:



3.6 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 829273, the FCC Designation No. : CN5044.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

3.7 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	9kHz~30MHz: 3.3dB, 30MHz~200MHz: 4.55 dB, 200MHz~1GHz: 5.92 dB, 1GHz~6GHz: 4.98 dB, 6GHz~18GHz: 5.89 dB, 18GHz~26.5GHz:5.47 dB, 26.5GHz~40GHz:5.63 dB
Unwanted Emissions, conducted	±2.47 dB
Temperature	±1°C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.11 dB (150 kHz to 30 MHz)

4. REQUIREMENTS AND TEST PROCEDURES

4.1 AC Line Conducted Emissions

4.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:

(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

RSS-Gen Clause 8.8

Unless stated otherwise in the applicable RSS, for radio apparatus that are designed to be connected to the public utility AC power network, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the range 150 kHz to 30 MHz shall not exceed the limits in table 4, as measured using a 50 μ H / 50 Ω line impedance stabilization network. This requirement applies for the radio frequency voltage measured between each power line and the ground terminal of each AC power-line mains cable of the EUT. For an EUT that connects to the AC power lines indirectly, through another device, the requirement for compliance with the limits in table 4 shall apply at the terminals of the AC power-line mains cable of a representative support device, while it provides power to the EUT. The lower limit applies at the boundary between the frequency ranges. The device used to power the EUT shall be representative of typical applications.

Table 4 – AC power-line conducted emissions limits

Frequency (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 ¹	56 to 46 ¹
0.5 – 5	56	46
5 – 30	60	50


Note 1: The level decreases linearly with the logarithm of the frequency.

For an EUT with a permanent or detachable antenna operating between 150 kHz and 30 MHz, the AC power-line conducted emissions must be measured using the following configurations:

(a) Perform the AC power-line conducted emissions test with the antenna connected to determine compliance with the limits of table 4 outside the transmitter's fundamental emission band.

(b) Retest with a dummy load instead of the antenna to determine compliance with the limits of table 4 within the transmitter's fundamental emission band. For a detachable antenna, remove the antenna and connect a suitable dummy load to the antenna connector. For a permanent antenna, remove the antenna and terminate the RF output with a dummy load or network that simulates the antenna in the fundamental frequency band.

4.1.2 EUT Setup



The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207, RSS-Gen limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

4.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

4.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

4.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

4.1.6 Test Result

Please refer to section 5.1.

4.2 Radiation Spurious Emissions

4.2.1 Applicable Standard

FCC §15.407 (b);

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of - 27 dBm/MHz.

(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of - 27 dBm/MHz.

(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of - 27 dBm/MHz.

(4) For transmitters operating solely in the 5.725-5.850 GHz band:

(i) All emissions shall be limited to a level of - 27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

(ii) Devices certified before March 2, 2017 with antenna gain greater than 10 dBi may demonstrate compliance with the emission limits in § 15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease by March 2, 2018. Devices certified before March 2, 2018 with antenna gain of 10 dBi or less may demonstrate compliance with the emission limits in § 15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease before March 2, 2020.

(8) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.

(9) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in § 15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in § 15.207.

(10) The provisions of § 15.205 apply to intentional radiators operating under this section.

(11) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the upper and lower frequency band edges as the design of the equipment permits.

(c) The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signalling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization a description of how this requirement is met.

Frequency band 5150-5250 MHz:

RSS-247 Clause 6.2.1.2

For transmitters with operating frequencies in the band 5150-5250 MHz, all emissions outside the band 5150-5350 MHz shall not exceed -27 dBm/MHz e.i.r.p. Any unwanted emissions that fall into the band 5250-5350 MHz shall be attenuated below the channel power by at least 26 dB, when measured using a resolution bandwidth between 1 and 5% of the occupied bandwidth (i.e. 99% bandwidth), above 5250 MHz. The 26 dB bandwidth may fall into the 5250-5350 MHz band; however, if the occupied bandwidth also falls within the 5250-5350 MHz band, the transmission is considered as intentional and the devices shall comply with all requirements in the band 5250-5350 MHz including implementing dynamic frequency selection (DFS) and TPC, on the portion of the emission that resides in the 5250-5350 MHz band.

Frequency band 5250-5350 MHz:

RSS-247 Clause 6.2.2.2

For transmitters with operating frequencies in the band 5150-5250 MHz, all emissions outside the band 5150-5350 MHz shall not exceed -27 dBm/MHz e.i.r.p. Any unwanted emissions that fall into the band 5250-5350 MHz shall be attenuated below the channel power by at least 26 dB, when measured using a resolution bandwidth between 1 and 5% of the occupied bandwidth (i.e. 99% bandwidth), above 5250 MHz. The 26 dB bandwidth may fall into the 5250-5350 MHz band; however, if the occupied bandwidth also falls within the 5250-5350 MHz band, the transmission is considered as intentional and the devices shall comply with all requirements in the band 5250-5350 MHz including implementing dynamic frequency selection (DFS) and TPC, on the portion of the emission that resides in the 5250-5350 MHz band.

Frequency bands 5470-5600 MHz and 5650-5725 MHz:

RSS-247 Clause 6.2.3.2

Emissions outside the band 5470-5600 MHz and 5650-5725 MHz shall not exceed -27 dBm/MHz e.i.r.p. However, devices with bandwidth overlapping the band edge of 5725 MHz can meet the emission limit of -27 dBm/MHz e.i.r.p. at 5850 MHz instead of 5725 MHz.

Frequency band 5725-5850 MHz

RSS-247 Clause 6.2.4.3


Devices operating in the band 5725-5850 MHz with antenna gain greater than 10 dBi can have unwanted emissions that comply with either the limits in this section or in section 5.5 until six (6) months after the publication date of this standard for certification. Certified devices that do not comply with emission limits in this section shall not be manufactured, imported, distributed, leased, offered for sale or sold after April 1, 2018.

Devices operating in the band 5725-5850 MHz with antenna gain of 10 dBi or less can have unwanted emissions that comply with either the limits in this section or in section 5.5 until April 1, 2018 for certification. Certified devices that do not comply with emission limits in this section shall not be manufactured, imported, distributed, leased, offered for sale or sold after April 1, 2020. Devices operating in the band 5725-5850 MHz shall have e.i.r.p. of unwanted emissions comply with the following:


- a) 27 dBm/MHz at frequencies from the band edges decreasing linearly to 15.6 dBm/MHz at 5 MHz above or below the band edges;
- b) 15.6 dBm/MHz at 5 MHz above or below the band edges decreasing linearly to 10 dBm/MHz at 25 MHz above or below the band edges;
- c) 10 dBm/MHz at 25 MHz above or below the band edges decreasing linearly to -27 dBm/MHz at 75 MHz above or below the band edges; and
- d) -27 dBm/MHz at frequencies more than 75 MHz above or below the band edges.


4.2.2 EUT Setup

9kHz~30MHz:



30MHz~1GHz:



Above 1GHz:

The radiated emission tests were performed in the semi-anechoic chamber, using the setup accordance with the ANSI C63.10-2013. The specification used was FCC 15.209, FCC 15.407, RSS-247, RSS-Gen limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

For 9kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

4.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9kHz-1000MHz:

Frequency Range	Measurement	RBW	Video B/W	IF B/W
9 kHz – 150 kHz	QP/AV	200 Hz	1 kHz	200 Hz
150 kHz – 30 MHz	QP/AV	9 kHz	30 kHz	9 kHz
30 MHz – 1000 MHz	PK	100 kHz	300 kHz	/
	QP	/	/	120 kHz

1GHz- 40GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
Ave.	>98%	1MHz	10 Hz
	<98%	1MHz	$\geq 1/T$

Note: T is minimum transmission duration

If the maximized peak measured value is under the QP limit by more than 6dB, then it is unnecessary to perform an QP measurement.

If the maximized peak measured value is under the average limit, then it is unnecessary to perform an QP measurement.

4.2.4 Test Procedure

Data was recorded in Quasi-peak detection mode for frequency range of 9 kHz -1 GHz, except 9-90 kHz, 110-490 kHz, employing an average detector, peak and Average detection modes for frequencies above 1 GHz.

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, emission shall be computed as: $E [dB\mu V/m] = EIRP[dBm] + 95.2$, for $d = 3$ meters.

For Radiated Bandedge test, which was performed at 1.5 m distance, according to C63.10, the test result shall be extrapolated to the specified distance using an extrapolation Factor of 20dB/decade from 3m to 1.5m

Distance extrapolation Factor = $20 \log (\text{specific distance } [3m] / \text{test distance } [1.5m])$ dB = 6.0dB

4.2.5 Corrected Result & Margin Calculation

The basic equation except radiated bandedge test is as follows:

Factor = Antenna Factor + Cable Loss- Amplifier Gain

Result = Reading + Factor

For Radiated Bandedge test:

Factor = Antenna Factor + Cable Loss-Distance extrapolation Factor

Result = Reading + Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

4.2.6 Test Result

Please refer to section 5.2.


4.3 26dB Attenuated Below The Channel Power

4.3.1 Applicable Standard

RSS-247 Clause 6.2.1.2

For transmitters with operating frequencies in the band 5150-5250 MHz, all emissions outside the band 5150-5350 MHz shall not exceed -27 dBm/MHz e.i.r.p. Any unwanted emissions that fall into the band 5250-5350 MHz shall be attenuated below the channel power by at least 26 dB, when measured using a resolution bandwidth between 1 and 5% of the occupied bandwidth (i.e. 99% bandwidth), above 5250 MHz. The 26 dB bandwidth may fall into the 5250-5350 MHz band; however, if the occupied bandwidth also falls within the 5250-5350 MHz band, the transmission is considered as intentional and the devices shall comply with all requirements in the band 5250-5350 MHz including implementing dynamic frequency selection (DFS) and TPC, on the portion of the emission that resides in the 5250-5350 MHz band.

4.3.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer.

4.3.3 Test Procedure

- Set RBW = 1%~5% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = RMS.
- Trace mode = max hold
- Measure the emission attenuated below the channel power

4.3.4 Test Result

Please refer to section 5.3.

4.4 Emission Bandwidth

4.4.1 Applicable Standard

FCC §15.407 (a),(h)

(h)(2) Radar Detection Function of Dynamic Frequency Selection (DFS). U-NII devices operating with any part of its 26 dB emission bandwidth in the 5.25-5.35 GHz and 5.47-5.725 GHz bands shall employ a DFS radar detection mechanism to detect the presence of radar systems and to avoid co-channel operation with radar systems.

FCC §15.407 (e)

Within the 5.725-5.850 GHz and 5.850-5.895 GHz bands, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

RSS-247 Clause 6.2.1.2

For transmitters with operating frequencies in the band 5150-5250 MHz, all emissions outside the band 5150-5350 MHz shall not exceed -27 dBm/MHz e.i.r.p. Any unwanted emissions that fall into the band 5250-5350 MHz shall be attenuated below the channel power by at least 26 dB, when measured using a resolution bandwidth between 1 and 5% of the occupied bandwidth (i.e. 99% bandwidth), above 5250 MHz. The 26 dB bandwidth may fall into the 5250-5350 MHz band; however, if the occupied bandwidth also falls within the 5250-5350 MHz band, the transmission is considered as intentional and the devices shall comply with all requirements in the band 5250-5350 MHz including implementing dynamic frequency selection (DFS) and TPC, on the portion of the emission that resides in the 5250-5350 MHz band.

RSS-247 Clause 6.2.2.1

Devices, other than devices installed in vehicles, shall comply with the following:

- a) The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10}B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band;
- b) The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10}B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W

RSS-247 Clause 6.2.3.1


The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10}B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band.

The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10}B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

RSS-247 Clause 6.2.4.1

For equipment operating in the band 5725-5850 MHz, the minimum 6 dB bandwidth shall be at least 500 kHz.

4.4.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer.

4.4.3 Test Procedure

26dB Emission Bandwidth:

According to ANSI C63.10-2013 Section 12.4.1

- Set RBW = approximately 1% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = peak.
- Trace mode = max hold
- Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

6 dB emission bandwidth:

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) ≥ 3 RBW.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described in this section. For devices that use channel aggregation refer to III.A and III.C for determining emission bandwidth.

99% Occupied Bandwidth:

According to ANSI C63.10-2013 Section 12.4.2&6.9.3

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

4.4.4 Test Result

Please refer to section 5.4 and section 5.5.

4.5 Maximum Conducted Output Power

4.5.1 Applicable Standard

FCC §15.407(a) (1)(iv)

For client devices in the 5.15 – 5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

FCC §15.407(a) (2)

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

FCC §15.407(a) (3)(i)

For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

RSS-247 Clause 6.2.1.1

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or $1.76 + 10 \log_{10} B$, dBm, whichever is less stringent. Devices shall implement transmitter power control (TPC) in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

For other devices, the maximum e.i.r.p. shall not exceed 200 mW or $10 + 10 \log_{10} B$, dBm, whichever power is less. B is the 99% emission bandwidth in megahertz. The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.

RSS-247 Clause 6.2.2.1

Devices, other than devices installed in vehicles, shall comply with the following:

- a) The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band;
- b) The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

RSS-247 Clause 6.2.3.1


The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band.

The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

RSS-247 Clause 6.2.4.2

The maximum conducted output power shall not exceed 1 W. The output power spectral density shall not exceed 30 dBm in any 500 kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the output power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications and multiple collocated transmitters transmitting the same information.

4.5.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer. The cable loss of this RF cable was offset into the setting of test equipment, which was provided by manufacturer ▲.

4.5.3 Test Procedure

According to ANSI C63.10-2013 Section 12.3.3.1

Method PM-G is measurement using a gated RF average power meter.

Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

4.5.4 Test Result

Please refer to section 5.6.

4.6 Maximum Power Spectral Density

4.6.1 Applicable Standard

FCC §15.407(a) (1)(iv)

For client devices in the 5.15 – 5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

FCC §15.407(a) (2)

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

FCC §15.407(a) (3)(i)

For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

RSS-247 Clause 6.2.1.1

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or $1.76 + 10 \log_{10} B$, dBm, whichever is less stringent. Devices shall implement transmitter power control (TPC) in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.

For other devices, the maximum e.i.r.p. shall not exceed 200 mW or $10 + 10 \log_{10} B$, dBm, whichever power is less. B is the 99% emission bandwidth in megahertz. The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.

RSS-247 Clause 6.2.2.1

Devices, other than devices installed in vehicles, shall comply with the following:

- a) The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band;
- b) The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

RSS-247 Clause 6.2.3.1


The maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band.

The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

RSS-247 Clause 6.2.4.2

The maximum conducted output power shall not exceed 1 W. The output power spectral density shall not exceed 30 dBm in any 500 kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the output power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications and multiple collocated transmitters transmitting the same information.

4.6.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer. The cable loss of this RF cable was offset into the setting of test equipment, which was provided by manufacturer▲.

4.6.3 Test Procedure

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01

Duty cycle $\geq 98\%$

KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-1 should be applied.

Duty cycle $< 98\%$, duty cycle variations are less than $\pm 2\%$

KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-2 should be applied.

Duty cycle $< 98\%$, duty cycle variations exceed $\pm 2\%$


KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-3 should be applied.

4.6.4 Test Result

Please refer to section 5.7.

4.7 Duty Cycle

4.7.1 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer.

4.7.2 Test Procedure

According to ANSI C63.10-2013 Section 12.2

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- 3) Set $VBW \geq RBW$. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

4.7.3 Judgment

Report Only. Please refer to section 5.8.

4.8 Antenna Requirement

4.8.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

RSS-Gen Clause 6.8

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below). When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

4.8.2 Judgment

Compliant. Please refer to the Antenna Information detail in Section 1.3.

4.9 Additional requirement

4.9.1 Applicable Standard

According to RSS-247 Clause 6.4 Additional requirement

The following requirements shall apply:

- a) The device shall automatically discontinue transmission in cases of absence of information to transmit, or operational failure. A description on how this is done shall accompany the application for equipment certification. Note that this is not intended to prohibit transmission of control or signalling information or the use of repetitive codes where required by the technology.
- b) All LE-LAN devices must contain security features to protect against modification of software by unauthorized parties.

Manufacturers must implement security features in any digitally modulated devices capable of operating in any of the frequency ranges within the 5 GHz band, so that third parties are not able to reprogram the device to operate outside the parameters for which the device was certified. The software must prevent the user from operating the transmitter with operating frequencies, output power, modulation types or other radio frequency parameters outside those that were approved for the device. Manufacturers may use various means, including the use of a private network that allows only authenticated users to download software, electronic signatures in software or coding in hardware that is decoded by software to verify that new software can be legally loaded into a device to meet these requirements and must describe the methods in their application for equipment certification.

Manufacturers must take steps to ensure that DFS functionality cannot be disabled by the operator of the LE-LAN device.

- c) The user manual for LE-LAN devices shall contain instructions related to the restrictions mentioned in the above sections, namely that:
 - i. the device for operation in the band 5150–5250 MHz is only for indoor use to reduce the potential for harmful interference to co-channel mobile satellite systems;⁴
 - ii. for devices with detachable antenna(s), the maximum antenna gain permitted for devices in the bands 5250-5350 MHz and 5470-5725 MHz shall be such that the equipment still complies with the e.i.r.p. limit;
 - iii. for devices with detachable antenna(s), the maximum antenna gain permitted for devices in the band 5725-5850 MHz shall be such that the equipment still complies with the e.i.r.p. limits as appropriate; and
 - iv. where applicable, antenna type(s), antenna models(s), and worst-case tilt angle(s) necessary to remain compliant with the e.i.r.p. elevation mask requirement set forth in section 6.2.2.3 shall be clearly indicated.

4.9.2 Judgment

RSS-247 Clause 6.4 a):

The device shall automatically discontinue transmission in cases of absence of information to transmit, or operational failure. Please refer to the declaration

RSS-247 Clause 6.4 b):

The devices must contain security features to protect against modification of software by unauthorized parties. Please refer to the declaration

RSS-247 Clause 6.4 c):

i). The device is only for indoor use.

ii). The device operates on 5250-5350MHz/5470-5725MHz meet the EIRP limit, please refer to the power test result.

iii). The antenna permanently attached to the unit, and all the EIRP compliance with RSS-247 requirement. Please refer to the conducted output power test result.

iv). The device EIRP less than 200mW(23 dBm)

5. Test DATA AND RESULTS

5.1 AC Line Conducted Emissions

Serial Number:	2HPA-3	Test Date:	2024/3/16
Test Site:	CE	Test Mode:	Transmitting
Tester:	Wright Lai	Test Result:	Pass

Environmental Conditions:


Temperature: (°C)	22.2	Relative Humidity: (%)	70	ATM Pressure: (kPa)	101.2
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101614	2023/10/18	2024/10/17
MICRO-COAX	Coaxial Cable	C-NJNJ-50	C-0200-01	2023/9/5	2024/9/4
R&S	EMI Test Receiver	ESCI	100035	2023/8/18	2024/8/17
R&S	Test Software	EMC32	V9.10.00	N/A	N/A

** Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*


Project No: XMDN240206-08120E-RF
Test Engineer: Wright Lai
Test Date: 2024/3/16
Port: L
Test Mode: Transmitting
Power Source: AC 120V/60Hz
Note: 802.11n ht20 5825MHz



Final Result

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.548615	35.59	---	56.00	20.41	9.000	L1	10.8
0.554114	---	29.84	46.00	16.16	9.000	L1	10.8
0.669745	37.57	---	56.00	18.43	9.000	L1	10.8
0.673094	---	29.06	46.00	16.94	9.000	L1	10.8
0.762478	---	37.13	46.00	8.87	9.000	L1	10.9
0.766291	44.40	---	56.00	11.60	9.000	L1	10.9
0.801471	---	32.69	46.00	13.31	9.000	L1	10.9
0.842459	---	32.97	46.00	13.03	9.000	L1	10.9
0.917005	36.10	---	56.00	19.90	9.000	L1	10.9
0.930829	---	28.84	46.00	17.16	9.000	L1	10.9
1.353083	35.20	---	56.00	20.80	9.000	L1	10.8
1.789056	33.12	---	56.00	22.88	9.000	L1	10.8

Project No: XMDN240206-08120E-RF
Test Engineer: Wright Lai
Test Date: 2024/3/16
Port: N
Test Mode: Transmitting
Power Source: AC 120V/60Hz
Note: 802.11n ht20 5825MHz



Final Result

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.562468	---	25.27	46.00	20.73	9.000	N	10.7
0.650000	32.14	---	56.00	23.86	9.000	N	10.7
0.686657	---	25.12	46.00	20.88	9.000	N	10.8
0.766291	---	32.12	46.00	13.88	9.000	N	10.8
0.773973	39.61	---	56.00	16.39	9.000	N	10.8
0.846671	---	27.59	46.00	18.41	9.000	N	10.8
0.846671	34.04	---	56.00	21.96	9.000	N	10.8
0.926198	---	24.09	46.00	21.91	9.000	N	10.8
1.928035	30.31	---	56.00	25.69	9.000	N	10.9
2.342024	30.93	---	56.00	25.07	9.000	N	10.9
2.844905	30.73	---	56.00	25.27	9.000	N	10.9
29.953587	---	27.81	50.00	22.19	9.000	N	11.0

5.2 Radiation Spurious Emissions

Serial Number:	2HPA-3, 2HPA-5	Test Date:	Below 1GHz: 2024/3/15~2024/5/20 Above 1GHz: 2024/5/20 ~2024/5/22
Test Site:	Chamber 10m, Chamber B	Test Mode:	Transmitting
Tester:	Leesin Xiang, Zoo Zou, Nat Zhou	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	22.2~26.3	Relative Humidity: (%)	47~62	ATM Pressure: (kPa)	99.9~101.0
----------------------	-----------	------------------------------	-------	------------------------	------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
9kHz~1000MHz					
EMCO	Passive Loop Antenna	6512	9706-1206	2023/10/21	2026/10/20
Sunol Sciences	Hybrid Antenna	JB3	A060611-1	2023/9/6	2026/9/5
Narda	Attenuator	779-6dB	04269	2023/9/6	2024/9/5
Unknown	Coaxial Cable	C-NJNJ-50	C-1000-01	2023/8/1	2024/7/31
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-04	2023/8/1	2024/7/31
Unknown	Coaxial Cable	C-NJNJ-50	C-0530-01	2023/8/1	2024/7/31
Sonoma	Amplifier	310N	185914	2023/8/1	2024/7/31
R&S	EMI Test Receiver	ESCI	100224	2023/8/18	2024/8/17
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
Above 1GHz					
ETS-Lindgren	Horn Antenna	3115	000 527 35	2023/9/7	2026/9/6
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-02 1304	2023/2/22	2026/2/21
Ducommun Technologies	Horn Antenna	ARH-2823-02	1007726-01 1302	2023/2/22	2026/2/21
Xinhang Macrowave	Coaxial Cable	XH750A-N/J-SMA/J-10M	20231117004 #0001	2023/11/17	2024/11/16
Xinhang Macrowave	Coaxial Cable	XH360A-2.92/J-2.92/J-6M-A	20231208001 #0001	2023/12/11	2024/12/10
AH	Preamplifier	PAM-0118P	469	2023/8/19	2024/8/18
AH	Preamplifier	PAM-1840VH	191	2023/9/7	2024/9/6
R&S	Spectrum Analyzer	FSV40	101944	2023/10/18	2024/10/17
Audix	Test Software	E3	191218 (V9)	N/A	N/A
Sinoscite	Band Rejection Filter	BSF5150-5850MN	0899003	2024/2/21	2025/2/20
Mini-Circuits	High Pass Filter	VHF-6010+	31118	2023/12/1	2024/11/30

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Please refer to the below table and plots.

After pre-scan in the X, Y and Z axes of orientation, the worst case is below:

1) 9kHz~30MHz


802.11n ht20 5825MHz was tested, the amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

2) 30MHz-1GHz

M20:

Project No: XMDN240206-08120E-RF
Test Engineer: Leesin Xiang
Test Date: 2024/3/15
Polarization: Horizontal
Test Mode: Transmitting
Power Source: AC 120V/60Hz
Note: 802.11n ht20 5825MHz


80.0 dBuV/m



No.	Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	154.1600	39.33	peak	-10.98	28.35	43.50	15.15
2	201.6900	41.97	peak	-11.69	30.28	43.50	13.22
3	225.9400	45.21	peak	-12.37	32.84	46.00	13.16
4	244.3700	42.87	peak	-11.61	31.26	46.00	14.74
5	345.2500	38.20	peak	-8.69	29.51	46.00	16.49
6	384.0500	38.13	peak	-7.48	30.65	46.00	15.35

Project No: XMDN240206-08120E-RF
Test Engineer: Leesin Xiang
Test Date: 2024/3/15
Polarization: Vertical
Test Mode: Transmitting
Power Source: AC 120V/60Hz
Note: 802.11n ht20 5825MHz


80.0 dBuV/m



No.	Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	32.9100	34.90	peak	-5.47	29.43	40.00	10.57
2	112.4500	35.48	peak	-10.97	24.51	43.50	18.99
3	152.2200	33.77	peak	-11.01	22.76	43.50	20.74
4	165.8000	34.26	peak	-11.45	22.81	43.50	20.69
5	225.9400	36.61	peak	-12.37	24.24	46.00	21.76
6	245.3400	35.57	peak	-11.57	24.00	46.00	22.00

M20SE:


Project No: XMDN240206-08120E-RF
Test Engineer: Zoo Zou
Test Date: 2024/5/20
Polarization: Horizontal
Test Mode: Transmitting
Power Source: AC 120V/60Hz
Note: 802.11n ht20 5825MHz



No.	Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	30.0000	27.50	peak	-3.80	23.70	40.00	16.30
2	155.1300	44.97	peak	-11.01	33.96	43.50	9.54
3	171.6200	44.38	peak	-11.77	32.61	43.50	10.89
4	194.9000	40.64	peak	-11.88	28.76	43.50	14.74
5	225.9400	47.53	peak	-12.37	35.16	46.00	10.84
6	231.7600	46.99	peak	-12.16	34.83	46.00	11.17

Project No: XMDN240206-08120E-RF
Test Engineer: Zoo Zou
Test Date: 2024/5/20
Polarization: Vertical
Test Mode: Transmitting
Power Source: AC 120V/60Hz
Note: 802.11n ht20 5825MHz

80.0 dBuV/m



No.	Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	30.9700	33.84	peak	-4.31	29.53	40.00	10.47
2	48.4300	40.63	peak	-16.11	24.52	40.00	15.48
3	61.0400	40.84	peak	-16.61	24.23	40.00	15.77
4	157.0700	38.72	peak	-11.12	27.60	43.50	15.90
5	171.6200	39.98	peak	-11.77	28.21	43.50	15.29
6	229.8200	43.69	peak	-12.23	31.46	46.00	14.54

3) 1-40GHz:**M20:****802.11a_U-NII-1_low channel****Frequency 5180 MHz**

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5150.00	28.73	PK	H	33.21	1.55	0.00	63.49	57.49	74.00	16.51
5150.00	18.47	AV	H	33.21	1.55	0.00	53.23	47.23	54.00	6.77
5150.00	29.30	PK	V	33.21	1.55	0.00	64.06	58.06	74.00	15.94
5150.00	18.79	AV	V	33.21	1.55	0.00	53.55	47.55	54.00	6.45
10360.00	47.05	PK	H	38.27	3.99	41.93	47.38	47.38	68.20	20.82
10360.00	47.25	PK	V	38.27	3.99	41.93	47.58	47.58	68.20	20.62
15540.00	46.48	PK	H	37.64	5.83	42.87	47.08	47.08	74.00	26.92
15540.00	36.27	AV	H	37.64	5.83	42.87	36.87	36.87	54.00	17.13
15540.00	47.56	PK	V	37.64	5.83	42.87	48.16	48.16	74.00	25.84
15540.00	37.38	AV	V	37.64	5.83	42.87	37.98	37.98	54.00	16.02
6906.79	63.65	PK	V	35.35	2.23	44.15	57.08	57.08	68.20	11.12
6906.79	60.13	PK	H	35.35	2.23	44.15	53.56	53.56	68.20	14.64

802.11a_U-NII-1_middle channel**Frequency 5200 MHz**

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
10400.00	46.27	PK	H	38.28	4.00	41.88	46.67	46.67	68.20	21.53
10400.00	46.47	PK	V	38.28	4.00	41.88	46.87	46.87	68.20	21.33
15600.00	47.38	PK	H	37.54	5.85	42.81	47.96	47.96	74.00	26.04
15600.00	37.15	AV	H	37.54	5.85	42.81	37.73	37.73	54.00	16.27
15600.00	48.39	PK	V	37.54	5.85	42.81	48.97	48.97	74.00	25.03
15600.00	38.08	AV	V	37.54	5.85	42.81	38.66	38.66	54.00	15.34

802.11a_U-NII-1_high channel**Frequency 5240 MHz**

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5350.00	28.21	PK	H	33.49	1.66	0.00	63.36	57.36	74.00	16.64
5350.00	18.26	AV	H	33.49	1.66	0.00	53.41	47.41	54.00	6.59
5350.00	28.27	PK	V	33.49	1.66	0.00	63.42	57.42	74.00	16.58
5350.00	18.38	AV	V	33.49	1.66	0.00	53.53	47.53	54.00	6.47
10480.00	46.77	PK	H	38.30	4.04	41.78	47.33	47.33	68.20	20.87
10480.00	47.27	PK	V	38.30	4.04	41.78	47.83	47.83	68.20	20.37
15720.00	47.31	PK	H	37.35	5.89	42.69	47.86	47.86	74.00	26.14
15720.00	37.24	AV	H	37.35	5.89	42.69	37.79	37.79	54.00	16.21
15720.00	48.35	PK	V	37.35	5.89	42.69	48.90	48.9	74.00	25.10
15720.00	38.18	AV	V	37.35	5.89	42.69	38.73	38.73	54.00	15.27
6987.40	61.66	PK	H	35.48	2.26	44.16	55.24	55.24	68.20	12.96
6987.40	65.52	PK	V	35.48	2.26	44.16	59.10	59.1	68.20	9.10

802.11n20_U-NII-1_low channel

Frequency 5180 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain		Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5150.00	30.98	PK	H	33.21	1.55	0.00	65.74	59.74	74.00	14.26
5150.00	20.75	AV	H	33.21	1.55	0.00	55.51	49.51	54.00	4.49
5150.00	35.12	PK	V	33.21	1.55	0.00	69.88	63.88	74.00	10.12
5150.00	24.20	AV	V	33.21	1.55	0.00	58.96	52.96	54.00	1.04
10360.00	47.23	PK	H	38.27	3.99	41.93	47.56	47.56	68.20	20.64
10360.00	47.35	PK	V	38.27	3.99	41.93	47.68	47.68	68.20	20.52
15540.00	46.38	PK	H	37.64	5.83	42.87	46.98	46.98	74.00	27.02
15540.00	36.11	AV	H	37.64	5.83	42.87	36.71	36.71	54.00	17.29
15540.00	46.24	PK	V	37.64	5.83	42.87	46.84	46.84	74.00	27.16
15540.00	36.18	AV	V	37.64	5.83	42.87	36.78	36.78	54.00	17.22
6905.00	60.08	PK	H	35.35	2.23	44.15	53.51	53.51	68.20	14.69
6905.00	63.46	PK	V	35.35	2.23	44.15	56.89	56.89	68.20	11.31

802.11n20_U-NII-1_middle channel

Frequency 5200 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
10400.00	47.47	PK	H	38.28	4.00	41.88	47.87	47.87	68.20	20.33
10400.00	46.37	PK	V	38.28	4.00	41.88	46.77	46.77	68.20	21.43
15600.00	46.56	PK	H	37.54	5.85	42.81	47.14	47.14	74.00	26.86
15600.00	36.34	AV	H	37.54	5.85	42.81	36.92	36.92	54.00	17.08
15600.00	46.68	PK	V	37.54	5.85	42.81	47.26	47.26	74.00	26.74
15600.00	36.42	AV	V	37.54	5.85	42.81	37.00	37	54.00	17.00

802.11n20_U-NII-1_high channel

Frequency 5240 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5350.00	28.66	PK	H	33.49	1.66	0.00	63.81	57.81	74.00	16.19
5350.00	18.42	AV	H	33.49	1.66	0.00	53.57	47.57	54.00	6.43
5350.00	28.74	PK	V	33.49	1.66	0.00	63.89	57.89	74.00	16.11
5350.00	18.67	AV	V	33.49	1.66	0.00	53.82	47.82	54.00	6.18
10480.00	47.57	PK	H	38.30	4.04	41.78	48.13	48.13	68.20	20.07
10480.00	46.77	PK	V	38.30	4.04	41.78	47.33	47.33	68.20	20.87
15720.00	46.36	PK	H	37.35	5.89	42.69	46.91	46.91	74.00	27.09
15720.00	36.24	AV	H	37.35	5.89	42.69	36.79	36.79	54.00	17.21
15720.00	46.59	PK	V	37.35	5.89	42.69	47.14	47.14	74.00	26.86
15720.00	36.65	AV	V	37.35	5.89	42.69	37.20	37.2	54.00	16.80
6987.40	61.65	PK	H	35.48	2.26	44.16	55.23	55.23	68.20	12.97
6987.40	64.47	PK	V	35.48	2.26	44.16	58.05	58.05	68.20	10.15

802.11n40_U-NII-1_low channel

Frequency 5190 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5150.00	31.33	PK	H	33.21	1.55	0.00	66.09	60.09	74.00	13.91
5150.00	21.27	AV	H	33.21	1.55	0.00	56.03	50.03	54.00	3.97
5150.00	33.86	PK	V	33.21	1.55	0.00	68.62	62.62	74.00	11.38
5150.00	23.38	AV	V	33.21	1.55	0.00	58.14	52.14	54.00	1.86
10380.00	47.36	PK	H	38.28	3.99	41.90	47.73	47.73	68.20	20.47
10380.00	47.59	PK	V	38.28	3.99	41.90	47.96	47.96	68.20	20.24
15570.00	47.38	PK	H	37.59	5.84	42.84	47.97	47.97	74.00	26.03
15570.00	37.14	AV	H	37.59	5.84	42.84	37.73	37.73	54.00	16.27
15570.00	47.54	PK	V	37.59	5.84	42.84	48.13	48.13	74.00	25.87
15570.00	37.26	AV	V	37.59	5.84	42.84	37.85	37.85	54.00	16.15
6920.00	60.56	PK	H	35.37	2.24	44.15	54.02	54.02	68.20	14.18
6920.00	64.43	PK	V	35.37	2.24	44.15	57.89	57.89	68.20	10.31

802.11n40_U-NII-1_high channel

Frequency 5230 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5350.00	28.36	PK	H	33.49	1.66	0.00	63.51	57.51	74.00	16.49
5350.00	18.20	AV	H	33.49	1.66	0.00	53.35	47.35	54.00	6.65
5350.00	28.47	PK	V	33.49	1.66	0.00	63.62	57.62	74.00	16.38
5350.00	18.55	AV	V	33.49	1.66	0.00	53.70	47.7	54.00	6.30
10460.00	47.67	PK	H	38.29	4.03	41.81	48.18	48.18	68.20	20.02
10460.00	46.13	PK	V	38.29	4.03	41.81	46.64	46.64	68.20	21.56
15690.00	47.36	PK	H	37.40	5.88	42.72	47.92	47.92	74.00	26.08
15690.00	37.28	AV	H	37.40	5.88	42.72	37.84	37.84	54.00	16.16
15690.00	46.98	PK	V	37.40	5.88	42.72	47.54	47.54	74.00	26.46
15690.00	37.12	AV	V	37.40	5.88	42.72	37.68	37.68	54.00	16.32
6973.00	61.31	PK	H	35.46	2.26	44.16	54.87	54.87	68.20	13.33
6973.00	65.34	PK	V	35.46	2.26	44.16	58.90	58.9	68.20	9.30

802.11ac80_U-NII-1_middle channel

Frequency 5210 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5150.00	30.77	PK	H	33.21	1.55	0.00	65.53	59.53	74.00	14.47
5150.00	18.81	AV	H	33.21	1.55	0.00	53.57	47.57	54.00	6.43
5150.00	34.58	PK	V	33.21	1.55	0.00	69.34	63.34	74.00	10.66
5150.00	24.52	AV	V	33.21	1.55	0.00	59.28	53.28	54.00	0.72
5350.00	28.24	PK	H	33.49	1.66	0.00	63.39	57.39	74.00	16.61
5350.00	18.36	AV	H	33.49	1.66	0.00	53.51	47.51	54.00	6.49
5350.00	28.65	PK	V	33.49	1.66	0.00	63.80	57.8	74.00	16.20
5350.00	18.48	AV	V	33.49	1.66	0.00	53.63	47.63	54.00	6.37
10420.00	47.38	PK	H	38.28	4.01	41.86	47.81	47.81	68.20	20.39
10420.00	47.51	PK	V	38.28	4.01	41.86	47.94	47.94	68.20	20.26
15630.00	47.13	PK	H	37.49	5.86	42.78	47.70	47.7	74.00	26.30
15630.00	37.17	AV	H	37.49	5.86	42.78	37.74	37.74	54.00	16.26
15630.00	47.33	PK	V	37.49	5.86	42.78	47.90	47.9	74.00	26.10
15630.00	37.24	AV	V	37.49	5.86	42.78	37.81	37.81	54.00	16.19

802.11a_U-NII-2A_low channel

Frequency 5260 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5150.00	28.20	PK	H	33.21	1.55	0.00	62.96	56.96	74.00	17.04
5150.00	18.52	AV	H	33.21	1.55	0.00	53.28	47.28	54.00	6.72
5150.00	29.30	PK	V	33.21	1.55	0.00	64.06	58.06	74.00	15.94
5150.00	19.05	AV	V	33.21	1.55	0.00	53.81	47.81	54.00	6.19
10520.00	46.24	PK	H	38.29	4.06	41.75	46.84	46.84	68.20	21.36
10520.00	46.52	PK	V	38.29	4.06	41.75	47.12	47.12	68.20	21.08
15780.00	46.47	PK	H	37.25	5.92	42.62	47.02	47.02	74.00	26.98
15780.00	36.51	AV	H	37.25	5.92	42.62	37.06	37.06	54.00	16.94
15780.00	46.88	PK	V	37.25	5.92	42.62	47.43	47.43	74.00	26.57
15780.00	36.77	AV	V	37.25	5.92	42.62	37.32	37.32	54.00	16.68

802.11a_U-NII-2A_middle channel

Frequency 5280 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
10560.00	46.42	PK	H	38.28	4.07	41.74	47.03	47.03	68.20	21.17
10560.00	46.76	PK	V	38.28	4.07	41.74	47.37	47.37	68.20	20.83
15840.00	46.43	PK	H	37.16	5.94	42.56	46.97	46.97	74.00	27.03
15840.00	36.28	AV	H	37.16	5.94	42.56	36.82	36.82	54.00	17.18
15840.00	46.76	PK	V	37.16	5.94	42.56	47.30	47.3	74.00	26.70
15840.00	36.51	AV	V	37.16	5.94	42.56	37.05	37.05	54.00	16.95

802.11a_U-NII-2A_high channel

Frequency 5320 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5350.00	28.77	PK	H	33.49	1.66	0.00	63.92	57.92	74.00	16.08
5350.00	18.46	AV	H	33.49	1.66	0.00	53.61	47.61	54.00	6.39
5350.00	28.93	PK	V	33.49	1.66	0.00	64.08	58.08	74.00	15.92
5350.00	18.69	AV	V	33.49	1.66	0.00	53.84	47.84	54.00	6.16
10640.00	46.43	PK	H	38.24	4.10	41.72	47.05	47.05	74.00	26.95
10640.00	36.33	AV	H	38.24	4.10	41.72	36.95	36.95	54.00	17.05
10640.00	46.66	PK	V	38.24	4.10	41.72	47.28	47.28	74.00	26.72
10640.00	36.48	AV	V	38.24	4.10	41.72	37.10	37.1	54.00	16.90
15960.00	46.63	PK	H	36.96	5.98	42.44	47.13	47.13	74.00	26.87
15960.00	36.38	AV	H	36.96	5.98	42.44	36.88	36.88	54.00	17.12
15960.00	46.83	PK	V	36.96	5.98	42.44	47.33	47.33	74.00	26.67
15960.00	36.47	AV	V	36.96	5.98	42.44	36.97	36.97	54.00	17.03

802.11n20_U-NII-2A_low channel

Frequency 5260 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5150.00	29.15	PK	H	33.21	1.55	0.00	63.91	57.91	74.00	16.09
5150.00	19.21	AV	H	33.21	1.55	0.00	53.97	47.97	54.00	6.03
5150.00	29.41	PK	V	33.21	1.55	0.00	64.17	58.17	74.00	15.83
5150.00	19.42	AV	V	33.21	1.55	0.00	54.18	48.18	54.00	5.82
10520.00	47.36	PK	H	38.29	4.06	41.75	47.96	47.96	68.20	20.24
10520.00	48.65	PK	V	38.29	4.06	41.75	49.25	49.25	68.20	18.95
15780.00	46.78	PK	H	37.25	5.92	42.62	47.33	47.33	74.00	26.67
15780.00	36.62	AV	H	37.25	5.92	42.62	37.17	37.17	54.00	16.83
15780.00	47.25	PK	V	37.25	5.92	42.62	47.80	47.8	74.00	26.20
15780.00	37.12	AV	V	37.25	5.92	42.62	37.67	37.67	54.00	16.33

802.11n20_U-NII-2A_middle channel

Frequency 5280 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
10560.00	47.26	PK	H	38.28	4.07	41.74	47.87	47.87	68.20	20.33
10560.00	47.65	PK	V	38.28	4.07	41.74	48.26	48.26	68.20	19.94
15840.00	46.48	PK	H	37.16	5.94	42.56	47.02	47.02	74.00	26.98
15840.00	36.32	AV	H	37.16	5.94	42.56	36.86	36.86	54.00	17.14
15840.00	46.55	PK	V	37.16	5.94	42.56	47.09	47.09	74.00	26.91
15840.00	36.47	AV	V	37.16	5.94	42.56	37.01	37.01	54.00	16.99

802.11n20_U-NII-2A_high channel

Frequency 5320 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5350.00	28.41	PK	H	33.49	1.66	0.00	63.56	57.56	74.00	16.44
5350.00	18.52	AV	H	33.49	1.66	0.00	53.67	47.67	54.00	6.33
5350.00	28.54	PK	V	33.49	1.66	0.00	63.69	57.69	74.00	16.31
5350.00	18.67	AV	V	33.49	1.66	0.00	53.82	47.82	54.00	6.18
10640.00	46.17	PK	H	38.24	4.10	41.72	46.79	46.79	74.00	27.21
10640.00	36.08	AV	H	38.24	4.10	41.72	36.70	36.7	54.00	17.30
10640.00	46.77	PK	V	38.24	4.10	41.72	47.39	47.39	74.00	26.61
10640.00	36.30	AV	V	38.24	4.10	41.72	36.92	36.92	54.00	17.08
15960.00	46.41	PK	H	36.96	5.98	42.44	46.91	46.91	74.00	27.09
15960.00	36.26	AV	H	36.96	5.98	42.44	36.76	36.76	54.00	17.24
15960.00	46.60	PK	V	36.96	5.98	42.44	47.10	47.1	74.00	26.90
15960.00	36.47	AV	V	36.96	5.98	42.44	36.97	36.97	54.00	17.03

802.11n40_U-NII-2A_low channel

Frequency 5270 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5150.00	28.51	PK	H	33.21	1.55	0.00	63.27	57.27	74.00	16.73
5150.00	18.69	AV	H	33.21	1.55	0.00	53.45	47.45	54.00	6.55
5150.00	28.63	PK	V	33.21	1.55	0.00	63.39	57.39	74.00	16.61
5150.00	18.76	AV	V	33.21	1.55	0.00	53.52	47.52	54.00	6.48
10540.00	46.41	PK	H	38.28	4.06	41.75	47.00	47	68.20	21.20
10540.00	46.55	PK	V	38.28	4.06	41.75	47.14	47.14	68.20	21.06
15810.00	46.54	PK	H	37.20	5.93	42.59	47.08	47.08	74.00	26.92
15810.00	36.61	AV	H	37.20	5.93	42.59	37.15	37.15	54.00	16.85
15810.00	46.82	PK	V	37.20	5.93	42.59	47.36	47.36	74.00	26.64
15810.00	36.78	AV	V	37.20	5.93	42.59	37.32	37.32	54.00	16.68

802.11n40_U-NII-2A_high channel

Frequency 5310 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5350.00	31.77	PK	H	33.49	1.66	0.00	66.92	60.92	74.00	13.08
5350.00	21.36	AV	H	33.49	1.66	0.00	56.51	50.51	54.00	3.49
5350.00	33.97	PK	V	33.49	1.66	0.00	69.12	63.12	74.00	10.88
5350.00	23.22	AV	V	33.49	1.66	0.00	58.37	52.37	54.00	1.63
10620.00	48.25	PK	H	38.25	4.09	41.72	48.87	48.87	74.00	25.13
10620.00	38.14	AV	H	38.25	4.09	41.72	38.76	38.76	54.00	15.24
10620.00	49.23	PK	V	38.25	4.09	41.72	49.85	49.85	74.00	24.15
10620.00	39.34	AV	V	38.25	4.09	41.72	39.96	39.96	54.00	14.04
15930.00	46.52	PK	H	37.01	5.97	42.47	47.03	47.03	74.00	26.97
15930.00	36.41	AV	H	37.01	5.97	42.47	36.92	36.92	54.00	17.08
15930.00	46.74	PK	V	37.01	5.97	42.47	47.25	47.25	74.00	26.75
15930.00	36.63	AV	V	37.01	5.97	42.47	37.14	37.14	54.00	16.86

802.11ac80_U-NII-2A_middle channel

Frequency 5290 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5150.00	28.99	PK	H	33.21	1.55	0.00	63.75	57.75	74.00	16.25
5150.00	18.45	AV	H	33.21	1.55	0.00	53.21	47.21	54.00	6.79
5150.00	28.82	PK	V	33.21	1.55	0.00	63.58	57.58	74.00	16.42
5150.00	18.92	AV	V	33.21	1.55	0.00	53.68	47.68	54.00	6.32
5350.00	32.83	PK	H	33.49	1.66	0.00	67.98	61.98	74.00	12.02
5350.00	23.45	AV	H	33.49	1.66	0.00	58.60	52.6	54.00	1.40
5350.00	33.44	PK	V	33.49	1.66	0.00	68.59	62.59	74.00	11.41
5350.00	23.53	AV	V	33.49	1.66	0.00	58.68	52.68	54.00	1.32
10580.00	47.18	PK	H	38.27	4.08	41.74	47.79	47.79	68.20	20.41
10580.00	47.26	PK	V	38.27	4.08	41.74	47.87	47.87	68.20	20.33
15870.00	46.22	PK	H	37.11	5.95	42.53	46.75	46.75	74.00	27.25
15870.00	36.18	AV	H	37.11	5.95	42.53	36.71	36.71	54.00	17.29
15870.00	46.27	PK	V	37.11	5.95	42.53	46.80	46.8	74.00	27.20
15870.00	36.37	AV	V	37.11	5.95	42.53	36.90	36.9	54.00	17.10

802.11a_U-NII-2C_low channel

Frequency 5500 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5470.00	29.18	PK	H	33.66	1.70	0.00	64.54	58.54	68.20	9.66
5470.00	29.53	PK	V	33.66	1.70	0.00	64.89	58.89	68.20	9.31
11000.00	47.80	PK	H	38.10	4.23	41.61	48.52	48.52	74.00	25.48
11000.00	37.64	AV	H	38.10	4.23	41.61	38.36	38.36	54.00	15.64
11000.00	48.05	PK	V	38.10	4.23	41.61	48.77	48.77	74.00	25.23
11000.00	37.84	AV	V	38.10	4.23	41.61	38.56	38.56	54.00	15.44
16500.00	47.29	PK	H	37.60	6.14	42.64	48.39	48.39	68.20	19.81
16500.00	47.46	PK	V	37.60	6.14	42.64	48.56	48.56	68.20	19.64

802.11a_U-NII-2C_middle channel

Frequency 5580 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
11160.00	46.53	PK	H	38.10	4.34	41.44	47.53	47.53	74.00	26.47
11160.00	36.64	AV	H	38.10	4.34	41.44	37.64	37.64	54.00	16.36
11160.00	47.15	PK	V	38.10	4.34	41.44	48.15	48.15	74.00	25.85
11160.00	36.97	AV	V	38.10	4.34	41.44	37.97	37.97	54.00	16.03
16740.00	47.52	PK	H	38.42	6.18	42.18	49.94	49.94	68.20	18.26
16740.00	47.67	PK	V	38.42	6.18	42.18	50.09	50.09	68.20	18.11

802.11a_U-NII-2C_high channel

Frequency 5700 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5725.00	29.80	PK	H	33.97	1.84	0.00	65.61	59.61	68.20	8.59
5725.00	30.63	PK	V	33.97	1.84	0.00	66.44	60.44	68.20	7.76
11400.00	46.46	PK	H	38.10	4.49	41.19	47.86	47.86	74.00	26.14
11400.00	36.38	AV	H	38.10	4.49	41.19	37.78	37.78	54.00	16.22
11400.00	46.52	PK	V	38.10	4.49	41.19	47.92	47.92	74.00	26.08
11400.00	36.44	AV	V	38.10	4.49	41.19	37.84	37.84	54.00	16.16
17100.00	46.58	PK	H	39.58	6.28	41.86	50.58	50.58	68.20	17.62
17100.00	46.72	PK	V	39.58	6.28	41.86	50.72	50.72	68.20	17.48
7600.00	54.43	PK	V	36.74	2.59	43.53	50.23	50.23	74.00	23.77
7600.00	50.43	AV	V	36.74	2.59	43.53	46.23	46.23	54.00	7.77

802.11n20_U-NII-2C_low channel

Frequency 5500 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5470.00	30.89	PK	H	33.66	1.70	0.00	66.25	60.25	68.20	7.95
5470.00	32.38	PK	V	33.66	1.70	0.00	67.74	61.74	68.20	6.46
11000.00	48.69	PK	H	38.10	4.23	41.61	49.41	49.41	74.00	24.59
11000.00	38.56	AV	H	38.10	4.23	41.61	39.28	39.28	54.00	14.72
11000.00	48.78	PK	V	38.10	4.23	41.61	49.50	49.5	74.00	24.50
11000.00	38.77	AV	V	38.10	4.23	41.61	39.49	39.49	54.00	14.51
16500.00	47.88	PK	H	37.60	6.14	42.64	48.98	48.98	68.20	19.22
16500.00	48.53	PK	V	37.60	6.14	42.64	49.63	49.63	68.20	18.57

802.11n20_U-NII-2C_middle channel

Frequency 5580 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
11160.00	48.35	PK	H	38.10	4.34	41.44	49.35	49.35	74.00	24.65
11160.00	38.62	AV	H	38.10	4.34	41.44	39.62	39.62	54.00	14.38
11160.00	48.79	PK	V	38.10	4.34	41.44	49.79	49.79	74.00	24.21
11160.00	38.73	AV	V	38.10	4.34	41.44	39.73	39.73	54.00	14.27
16740.00	48.21	PK	H	38.42	6.18	42.18	50.63	50.63	68.20	17.57
16740.00	48.46	PK	V	38.42	6.18	42.18	50.88	50.88	68.20	17.32

802.11n20_U-NII-2C_high channel

Frequency 5700 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5725.00	30.87	PK	H	33.97	1.84	0.00	66.68	60.68	68.20	7.52
5725.00	31.44	PK	V	33.97	1.84	0.00	67.25	61.25	68.20	6.95
11400.00	46.52	PK	H	38.10	4.49	41.19	47.92	47.92	74.00	26.08
11400.00	36.48	AV	H	38.10	4.49	41.19	37.88	37.88	54.00	16.12
11400.00	46.77	PK	V	38.10	4.49	41.19	48.17	48.17	74.00	25.83
11400.00	36.45	AV	V	38.10	4.49	41.19	37.85	37.85	54.00	16.15
17100.00	46.44	PK	H	39.58	6.28	41.86	50.44	50.44	68.20	17.76
17100.00	46.54	PK	V	39.58	6.28	41.86	50.54	50.54	68.20	17.66
7598.40	58.24	PK	V	36.74	2.59	43.53	54.04	54.04	74.00	19.96
7598.40	55.40	AV	V	36.74	2.59	43.53	51.20	51.2	54.00	2.80
7598.40	54.16	PK	H	36.74	2.59	43.53	49.96	49.96	74.00	24.04
7598.40	51.24	AV	H	36.74	2.59	43.53	47.04	47.04	54.00	6.96

802.11n40_U-NII-2C_low channel

Frequency 5510 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5470.00	34.80	PK	H	33.66	1.70	0.00	70.16	64.16	68.20	4.04
5470.00	36.31	PK	V	33.66	1.70	0.00	71.67	65.67	68.20	2.53
11020.00	47.44	PK	H	38.10	4.24	41.59	48.19	48.19	74.00	25.81
11020.00	37.51	AV	H	38.10	4.24	41.59	38.26	38.26	54.00	15.74
11020.00	47.53	PK	V	38.10	4.24	41.59	48.28	48.28	74.00	25.72
11020.00	37.66	AV	V	38.10	4.24	41.59	38.41	38.41	54.00	15.59
16530.00	46.89	PK	H	37.70	6.15	42.58	48.16	48.16	68.20	20.04
16530.00	47.28	PK	V	37.70	6.15	42.58	48.55	48.55	68.20	19.65

802.11n40_U-NII-2C_middle channel

Frequency 5550 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
11100.00	46.81	PK	H	38.10	4.30	41.51	47.70	47.7	74.00	26.30
11100.00	36.52	AV	H	38.10	4.30	41.51	37.41	37.41	54.00	16.59
11100.00	46.93	PK	V	38.10	4.30	41.51	47.82	47.82	74.00	26.18
11100.00	36.64	AV	V	38.10	4.30	41.51	37.53	37.53	54.00	16.47
16650.00	47.35	PK	H	38.11	6.17	42.35	49.28	49.28	68.20	18.92
16650.00	47.47	PK	V	38.11	6.17	42.35	49.40	49.4	68.20	18.80

802.11n40_U-NII-2C_high channel

Frequency 5670 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5725.00	29.66	PK	H	33.97	1.84	0.00	65.47	59.47	68.20	8.73
5725.00	29.72	PK	V	33.97	1.84	0.00	65.53	59.53	68.20	8.67
11340.00	46.86	PK	H	38.10	4.45	41.26	48.15	48.15	74.00	25.85
11340.00	36.77	AV	H	38.10	4.45	41.26	38.06	38.06	54.00	15.94
11340.00	47.24	PK	V	38.10	4.45	41.26	48.53	48.53	74.00	25.47
11340.00	37.39	AV	V	38.10	4.45	41.26	38.68	38.68	54.00	15.32
17010.00	46.38	PK	H	39.33	6.24	41.70	50.25	50.25	68.20	17.95
17010.00	46.42	PK	V	39.33	6.24	41.70	50.29	50.29	68.20	17.91

802.11ac80_U-NII-2C_low channel

Frequency 5530 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5470.00	38.46	PK	H	33.66	1.70	0.00	73.82	67.82	68.20	0.38
5470.00	38.13	PK	V	33.66	1.70	0.00	73.49	67.49	68.20	0.71
11060.00	46.22	PK	H	38.10	4.27	41.55	47.04	47.04	74.00	26.96
11060.00	36.11	AV	H	38.10	4.27	41.55	36.93	36.93	54.00	17.07
11060.00	46.27	PK	V	38.10	4.27	41.55	47.09	47.09	74.00	26.91
11060.00	36.15	AV	V	38.10	4.27	41.55	36.97	36.97	54.00	17.03
16590.00	47.36	PK	H	37.91	6.16	42.47	48.96	48.96	68.20	19.24
16590.00	47.48	PK	V	37.91	6.16	42.47	49.08	49.08	68.20	19.12

802.11ac80_U-NII-2C_high channel

Frequency 5610 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5725.00	29.96	PK	H	33.97	1.84	0.00	65.77	59.77	68.20	8.43
5725.00	30.87	PK	V	33.97	1.84	0.00	66.68	60.68	68.20	7.52
11220.00	46.36	PK	H	38.10	4.38	41.38	47.46	47.46	74.00	26.54
11220.00	36.33	AV	H	38.10	4.38	41.38	37.43	37.43	54.00	16.57
11220.00	46.58	PK	V	38.10	4.38	41.38	47.68	47.68	74.00	26.32
11220.00	36.67	AV	V	38.10	4.38	41.38	37.77	37.77	54.00	16.23
16830.00	47.46	PK	H	38.72	6.20	42.01	50.37	50.37	68.20	17.83
16830.00	47.88	PK	V	38.72	6.20	42.01	50.79	50.79	68.20	17.41

802.11a_U-NII-3_low channel

Frequency 5745 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5725.00	31.24	PK	H	33.97	1.84	0.00	67.05	61.05	122.20	61.15
5720.00	30.16	PK	H	33.96	1.84	0.00	65.96	59.96	110.80	50.84
5700.00	30.08	PK	H	33.94	1.83	0.00	65.85	59.85	105.20	45.35
5650.00	30.37	PK	H	33.88	1.81	0.00	66.06	60.06	68.20	8.14
5725.00	31.02	PK	V	33.97	1.84	0.00	66.83	60.83	122.20	61.37
5720.00	29.98	PK	V	33.96	1.84	0.00	65.78	59.78	110.80	51.02
5700.00	31.59	PK	V	33.94	1.83	0.00	67.36	61.36	105.20	43.84
5650.00	29.74	PK	V	33.88	1.81	0.00	65.43	59.43	68.20	8.77
11490.00	47.88	PK	H	38.10	4.55	41.10	49.43	49.43	74.00	24.57
11490.00	37.68	AV	H	38.10	4.55	41.10	39.23	39.23	54.00	14.77
11490.00	48.34	PK	V	38.10	4.55	41.10	49.89	49.89	74.00	24.11
11490.00	38.37	AV	V	38.10	4.55	41.10	39.92	39.92	54.00	14.08
17235.00	47.34	PK	H	39.96	6.35	42.11	51.54	51.54	68.20	16.66
17235.00	47.48	PK	V	39.96	6.35	42.11	51.68	51.68	68.20	16.52
7660.00	56.69	PK	V	36.76	2.60	43.54	52.51	52.51	74.00	21.49
7660.00	53.82	AV	V	36.76	2.60	43.54	49.64	49.64	54.00	4.36
7660.00	55.14	PK	H	36.76	2.60	43.54	50.96	50.96	74.00	23.04
7660.00	51.50	AV	H	36.76	2.60	43.54	47.32	47.32	54.00	6.68

802.11a_U-NII-3_middle channel

Frequency 5785 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
11570.00	47.39	PK	H	38.09	4.58	41.08	48.98	48.98	74.00	25.02
11570.00	37.41	AV	H	38.09	4.58	41.08	39.00	39	54.00	15.00
11570.00	47.56	PK	V	38.09	4.58	41.08	49.15	49.15	74.00	24.85
11570.00	37.67	AV	V	38.09	4.58	41.08	39.26	39.26	54.00	14.74
17355.00	47.48	PK	H	40.29	6.41	42.33	51.85	51.85	68.20	16.35
17355.00	47.69	PK	V	40.29	6.41	42.33	52.06	52.06	68.20	16.14

802.11a_U-NII-3_high channel

Frequency 5825 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5850.00	31.21	PK	H	34.12	1.88	0.00	67.21	61.21	122.20	60.99
5855.00	31.12	PK	H	34.13	1.88	0.00	67.13	61.13	110.80	49.67
5875.00	30.29	PK	H	34.15	1.89	0.00	66.33	60.33	105.20	44.87
5925.00	29.99	PK	H	34.21	1.91	0.00	66.11	60.11	68.20	8.09
5850.00	31.06	PK	V	34.12	1.88	0.00	67.06	61.06	122.20	61.14
5855.00	31.16	PK	V	34.13	1.88	0.00	67.17	61.17	110.80	49.63
5875.00	31.14	PK	V	34.15	1.89	0.00	67.18	61.18	105.20	44.02
5925.00	31.73	PK	V	34.21	1.91	0.00	67.85	61.85	68.20	6.35
11650.00	47.38	PK	H	38.07	4.60	41.08	48.97	48.97	74.00	25.03
11650.00	37.25	AV	H	38.07	4.60	41.08	38.84	38.84	54.00	15.16
11650.00	47.64	PK	V	38.07	4.60	41.08	49.23	49.23	74.00	24.77
11650.00	37.59	AV	V	38.07	4.60	41.08	39.18	39.18	54.00	14.82
17475.00	48.33	PK	H	40.63	6.48	42.55	52.89	52.89	68.20	15.31
17475.00	48.46	PK	V	40.63	6.48	42.55	53.02	53.02	68.20	15.18
7766.00	56.50	PK	H	36.81	2.62	43.55	52.38	52.38	68.20	15.82
7766.00	53.87	PK	V	36.81	2.62	43.55	49.75	49.75	68.20	18.45

802.11n20_U-NII-3_low channel

Frequency 5745 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5725.00	31.30	PK	H	33.97	1.84	0.00	67.11	61.11	122.20	61.09
5720.00	31.14	PK	H	33.96	1.84	0.00	66.94	60.94	110.80	49.86
5700.00	30.67	PK	H	33.94	1.83	0.00	66.44	60.44	105.20	44.76
5650.00	30.05	PK	H	33.88	1.81	0.00	65.74	59.74	68.20	8.46
5725.00	31.60	PK	V	33.97	1.84	0.00	67.41	61.41	122.20	60.79
5720.00	30.32	PK	V	33.96	1.84	0.00	66.12	60.12	110.80	50.68
5700.00	30.15	PK	V	33.94	1.83	0.00	65.92	59.92	105.20	45.28
5650.00	29.99	PK	V	33.88	1.81	0.00	65.68	59.68	68.20	8.52
11490.00	46.44	PK	H	38.10	4.55	41.10	47.99	47.99	74.00	26.01
11490.00	36.37	AV	H	38.10	4.55	41.10	37.92	37.92	54.00	16.08
11490.00	46.59	PK	V	38.10	4.55	41.10	48.14	48.14	74.00	25.86
11490.00	36.64	AV	V	38.10	4.55	41.10	38.19	38.19	54.00	15.81
17235.00	46.29	PK	H	39.96	6.35	42.11	50.49	50.49	68.20	17.71
17235.00	46.35	PK	V	39.96	6.35	42.11	50.55	50.55	68.20	17.65

802.11n20_U-NII-3_middle channel

Frequency 5785 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
11570.00	46.45	PK	H	38.09	4.58	41.08	48.04	48.04	74.00	25.96
11570.00	36.28	AV	H	38.09	4.58	41.08	37.87	37.87	54.00	16.13
11570.00	46.54	PK	V	38.09	4.58	41.08	48.13	48.13	74.00	25.87
11570.00	36.34	AV	V	38.09	4.58	41.08	37.93	37.93	54.00	16.07
17355.00	47.45	PK	H	40.29	6.41	42.33	51.82	51.82	68.20	16.38
17355.00	47.24	PK	V	40.29	6.41	42.33	51.61	51.61	68.20	16.59

802.11n20_U-NII-3_high channel

Frequency 5825 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5850.00	32.30	PK	H	34.12	1.88	0.00	68.30	62.3	122.20	59.90
5855.00	31.05	PK	H	34.13	1.88	0.00	67.06	61.06	110.80	49.74
5875.00	30.73	PK	H	34.15	1.89	0.00	66.77	60.77	105.20	44.43
5925.00	30.88	PK	H	34.21	1.91	0.00	67.00	61	68.20	7.20
5850.00	31.92	PK	V	34.12	1.88	0.00	67.92	61.92	122.20	60.28
5855.00	31.25	PK	V	34.13	1.88	0.00	67.26	61.26	110.80	49.54
5875.00	30.47	PK	V	34.15	1.89	0.00	66.51	60.51	105.20	44.69
5925.00	30.93	PK	V	34.21	1.91	0.00	67.05	61.05	68.20	7.15
11650.00	46.61	PK	H	38.07	4.60	41.08	48.20	48.2	74.00	25.80
11650.00	36.49	AV	H	38.07	4.60	41.08	38.08	38.08	54.00	15.92
11650.00	46.70	PK	V	38.07	4.60	41.08	48.29	48.29	74.00	25.71
11650.00	36.56	AV	V	38.07	4.60	41.08	38.15	38.15	54.00	15.85
17475.00	47.35	PK	H	40.63	6.48	42.55	51.91	51.91	68.20	16.29
17475.00	47.48	PK	V	40.63	6.48	42.55	52.04	52.04	68.20	16.16

802.11n40_U-NII-3_low channel

Frequency 5755 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5725.00	30.57	PK	H	33.97	1.84	0.00	66.38	60.38	122.20	61.82
5720.00	30.45	PK	H	33.96	1.84	0.00	66.25	60.25	110.80	50.55
5700.00	29.63	PK	H	33.94	1.83	0.00	65.40	59.4	105.20	45.80
5650.00	29.49	PK	H	33.88	1.81	0.00	65.18	59.18	68.20	9.02
5725.00	30.62	PK	V	33.97	1.84	0.00	66.43	60.43	122.20	61.77
5720.00	30.06	PK	V	33.96	1.84	0.00	65.86	59.86	110.80	50.94
5700.00	30.96	PK	V	33.94	1.83	0.00	66.73	60.73	105.20	44.47
5650.00	29.82	PK	V	33.88	1.81	0.00	65.51	59.51	68.20	8.69
11510.00	47.19	PK	H	38.10	4.56	41.09	48.76	48.76	74.00	25.24
11510.00	37.41	AV	H	38.10	4.56	41.09	38.98	38.98	54.00	15.02
11510.00	47.28	PK	V	38.10	4.56	41.09	48.85	48.85	74.00	25.15
11510.00	37.59	AV	V	38.10	4.56	41.09	39.16	39.16	54.00	14.84
17265.00	47.29	PK	H	40.04	6.37	42.17	51.53	51.53	68.20	16.67
17265.00	47.42	PK	V	40.04	6.37	42.17	51.66	51.66	68.20	16.54

802.11n40_U-NII-3_high channel

Frequency 5795 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5850.00	31.17	PK	H	34.12	1.88	0.00	67.17	61.17	122.20	61.03
5855.00	30.91	PK	H	34.13	1.88	0.00	66.92	60.92	110.80	49.88
5875.00	31.72	PK	H	34.15	1.89	0.00	67.76	61.76	105.20	43.44
5925.00	30.95	PK	H	34.21	1.91	0.00	67.07	61.07	68.20	7.13
5850.00	31.23	PK	V	34.12	1.88	0.00	67.23	61.23	122.20	60.97
5855.00	30.63	PK	V	34.13	1.88	0.00	66.64	60.64	110.80	50.16
5875.00	31.03	PK	V	34.15	1.89	0.00	67.07	61.07	105.20	44.13
5925.00	31.64	PK	V	34.21	1.91	0.00	67.76	61.76	68.20	6.44
11590.00	47.56	PK	H	38.08	4.58	41.08	49.14	49.14	74.00	24.86
11590.00	37.26	AV	H	38.08	4.58	41.08	38.84	38.84	54.00	15.16
11590.00	47.70	PK	V	38.08	4.58	41.08	49.28	49.28	74.00	24.72
11590.00	37.38	AV	V	38.08	4.58	41.08	38.96	38.96	54.00	15.04
17385.00	47.18	PK	H	40.38	6.43	42.39	51.60	51.6	68.20	16.60
17385.00	47.23	PK	V	40.38	6.43	42.39	51.65	51.65	68.20	16.55

802.11ac80_U-NII-3_middle channel

Frequency 5775 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5725.00	34.44	PK	H	33.97	1.84	0.00	70.25	64.25	122.20	57.95
5720.00	32.20	PK	H	33.96	1.84	0.00	68.00	62	110.80	48.80
5700.00	31.27	PK	H	33.94	1.83	0.00	67.04	61.04	105.20	44.16
5650.00	30.31	PK	H	33.88	1.81	0.00	66.00	60	68.20	8.20
5850.00	31.52	PK	H	34.12	1.88	0.00	67.52	61.52	122.20	60.68
5855.00	30.88	PK	H	34.13	1.88	0.00	66.89	60.89	110.80	49.91
5875.00	30.90	PK	H	34.15	1.89	0.00	66.94	60.94	105.20	44.26
5925.00	30.65	PK	H	34.21	1.91	0.00	66.77	60.77	68.20	7.43
5725.00	31.48	PK	V	33.97	1.84	0.00	67.29	61.29	122.20	60.91
5720.00	31.01	PK	V	33.96	1.84	0.00	66.81	60.81	110.80	49.99
5700.00	30.01	PK	V	33.94	1.83	0.00	65.78	59.78	105.20	45.42
5650.00	30.45	PK	V	33.88	1.81	0.00	66.14	60.14	68.20	8.06
5850.00	32.20	PK	V	34.12	1.88	0.00	68.20	62.2	122.20	60.00
5855.00	31.05	PK	V	34.13	1.88	0.00	67.06	61.06	110.80	49.74
5875.00	31.30	PK	V	34.15	1.89	0.00	67.34	61.34	105.20	43.86
5925.00	31.04	PK	V	34.21	1.91	0.00	67.16	61.16	68.20	7.04
11550.00	46.34	PK	H	38.09	4.57	41.09	47.91	47.91	74.00	26.09
11550.00	36.11	AV	H	38.09	4.57	41.09	37.68	37.68	54.00	16.32
11550.00	46.26	PK	V	38.09	4.57	41.09	47.83	47.83	74.00	26.17
11550.00	36.15	AV	V	38.09	4.57	41.09	37.72	37.72	54.00	16.28
17325.00	48.37	PK	H	40.21	6.40	42.28	52.70	52.7	68.20	15.50
17325.00	48.77	PK	V	40.21	6.40	42.28	53.10	53.1	68.20	15.10

M20SE:**802.11a_U-NII-1_low channel****Frequency 5180 MHz**

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5150.00	28.60	PK	H	33.21	1.55	0.00	63.36	57.36	74.00	16.64
5150.00	18.45	AV	H	33.21	1.55	0.00	53.21	47.21	54.00	6.79
5150.00	29.62	PK	V	33.21	1.55	0.00	64.38	58.38	74.00	15.62
5150.00	19.22	AV	V	33.21	1.55	0.00	53.98	47.98	54.00	6.02
10360.00	46.45	PK	H	38.27	3.99	41.93	46.78	46.78	68.20	21.42
10360.00	46.30	PK	V	38.27	3.99	41.93	46.63	46.63	68.20	21.57
15540.00	46.13	PK	H	37.64	5.83	42.87	46.73	46.73	74.00	27.27
15540.00	36.21	AV	H	37.64	5.83	42.87	36.81	36.81	54.00	17.19
15540.00	46.00	PK	V	37.64	5.83	42.87	46.60	46.6	74.00	27.40
15540.00	36.25	AV	V	37.64	5.83	42.87	36.85	36.85	54.00	17.15
6906.60	59.10	PK	H	35.35	2.23	44.15	52.53	52.53	68.20	15.67
6906.60	60.63	PK	V	35.35	2.23	44.15	54.06	54.06	68.20	14.14

802.11a_U-NII-1_middle channel**Frequency 5200 MHz**

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
10400.00	46.58	PK	H	38.28	4.00	41.88	46.98	46.98	68.20	21.22
10400.00	46.47	PK	V	38.28	4.00	41.88	46.87	46.87	68.20	21.33
15600.00	46.44	PK	H	37.54	5.85	42.81	47.02	47.02	74.00	26.98
15600.00	36.37	AV	H	37.54	5.85	42.81	36.95	36.95	54.00	17.05
15600.00	46.52	PK	V	37.54	5.85	42.81	47.10	47.1	74.00	26.90
15600.00	36.46	AV	V	37.54	5.85	42.81	37.04	37.04	54.00	16.96

802.11a_U-NII-1_high channel**Frequency 5240 MHz**

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5350.00	28.37	PK	H	33.49	1.66	0.00	63.52	57.52	74.00	16.48
5350.00	18.52	AV	H	33.49	1.66	0.00	53.67	47.67	54.00	6.33
5350.00	28.64	PK	V	33.49	1.66	0.00	63.79	57.79	74.00	16.21
5350.00	18.77	AV	V	33.49	1.66	0.00	53.92	47.92	54.00	6.08
10480.00	46.50	PK	H	38.30	4.04	41.78	47.06	47.06	68.20	21.14
10480.00	46.63	PK	V	38.30	4.04	41.78	47.19	47.19	68.20	21.01
15720.00	46.21	PK	H	37.35	5.89	42.69	46.76	46.76	74.00	27.24
15720.00	36.24	AV	H	37.35	5.89	42.69	36.79	36.79	54.00	17.21
15720.00	46.34	PK	V	37.35	5.89	42.69	46.89	46.89	74.00	27.11
15720.00	36.28	AV	V	37.35	5.89	42.69	36.83	36.83	54.00	17.17

802.11n20_U-NII-1_low channel

Frequency 5180 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain		Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5150.00	29.42	PK	H	33.21	1.55	0.00	64.18	58.18	74.00	15.82
5150.00	19.37	AV	H	33.21	1.55	0.00	54.13	48.13	54.00	5.87
5150.00	30.38	PK	V	33.21	1.55	0.00	65.14	59.14	74.00	14.86
5150.00	19.88	AV	V	33.21	1.55	0.00	54.64	48.64	54.00	5.36
10360.00	46.24	PK	H	38.27	3.99	41.93	46.57	46.57	68.20	21.63
10360.00	46.76	PK	V	38.27	3.99	41.93	47.09	47.09	68.20	21.11
15540.00	46.23	PK	H	37.64	5.83	42.87	46.83	46.83	74.00	27.17
15540.00	36.11	AV	H	37.64	5.83	42.87	36.71	36.71	54.00	17.29
15540.00	46.25	PK	V	37.64	5.83	42.87	46.85	46.85	74.00	27.15
15540.00	36.19	AV	V	37.64	5.83	42.87	36.79	36.79	54.00	17.21

802.11n20_U-NII-1_middle channel

Frequency 5200 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
10400.00	46.56	PK	H	38.28	4.00	41.88	46.96	46.96	68.20	21.24
10400.00	46.44	PK	V	38.28	4.00	41.88	46.84	46.84	68.20	21.36
15600.00	46.37	PK	H	37.54	5.85	42.81	46.95	46.95	74.00	27.05
15600.00	36.28	AV	H	37.54	5.85	42.81	36.86	36.86	54.00	17.14
15600.00	46.41	PK	V	37.54	5.85	42.81	46.99	46.99	74.00	27.01
15600.00	36.15	AV	V	37.54	5.85	42.81	36.73	36.73	54.00	17.27

802.11n20_U-NII-1_high channel

Frequency 5240 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5350.00	28.67	PK	H	33.49	1.66	0.00	63.82	57.82	74.00	16.18
5350.00	18.72	AV	H	33.49	1.66	0.00	53.87	47.87	54.00	6.13
5350.00	28.13	PK	V	33.49	1.66	0.00	63.28	57.28	74.00	16.72
5350.00	18.32	AV	V	33.49	1.66	0.00	53.47	47.47	54.00	6.53
10480.00	46.94	PK	H	38.30	4.04	41.78	47.50	47.5	68.20	20.70
10480.00	46.47	PK	V	38.30	4.04	41.78	47.03	47.03	68.20	21.17
15720.00	46.39	PK	H	37.35	5.89	42.69	46.94	46.94	74.00	27.06
15720.00	36.36	AV	H	37.35	5.89	42.69	36.91	36.91	54.00	17.09
15720.00	46.28	PK	V	37.35	5.89	42.69	46.83	46.83	74.00	27.17
15720.00	36.14	AV	V	37.35	5.89	42.69	36.69	36.69	54.00	17.31

802.11n40_U-NII-1_low channel

Frequency 5190 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5150.00	30.83	PK	H	33.21	1.55	0.00	65.59	59.59	74.00	14.41
5150.00	20.28	AV	H	33.21	1.55	0.00	55.04	49.04	54.00	4.96
5150.00	31.12	PK	V	33.21	1.55	0.00	65.88	59.88	74.00	14.12
5150.00	21.06	AV	V	33.21	1.55	0.00	55.82	49.82	54.00	4.18
10380.00	46.67	PK	H	38.28	3.99	41.90	47.04	47.04	68.20	21.16
10380.00	46.76	PK	V	38.28	3.99	41.90	47.13	47.13	68.20	21.07
15570.00	46.66	PK	H	37.59	5.84	42.84	47.25	47.25	74.00	26.75
15570.00	36.58	AV	H	37.59	5.84	42.84	37.17	37.17	54.00	16.83
15570.00	46.62	PK	V	37.59	5.84	42.84	47.21	47.21	74.00	26.79
15570.00	36.49	AV	V	37.59	5.84	42.84	37.08	37.08	54.00	16.92

802.11n40_U-NII-1_high channel

Frequency 5230 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5350.00	28.42	PK	H	33.49	1.66	0.00	63.57	57.57	74.00	16.43
5350.00	18.53	AV	H	33.49	1.66	0.00	53.68	47.68	54.00	6.32
5350.00	28.64	PK	V	33.49	1.66	0.00	63.79	57.79	74.00	16.21
5350.00	18.71	AV	V	33.49	1.66	0.00	53.86	47.86	54.00	6.14
10460.00	46.23	PK	H	38.29	4.03	41.81	46.74	46.74	68.20	21.46
10460.00	46.44	PK	V	38.29	4.03	41.81	46.95	46.95	68.20	21.25
15690.00	46.77	PK	H	37.40	5.88	42.72	47.33	47.33	74.00	26.67
15690.00	36.58	AV	H	37.40	5.88	42.72	37.14	37.14	54.00	16.86
15690.00	46.59	PK	V	37.40	5.88	42.72	47.15	47.15	74.00	26.85
15690.00	36.42	AV	V	37.40	5.88	42.72	36.98	36.98	54.00	17.02

802.11ac80_U-NII-1_middle channel

Frequency 5210 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5150.00	29.56	PK	H	33.21	1.55	0.00	64.32	58.32	74.00	15.68
5150.00	19.60	AV	H	33.21	1.55	0.00	54.36	48.36	54.00	5.64
5150.00	29.24	PK	V	33.21	1.55	0.00	64.00	58	74.00	16.00
5150.00	19.15	AV	V	33.21	1.55	0.00	53.91	47.91	54.00	6.09
5350.00	29.61	PK	H	33.49	1.66	0.00	64.76	58.76	74.00	15.24
5350.00	18.45	AV	H	33.49	1.66	0.00	53.60	47.6	54.00	6.40
5350.00	28.91	PK	V	33.49	1.66	0.00	64.06	58.06	74.00	15.94
5350.00	18.32	AV	V	33.49	1.66	0.00	53.47	47.47	54.00	6.53
10420.00	46.56	PK	H	38.28	4.01	41.86	46.99	46.99	68.20	21.21
10420.00	46.34	PK	V	38.28	4.01	41.86	46.77	46.77	68.20	21.43
15630.00	47.05	PK	H	37.49	5.86	42.78	47.62	47.62	74.00	26.38
15630.00	36.42	AV	H	37.49	5.86	42.78	36.99	36.99	54.00	17.01
15630.00	46.93	PK	V	37.49	5.86	42.78	47.50	47.5	74.00	26.50
15630.00	36.33	AV	V	37.49	5.86	42.78	36.90	36.9	54.00	17.10

802.11a_U-NII-2A_low channel

Frequency 5260 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5150.00	29.42	PK	H	33.21	1.55	0.00	64.18	58.18	74.00	15.82
5150.00	18.60	AV	H	33.21	1.55	0.00	53.36	47.36	54.00	6.64
5150.00	30.05	PK	V	33.21	1.55	0.00	64.81	58.81	74.00	15.19
5150.00	19.02	AV	V	33.21	1.55	0.00	53.78	47.78	54.00	6.22
10520.00	46.92	PK	H	38.29	4.06	41.75	47.52	47.52	68.20	20.68
10520.00	46.22	PK	V	38.29	4.06	41.75	46.82	46.82	68.20	21.38
15780.00	47.13	PK	H	37.25	5.92	42.62	47.68	47.68	74.00	26.32
15780.00	36.88	AV	H	37.25	5.92	42.62	37.43	37.43	54.00	16.57
15780.00	47.56	PK	V	37.25	5.92	42.62	48.11	48.11	74.00	25.89
15780.00	37.37	AV	V	37.25	5.92	42.62	37.92	37.92	54.00	16.08

802.11a_U-NII-2A_middle channel

Frequency 5280 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
10560.00	46.51	PK	H	38.28	4.07	41.74	47.12	47.12	68.20	21.08
10560.00	46.28	PK	V	38.28	4.07	41.74	46.89	46.89	68.20	21.31
15840.00	47.25	PK	H	37.16	5.94	42.56	47.79	47.79	74.00	26.21
15840.00	36.89	AV	H	37.16	5.94	42.56	37.43	37.43	54.00	16.57
15840.00	47.24	PK	V	37.16	5.94	42.56	47.78	47.78	74.00	26.22
15840.00	37.11	AV	V	37.16	5.94	42.56	37.65	37.65	54.00	16.35

802.11a_U-NII-2A_high channel

Frequency 5320 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5350.00	28.56	PK	H	33.49	1.66	0.00	63.71	57.71	74.00	16.29
5350.00	18.66	AV	H	33.49	1.66	0.00	53.81	47.81	54.00	6.19
5350.00	28.67	PK	V	33.49	1.66	0.00	63.82	57.82	74.00	16.18
5350.00	18.61	AV	V	33.49	1.66	0.00	53.76	47.76	54.00	6.24
10640.00	46.74	PK	H	38.24	4.10	41.72	47.36	47.36	74.00	26.64
10640.00	36.67	AV	H	38.24	4.10	41.72	37.29	37.29	54.00	16.71
10640.00	47.65	PK	V	38.24	4.10	41.72	48.27	48.27	74.00	25.73
10640.00	37.38	AV	V	38.24	4.10	41.72	38.00	38	54.00	16.00
15960.00	46.80	PK	H	36.96	5.98	42.44	47.30	47.3	74.00	26.70
15960.00	36.48	AV	H	36.96	5.98	42.44	36.98	36.98	54.00	17.02
15960.00	46.65	PK	V	36.96	5.98	42.44	47.15	47.15	74.00	26.85
15960.00	36.56	AV	V	36.96	5.98	42.44	37.06	37.06	54.00	16.94

802.11n20_U-NII-2A_low channel

Frequency 5260 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5150.00	29.42	PK	H	33.21	1.55	0.00	64.18	58.18	74.00	15.82
5150.00	18.78	AV	H	33.21	1.55	0.00	53.54	47.54	54.00	6.46
5150.00	29.67	PK	V	33.21	1.55	0.00	64.43	58.43	74.00	15.57
5150.00	18.89	AV	V	33.21	1.55	0.00	53.65	47.65	54.00	6.35
10520.00	47.73	PK	H	38.29	4.06	41.75	48.33	48.33	68.20	19.87
10520.00	46.77	PK	V	38.29	4.06	41.75	47.37	47.37	68.20	20.83
15780.00	46.49	PK	H	37.25	5.92	42.62	47.04	47.04	74.00	26.96
15780.00	36.38	AV	H	37.25	5.92	42.62	36.93	36.93	54.00	17.07
15780.00	46.38	PK	V	37.25	5.92	42.62	46.93	46.93	74.00	27.07
15780.00	36.22	AV	V	37.25	5.92	42.62	36.77	36.77	54.00	17.23
7013.30	60.79	PK	V	35.53	2.28	44.14	54.46	54.46	68.20	13.74
7013.30	59.44	PK	H	35.53	2.28	44.14	53.11	53.11	68.20	15.09

802.11n20_U-NII-2A_middle channel

Frequency 5280 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
10560.00	46.75	PK	H	38.28	4.07	41.74	47.36	47.36	68.20	20.84
10560.00	46.88	PK	V	38.28	4.07	41.74	47.49	47.49	68.20	20.71
15840.00	46.78	PK	H	37.16	5.94	42.56	47.32	47.32	74.00	26.68
15840.00	36.33	AV	H	37.16	5.94	42.56	36.87	36.87	54.00	17.13
15840.00	46.89	PK	V	37.16	5.94	42.56	47.43	47.43	74.00	26.57
15840.00	36.45	AV	V	37.16	5.94	42.56	36.99	36.99	54.00	17.01

802.11n20_U-NII-2A_high channel

Frequency 5320 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5350.00	28.41	PK	H	33.49	1.66	0.00	63.56	57.56	74.00	16.44
5350.00	18.29	AV	H	33.49	1.66	0.00	53.44	47.44	54.00	6.56
5350.00	29.45	PK	V	33.49	1.66	0.00	64.60	58.6	74.00	15.40
5350.00	19.11	AV	V	33.49	1.66	0.00	54.26	48.26	54.00	5.74
10640.00	46.69	PK	H	38.24	4.10	41.72	47.31	47.31	74.00	26.69
10640.00	36.51	AV	H	38.24	4.10	41.72	37.13	37.13	54.00	16.87
10640.00	46.58	PK	V	38.24	4.10	41.72	47.20	47.2	74.00	26.80
10640.00	36.44	AV	V	38.24	4.10	41.72	37.06	37.06	54.00	16.94
15960.00	46.85	PK	H	36.96	5.98	42.44	47.35	47.35	74.00	26.65
15960.00	36.64	AV	H	36.96	5.98	42.44	37.14	37.14	54.00	16.86
15960.00	46.78	PK	V	36.96	5.98	42.44	47.28	47.28	74.00	26.72
15960.00	36.56	AV	V	36.96	5.98	42.44	37.06	37.06	54.00	16.94

802.11n40_U-NII-2A_low channel

Frequency 5270 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5150.00	28.76	PK	H	33.21	1.55	0.00	63.52	57.52	74.00	16.48
5150.00	18.47	AV	H	33.21	1.55	0.00	53.23	47.23	54.00	6.77
5150.00	28.65	PK	V	33.21	1.55	0.00	63.41	57.41	74.00	16.59
5150.00	18.52	AV	V	33.21	1.55	0.00	53.28	47.28	54.00	6.72
10540.00	46.34	PK	H	38.28	4.06	41.75	46.93	46.93	68.20	21.27
10540.00	46.09	PK	V	38.28	4.06	41.75	46.68	46.68	68.20	21.52
15810.00	46.38	PK	H	37.20	5.93	42.59	46.92	46.92	74.00	27.08
15810.00	36.45	AV	H	37.20	5.93	42.59	36.99	36.99	54.00	17.01
15810.00	46.70	PK	V	37.20	5.93	42.59	47.24	47.24	74.00	26.76
15810.00	36.66	AV	V	37.20	5.93	42.59	37.20	37.2	54.00	16.80

802.11n40_U-NII-2A_high channel

Frequency 5310 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5350.00	29.30	PK	H	33.49	1.66	0.00	64.45	58.45	74.00	15.55
5350.00	19.50	AV	H	33.49	1.66	0.00	54.65	48.65	54.00	5.35
5350.00	29.09	PK	V	33.49	1.66	0.00	64.24	58.24	74.00	15.76
5350.00	18.84	AV	V	33.49	1.66	0.00	53.99	47.99	54.00	6.01
10620.00	46.41	PK	H	38.25	4.09	41.72	47.03	47.03	74.00	26.97
10620.00	36.46	AV	H	38.25	4.09	41.72	37.08	37.08	54.00	16.92
10620.00	46.76	PK	V	38.25	4.09	41.72	47.38	47.38	74.00	26.62
10620.00	36.67	AV	V	38.25	4.09	41.72	37.29	37.29	54.00	16.71
15930.00	45.91	PK	H	37.01	5.97	42.47	46.42	46.42	74.00	27.58
15930.00	35.88	AV	H	37.01	5.97	42.47	36.39	36.39	54.00	17.61
15930.00	46.17	PK	V	37.01	5.97	42.47	46.68	46.68	74.00	27.32
15930.00	36.56	AV	V	37.01	5.97	42.47	37.07	37.07	54.00	16.93

802.11ac80_U-NII-2A_middle channel

Frequency 5290 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dB μ V	PK/QP/AV	H/V	dB/m	dB	dB	dB μ V/m	dB μ V/m	dB μ V/m	dB
5150.00	29.11	PK	H	33.21	1.55	0.00	63.87	57.87	74.00	16.13
5150.00	18.87	AV	H	33.21	1.55	0.00	53.63	47.63	54.00	6.37
5150.00	29.64	PK	V	33.21	1.55	0.00	64.40	58.4	74.00	15.60
5150.00	18.89	AV	V	33.21	1.55	0.00	53.65	47.65	54.00	6.35
5350.00	32.91	PK	H	33.49	1.66	0.00	68.06	62.06	74.00	11.94
5350.00	21.47	AV	H	33.49	1.66	0.00	56.62	50.62	54.00	3.38
5350.00	33.60	PK	V	33.49	1.66	0.00	68.75	62.75	74.00	11.25
5350.00	23.69	AV	V	33.49	1.66	0.00	58.84	52.84	54.00	1.16
10580.00	46.24	PK	H	38.27	4.08	41.74	46.85	46.85	68.20	21.35
10580.00	46.38	PK	V	38.27	4.08	41.74	46.99	46.99	68.20	21.21
15870.00	45.97	PK	H	37.11	5.95	42.53	46.50	46.5	74.00	27.50
15870.00	35.89	AV	H	37.11	5.95	42.53	36.42	36.42	54.00	17.58
15870.00	46.52	PK	V	37.11	5.95	42.53	47.05	47.05	74.00	26.95
15870.00	36.43	AV	V	37.11	5.95	42.53	36.96	36.96	54.00	17.04

802.11a_U-NII-2C_low channel

Frequency 5500 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5470.00	30.38	PK	H	33.66	1.70	0.00	65.74	59.74	68.20	8.46
5470.00	30.49	PK	V	33.66	1.70	0.00	65.85	59.85	68.20	8.35
11000.00	45.35	PK	H	38.10	4.23	41.61	46.07	46.07	74.00	27.93
11000.00	35.90	AV	H	38.10	4.23	41.61	36.62	36.62	54.00	17.38
11000.00	46.27	PK	V	38.10	4.23	41.61	46.99	46.99	74.00	27.01
11000.00	36.81	AV	V	38.10	4.23	41.61	37.53	37.53	54.00	16.47
16500.00	46.55	PK	H	37.60	6.14	42.64	47.65	47.65	68.20	20.55
16500.00	46.35	PK	V	37.60	6.14	42.64	47.45	47.45	68.20	20.75

802.11a_U-NII-2C_middle channel

Frequency 5580 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
11160.00	45.38	PK	H	38.10	4.34	41.44	46.38	46.38	74.00	27.62
11160.00	35.73	AV	H	38.10	4.34	41.44	36.73	36.73	54.00	17.27
11160.00	45.62	PK	V	38.10	4.34	41.44	46.62	46.62	74.00	27.38
11160.00	35.78	AV	V	38.10	4.34	41.44	36.78	36.78	54.00	17.22
16740.00	45.32	PK	H	38.42	6.18	42.18	47.74	47.74	68.20	20.46
16740.00	45.26	PK	V	38.42	6.18	42.18	47.68	47.68	68.20	20.52

802.11a_U-NII-2C_high channel

Frequency 5700 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5725.00	30.23	PK	H	33.97	1.84	0.00	66.04	60.04	68.20	8.16
5725.00	29.67	PK	V	33.97	1.84	0.00	65.48	59.48	68.20	8.72
11400.00	45.43	PK	H	38.10	4.49	41.19	46.83	46.83	74.00	27.17
11400.00	35.16	AV	H	38.10	4.49	41.19	36.56	36.56	54.00	17.44
11400.00	45.99	PK	V	38.10	4.49	41.19	47.39	47.39	74.00	26.61
11400.00	35.41	AV	V	38.10	4.49	41.19	36.81	36.81	54.00	17.19
17100.00	45.16	PK	H	39.58	6.28	41.86	49.16	49.16	68.20	19.04
17100.00	45.17	PK	V	39.58	6.28	41.86	49.17	49.17	68.20	19.03
7598.40	54.80	PK	H	36.74	2.59	43.53	50.60	50.6	74.00	23.40
7598.40	53.38	AV	H	36.74	2.59	43.53	49.18	49.18	54.00	4.82
7598.40	56.22	PK	V	36.74	2.59	43.53	52.02	52.02	74.00	21.98
7598.40	52.95	AV	V	36.74	2.59	43.53	48.75	48.75	54.00	5.25

802.11n20_U-NII-2C_low channel

Frequency 5500 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5470.00	30.37	PK	H	33.66	1.70	0.00	65.73	59.73	68.20	8.47
5470.00	31.75	PK	V	33.66	1.70	0.00	67.11	61.11	68.20	7.09
11000.00	45.93	PK	H	38.10	4.23	41.61	46.65	46.65	74.00	27.35
11000.00	35.54	AV	H	38.10	4.23	41.61	36.26	36.26	54.00	17.74
11000.00	45.89	PK	V	38.10	4.23	41.61	46.61	46.61	74.00	27.39
11000.00	35.73	AV	V	38.10	4.23	41.61	36.45	36.45	54.00	17.55
16500.00	45.76	PK	H	37.60	6.14	42.64	46.86	46.86	68.20	21.34
16500.00	46.17	PK	V	37.60	6.14	42.64	47.27	47.27	68.20	20.93

802.11n20_U-NII-2C_middle channel

Frequency 5580 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
11160.00	45.37	PK	H	38.10	4.34	41.44	46.37	46.37	74.00	27.63
11160.00	35.33	AV	H	38.10	4.34	41.44	36.33	36.33	54.00	17.67
11160.00	45.62	PK	V	38.10	4.34	41.44	46.62	46.62	74.00	27.38
11160.00	35.32	AV	V	38.10	4.34	41.44	36.32	36.32	54.00	17.68
16740.00	45.88	PK	H	38.42	6.18	42.18	48.30	48.3	68.20	19.90
16740.00	45.36	PK	V	38.42	6.18	42.18	47.78	47.78	68.20	20.42

802.11n20_U-NII-2C_high channel

Frequency 5700 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5725.00	31.64	PK	H	33.97	1.84	0.00	67.45	61.45	68.20	6.75
5725.00	31.77	PK	V	33.97	1.84	0.00	67.58	61.58	68.20	6.62
11400.00	45.84	PK	H	38.10	4.49	41.19	47.24	47.24	74.00	26.76
11400.00	35.76	AV	H	38.10	4.49	41.19	37.16	37.16	54.00	16.84
11400.00	45.91	PK	V	38.10	4.49	41.19	47.31	47.31	74.00	26.69
11400.00	35.49	AV	V	38.10	4.49	41.19	36.89	36.89	54.00	17.11
17100.00	45.26	PK	H	39.58	6.28	41.86	49.26	49.26	68.20	18.94
17100.00	45.13	PK	V	39.58	6.28	41.86	49.13	49.13	68.20	19.07

802.11n40_U-NII-2C_low channel

Frequency 5510 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5470.00	32.99	PK	H	33.66	1.70	0.00	68.35	62.35	68.20	5.85
5470.00	34.21	PK	V	33.66	1.70	0.00	69.57	63.57	68.20	4.63
11020.00	46.67	PK	H	38.10	4.24	41.59	47.42	47.42	74.00	26.58
11020.00	36.85	AV	H	38.10	4.24	41.59	37.60	37.6	54.00	16.40
11020.00	45.90	PK	V	38.10	4.24	41.59	46.65	46.65	74.00	27.35
11020.00	35.43	AV	V	38.10	4.24	41.59	36.18	36.18	54.00	17.82
16530.00	45.68	PK	H	37.70	6.15	42.58	46.95	46.95	68.20	21.25
16530.00	47.15	PK	V	37.70	6.15	42.58	48.42	48.42	68.20	19.78

802.11n40_U-NII-2C_middle channel

Frequency 5550 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
11100.00	45.27	PK	H	38.10	4.30	41.51	46.16	46.16	74.00	27.84
11100.00	35.58	AV	H	38.10	4.30	41.51	36.47	36.47	54.00	17.53
11100.00	45.85	PK	V	38.10	4.30	41.51	46.74	46.74	74.00	27.26
11100.00	35.36	AV	V	38.10	4.30	41.51	36.25	36.25	54.00	17.75
16650.00	44.27	PK	H	38.11	6.17	42.35	46.20	46.2	68.20	22.00
16650.00	45.50	PK	V	38.11	6.17	42.35	47.43	47.43	68.20	20.77

802.11n40_U-NII-2C_high channel

Frequency 5670 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5725.00	30.43	PK	H	33.97	1.84	0.00	66.24	60.24	68.20	7.96
5725.00	30.62	PK	V	33.97	1.84	0.00	66.43	60.43	68.20	7.77
11340.00	45.09	PK	H	38.10	4.45	41.26	46.38	46.38	74.00	27.62
11340.00	35.23	AV	H	38.10	4.45	41.26	36.52	36.52	54.00	17.48
11340.00	45.38	PK	V	38.10	4.45	41.26	46.67	46.67	74.00	27.33
11340.00	35.43	AV	V	38.10	4.45	41.26	36.72	36.72	54.00	17.28
17010.00	44.94	PK	H	39.33	6.24	41.70	48.81	48.81	68.20	19.39
17010.00	44.84	PK	V	39.33	6.24	41.70	48.71	48.71	68.20	19.49

802.11ac80_U-NII-2C_low channel

Frequency 5530 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5470.00	33.60	PK	H	33.66	1.70	0.00	68.96	62.96	68.20	5.24
5470.00	36.66	PK	V	33.66	1.70	0.00	72.02	66.02	68.20	2.18
11060.00	45.34	PK	H	38.10	4.27	41.55	46.16	46.16	74.00	27.84
11060.00	35.49	AV	H	38.10	4.27	41.55	36.31	36.31	54.00	17.69
11060.00	45.86	PK	V	38.10	4.27	41.55	46.68	46.68	74.00	27.32
11060.00	35.29	AV	V	38.10	4.27	41.55	36.11	36.11	54.00	17.89
16590.00	45.38	PK	H	37.91	6.16	42.47	46.98	46.98	68.20	21.22
16590.00	45.92	PK	V	37.91	6.16	42.47	47.52	47.52	68.20	20.68

802.11ac80_U-NII-2C_high channel

Frequency 5610 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5725.00	30.85	PK	H	33.97	1.84	0.00	66.66	60.66	68.20	7.54
5725.00	30.59	PK	V	33.97	1.84	0.00	66.40	60.4	68.20	7.80
11220.00	45.91	PK	H	38.10	4.38	41.38	47.01	47.01	74.00	26.99
11220.00	35.91	AV	H	38.10	4.38	41.38	37.01	37.01	54.00	16.99
11220.00	45.09	PK	V	38.10	4.38	41.38	46.19	46.19	74.00	27.81
11220.00	35.38	AV	V	38.10	4.38	41.38	36.48	36.48	54.00	17.52
16830.00	46.16	PK	H	38.72	6.20	42.01	49.07	49.07	68.20	19.13
16830.00	45.42	PK	V	38.72	6.20	42.01	48.33	48.33	68.20	19.87

802.11a_U-NII-3_low channel

Frequency 5745 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5725.00	31.86	PK	H	33.97	1.84	0.00	67.67	61.67	122.20	60.53
5720.00	30.30	PK	H	33.96	1.84	0.00	66.10	60.1	110.80	50.70
5700.00	30.57	PK	H	33.94	1.83	0.00	66.34	60.34	105.20	44.86
5650.00	29.78	PK	H	33.88	1.81	0.00	65.47	59.47	68.20	8.73
5725.00	31.57	PK	V	33.97	1.84	0.00	67.38	61.38	122.20	60.82
5720.00	30.23	PK	V	33.96	1.84	0.00	66.03	60.03	110.80	50.77
5700.00	30.27	PK	V	33.94	1.83	0.00	66.04	60.04	105.20	45.16
5650.00	29.76	PK	V	33.88	1.81	0.00	65.45	59.45	68.20	8.75
11490.00	46.85	PK	H	38.10	4.55	41.10	48.40	48.4	74.00	25.60
11490.00	36.70	AV	H	38.10	4.55	41.10	38.25	38.25	54.00	15.75
11490.00	46.67	PK	V	38.10	4.55	41.10	48.22	48.22	74.00	25.78
11490.00	36.58	AV	V	38.10	4.55	41.10	38.13	38.13	54.00	15.87
17235.00	45.78	PK	H	39.96	6.35	42.11	49.98	49.98	68.20	18.22
17235.00	45.72	PK	V	39.96	6.35	42.11	49.92	49.92	68.20	18.28
7660.00	54.59	PK	V	36.76	2.60	43.54	50.41	50.41	74.00	23.59
7660.00	50.38	AV	V	36.76	2.60	43.54	46.20	46.2	54.00	7.80

802.11a_U-NII-3_middle channel

Frequency 5785 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
11570.00	45.89	PK	H	38.09	4.58	41.08	47.48	47.48	74.00	26.52
11570.00	35.85	AV	H	38.09	4.58	41.08	37.44	37.44	54.00	16.56
11570.00	46.26	PK	V	38.09	4.58	41.08	47.85	47.85	74.00	26.15
11570.00	36.51	AV	V	38.09	4.58	41.08	38.10	38.1	54.00	15.90
17355.00	45.50	PK	H	40.29	6.41	42.33	49.87	49.87	68.20	18.33
17355.00	45.93	PK	V	40.29	6.41	42.33	50.30	50.3	68.20	17.90
7713.00	54.46	PK	V	36.79	2.61	43.55	50.31	50.31	74.00	23.69
7713.00	51.06	AV	V	36.79	2.61	43.55	46.91	46.91	54.00	7.09

802.11a_U-NII-3_high channel Frequency 5825 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5850.00	31.21	PK	H	34.12	1.88	0.00	67.21	61.21	122.20	60.99
5855.00	31.09	PK	H	34.13	1.88	0.00	67.10	61.1	110.80	49.70
5875.00	30.74	PK	H	34.15	1.89	0.00	66.78	60.78	105.20	44.42
5925.00	30.20	PK	H	34.21	1.91	0.00	66.32	60.32	68.20	7.88
5850.00	31.61	PK	V	34.12	1.88	0.00	67.61	61.61	122.20	60.59
5855.00	30.58	PK	V	34.13	1.88	0.00	66.59	60.59	110.80	50.21
5875.00	30.19	PK	V	34.15	1.89	0.00	66.23	60.23	105.20	44.97
5925.00	29.71	PK	V	34.21	1.91	0.00	65.83	59.83	68.20	8.37
11650.00	45.96	PK	H	38.07	4.60	41.08	47.55	47.55	74.00	26.45
11650.00	35.39	AV	H	38.07	4.60	41.08	36.98	36.98	54.00	17.02
11650.00	46.47	PK	V	38.07	4.60	41.08	48.06	48.06	74.00	25.94
11650.00	36.45	AV	V	38.07	4.60	41.08	38.04	38.04	54.00	15.96
17475.00	45.49	PK	H	40.63	6.48	42.55	50.05	50.05	68.20	18.15
17475.00	45.04	PK	V	40.63	6.48	42.55	49.60	49.6	68.20	18.60

802.11n20_U-NII-3_low channel Frequency 5745 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5725.00	31.16	PK	H	33.97	1.84	0.00	66.97	60.97	122.20	61.23
5720.00	30.50	PK	H	33.96	1.84	0.00	66.30	60.3	110.80	50.50
5700.00	30.25	PK	H	33.94	1.83	0.00	66.02	60.02	105.20	45.18
5650.00	29.51	PK	H	33.88	1.81	0.00	65.20	59.2	68.20	9.00
5725.00	31.80	PK	V	33.97	1.84	0.00	67.61	61.61	122.20	60.59
5720.00	30.42	PK	V	33.96	1.84	0.00	66.22	60.22	110.80	50.58
5700.00	29.98	PK	V	33.94	1.83	0.00	65.75	59.75	105.20	45.45
5650.00	30.55	PK	V	33.88	1.81	0.00	66.24	60.24	68.20	7.96
11490.00	46.76	PK	H	38.10	4.55	41.10	48.31	48.31	74.00	25.69
11490.00	36.66	AV	H	38.10	4.55	41.10	38.21	38.21	54.00	15.79
11490.00	46.20	PK	V	38.10	4.55	41.10	47.75	47.75	74.00	26.25
11490.00	36.95	AV	V	38.10	4.55	41.10	38.50	38.5	54.00	15.50
17235.00	46.25	PK	H	39.96	6.35	42.11	50.45	50.45	68.20	17.75
17235.00	45.05	PK	V	39.96	6.35	42.11	49.25	49.25	68.20	18.95

802.11n20_U-NII-3_middle channel

Frequency 5785 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
11570.00	46.90	PK	H	38.09	4.58	41.08	48.49	48.49	74.00	25.51
11570.00	36.55	AV	H	38.09	4.58	41.08	38.14	38.14	54.00	15.86
11570.00	46.56	PK	V	38.09	4.58	41.08	48.15	48.15	74.00	25.85
11570.00	36.65	AV	V	38.09	4.58	41.08	38.24	38.24	54.00	15.76
17355.00	45.87	PK	H	40.29	6.41	42.33	50.24	50.24	68.20	17.96
17355.00	45.62	PK	V	40.29	6.41	42.33	49.99	49.99	68.20	18.21

802.11n20_U-NII-3_high channel

Frequency 5825 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5850.00	31.29	PK	H	34.12	1.88	0.00	67.29	61.29	122.20	60.91
5855.00	30.92	PK	H	34.13	1.88	0.00	66.93	60.93	110.80	49.87
5875.00	30.17	PK	H	34.15	1.89	0.00	66.21	60.21	105.20	44.99
5925.00	30.75	PK	H	34.21	1.91	0.00	66.87	60.87	68.20	7.33
5850.00	30.93	PK	V	34.12	1.88	0.00	66.93	60.93	122.20	61.27
5855.00	30.32	PK	V	34.13	1.88	0.00	66.33	60.33	110.80	50.47
5875.00	30.42	PK	V	34.15	1.89	0.00	66.46	60.46	105.20	44.74
5925.00	30.14	PK	V	34.21	1.91	0.00	66.26	60.26	68.20	7.94
11650.00	46.79	PK	H	38.07	4.60	41.08	48.38	48.38	74.00	25.62
11650.00	36.61	AV	H	38.07	4.60	41.08	38.20	38.2	54.00	15.80
11650.00	46.71	PK	V	38.07	4.60	41.08	48.30	48.3	74.00	25.70
11650.00	36.87	AV	V	38.07	4.60	41.08	38.46	38.46	54.00	15.54
17475.00	46.53	PK	H	40.63	6.48	42.55	51.09	51.09	68.20	17.11
17475.00	45.81	PK	V	40.63	6.48	42.55	50.37	50.37	68.20	17.83

802.11n40_U-NII-3_low channel

Frequency 5755 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5725.00	31.31	PK	H	33.97	1.84	0.00	67.12	61.12	122.20	61.08
5720.00	30.61	PK	H	33.96	1.84	0.00	66.41	60.41	110.80	50.39
5700.00	30.03	PK	H	33.94	1.83	0.00	65.80	59.8	105.20	45.40
5650.00	29.34	PK	H	33.88	1.81	0.00	65.03	59.03	68.20	9.17
5725.00	30.41	PK	V	33.97	1.84	0.00	66.22	60.22	122.20	61.98
5720.00	30.57	PK	V	33.96	1.84	0.00	66.37	60.37	110.80	50.43
5700.00	30.30	PK	V	33.94	1.83	0.00	66.07	60.07	105.20	45.13
5650.00	30.22	PK	V	33.88	1.81	0.00	65.91	59.91	68.20	8.29
11510.00	45.80	PK	H	38.10	4.56	41.09	47.37	47.37	74.00	26.63
11510.00	35.32	AV	H	38.10	4.56	41.09	36.89	36.89	54.00	17.11
11510.00	45.18	PK	V	38.10	4.56	41.09	46.75	46.75	74.00	27.25
11510.00	35.15	AV	V	38.10	4.56	41.09	36.72	36.72	54.00	17.28
17265.00	46.22	PK	H	40.04	6.37	42.17	50.46	50.46	68.20	17.74
17265.00	46.84	PK	V	40.04	6.37	42.17	51.08	51.08	68.20	17.12

802.11n40_U-NII-3_high channel

Frequency 5795 MHz

Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5850.00	31.57	PK	H	34.12	1.88	0.00	67.57	61.57	122.20	60.63
5855.00	30.56	PK	H	34.13	1.88	0.00	66.57	60.57	110.80	50.23
5875.00	30.48	PK	H	34.15	1.89	0.00	66.52	60.52	105.20	44.68
5925.00	29.80	PK	H	34.21	1.91	0.00	65.92	59.92	68.20	8.28
5850.00	31.62	PK	V	34.12	1.88	0.00	67.62	61.62	122.20	60.58
5855.00	30.25	PK	V	34.13	1.88	0.00	66.26	60.26	110.80	50.54
5875.00	30.55	PK	V	34.15	1.89	0.00	66.59	60.59	105.20	44.61
5925.00	29.79	PK	V	34.21	1.91	0.00	65.91	59.91	68.20	8.29
11590.00	45.60	PK	H	38.08	4.58	41.08	47.18	47.18	74.00	26.82
11590.00	35.70	AV	H	38.08	4.58	41.08	37.28	37.28	54.00	16.72
11590.00	45.36	PK	V	38.08	4.58	41.08	46.94	46.94	74.00	27.06
11590.00	35.26	AV	V	38.08	4.58	41.08	36.84	36.84	54.00	17.16
17385.00	46.65	PK	H	40.38	6.43	42.39	51.07	51.07	68.20	17.13
17385.00	46.63	PK	V	40.38	6.43	42.39	51.05	51.05	68.20	17.15

802.11ac80_U-NII-3_middle channel

Frequency 5775 MHz


Frequency	Reading	Detector	Rx Antenna		Cable loss	Amplifier Gain	Corrected Amplitude	Extrapolation result	Limit	Margin
			Polar	Factor						
MHz	dBμV	PK/QP/AV	H/V	dB/m	dB	dB	dBμV/m	dBμV/m	dBμV/m	dB
5725.00	34.15	PK	H	33.97	1.84	0.00	69.96	63.96	122.20	58.24
5720.00	33.78	PK	H	33.96	1.84	0.00	69.58	63.58	110.80	47.22
5700.00	31.65	PK	H	33.94	1.83	0.00	67.42	61.42	105.20	43.78
5650.00	30.28	PK	H	33.88	1.81	0.00	65.97	59.97	68.20	8.23
5850.00	32.05	PK	H	34.12	1.88	0.00	68.05	62.05	122.20	60.15
5855.00	31.26	PK	H	34.13	1.88	0.00	67.27	61.27	110.80	49.53
5875.00	30.53	PK	H	34.15	1.89	0.00	66.57	60.57	105.20	44.63
5925.00	30.22	PK	H	34.21	1.91	0.00	66.34	60.34	68.20	7.86
5725.00	33.30	PK	V	33.97	1.84	0.00	69.11	63.11	122.20	59.09
5720.00	33.47	PK	V	33.96	1.84	0.00	69.27	63.27	110.80	47.53
5700.00	31.31	PK	V	33.94	1.83	0.00	67.08	61.08	105.20	44.12
5650.00	30.51	PK	V	33.88	1.81	0.00	66.20	60.2	68.20	8.00
5850.00	32.37	PK	V	34.12	1.88	0.00	68.37	62.37	122.20	59.83
5855.00	31.36	PK	V	34.13	1.88	0.00	67.37	61.37	110.80	49.43
5875.00	30.33	PK	V	34.15	1.89	0.00	66.37	60.37	105.20	44.83
5925.00	29.48	PK	V	34.21	1.91	0.00	65.60	59.6	68.20	8.60
11550.00	45.84	PK	H	38.09	4.57	41.09	47.41	47.41	74.00	26.59
11550.00	35.53	AV	H	38.09	4.57	41.09	37.10	37.1	54.00	16.90
11550.00	45.09	PK	V	38.09	4.57	41.09	46.66	46.66	74.00	27.34
11550.00	35.04	AV	V	38.09	4.57	41.09	36.61	36.61	54.00	17.39
17325.00	45.19	PK	H	40.21	6.40	42.28	49.52	49.52	68.20	18.68
17325.00	46.16	PK	V	40.21	6.40	42.28	50.49	50.49	68.20	17.71

M20:

802.11n ht20 mode, High Channel, Horizontal

Project No.: XMDN240206-08120E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n20_U-NII-2C_high channel 5700MHz

Serial No.: 2HPA-3
Tester: Nat Zhou




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4704.00	49.68	-10.11	39.57	74.00	34.43	Peak
2	4704.00	39.58	-10.11	29.47	54.00	24.53	Average

802.11n ht20 mode, High Channel, Vertical

Project No.: XMDN240206-08120E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n20_U-NII-2C_high channel 5700MHz


Serial No.: 2HPA-3
Tester: Nat Zhou



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4821.00	49.62	-10.09	39.53	74.00	34.47	Peak
2	4821.00	39.72	-10.09	29.63	54.00	24.37	Average

Project No.: XMDN240206-08120E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n20_U-NII-2C_high channel 5700MHz


Serial No.: 2HPA-3
Tester: Nat Zhou



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	7598.40	54.16	-4.20	49.96	74.00	24.04	Peak
2	7598.40	51.24	-4.20	47.04	54.00	6.96	Average
3	11400.00	46.52	1.40	47.92	74.00	26.08	Peak
4	11400.00	36.48	1.40	37.88	54.00	16.12	Average
5	17100.00	46.44	4.00	50.44	68.20	17.76	Peak

Project No.: XMDN240206-08120E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n20_U-NII-2C_high channel 5700MHz


Serial No.: 2HPA-3
Tester: Nat Zhou



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	7598.40	58.24	-4.20	54.04	74.00	19.96	Peak
2	7598.40	55.40	-4.20	51.20	54.00	2.80	Average
3	11400.00	46.77	1.40	48.17	74.00	25.83	Peak
4	11400.00	36.45	1.40	37.85	54.00	16.15	Average
5	17100.00	46.54	4.00	50.54	68.20	17.66	Peak

802.11n ht20 mode, High Channel, Bandedge,
Horizontal


Project No.: XMDN240206-08120E-RF
Polarization: Horizontal
Test Mode: Transmitting
Serial No.: ZHPA-3
Tester: Nat Zhou
Note: 802.11n20_U-NII-2C_high channel 5700MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5725.00	30.87	29.81	60.68	68.20	7.52	Peak

802.11n ht20 mode, High Channel, Bandedge,
Vertical


Project No.: XMDN240206-08120E-RF
Polarization: Vertical
Test Mode: Transmitting
Serial No.: ZHPA-3
Tester: Nat Zhou
Note: 802.11n20_U-NII-2C_high channel 5700MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5725.00	31.44	29.81	61.25	68.20	6.95	Peak

Horizontal


Project No.: XMDN240206-08120E-RF
Polarization: Horizontal
Test Mode: Transmitting
Serial No.: 2HPA-3
Tester: Nat Zhou
Note: 802.11n20_U-NII-2C_high channel 5700MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	22794.00	43.23	8.33	51.56	74.00	22.44	Peak
2	22794.00	33.11	8.33	41.44	54.00	12.56	Average


Vertical

Project No.: XMDN240206-08120E-RF
Polarization: Vertical
Test Mode: Transmitting
Serial No.: 2HPA-3
Tester: Nat Zhou
Note: 802.11n20_U-NII-2C_high channel 5700MHz




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	22156.50	44.02	7.70	51.72	74.00	22.28	Peak
2	22156.50	33.94	7.70	41.64	54.00	12.36	Average

Project No.: XMDN240206-08120E-RF
Polarization: Horizontal
Test Mode: Transmitting
Serial No.: 2HPA-3
Tester: Nat Zhou
Note: 802.11n20_U-NII-2C_high channel 5700MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	39708.40	44.35	17.30	61.65	74.00	12.35	Peak
2	39708.40	30.30	17.30	47.60	54.00	6.40	Average

Project No.: XMDN240206-08120E-RF
Polarization: Vertical
Test Mode: Transmitting
Serial No.: 2HPA-3
Tester: Nat Zhou
Note: 802.11n20_U-NII-2C_high channel 5700MHz




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	39765.10	43.66	17.33	60.99	74.00	13.01	Peak
2	39765.10	30.59	17.33	47.92	54.00	6.08	Average

M20SE:**802.11a mode, High Channel, Horizontal**

Project No.: XMDN240206-08120E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11a_U-NII-2C_high channel 5700 MHz

Serial No.: 2HPA-5
Tester: Nat Zhou




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4702.00	49.42	-10.10	39.32	74.00	34.68	Peak
2	4702.00	39.31	-10.10	29.21	54.00	24.79	Average

802.11a mode, High Channel, Vertical

Project No.: XMDN240206-08120E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11a_U-NII-2C_high channel 5700 MHz


Serial No.: 2HPA-5
Tester: Nat Zhou



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4685.00	49.55	-10.10	39.45	74.00	34.55	Peak
2	4685.00	39.62	-10.10	29.52	54.00	24.48	Average

Project No.: XMDN240206-08120E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11a_U-NII-2C_high channel 5700 MHz


Serial No.: 2HPA-5
Tester: Nat Zhou



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	7598.40	54.80	-4.20	50.60	74.00	23.40	Peak
2	7598.40	53.38	-4.20	49.18	54.00	4.82	Average
3	11400.00	45.43	1.40	46.83	74.00	27.17	Peak
4	11400.00	35.16	1.40	36.56	54.00	17.44	Average
5	17100.00	45.16	4.00	49.16	68.20	19.04	Peak

Project No.: XMDN240206-08120E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11a_U-NII-2C_high channel 5700 MHz

Serial No.: 2HPA-5
Tester: Nat Zhou




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	7598.40	56.22	-4.20	52.02	74.00	21.98	Peak
2	7598.40	52.95	-4.20	48.75	54.00	5.25	Average
3	11400.00	45.99	1.40	47.39	74.00	26.61	Peak
4	11400.00	35.41	1.40	36.81	54.00	17.19	Average
5	17100.00	45.17	4.00	49.17	68.20	19.03	Peak

802.11a mode, High Channel, Bandedge, Horizontal

Project No.: XMDN240206-08120E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11a_U-NII-2C_high channel 5700 MHz

Serial No.: ZHPA-5
Tester: Nat Zhou




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5725.00	30.23	29.81	60.04	68.20	8.16	Peak

802.11a mode, High Channel, Bandedge, Vertical

Project No.: XMDN240206-08120E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11a_U-NII-2C_high channel 5700 MHz


Serial No.: ZHPA-5
Tester: Nat Zhou



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5725.00	29.67	29.81	59.48	68.20	8.72	Peak

Horizontal


Project No.: XMDN240206-08120E-RF
Polarization: Horizontal
Test Mode: Transmitting
Serial No.: 2HPA-5
Tester: Nat Zhou
Note: 802.11a_U-NII-2C_high channel 5700 MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	22515.20	43.30	7.89	51.19	74.00	22.81	Peak
2	22515.20	33.22	7.89	41.11	54.00	12.89	Average


Vertical

Project No.: XMDN240206-08120E-RF
Polarization: Vertical
Test Mode: Transmitting
Serial No.: 2HPA-5
Tester: Nat Zhou
Note: 802.11a_U-NII-2C_high channel 5700 MHz




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	18759.90	45.20	6.34	51.54	74.00	22.46	Peak
2	18759.90	35.05	6.34	41.39	54.00	12.61	Average

Project No.: XMDN240206-08120E-RF
Polarization: Horizontal
Test Mode: Transmitting
Serial No.: 2HPA-5
Tester: Nat Zhou
Note: 802.11a_U-NII-2C_high channel 5700 MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	39697.60	44.08	17.29	61.37	74.00	12.63	Peak
2	39697.60	29.49	17.29	46.78	54.00	7.22	Average

Project No.: XMDN240206-08120E-RF
Polarization: Vertical
Test Mode: Transmitting
Serial No.: 2HPA-5
Tester: Nat Zhou
Note: 802.11a_U-NII-2C_high channel 5700 MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	39705.70	44.59	17.30	61.89	74.00	12.11	Peak
2	39705.70	30.64	17.30	47.94	54.00	6.06	Average

5.3 26dB attenuated below the channel power

Serial No.:	2HPA-1	Test Date:	2024/05/06
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jojo Zhou	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.2	Relative Humidity: (%)	61	ATM Pressure: (kPa)	100.5
-----------------------------	------	----------------------------------	----	-------------------------------	-------

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101947	2023/10/18	2024/10/17
Eastsheep	Coaxial Attenuator	5W-N-JK-6G-10dB	F-08-EM488	2023/09/10	2024/09/09

** Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*


Test Data:

The channel power please refer to the power test result. Please refer to the following plots.


a_5180MHz_Chain 0




a_5200MHz_Chain 0




a_5240MHz_Chain 0




n20_5180MHz_Chain 0



n20_5200MHz_Chain 0



n20_5240MHz_Chain 0




n40_5190MHz_Chain 0



ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 15:08:54

n40_5230MHz_Chain 0



ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 15:09:32

ac80_5210MHz_Chain 0



ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 15:11:04

5.4 Emission Bandwidth

Serial No.:	2HPA-1	Test Date:	2024/05/06
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jojo Zhou	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.2	Relative Humidity: (%)	61	ATM Pressure: (kPa)	100.5
-----------------------------	------	----------------------------------	----	-------------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101947	2023/10/18	2024/10/17
Eastsheep	Coaxial Attenuator	5W-N-JK-6G-10dB	F-08-EM488	2023/09/10	2024/09/09

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:**26 dB Emission Bandwidth:****5150-5250 MHz**

Mode	Value (MHz)
a_5180MHz_Chain 0	23.970
a_5200MHz_Chain 0	23.669
a_5240MHz_Chain 0	23.575
n20_5180MHz_Chain 0	25.510
n20_5200MHz_Chain 0	24.990
n20_5240MHz_Chain 0	24.506
n40_5190MHz_Chain 0	41.900
n40_5230MHz_Chain 0	42.000
ac80_5210MHz_Chain 0	87.800

5250-5350 MHz

Mode	Value (MHz)
a_5260MHz_Chain 0	24.016
a_5280MHz_Chain 0	23.972
a_5320MHz_Chain 0	23.927
n20_5260MHz_Chain 0	24.673
n20_5280MHz_Chain 0	25.116
n20_5320MHz_Chain 0	25.155
n40_5270MHz_Chain 0	41.800
n40_5310MHz_Chain 0	41.500
ac80_5290MHz_Chain 0	92.000

5470-5725 MHz


Mode	Value (MHz)
a_5500MHz_Chain 0	23.216
a_5580MHz_Chain 0	23.278
a_5700MHz_Chain 0	23.729
a_5720MHz_Chain 0	24.093
n20_5500MHz_Chain 0	25.237
n20_5580MHz_Chain 0	25.802
n20_5700MHz_Chain 0	25.872
n20_5720MHz_Chain 0	27.401
n40_5510MHz_Chain 0	41.300
n40_5550MHz_Chain 0	41.400
n40_5670MHz_Chain 0	41.900
n40_5710MHz_Chain 0	41.700
ac80_5530MHz_Chain 0	96.000
ac80_5610MHz_Chain 0	96.200
ac80_5690MHz_Chain 0	92.800

Minimum 6dB Emission Bandwidth:**5725-5850 MHz**

Mode	Value (MHz)	Limit (MHz)	Result
a_5745MHz_Chain 0	15.700	0.500	Pass
a_5785MHz_Chain 0	16.150	0.500	Pass
a_5825MHz_Chain 0	15.500	0.500	Pass
n20_5745MHz_Chain 0	15.650	0.500	Pass
n20_5785MHz_Chain 0	16.450	0.500	Pass
n20_5825MHz_Chain 0	16.150	0.500	Pass
n40_5755MHz_Chain 0	35.80	0.500	Pass
n40_5795MHz_Chain 0	35.80	0.500	Pass
ac80_5775MHz_Chain 0	75.60	0.500	Pass


5150-5250MHz:

a_5180MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 10:03:32

a_5200MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 10:04:54

a_5240MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 10:06:13

n20_5180MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 10:07:50

n20_5200MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 10:08:57

n20_5240MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 10:10:12

n40_5190MHz_Chain 0



ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 10:11:18


n40_5230MHz_Chain 0



ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 10:12:18


5250-5350MHz:

ac80_5210MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 10:15:14

a_5260MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 10:19:27

a_5280MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 10:21:57

a_5320MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 10:23:17


n20_5260MHz_Chain 0




n20_5280MHz_Chain 0




n20_5320MHz_Chain 0




n40_5270MHz_Chain 0



n40_5310MHz_Chain 0




ac80_5290MHz_Chain 0




5470-5725MHz:


a_5500MHz_Chain 0




a_5580MHz_Chain 0




a_5700MHz_Chain 0




a_5720MHz_Chain 0




n20_5500MHz_Chain 0




n20_5580MHz_Chain 0




n20_5700MHz_Chain 0




n20_5720MHz_Chain 0




n40_5510MHz_Chain 0




n40_5550MHz_Chain 0




n40_5670MHz_Chain 0



n40_5710MHz_Chain 0




ac80_5530MHz_Chain 0



ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 11:21:27


ac80_5610MHz_Chain 0



ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 11:26:50


5725-5850MHz:

ac80_5690MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 11:27:45

a_5745MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 11:36:11

a_5785MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 11:38:00

a_5825MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 11:39:02


n20_5745MHz_Chain 0




n20_5785MHz_Chain 0




n20_5825MHz_Chain 0




n40_5755MHz_Chain 0



n40_5795MHz_Chain 0



ac80_5775MHz_Chain 0



5.5 99% Occupied Bandwidth

Serial No.:	2HPA-1	Test Date:	2024/05/06
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jojo Zhou	Test Result:	/

Environmental Conditions:

Temperature: (°C)	26.2	Relative Humidity: (%)	61	ATM Pressure: (kPa)	100.5
-----------------------------	------	----------------------------------	----	-------------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101947	2023/10/18	2024/10/17
Eastsheep	Coaxial Attenuator	5W-N-JK-6G-10dB	F-08-EM488	2023/09/10	2024/09/09

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:**5150-5250 MHz**

Mode	99% OBW (MHz)
a_5180MHz_Chain 0	16.650
a_5200MHz_Chain 0	16.700
a_5240MHz_Chain 0	16.600
n20_5180MHz_Chain 0	17.850
n20_5200MHz_Chain 0	17.900
n20_5240MHz_Chain 0	17.850
n40_5190MHz_Chain 0	36.400
n40_5230MHz_Chain 0	36.400
ac80_5210MHz_Chain 0	75.800

Note:

The 99% Occupied Bandwidth have not fall into the band 5250-5350MHz, please refer to the test plots of 99% Occupied Bandwidth.

5250-5350 MHz

Mode	99% OBW (MHz)
a_5260MHz_Chain 0	16.600
a_5280MHz_Chain 0	16.600
a_5320MHz_Chain 0	16.700
n20_5260MHz_Chain 0	17.850
n20_5280MHz_Chain 0	17.850
n20_5320MHz_Chain 0	17.850
n40_5270MHz_Chain 0	36.400
n40_5310MHz_Chain 0	36.400
ac80_5290MHz_Chain 0	76.000

5470-5725 MHz

Mode	99% OBW (MHz)
a_5500MHz_Chain 0	16.600
a_5580MHz_Chain 0	16.600
a_5700MHz_Chain 0	16.700
a_5720MHz_Chain 0	16.650
n20_5500MHz_Chain 0	17.800
n20_5580MHz_Chain 0	17.950
n20_5700MHz_Chain 0	17.950
n20_5720MHz_Chain 0	17.950
n40_5510MHz_Chain 0	36.300
n40_5550MHz_Chain 0	36.300
n40_5670MHz_Chain 0	36.400
n40_5710MHz_Chain 0	36.400
ac80_5530MHz_Chain 0	76.000
ac80_5610MHz_Chain 0	76.400
ac80_5690MHz_Chain 0	76.000

5725-5850 MHz


Mode	99% OBW (MHz)
a_5745MHz_Chain 0	16.700
a_5785MHz_Chain 0	16.650
a_5825MHz_Chain 0	16.650
n20_5745MHz_Chain 0	17.900
n20_5785MHz_Chain 0	17.950
n20_5825MHz_Chain 0	17.900
n40_5755MHz_Chain 0	36.400
n40_5795MHz_Chain 0	36.300
ac80_5775MHz_Chain 0	75.800

Note:


The 99% Occupied Bandwidth have not fall into the band 5470-5725MHz, please refer to the test plots of 99% Occupied Bandwidth.

5150-5250MHz:


a_5180MHz_Chain 0




a_5200MHz_Chain 0




a_5240MHz_Chain 0




n20_5180MHz_Chain 0




n20_5200MHz_Chain 0



n20_5240MHz_Chain 0




n40_5190MHz_Chain 0



ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 10:11:04


n40_5230MHz_Chain 0



ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 10:12:03


5250-5350MHz

ac80_5210MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 10:15:17

a_5260MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 10:18:56

a_5280MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 10:21:24

a_5320MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 10:22:46

n20_5260MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 10:24:16

n20_5280MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 10:25:35

n20_5320MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 10:26:54

n40_5270MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 10:28:31

n40_5310MHz_Chain 0



ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 10:29:14


ac80_5290MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 10:30:42

5470-5725MHz:


a_5500MHz_Chain 0




a_5580MHz_Chain 0




a_5700MHz_Chain 0




a_5720MHz_Chain 0




n20_5500MHz_Chain 0




n20_5580MHz_Chain 0




n20_5700MHz_Chain 0




n20_5720MHz_Chain 0




n40_5510MHz_Chain 0




n40_5550MHz_Chain 0




n40_5670MHz_Chain 0



n40_5710MHz_Chain 0




ac80_5530MHz_Chain 0



ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 11:21:08


ac80_5610MHz_Chain 0



ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 11:26:23


5725-5850MHz

ac80_5690MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 11:27:27

a_5745MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 11:35:46

a_5785MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 11:37:32

a_5825MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 11:38:42

n20_5745MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 11:41:00

n20_5785MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 11:42:12

n20_5825MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 11:43:12

n40_5755MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 11:44:35

n40_5795MHz_Chain 0



ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 11:46:01

ac80_5775MHz_Chain 0



ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 11:47:10

5.6 Maximum Conducted Output Power

Serial No.:	2HPA-1	Test Date:	2024/05/05
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jojo Zhou	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.5	Relative Humidity: (%)	56	ATM Pressure: (kPa)	100.3
----------------------	------	---------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Anritsu	Microwave Peak Power Sensor	MA24418A	12618	2023/09/04	2024/09/03
Eastsheep	Coaxial Attenuator	5W-N-JK-6G-10dB	F-08-EM502	2023/09/10	2024/09/09

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

5150-5250MHz

Mode	Conducted Average Output Power (dBm)	FCC Limit (dBm)	EIRP (dBm)	RSS-247 EIRP Limit
a_5180MHz_Chain 0	12.62	24.00	15.77	22.21
a_5200MHz_Chain 0	12.59	24.00	15.74	22.23
a_5240MHz_Chain 0	12.16	24.00	15.31	22.20
n20_5180MHz_Chain 0	15.42	24.00	18.57	22.52
n20_5200MHz_Chain 0	15.42	24.00	18.57	22.53
n20_5240MHz_Chain 0	15.02	24.00	18.17	22.52
n40_5190MHz_Chain 0	13.50	24.00	16.65	23.00
n40_5230MHz_Chain 0	13.30	24.00	16.45	23.00
ac80_5210MHz_Chain 0	14.67	24.00	17.82	23.00

Note: EIRP was calculated with the maximum gain of the antennas.

5250-5350MHz

Mode	Conducted Average Output Power (dBm)	FCC Conducted Limit (dBm)	RSS-247 Conducted Limit (dBm)	EIRP (dBm)	RSS-247 EIRP Limit (dBm)
a_5260MHz_Chain 0	12.43	24.00	23.20	15.87	29.20
a_5280MHz_Chain 0	12.54	24.00	23.20	15.98	29.20
a_5320MHz_Chain 0	12.65	24.00	23.23	16.09	29.23
n20_5260MHz_Chain 0	15.31	24.00	23.52	18.75	29.52
n20_5280MHz_Chain 0	15.38	24.00	23.52	18.82	29.52
n20_5320MHz_Chain 0	15.46	24.00	23.52	18.9	29.52
n40_5270MHz_Chain 0	13.11	24.00	24.00	16.55	30.00
n40_5310MHz_Chain 0	13.21	24.00	24.00	16.65	30.00
ac80_5290MHz_Chain 0	14.41	24.00	24.00	17.85	30.00

Note: EIRP was calculated with the maximum gain of the antennas.

5470-5725MHz

Mode	Conducted Average Output Power (dBm)	FCC Conducted Limit (dBm)	RSS-247 Conducted Limit (dBm)	EIRP (dBm)	RSS-247 EIRP Limit (dBm)
a_5500MHz_Chain 0	12.40	24.00	23.20	15.47	29.20
a_5580MHz_Chain 0	12.72	24.00	23.20	15.79	29.20
a_5700MHz_Chain 0	12.92	24.00	23.23	15.99	29.23
a_5720MHz_Chain 0	12.36	24.00	23.21	15.43	29.21
n20_5500MHz_Chain 0	15.25	24.00	23.50	18.32	29.5
n20_5580MHz_Chain 0	15.59	24.00	23.54	18.66	29.54
n20_5700MHz_Chain 0	15.35	24.00	23.54	18.42	29.54
n20_5720MHz_Chain 0	15.73	24.00	23.54	18.8	29.54
n40_5510MHz_Chain 0	13.93	24.00	24.00	17	30.00
n40_5550MHz_Chain 0	13.65	24.00	24.00	16.72	30.00
n40_5670MHz_Chain 0	13.32	24.00	24.00	16.39	30.00
n40_5710MHz_Chain 0	13.74	24.00	24.00	16.81	30.00
ac80_5530MHz_Chain 0	14.49	24.00	24.00	17.56	30.00
ac80_5610MHz_Chain 0	14.30	24.00	24.00	17.37	30.00
ac80_5690MHz_Chain 0	14.66	24.00	24.00	17.73	30.00

Note: EIRP was calculated with the maximum gain of the antennas.

5725-5850MHz

Mode	Average Output Power (dBm)	Limit (dBm)	Result
a_5745MHz_Chain 0	12.98	30.00	Pass
a_5785MHz_Chain 0	13.09	30.00	Pass
a_5825MHz_Chain 0	13.09	30.00	Pass
n20_5745MHz_Chain 0	15.91	30.00	Pass
n20_5785MHz_Chain 0	15.92	30.00	Pass
n20_5825MHz_Chain 0	16.28	30.00	Pass
n40_5755MHz_Chain 0	13.78	30.00	Pass
n40_5795MHz_Chain 0	13.52	30.00	Pass
ac80_5775MHz_Chain 0	14.60	30.00	Pass

5.7 Maximum power spectral density

Serial No.:	2HPA-1	Test Date:	2024/05/06
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jojo Zhou	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	26.2	Relative Humidity: (%)	61	ATM Pressure: (kPa)	100.5
----------------------	------	---------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101947	2023/10/18	2024/10/17
Eastsheep	Coaxial Attenuator	5W-N-JK-6G-10dB	F-08-EM488	2023/09/10	2024/09/09

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

5150-5250MHz:

Mode	Reading (dBm/MHz)	Duty Cycle Factor (dB)	PSD (dBm/MHz)	FCC Conducted PSD Limit (dBm/MHz)	EIRP PSD (dBm/MHz)	RSS-247 EIRP PSD Limit (dBm/MHz)
a 5180MHz Chain 0	1.35	0	1.35	11.00	4.5	10.00
a 5200MHz Chain 0	1.07	0	1.07	11.00	4.22	10.00
a 5240MHz Chain 0	0.69	0	0.69	11.00	3.84	10.00
n20 5180MHz Chain 0	4.17	0.09	4.26	11.00	7.41	10.00
n20 5200MHz Chain 0	3.97	0.09	4.06	11.00	7.21	10.00
n20 5240MHz Chain 0	3.62	0.09	3.71	11.00	6.86	10.00
n40 5190MHz Chain 0	-1.36	0.19	-1.17	11.00	1.98	10.00
n40 5230MHz Chain 0	-1.46	0.19	-1.27	11.00	1.88	10.00
ac80 5210MHz Chain 0	-3.06	0.37	-2.69	11.00	0.46	10.00

5250-5350MHz:






Mode	Value (dBm/MHz)	Duty Cycle Factor (dB)	PSD (dBm/MHz)	Limit (dBm/MHz)	Result
a_5260MHz_Chain 0	0.78	0	0.78	11.00	Pass
a_5280MHz_Chain 0	0.67	0	0.67	11.00	Pass
a_5320MHz_Chain 0	0.48	0	0.48	11.00	Pass
n20_5260MHz_Chain 0	3.31	0.09	3.4	11.00	Pass
n20_5280MHz_Chain 0	3.40	0.09	3.49	11.00	Pass
n20_5320MHz_Chain 0	3.37	0.09	3.46	11.00	Pass
n40_5270MHz_Chain 0	-2.11	0.19	-1.92	11.00	Pass
n40_5310MHz_Chain 0	-2.04	0.19	-1.85	11.00	Pass
ac80_5290MHz_Chain 0	-3.62	0.37	-3.25	11.00	Pass

5470-5725MHz:


Mode	Value (dBm/MHz)	Duty Cycle Factor (dB)	PSD (dBm/MHz)	Limit (dBm/MHz)	Result
a_5500MHz_Chain 0	0.00	0	0	11.00	Pass
a_5580MHz_Chain 0	0.38	0	0.38	11.00	Pass
a_5700MHz_Chain 0	0.84	0	0.84	11.00	Pass
a_5720MHz_Chain 0	1.24	0	1.24	11.00	Pass
n20_5500MHz_Chain 0	3.84	0.09	3.93	11.00	Pass
n20_5580MHz_Chain 0	4.14	0.09	4.23	11.00	Pass
n20_5700MHz_Chain 0	3.47	0.09	3.56	11.00	Pass
n20_5720MHz_Chain 0	3.38	0.09	3.47	11.00	Pass
n40_5510MHz_Chain 0	-2.56	0.19	-2.37	11.00	Pass
n40_5550MHz_Chain 0	-1.55	0.19	-1.36	11.00	Pass
n40_5670MHz_Chain 0	-2.15	0.19	-1.96	11.00	Pass
n40_5710MHz_Chain 0	-1.68	0.19	-1.49	11.00	Pass
ac80_5530MHz_Chain 0	-3.97	0.37	-3.6	11.00	Pass
ac80_5610MHz_Chain 0	-4.18	0.37	-3.81	11.00	Pass
ac80_5690MHz_Chain 0	-3.73	0.37	-3.36	11.00	Pass

5725-5850MHz:

Mode	Value (dBm/500kHz)	Duty Cycle Factor (dB)	PSD (dBm/500kHz)	Limit (dBm/500kHz)	Result
a_5745MHz_Chain 0	-2.06	0	-2.06	30.00	Pass
a_5785MHz_Chain 0	-2.11	0	-2.11	30.00	Pass
a_5825MHz_Chain 0	-1.94	0	-1.94	30.00	Pass
n20_5745MHz_Chain 0	0.29	0.09	0.38	30.00	Pass
n20_5785MHz_Chain 0	0.94	0.09	1.03	30.00	Pass
n20_5825MHz_Chain 0	1.03	0.09	1.12	30.00	Pass
n40_5755MHz_Chain 0	-4.45	0.19	-4.26	30.00	Pass
n40_5795MHz_Chain 0	-4.72	0.19	-4.53	30.00	Pass
ac80_5775MHz_Chain 0	-6.69	0.37	-6.32	30.00	Pass


5150-5250 MHz:**a_5180MHz_Chain 0****a_5200MHz_Chain 0****a_5240MHz_Chain 0****n20_5180MHz_Chain 0****n20_5200MHz_Chain 0****n20_5240MHz_Chain 0**

n40_5190MHz_Chain 0



ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 14:04:20


n40_5230MHz_Chain 0



ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 14:04:59


5250-5350MHz

ac80_5210MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 15:12:23

a_5260MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 14:11:51

a_5280MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 14:12:23

a_5320MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 14:12:58

n20_5260MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 14:13:45

n20_5280MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 14:14:24

n20_5320MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 14:17:10

n40_5270MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 14:19:03

n40_5310MHz_Chain 0



ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 14:19:44


ac80_5290MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 14:21:06

5470-5725MHz:


a_5500MHz_Chain 0




a_5580MHz_Chain 0




a_5700MHz_Chain 0




a_5720MHz_Chain 0




n20_5500MHz_Chain 0



n20_5580MHz_Chain 0




n20_5700MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 14:43:13

n20_5720MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 14:44:19

n40_5510MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 14:45:15

n40_5550MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 14:46:18

n40_5670MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 14:47:06

n40_5710MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 14:47:39

ac80_5530MHz_Chain 0



ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 14:48:46


ac80_5610MHz_Chain 0



ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 14:49:32


5725-5850MHz

ac80_5690MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 14:51:15

a_5745MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 15:14:15

a_5785MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 15:14:53

a_5825MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 15:15:24

n20_5745MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 15:16:32

n20_5785MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 15:17:26

n20_5825MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 15:17:55

n40_5755MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 15:18:44

n40_5795MHz_Chain 0



ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 15:19:35

ac80_5775MHz_Chain 0



ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 15:20:11

5.8 Duty Cycle

Serial No.:	2HPA-1	Test Date:	2024/05/06
Test Site:	RF	Test Mode:	Transmitting
Tester:	Jojo Zhou	Test Result:	/

Environmental Conditions:

Temperature: (°C)	26.2	Relative Humidity: (%)	61	ATM Pressure: (kPa)	100.5
-----------------------------	------	----------------------------------	----	-------------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101947	2023/10/18	2024/10/17
Eastsheep	Coaxial Attenuator	5W-N-JK-6G-10dB	F-08-EM488	2023/09/10	2024/09/09


** Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data:

Mode	Ton (ms)	Ton+Toff (ms)	Duty Cycle (%)	Duty Cycle Factor (dB)	1/Ton (Hz)	VBW Setting (kHz)
a_5200MHz_Chain 0	2.026	2.065	98.11	/	/	0.01
n20_5200MHz_Chain 0	1.701	1.738	97.87	0.09	588	1
n40_5190MHz_Chain 0	0.838	0.875	95.77	0.19	1193	2
ac80_5210MHz_Chain 0	0.411	0.448	91.74	0.37	2433	3


Duty Cycle = Ton/(Ton+Toff)*100%

a_5200MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 13:07:58

n20_5200MHz_Chain 0




ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 13:08:46

n40_5190MHz_Chain 0



ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 13:09:57

ac80_5210MHz_Chain 0



ProjectNo.:XMDN240206-08120E-RF Tester:Jojo Zhou
Date: 6.MAY.2024 13:12:02

APPENDIX A - EUT PHOTOGRAPHS

Please refer to the attachment XMDN240206-08120E-RF-EXP EUT EXTERNAL PHOTOGRAPHS and XMDN240206-08120E-RF-INP EUT INTERNAL PHOTOGRAPHS.

APPENDIX B - TEST SETUP PHOTOGRAPHS

Please refer to the attachment XMDN240206-08120E-RF-00D-TSP TEST SETUP PHOTOGRAPHS.

******* END OF REPORT *******