

RF EXPOSURE EVALUATION

EUT Specification

EUT	Bluetooth Digital Karaoke with Party Lights
Model Number	iSF-36, M1 - 36 M2M3M4M5M6M7M8M9M10 (M1 - M10, please refer to model no. table)
FCC ID	EMO36A
Antenna gain (Max)	0 dBi
Operation Frequency	2.4G:2402MHz-2480MHz
Input Rating	AC 120V/60Hz
Classification Per Stipulated Test Standard	§ 15.247(i), § 2.1093
Modulation	GFSK, pi/4-DQPSK , 8-DPSK
Max. output power	-1.28 dBm(0.000745W)
Evaluation applied	☒ MPE Evaluation ☐ SAR Evaluation

Test Requirement:

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

1 Friis transmission formula: $P_d = \frac{P_{out} \cdot G}{4 \cdot \pi \cdot R^2}$

Where

P_d = Power density in mW/cm^2

P_{out} = output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

$\pi = 3.1416$

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, $1mW/cm^2$. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

2 Measurement Result

Antenna gain: 0 dBi

Mode	Frequency (MHz)	Output Power (dBm)	Target Power W/tolerance (dBm)	Max tune up power tolerance (dBm)	Max tune up power tolerance (mW)	Power Density at $R=20cm$ (mW/cm^2)	Limit (mW/cm^2)	Verdict
GFSK	2402	-3.89	-4 ± 1	-3	0.50	0.000100	1.0	PASS
	2441	-4.30	-5 ± 1	-4	0.40	0.000079	1.0	PASS
	2480	-4.62	-5 ± 1	-4	0.40	0.000079	1.0	PASS
$\pi/4$ -DQPSK	2402	-1.70	-2 ± 1	-1	0.79	0.000158	1.0	PASS
	2441	-2.14	-3 ± 1	-2	0.63	0.000126	1.0	PASS
	2480	-2.48	-3 ± 1	-2	0.63	0.000126	1.0	PASS
8-DPSK	2402	-1.28	-2 ± 1	-1	0.79	0.000158	1.0	PASS
	2441	-1.69	-2 ± 1	-1	0.79	0.000158	1.0	PASS
	2480	-2.04	-3 ± 1	-2	0.63	0.000126	1.0	PASS

Signature:

A handwritten signature in black ink is positioned to the left of a circular purple stamp. The stamp contains the text "EMTEK (HONGGUAN) CO., LTD." around the top and "TESTING" around the bottom, with a stylized "M" logo in the center.

Sam Lv

Date: 2021-05-18