

RF EXPOSURE EVALUATION REPORT

FCC ID : UZ7CR6080PC
Equipment : HC Cradle
Brand Name : Zebra
Model Name : CR6080-PC
Applicant : Zebra Technologies Corporation
1 Zebra Plaza, Holtsville, NY 11742
Standard : 47 CFR Part 2.1093
FCC KDB 447498 D01 v06

We, SPORTON INTERNATIONAL INC has been evaluated this product in accordance with 47 CFR Part 2.1093 and it complies with applicable limit.

The results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Cona Huang / Deputy Manager

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

1.	General Information	3
1.1	Description of Device Under Test (DUT)	3
2.	Maximum RF output power among production units	3
3.	RF Exposure Evaluation	4

History of this test report

Report No.	Version	Description	Issued Date
FA050617-01B	Rev. 01	Initial issue of report	Aug. 17, 2020
FA050617-01B	Rev. 02	Update Equipment Name	Aug. 24, 2020

**1. General Information****1.1 Description of Device Under Test (DUT)**

Product Feature & Specification	
DUT Type	HC Cradle
Brand Name	Zebra
Model Name	CR6080-PC
FCC ID	UZ7CR6080PC
Wireless Technology and Frequency Range	Bluetooth: 2402 MHz ~ 2480 MHz
Mode	Bluetooth BR/EDR/LE
HW Version	EV2
SW Version	N16
MFD	30APR20
DUT Stage	Engineering sample

Remark: The above DUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Reviewed by: Jason Wang

Report Producer: Wan Liu

2. Maximum RF output power among production units

Bluetooth	
2.4GHz Bluetooth	6.47



3. RF Exposure Evaluation

Bluetooth Max Power (dBm)	mW	Separation Distance (mm)	Frequency (GHz)	Exclusion Thresholds
6.47	4.44	5	2.48	1.4

Note:

1. Per KDB 447498 D01v06 the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Conclusion: Per KDB 447498 D01v06, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 1.4 which is ≤ 3 , SAR testing is not required.