



Spurious Emissions at Antenna Terminal



Channel

10MHz Bandwidth QPSK



Lowest




Middle




Highest




RB1 Out of band emission, Band Edge




RB1 Out of band emission, Band Edge



RB6 Out of band emission, Band Edge



RB5 Out of band emission, Band Edge



4.10 Radiated Spurious Emissions

Serial Number:	2A93-5	Test Date:	2023/9/10~2023/10/5
Test Site:	966-1, 966-2	Test Mode:	Transmitting
Tester:	Vic Du ,Mack Huang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.1~26.3	Relative Humidity: (%)	54~58	ATM Pressure: (kPa)	100.1~100.2
----------------------	-----------	---------------------------	-------	---------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Antenna	JB6	A082520-5	2020/10/19	2023/10/18
R&S	EMI Test Receiver	ESR3	102724	2023/3/31	2024/3/30
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2023/7/16	2024/7/15
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2023/7/16	2024/7/15
Sonoma	Amplifier	310N	186165	2023/7/16	2024/7/15
EMCO	Adjustable Dipole Antenna	3121C	9109-756	N/A	N/A
MICRO-COAX	Coaxial Cable	UFA210B-0-0720-300300	99G1448	2022/7/16	2024/7/15
Agilent	Signal Generator	E8247C	MY43321352	2022/11/18	2023/11/17
ETS-Lindgren	Horn Antenna	3115	9912-5985	2020/10/13	2023/10/12
R&S	Spectrum Analyzer	FSV40	101591	2023/3/31	2024/3/30
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2023/8/6	2024/8/5
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2023/8/6	2024/8/5
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2022/11/9	2023/11/8
AH	Double Ridge Guide Horn Antenna	SAS-571	1396	2021/10/18	2024/10/17
MICRO-COAX	Coaxial Cable	UFA210B-0-0720-300300	99G1448	2022/7/16	2024/7/15
PASTERNAK	Horn Antenna	PE9852/2F-20	112002	2021/2/5	2024/2/4
PASTERNAK	Horn Antenna	PE9852/2F-20	112001	2021/2/5	2024/2/4
Quinstar	Preamplifier	QLW-18405536-JO	15964001005	2023/9/15	2024/9/14
PASTERNAK	Horn Antenna	PE9850/2F-20	072001	2021/2/5	2024/2/4
PASTERNAK	Horn Antenna	PE9850/2F-20	072002	2021/2/5	2024/2/4
MICRO-COAX	Coaxial Cable	UFB142A-1-2362-200200	235772-001	2023/8/6	2024/8/5

*** Statement of Traceability:** China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Band 2 Low channel:

The maximum value of the fundamental on the X-axis: 116.03dBuV/m.

The maximum value of the fundamental on the Y-axis: 106.23dBuV/m.

After pre-scan in the X and Y axes of orientation, the worst case is below:

LTE Bands:

(The Worst modulation and bandwidth was below)

LTE Band 2 (30MHz-20GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4M QPSK,Frequency:1850.7 MHz								
60.32	H	39.65	-64.23	-10.13	0.14	-74.50	-13.00	61.50
212.54	V	42.11	-67.61	0.00	0.27	-67.88	-13.00	54.88
3701.400	H	51.32	-45.99	10.60	1.25	-36.64	-13.00	23.64
3701.400	V	47.27	-50.02	10.60	1.25	-40.67	-13.00	27.67
5552.100	H	39.08	-54.19	11.44	1.49	-44.24	-13.00	31.24
5552.100	V	38.12	-54.98	11.44	1.49	-45.03	-13.00	32.03
1.4M QPSK,Frequency:1880 MHz								
60.59	H	39.54	-64.33	-9.99	0.14	-74.46	-13.00	61.46
212.58	V	42.35	-67.37	0.00	0.27	-67.64	-13.00	54.64
3760.000	H	47.06	-49.35	10.66	1.24	-39.93	-13.00	26.93
3760.000	V	43.57	-52.72	10.66	1.24	-43.30	-13.00	30.30
5640.000	H	39.19	-54.26	11.33	1.54	-44.47	-13.00	31.47
5640.000	V	36.58	-56.75	11.33	1.54	-46.96	-13.00	33.96
1.4M QPSK,Frequency:1909.3 MHz								
60.74	H	36.84	-67.03	-9.91	0.14	-77.08	-13.00	64.08
212.95	V	42.51	-67.22	0.00	0.27	-67.49	-13.00	54.49
3818.600	H	47.81	-48.05	10.72	1.29	-38.62	-13.00	25.62
3818.600	V	40.16	-55.55	10.72	1.29	-46.12	-13.00	33.12
5727.900	H	39.16	-54.32	11.23	1.59	-44.68	-13.00	31.68
5727.900	V	37.49	-55.87	11.23	1.59	-46.23	-13.00	33.23

LTE Band 4 (30MHz-20GHz):

EME Data 1 (Common Only)								
Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4M QPSK, Frequency: 1710.7 MHz								
60.94	H	36.45	-67.42	-9.80	0.14	-77.36	-13.00	64.36
212.48	V	42.35	-67.37	0.00	0.26	-67.63	-13.00	54.63
3421.400	H	59.13	-38.63	10.37	1.17	-29.43	-13.00	16.43
3421.400	V	55.28	-42.45	10.37	1.17	-33.25	-13.00	20.25
5132.100	H	36.25	-57.32	11.28	1.47	-47.51	-13.00	34.51
5132.100	V	37.43	-56.03	11.28	1.47	-46.22	-13.00	33.22
1.4M QPSK, Frequency: 1732.5 MHz								
60.38	H	36.54	-67.34	-10.10	0.14	-77.58	-13.00	64.58
212.39	V	42.85	-66.86	0.00	0.26	-67.12	-13.00	54.12
3465.000	H	58.98	-38.83	10.39	1.15	-29.59	-13.00	16.59
3465.000	V	59.35	-38.42	10.39	1.15	-29.18	-13.00	16.18
5197.500	H	35.52	-58.61	11.32	1.44	-48.73	-13.00	35.73
5197.500	V	37.47	-56.51	11.32	1.44	-46.63	-13.00	33.63
1.4M QPSK, Frequency: 1754.3MHz								
60.54	H	36.84	-67.03	-10.01	0.14	-77.18	-13.00	64.18
212.95	V	41.95	-67.78	0.00	0.27	-68.05	-13.00	55.05
3508.600	H	56.38	-41.44	10.41	1.19	-32.22	-13.00	19.22
3508.600	V	53.22	-44.54	10.41	1.19	-35.32	-13.00	22.32
5262.900	H	40.15	-53.55	11.36	1.47	-43.66	-13.00	30.66
5262.900	V	37.68	-55.79	11.36	1.47	-45.90	-13.00	32.90

LTE Band 5(30MHz-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4M QPSK, Frequency: 824.7 MHz								
60.95	H	36.75	-67.12	-9.80	0.14	-77.06	-13.00	64.06
212.54	V	41.58	-68.14	0.00	0.27	-68.41	-13.00	55.41
1649.400	H	41.50	-62.83	8.68	0.80	-54.95	-13.00	41.95
1649.400	V	38.55	-65.86	8.68	0.80	-57.98	-13.00	44.98
2474.100	H	45.12	-55.66	9.38	1.00	-47.28	-13.00	34.28
2474.100	V	40.85	-59.88	9.38	1.00	-51.50	-13.00	38.50
3298.800	H	33.95	-62.73	10.32	1.15	-53.56	-13.00	40.56
3298.800	V	34.31	-62.13	10.32	1.15	-52.96	-13.00	39.96
1.4M QPSK, Frequency: 836.5 MHz								
60.49	H	36.55	-67.33	-10.04	0.14	-77.51	-13.00	64.51
212.95	V	42.95	-66.78	0.00	0.27	-67.05	-13.00	54.05
1673.000	H	41.33	-62.98	8.71	0.85	-55.12	-13.00	42.12
1673.000	V	39.62	-64.79	8.71	0.85	-56.93	-13.00	43.93
2509.500	H	50.35	-50.26	9.42	1.01	-41.85	-13.00	28.85
2509.500	V	41.02	-59.60	9.42	1.01	-51.19	-13.00	38.19
3346.000	H	33.28	-63.88	10.34	1.16	-54.70	-13.00	41.70
3346.000	V	33.96	-63.06	10.34	1.16	-53.88	-13.00	40.88
1.4M QPSK, Frequency: 848.3 MHz								
60.38	H	36.44	-67.44	-10.10	0.14	-77.68	-13.00	64.68
212.97	V	42.18	-67.55	0.00	0.27	-67.82	-13.00	54.82
1696.600	H	40.97	-63.32	8.74	0.89	-55.47	-13.00	42.47
1696.600	V	39.71	-64.71	8.74	0.89	-56.86	-13.00	43.86
2544.900	H	45.18	-55.16	9.47	1.01	-46.70	-13.00	33.70
2544.900	V	41.31	-58.99	9.47	1.01	-50.53	-13.00	37.53
3393.200	H	34.13	-63.54	10.36	1.19	-54.37	-13.00	41.37
3393.200	V	35.16	-62.47	10.36	1.19	-53.30	-13.00	40.30

LTE Band 12(30MHz-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 699.7 MHz								
60.84	H	36.49	-67.38	-9.85	0.14	-77.37	-13.00	64.37
212.33	V	42.81	-66.90	0.00	0.26	-67.16	-13.00	54.16
1399.400	H	44.54	-59.16	8.22	0.71	-51.65	-13.00	38.65
1399.400	V	42.57	-61.18	8.22	0.71	-53.67	-13.00	40.67
2099.100	H	48.27	-53.61	9.16	0.91	-45.36	-13.00	32.36
2099.100	V	45.58	-56.25	9.16	0.91	-48.00	-13.00	35.00
2798.800	H	37.85	-62.08	9.88	1.04	-53.24	-13.00	40.24
2798.800	V	36.83	-62.97	9.88	1.04	-54.13	-13.00	41.13
1.4MHz QPSK, Frequency: 707.5 MHz								
60.46	H	36.75	-67.13	-10.06	0.14	-77.33	-13.00	64.33
212.59	V	42.19	-67.53	0.00	0.27	-67.80	-13.00	54.80
1415.000	H	49.32	-54.35	8.26	0.72	-46.81	-13.00	33.81
1415.000	V	43.55	-60.17	8.26	0.72	-52.63	-13.00	39.63
2122.500	H	49.33	-52.66	9.17	0.92	-44.41	-13.00	31.41
2122.500	V	46.01	-55.96	9.17	0.92	-47.71	-13.00	34.71
2830.000	H	37.13	-62.67	9.93	1.06	-53.80	-13.00	40.80
2830.000	V	37.04	-62.69	9.93	1.06	-53.82	-13.00	40.82
1.4MHz QPSK, Frequency: 715.3 MHz								
60.28	H	36.46	-67.42	-10.15	0.14	-77.71	-13.00	64.71
212.74	V	42.39	-67.34	0.00	0.27	-67.61	-13.00	54.61
1430.600	H	48.97	-54.66	8.31	0.73	-47.08	-13.00	34.08
1430.600	V	44.12	-59.57	8.31	0.73	-51.99	-13.00	38.99
2145.900	H	50.15	-51.95	9.19	0.93	-43.69	-13.00	30.69
2145.900	V	46.03	-56.08	9.19	0.93	-47.82	-13.00	34.82
2861.200	H	36.58	-63.07	9.98	1.07	-54.16	-13.00	41.16
2861.200	V	36.47	-63.20	9.98	1.07	-54.29	-13.00	41.29

LTE Band 13 (30MHz-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 779.5 MHz								
60.97	H	36.45	-67.42	-9.79	0.14	-77.35	-13.00	64.35
212.78	V	42.84	-66.89	0.00	0.27	-67.16	-13.00	54.16
1559.000	H	40.11	-63.88	8.57	0.80	-56.11	-40.00	16.11
1559.000	V	39.34	-64.71	8.57	0.80	-56.94	-40.00	16.94
2338.500	H	43.17	-58.42	9.30	0.97	-50.09	-13.00	37.09
2338.500	V	36.97	-64.39	9.30	0.97	-56.06	-13.00	43.06
3118.000	H	33.59	-63.90	10.25	1.13	-54.78	-13.00	41.78
3118.000	V	34.19	-63.16	10.25	1.13	-54.04	-13.00	41.04
5MHz QPSK, Frequency: 784.5 MHz								
60.58	H	36.75	-67.12	-9.99	0.14	-77.25	-13.00	64.25
212.38	V	42.51	-67.20	0.00	0.26	-67.46	-13.00	54.46
1569.000	H	36.52	-67.56	8.58	0.81	-59.79	-40.00	19.79
1569.000	V	38.46	-65.67	8.58	0.81	-57.90	-40.00	17.90
2353.500	H	47.03	-54.42	9.31	0.97	-46.08	-13.00	33.08
2353.500	V	35.15	-66.07	9.31	0.97	-57.73	-13.00	44.73
3138.000	H	34.81	-62.59	10.26	1.14	-53.47	-13.00	40.47
3138.000	V	35.06	-62.17	10.26	1.14	-53.05	-13.00	40.05

LTE Band 25(30MHz-20GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 1850.4 MHz								
60.74	H	36.54	-67.33	-9.91	0.14	-77.38	-13.00	64.38
212.55	V	42.87	-66.85	0.00	0.27	-67.12	-13.00	54.12
3700.800	H	49.63	-47.69	10.60	1.25	-38.34	-13.00	25.34
3700.800	V	48.43	-48.87	10.60	1.25	-39.52	-13.00	26.52
5551.200	H	40.38	-52.88	11.44	1.49	-42.93	-13.00	29.93
5551.200	V	35.02	-58.08	11.44	1.49	-48.13	-13.00	35.13
1.4MHz QPSK, Frequency: 1882.5 MHz								
60.84	H	36.45	-67.42	-9.85	0.14	-77.41	-13.00	64.41
212.38	V	42.82	-66.89	0.00	0.26	-67.15	-13.00	54.15
3765.000	H	45.13	-51.20	10.67	1.25	-41.78	-13.00	28.78
3765.000	V	41.57	-54.64	10.67	1.25	-45.22	-13.00	32.22
5647.500	H	41.05	-52.40	11.32	1.55	-42.63	-13.00	29.63
5647.500	V	36.36	-56.97	11.32	1.55	-47.20	-13.00	34.20
1.4MHz QPSK, Frequency: 1914.3 MHz								
60.22	H	36.44	-67.44	-10.18	0.14	-77.76	-13.00	64.76
212.58	V	41.87	-67.85	0.00	0.27	-68.12	-13.00	55.12
3828.600	H	44.17	-51.73	10.73	1.28	-42.28	-13.00	29.28
3828.600	V	41.29	-54.48	10.73	1.28	-45.03	-13.00	32.03
5742.900	H	40.38	-53.10	11.21	1.60	-43.49	-13.00	30.49
5742.900	V	40.36	-53.00	11.21	1.60	-43.39	-13.00	30.39

LTE Band 26 (30MHz-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4MHz QPSK, Frequency: 814.7 MHz								
60.74	H	36.99	-66.88	-9.91	0.14	-76.93	-13.00	63.93
212.39	V	41.57	-68.14	0.00	0.26	-68.40	-13.00	55.40
1629.400	H	41.02	-63.33	8.66	0.81	-55.48	-13.00	42.48
1629.400	V	39.15	-65.26	8.66	0.81	-57.41	-13.00	44.41
2444.100	H	49.85	-51.04	9.37	1.00	-42.67	-13.00	29.67
2444.100	V	40.57	-60.18	9.37	1.00	-51.81	-13.00	38.81
3258.800	H	34.13	-62.73	10.30	1.17	-53.60	-13.00	40.60
3258.800	V	33.61	-63.00	10.30	1.17	-53.87	-13.00	40.87
1.4MHz QPSK, Frequency: 831.5 MHz								
60.49	H	36.78	-67.10	-10.04	0.14	-77.28	-13.00	64.28
212.84	V	41.21	-68.52	0.00	0.27	-68.79	-13.00	55.79
1663.000	H	38.13	-66.19	8.70	0.83	-58.32	-13.00	45.32
1663.000	V	38.59	-65.82	8.70	0.83	-57.95	-13.00	44.95
2494.500	H	50.32	-50.38	9.40	1.01	-41.99	-13.00	28.99
2494.500	V	41.11	-59.60	9.40	1.01	-51.21	-13.00	38.21
3326.000	H	33.65	-63.30	10.33	1.16	-54.13	-13.00	41.13
3326.000	V	33.94	-62.82	10.33	1.16	-53.65	-13.00	40.65
1.4MHz QPSK, Frequency: 848.3 MHz								
60.55	H	36.45	-67.42	-10.01	0.14	-77.57	-13.00	64.57
212.58	V	41.57	-68.15	0.00	0.27	-68.42	-13.00	55.42
1696.600	H	43.05	-61.24	8.74	0.89	-53.39	-13.00	40.39
1696.600	V	40.17	-64.25	8.74	0.89	-56.40	-13.00	43.40
2544.900	H	48.74	-51.60	9.47	1.01	-43.14	-13.00	30.14
2544.900	V	41.58	-58.72	9.47	1.01	-50.26	-13.00	37.26
3393.200	H	34.12	-63.55	10.36	1.19	-54.38	-13.00	41.38
3393.200	V	33.91	-63.72	10.36	1.19	-54.55	-13.00	41.55

LTE Band 66 (30MHz-20GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1.4M QPSK, Frequency: 1710.7MHz								
63.58	H	35.89	-67.95	-8.40	0.14	-76.49	-13.00	63.49
212.48	V	42.11	-67.61	0.00	0.26	-67.87	-13.00	54.87
3421.400	H	53.14	-44.62	10.37	1.17	-35.42	-13.00	22.42
3421.400	V	55.25	-42.48	10.37	1.17	-33.28	-13.00	20.28
5132.100	H	39.63	-53.94	11.28	1.47	-44.13	-13.00	31.13
5132.100	V	35.69	-57.77	11.28	1.47	-47.96	-13.00	34.96
1.4M QPSK, Frequency:1745 MHz								
62.35	H	36.87	-66.99	-9.05	0.14	-76.18	-13.00	63.18
212.54	V	41.57	-68.15	0.00	0.27	-68.42	-13.00	55.42
3490.000	H	53.27	-44.57	10.40	1.17	-35.34	-13.00	22.34
3490.000	V	57.18	-40.60	10.40	1.17	-31.37	-13.00	18.37
5235.000	H	38.77	-55.13	11.34	1.46	-45.25	-13.00	32.25
5235.000	V	39.63	-54.08	11.34	1.46	-44.20	-13.00	31.20
1.4M QPSK, Frequency: 1779.3 MHz								
61.32	H	36.74	-67.13	-9.60	0.14	-76.87	-13.00	63.87
212.87	V	42.35	-67.38	0.00	0.27	-67.65	-13.00	54.65
3558.600	H	55.18	-42.49	10.46	1.22	-33.25	-13.00	20.25
3558.600	V	54.12	-43.45	10.46	1.22	-34.21	-13.00	21.21
5337.900	H	38.53	-54.94	11.40	1.47	-45.01	-13.00	32.01
5337.900	V	34.58	-58.75	11.40	1.47	-48.82	-13.00	35.82

LTE Band 85(30MHz-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
5MHz QPSK, Frequency: 700.5 MHz								
60.95	H	36.58	-67.29	-9.80	0.14	-77.23	-13.00	64.23
212.38	V	42.19	-67.52	0.00	0.26	-67.78	-13.00	54.78
1401.000	H	39.06	-64.65	8.22	0.71	-57.14	-13.00	44.14
1401.000	V	40.83	-62.92	8.22	0.71	-55.41	-13.00	42.41
2101.500	H	38.94	-62.95	9.16	0.91	-54.70	-13.00	41.70
2101.500	V	38.27	-63.57	9.16	0.91	-55.32	-13.00	42.32
2802.000	H	35.77	-64.15	9.88	1.04	-55.31	-13.00	42.31
2802.000	V	37.84	-61.96	9.88	1.04	-53.12	-13.00	40.12
5MHz QPSK, Frequency: 707 MHz								
60.85	H	36.47	-67.40	-9.85	0.14	-77.39	-13.00	64.39
212.54	V	42.83	-66.89	0.00	0.27	-67.16	-13.00	54.16
1414.000	H	37.78	-65.89	8.26	0.72	-58.35	-13.00	45.35
1414.000	V	40.51	-63.21	8.26	0.72	-55.67	-13.00	42.67
2121.000	H	38.15	-63.83	9.17	0.92	-55.58	-13.00	42.58
2121.000	V	37.85	-64.11	9.17	0.92	-55.86	-13.00	42.86
2828.000	H	36.55	-63.25	9.92	1.06	-54.39	-13.00	41.39
2828.000	V	36.14	-63.60	9.92	1.06	-54.74	-13.00	41.74
5MHz QPSK, Frequency: 713.5 MHz								
60.28	H	36.87	-67.01	-10.15	0.14	-77.30	-13.00	64.30
212.89	V	42.51	-67.22	0.00	0.27	-67.49	-13.00	54.49
1427.000	H	39.25	-64.39	8.30	0.73	-56.82	-13.00	43.82
1427.000	V	38.66	-65.03	8.30	0.73	-57.46	-13.00	44.46
2140.500	H	37.05	-65.02	9.18	0.93	-56.77	-13.00	43.77
2140.500	V	38.07	-64.01	9.18	0.93	-55.76	-13.00	42.76
2854.000	H	37.04	-62.65	9.97	1.07	-53.75	-13.00	40.75
2854.000	V	35.97	-63.71	9.97	1.07	-54.81	-13.00	41.81

Note:

- 1) The unit of Antenna Gain is dBd for frequency below 1GHz, and the unit of Antenna Gain is dBi for frequency above 1GHz.
- 2) Absolute Level = Substituted Level - Cable loss + Antenna Gain
- 3) Margin = Limit-Absolute Level

5. EUT PHOTOGRAPHS

Please refer to the attachment CR230851060-EXP EUT EXTERNAL PHOTOGRAPHS and
CR230851060-INP EUT INTERNAL PHOTOGRAPHS

6. TEST SETUP PHOTOGRAPHS

Please refer to the attachment CR230851060-00-TSP TEST SETUP PHOTOGRAPHS.

==== END OF REPORT =====