

ISED CABid: ES1909 Lab. Company Number: 4621A

Test report No:

NIE: 78153RAN.002

Assessment report RF EXPOSURE REPORT ACCORDING TO ISED RSS - 102 Issue 5 (2015-03) AMD 1 (2021-02)

(*) Identification of item under evaluation	Square Tracker Xtreme
(*) Trademark	Sensative AB
(*) Model and /or type reference	3307002
(*) Derived model not evaluated	
(*) Other identification of the product	FCC ID : 2AHIR-005 IC ID : 21254-005 HW version : R5 SW Version : R12
(*) Features	LoRaWAN 902 - 928 MHz
(*) Manufacturer	Sensative AB Mobilvägen 10, 223 62 LUND, SWEDEN
Test method requested, standard	ISED RSS-102 Issue 5 (2015-03) Amendment 1 (February 2, 2021) – Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)
Summary	IN COMPLIANCE
Approved by (name / position & signature)	Miguel Lacave Antennas Lab Manager
Date of issue	2024-02-29
Report template No	FAN36_02 (*) "Data provided by the client"



Index

Competences and guarantees	3
General conditions	3
Data provided by the client	3
dentification of the client	5
Document history	5
Appendix A: ISED RF Exposure assessment result	5
General description of the device under evaluation	6
RF Exposure Assessment result and verdict	7
Appendix B: ISED RF Exposure information	8
RF Exposure evaluation for mobile devices	9
Evaluation Method	11



Competences and guarantees

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification, S.A.U. has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification, S.A.U. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification, S.A.U. at the time of performance of the test.

DEKRA Testing and Certification, S.A.U. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Assessment Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification, S.A.U.

General conditions

- 1. This report is only referred to the item that has undergone the assessment.
- 2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
- 3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification, S.A.U.
- 4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification, S.A.U. and the Accreditation Bodies

Data provided by the client

The following data has been provided by the client:

- Information relating to the description of the sample ("Identification of the item under evaluation", "Trademark", "Model and/or type reference", "Derived model not evaluated", "General description of the device", "Other identification of the product").
- 2. Maximum output power, maximum antenna gain and use distance information.
- 3. The device under evaluation consists of a compact indoor/outdoor asset tracker, air pressure sensor (enabling 3D positioning) and motion controlled.
- 4. Derived model not evaluated. These models have been declared by the supplier of the sample as being the same as the model under evaluation.



	Sensative Confidential	Page 1(1)
Prepared by: Dhiraj Paryani	Document number:	Revision: A
Approved by:	Date: 2024-01-18	Remarks:

Sensative AB

Mobilvägen 10, 223 62 Lund, Sweden

Product Similarity Declaration

Date: January 12th, 2024

FCC ID: 2AHIR-005

Model Numbers: 3302002, 3303002, 3306002, 3307002, 3310002, 3311002, 3312002, 3313002

To Whom It May Concern,

We, Sensative AB, hereby declare that our product (Square LoRa Sensors) Model Number: 3302002, 3303002, 3306002, 3307002, 3311002, 3312002, 3312002, 3313002 board, Schematic, Hardware version, Software version, structure and internal photos are same, named differently due to marketing purposes.

Should you have any questions or comments regarding this matter, please have my best attention.

Sincerely,

Name / Title: Mats Pettersson / CTO Company: Sensative AB Address: Mobilvägen 10, 223 62 Lund, Sweden Tel: +46 70 510 03 84 E-Mail: Mats.Pettersson@sensative.com

DEKRA

Testing and Certification S.A.U. declines any responsibility with respect to the information provided by the client and that may affect the validity of results.



Identification of the client

Sensative AB

Mobilvägen 10, 223 62 LUND, SWEDEN

Document history

Report number	Date	Description
78153RAN.002	2024-02-29	First release

Appendix A: ISED RF Exposure assessment result



General description of the device under evaluation

Table 1 shows information used for the RF Evaluation, considering the following declared specifications for the device:

Description and technologies: the device under evaluation consists of a compact indoor/outdoor asset tracker, air pressure sensor (enabling 3D positioning) and motion controlled with the following features: LoRaWAN. For RF Exposure evaluation, only transmission technologies: LoRaWAN are considered.

Evaluation Distance: according to the manufacturer, during its normal use, the separation distance between the radiating structures of the device and nearby users will be greater than 20 cm. In order to perform the assessment a conservative evaluation distance of 20 cm has been used.

Maximum output power:

- Values corresponding to maximum output power have been declared by the device manufacturer (maximum output power values stated in manufacturer's technical description document.

Antennas: the device supports one antenna for the LoRaWAN transmitting technology:

- "Omnidirectional" antenna for LoRaWAN transmissions.
- Values corresponding to antenna gain have been declared by the device manufacturer (maximum peak gain stated in antenna manufacturer's technical description document).

The following table shows the information provided above:

Technology / Mode	Operating Band	Frequency under evaluation (MHz)	Maximum Conducted Output Power (Incl. Tune-Up) (dBm)	Antenna peak gain (dBi)	Maximum E.I.R.P. (dBm)	Maximum E.I.R.P. (mW)
LoRa	ISM (USA)	902 - 928	12.00	1.70	13.70	23.44

Table 1: Equipment specifications



RF Exposure Assessment result and verdict

RF Exposure Exemption evaluation:

According to RSS-102 Issue 5, paragraph "2.5.2.Exemption Limits for Routine Evaluation – RF Exposure Evaluation", each transmitting technology must be assessed against specific exemption limits.

Technology / Mode	Operating Band	Frequency under evaluation (MHz)	Distance (cm)	Time- averaged maximum e.i.r.p (mW)	RF Exposure Exclusion Limit (mW)	Verdict
LoRa	ISM (USA)	902 - 928	20.00	23.44	1370.44	Pass

Table 2: Exemption Evaluation verdict

The device under evaluation is exempt of RF Exposure evaluation as maximum E.I.R.P. for each supported technology meets these limit exemptions.



Appendix B: ISED RF Exposure information

Report No: (NIE) 78153RAN.002

Page 8 of 11

2024-02-29



RF Exposure evaluation for mobile devices

According to RSS-102 Issue 5, Paragraph "2.5.2. Exemption Limits for Routine Evaluation – RF Exposure Evaluation":

2.5.2 Exemption Limits for Routine Evaluation – RF Exposure Evaluation

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz⁶ and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 22.48/f^{0.5} W (adjusted for tune-up tolerance), where *f* is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1.31 x 10⁻² f^{0.6834} W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

According to RSS-102 Issue 5, Paragraph "4. Exposure Limits", Industry of Canada has adopted the RF field strength limits established in Health Canada's RF exposure guideline, Safety code 6:

Frequency Range	Electric Field	Magnetic Field	Power Density	Reference Period		
(MHz)	(V/m rms)	(A/m rms)	(W/m^2)	(minutes)		
$0.003 - 10^{21}$	83	90	-	Instantaneous*		
0.1-10	-	0.73/ f	-	6**		
1.1-10	$87/f^{0.5}$	-	-	6**		
10-20	27.46	0.0728	2	6		
20-48	$58.07/f^{0.25}$	$0.1540/f^{0.25}$	$8.944/f^{0.5}$	6		
48-300	22.06	0.05852	1.291	6		
300-6000	$3.142 f^{0.3417}$	$0.008335 f^{0.3417}$	$0.02619 f^{0.6834}$	6		
6000-15000	61.4	0.163	10	6		
15000-150000	61.4	0.163	10	$616000/f^{1.2}$		
150000-300000	$0.158 f^{0.5}$	$4.21 \ge 10^{-4} f^{0.5}$	6.67 x 10 ⁻⁵ f	$616000/f^{1.2}$		
Note: <i>f</i> is frequency in MHz.						
*Based on nerve stimulation (NS).						
** Based on specific absorption rate (SAR).						

Table 4: RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)



Table 6: RF Field Strength Limits for Controlled Use Devices (Controlled Environment)

Frequency Range	Electric Field	Magnetic Field	Power Density	Reference Period	
(MHz)	(V/m rms)	(A/m rms)	(W/m^2)	(minutes)	
$0.003 - 10^{23}$	170	180	-	Instantaneous*	
0.1-10	-	1.6/f	-	6**	
1.29-10	$193/f^{0.5}$	-	-	6**	
10-20	61.4	0.163	10	6	
20-48	$129.8/f^{0.25}$	$0.3444/f^{0.25}$	$44.72/f^{0.5}$	6	
48-100	49.33	0.1309	6.455	6	
100-6000	$15.60 f^{0.25}$	$0.04138 f^{0.25}$	$0.6455 f^{0.5}$	6	
6000-15000	137	0.364	50	6	
15000-150000	137	0.364	50	$616000/f^{1.2}$	
150000-300000	$0.354 f^{0.5}$	$9.40 \ge 10^{-4} f^{0.5}$	$3.33 \ge 10^{-4} f$	$616000/f^{1.2}$	
Note: <i>f</i> is frequency in MHz.					
*Based on nerve stimulation (NS).					
** Based on specific absorption rate (SAR).					



Evaluation Method

When the device is exempt from RF Exposure evaluation because its operation matches any of the cases indicated in RSS-102 Issue 5, clause 2.5.2 ("Exemption Limits for Routine Evaluation – RF Exposure Evaluation"), the maximum E.I.R.P. can be calculated using the following formula to assess compliance with the Exemption Limits:

 $P_{EIRP} = \mathsf{P}_{\mathsf{T}} + \mathsf{G}_{\mathsf{T}} - \mathsf{L}_{\mathsf{C}}$

Where:

P_T= transmitter output power (including tune-up tolerance)

G_T= gain of the transmitting antenna

Lc = signal attenuation in the connecting cable between the transmitter and the antenna, if applicable

When RF Exposure evaluation is needed to determine compliance with RSS-102 Issue 5, RF Field Strength Limits, the following equations have been used for the calculations; these equations are accurate in the far-field of an antenna and will over-predict power density in the near field, where they could be used for making a "worst-case" or conservative prediction:

Power density:
$$S[W/m^2] = \frac{P_{E.I.R.P.}[W]}{4\Pi R[m]^2}$$

Where:

S = power density

 $P_{E,I,R,P}$ = Equivalent isotropically radiated power

R = distance to the center of radiation of the antenna (evaluation distance)

 $P_{E,I,R,P} = \mathsf{P}_\mathsf{T} + \mathsf{G}_\mathsf{T} - \mathsf{L}_\mathsf{C}$

Where:

P_T= transmitter output power (including tune-up tolerance)

 G_T = gain of the transmitting antenna

Lc = signal attenuation in the connecting cable between the transmitter and the antenna if applicable

Multiple frequencies assessment

When multiple sources are introduced into an environment, it becomes necessary to address the sources interdependently, since each source will contribute some percentage of the maximum exposure towards the total exposure at a fixed location. The sum of the ratios of the exposure from each source to the corresponding maximum exposure for the frequency of each source must be evaluated.

The exposure complies with the maximum permissible exposure if the sum of the ratios is less or equal than unity:

$$\sum_{i=1}^{n} \frac{\text{Evaluated}_{i}}{\text{Exposure limit}_{i}} \leq 1$$

Where:

Evaluated_i = RF source evaluated at the minimun use distance

Exposure limit_i = Applicable exposure limit for the evaluation of the RF source