PCTEST ENGINEERING LABORATORY, INC. 6660 – B Dobbin Road · Columbia, MD 21045 · USA Telephone 410.290.6652 / Fax 410.290.6654 http://www.pctestlab.com (email: randy@pctestlab.com) CERTIFICATE OF COMPLIANCE (SAR EVALUATION)



APPLICANT NAME & ADDRESS: Uniden Engineering Services 216 John Street, P.O. Box 580 Lake City, SC 92560-0580

DATE & LOCATION OF TESTING: Dates of Tests: October 15-22, 2003

Test Report S/N: SAR.230924533-R1.AMW Test Site: PCTEST Lab, Columbia MD

FCC ID:	AMWUP717
APPLICANT:	UNIDEN ENGINEERING SERVICES
EUT Type:	5.8 GHz Cordless Phone
Tx Frequency:	5741 – 5828 MHz
Rx Frequency:	5741 – 5828 MHz
Max. RF Output Power:	18.67 dBm EIRP (HS), 24.18 dBm EIRP (BASE)
Max. SAR Measurement:	0.099 W/kg Head SAR; 0.571 W/kg Body SAR;
Trade Name/Model(s):	TRU8885
FCC Classification:	FCC Part 15 Digital Transmission System (DTS)
FCC Rule Part(s):	§2.1093; FCC/OET Bulletin 65 Supplement C [July 2001]
Application Type:	Certification
Test Device Serial No.:	identical prototype [S/N: 2]

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE Std. C95.1-1992 and had been tested in accordance with the measurement procedures specified in FCC/OET Bulletin 65 Supplement C (2001) and IEEE Std. 1528-200X (Draft 6.5, January 15, 2002).

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Grant Conditions: Output power is EIRP. This transmitter has been tested for SAR compliance for head and bodyworn configurations. SAR compliance for body-worn operating configurations is limited to the specific belt-clip tested for this filing. Users must be informed of the operating requirements for satisfying body-worn RF exposure compliance.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.

Alfred Cirwithian Vice President Engineering



PCTESTÔ SAR REPORT	PCYERT	FCC Measurement Report		Reviewed by: Quality Manager
SAR Filename:	Test Dates:	Phone Type:	FCC ID:	Page 1 of 29
SAR-230924533-R1.AMW	October 15-22, 2003	5.8 GHz Cordless Phone	AMWUP717	



3. DASY4 E-FIELD PROBE SYSTEM

Probe Measurement System



Figure 3.1 DAE System

The SAR measurements were conducted with the dosimetric probe ET3DV6, designed in the classical triangular configuration [7] (see Fig. 3.2) and optimized for dosimetric evaluation. The probe is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multifiber line ending at the front of the probe tip (see Fig. 3.3). It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY4 software reads the reflection during a software approach and looks for the maximum using a 2^{nd} order fitting (see Fig.3.1). The approach is stopped at reaching the maximum.

Probe Specifications

Calibration:	In air from 10 MHz to 6 GHz	
	In brain and muscle simulating tissue at	547 00 100
	Frequencies of 150 MHz, 450 MHz, 835 MHz, 900 MHz, 1900MHz, 2450MHz, 5300MHz, & 5800MHz	A-BEAM
Frequency:	10 MHz to > 6 GHz; Linearity: ± 0.2 dB (30 MHz to 6 GHz)	Figure 3.1 Triangular Probe Configuration
Directivity:	±0.2 dB in HSL (rotation around probe axis)	
	\pm 0.4 dB in HSL (rotation normal probe axis)	
Dynamic:	5 :W/g to > 100 mW/g;	
Range:	Linearity: ± 0.2 dB	
Dimensions:	Overall length: 330 mm	
	Tip length: 16 mm	e /
	Body diameter: 12 mm	0
	Tip diameter: 3 mm	
	Distance from probe tip to dipole centers: 2 mm	
Application:	General dosimetry up to 6 GHz	
	Compliance tests of mobile phones	
	Fast automatic scanning in arbitrary phantoms	Figure 3.2 Probe Thick-Film Technique

PCTESTÔ SAR REPORT	PCTERT	CC Measurement Report	uniden	Reviewed by: Quality Manager
SAR Filename:	Test Dates:	Phone Type:	FCC ID:	Page 5 of 29
SAR-230924533-R1.AMW	October 15-22, 2003	5.8 GHz Cordless Phone	AMWUP717	



5. PHANTOM & EQUIVALENT TISSUES

SAM Phantom



Figure 5.1 SAM Twin Phantom



Brain & Muscle Simulating Mixture Characterization



The brain and muscle mixtures consist of a viscous gel using hydroxethylcellullose (HEC) gelling agent and saline solution (see Table 6.1). Preservation with a bacteriacide is added and visual inspection is made to make sure air bubbles are not trapped during the mixing process. The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the desired tissue. The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 have been incorporated in the following table. Other head and body tissue parameters that have not bee specified in P1528 are derived from the issue dielectric parameters computed from the 4-Cole-Cole equations The mixture characterizations used for the brain and muscle tissue simulating liquids are according to the data by C. Gabriel and G. Hartsgrove [13].(see Fig. 5.2)

Table 5.1 Composition of the Brain & Muscle Tissue Equivalent Matter

Figure 5.2 Simulated

115540		•		•				
		SIMULATING TISSUE						
INGREDIENTS		1900MHz Brain 1900MHz Muscle		5800MHz Brain	5800MHz Muscle			
Mixture Percentage								
WATER		54.90	40.40	65.67	77.18			
DGBE		44.92	0.000	6.120	9.690			
SUGAR		0.000	58.00	0.000	0.000			
SALT		0.180	0.500	0.000	0.000			
BACTERIACIDE		0.000	0.100	0.000	0.000			
HEC		0.000	1.000	0.000	0.000			
Triton X-100		0.000	0.000	28.21	13.13			
Dielectric Constant	Target	40.00	53.30	35.30	48.20			
Conductivity (S/m)	Target	1.400	1.520	5.270	6.000			

Device Holder for Transmitters



In combination with the SAM Twin Phantom V4.0, the Mounting Device (see Fig. 5.2) enables the rotation of the mounted transmitter in spherical coordinates whereby the rotation point is the ear opening. The devices can be easily, accurately, and repeatably be positioned according to the FCC specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).

* Note: A simulating human hand is not used due to the complex anatomical and geometrical structure of the hand that may produce infinite number of configurations [12]. To produce the worst-case condition (the hand absorbs antenna output power), the hand is omitted during the tests.

Figure 5.2 Mounting Device

PCTESTÔ SAR REPORT	POTEST	FCC Measurement Report		Reviewed by: Quality Manager
SAR Filename:	Test Dates:	Phone Type:	FCC ID:	Page 7 of 29
SAR-230924533-R1.AMW	October 15-22, 2003	5.8 GHz Cordless Phone	AMWUP717	



11. MEASUREMENT UNCERTAINTIES

а	b	С	d	e=	f	g	h =	i =	k
				f(d,k)			cxf/e	cxg/e	
Uncertainty		Tol.	Prob.		Ci	Ci	1 - g	10 - g	
Component	Sec.	(± %)	Dist.	Div.	(1 - g)	(10 - g)	ui	ui	vi
							(± %)	(± %)	
Measurement System									
Probe Calibration	E1.1	4.8	Ν	1	1	1	8.0	8.0	∞
Axial Isotropy	E1.2	4.7	R	$\sqrt{3}$	0.7	0.7	1.9	1.9	∞
Hemishperical Isotropy	E1.2	9.6	R	$\sqrt{3}$	0.7	0.7	3.9	3.9	∞
Boundary Effect	E1.3	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
Linearity	E1.4	4.7	R	$\sqrt{3}$	1	1	2.7	2.7	∞
System Detection Limits	E1.5	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	∞
Readout Electronics	E1.6	1.0	Ν	1	1	1	1.0	1.0	∞
Response Time	E1.7	0.8	R	$\sqrt{3}$	1	1	0.5	0.5	∞
Integration Time	E1.8	2.6	R	$\sqrt{3}$	1	1	1.5	1.5	∞
RF Ambient Conditions	E5.1	3.0	R	$\sqrt{3}$	1	1	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	E5.2	0.4	R	$\sqrt{3}$	1	1	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	E5.3	2.9	R	$\sqrt{3}$	1	1	1.7	1.7	∞
Extrapolation, Interpolation & Integration	E4.2	1.0	R	$\sqrt{3}$	1	1	0.6	0.6	~
Algorithms for Max. SAR Evaluation									
Test Sample Related									
Test Sample Positioning	E3.2.1	2.9	Ν	1	1	1	2.9	2.9	145
Device Holder Uncertainty	E3.1.1	3.6	Ν	1	1	1	3.6	3.6	5
Output Power Variation - SAR drift	5.6.2	5.0	R	$\sqrt{3}$	1	1	2.9	2.9	∞
measurement									
Phantom & Tissue Parameters									
Phantom Uncertainty (Shape & Thickness	E2.1	4.0	R	$\sqrt{3}$	1	1	2.3	2.3	∞
tolerances)									
Liquid Conductivity - deviation from	E2.2	5.0	R	$\sqrt{3}$	0.64	0.43	1.8	1.2	∞
target values									
Liquid Conductivity - measurement	E2.2	2.5	Ν	1	0.64	0.43	1.6	1.1	∞
uncertainty									
Liquid Permittivity - deviation from	E2.2	5.0	R	$\sqrt{3}$	0.6	0.5	1.7	1.4	∞
target values									
Liquid Permittivity - measurement	E2.2	2.5	Ν	1	0.6	0.5	1.5	1.2	∞
uncertainty									
Combined Standard Uncertainty (k=1)			RSS				12.1	11.9	
Expanded Uncertainty (k=2)							24.2	23.8	
(95% CONFIDENCE LEVEL)									

The above measurement uncertainties are according to IEEE Std. 1528-200x (Jan. 2002)

PCTESTÔ SAR REPORT	PCTERT	FCC Measurement Report		Reviewed by: Quality Manager
SAR Filename:	Test Dates:	Phone Type:	FCC ID:	Page 15 of 29
SAR-230924533-R1.AMW	October 15-22, 2003	5.8 GHz Cordless Phone	AMWUP717	